

you can
Canon

i-SENSYS
FAX-L140



Superb laser fax quality in a compact and stylish unit

The i-SENSYS FAX-L140 is part of the Canon laser fax range

The Fax line-up will be: FAX-L3000IP, FAX-L3000, FAX-L390, FAX-L380S, FAX-L160, **FAX-L140**

Embargo Date: 24th January 2008
Sales Start Date: February 2008
Target Market: Small to medium office market

Key Features

- Super G3 fax modem (33.6kbps) - 3 seconds per page* transmission
- Stylish, compact and robust design
- Ultra High Quality 256 greyscale imaging for faxing fine details
- 340-page* transmit and receive fax memory
- 15 one-touch and 100 coded speed dials
- Easy to use All-in-One cartridge, ensures continuous high quality output
- 150-sheet paper capacity
- 30-page Automatic Document Feeder
- 2-line backlight display
- Copying: 12 copies per minute – zero warm up time from sleep mode
- Energy efficient – only 3 watts in sleep mode

* based on ITU-T Standard Chart No. 1

Product Name	Mercury Code	EAN Code	Recommended Retail Price
i-SENSYS FAX-L140	2234B043AA	8714574513249	TBC

What's in the box:

Main unit, All-in-One cartridge FX-10, USB cable, power cord, telephone line cable, document tray, destination labels, CD-ROM for driver, CD-ROM user manual, starter guide, warranty card

Optional accessories	Mercury Code	EAN Code
Telephone kit 6 long cord	0752A053AA (UK)	4960999453897 (UK)

Consumables	Mercury Code	EAN Code
All-in-One cartridge FX-10	0263B002AA	4960999270616

you can
Canon

i-SENSYS
FAX-L140



Technical Specifications

FAX UNIT TYPE	
Type	Standalone facsimile
Compatibility	Group 3
Applicable line	PSTN
Modem speed	33.6K bps (Super G3)
Print technology	Laser beam printing
Scanner type	Sheet fed
Body colour	Titanium white
FAX SCANNING FEATURES	
Automatic document feeder	30 sheets
Document size	Width - 216mm(Max), 148mm(Min) Length - 400mm(Max), 105mm(Min)
Effective scanning width	208 mm
Scanning speed	Approx. 3.5 sec/page Approx. 15.5 pages/minute
Fax resolution	STANDARD: 8 pels/mm × 3.85 lines/mm FINE: 8 pels/mm × 7.7 lines/mm SUPER FINE: 8 pels/mm × 15.4 lines/mm PHOTO: 8 pels/mm × 7.7 lines/mm
Image processing system	UHQ (Ultra High Quality)
Halftone	256 shades of grey scale
FAX PRINTING FEATURES	
Printing method	Laser Beam Printing
Print speed	12 pages per minute
Print resolution	600 x 600 dpi
Smoothing	Yes
Paper capacity	150 sheet Auto Sheet Feeder
Print cartridge	
Yield	FX-10 all in one laser cartridge approx. 2000 pages (based on 5% print coverage)
Page collated print	Yes (Face down print)
Printing width	206mm
Toner save mode	Yes (Toner yield approx. 3000 pages)
Auto image reduction on reception	Yes
TRANSMISSION AND RECEPTION FEATURES	
Transmission speed	3 seconds per page with 33.6K bps modem (based on ITU-T Chart No.1)
Compression method	MH, MR, MMR
Direct transmission	Yes
Memory transmission	Yes
Quick memory transmission	Yes
FAX memory	340 pages (based on ITU-T Chart No.1)
Memory reception	Yes
Dual access	Yes
Error correction mode(ECM)	Yes
Delayed transmission	Yes (50 locations)
Sequential broadcast	Yes (max. 131 recipients)
Polling Transmission	Yes (Memory)
Polling Reception	Yes
Sub-address transmission	Yes
Relay broadcasting command	Yes (by sub address)
Relay broadcast	Yes
SECURITY AND MANAGEMENT FEATURES	
Direct mail prevention	Yes
Confidential transmission	Yes (by sub address)
Forced memory reception	Yes

System management password	Yes
Reports	Activity Report, TX Result Report, RX Result Report, Memory Data List, Memory Image Print, One-Touch/Coded/Group Dial List, User Data List, Status List, Lost Report
Transmission header	Yes
Reception footer	Yes
TELEPHONY FEATURES	
One-touch dials	15
Coded dials	100
Group dials	15 (max. 50 locations)
Program dial	Yes
Redial	Yes (automatic and manual)
Dial search	Yes
FAX/TEL auto switch	Yes
Answering machine Hook-up	Yes
Extension Telephone Hook-up	Yes
Remote reception	Yes
On Hook key	Yes
Telephone handset	Option
Type	Telephone 6
Cradle	Included with handset
COPIER FEATURES	
Copy	Yes
Copy resolution	TEXT/PHOTO mode, TEXT mode, PHOTO mode: 203 dpi × 300 dpi
Copy speed (Mono)	12 pages per minute
Multiple copy	Up to 99 copies
Zoom	50% - 200% in 1% increments
First copy output time(FCOT)	Less than 23 secs
OTHER FEATURES	
Display	
Type	backlight LCD
Size	20 x 2
Languages	17 languages (Czech, Danish, Dutch, English, Finnish, French, German, Hungarian, Italian, Norwegian, Polish, Portuguese, Russian, Slovenian, Spanish, Swedish, Turkish)
Energy saver key	Yes
Others	Auto Summer time adjustment
OPTIONS	
Items	Handset (Tel 6)
GENERAL FEATURES	
Dimensions without trays	400(W) x 386(D) x 221(H) mm
Dimensions with tray	400(W) x 580(D) x 370(H) mm
Installation space (including trays & optional handset)	684(W) x 780(D) mm
Weight	Approx. 8kg
Power source consumption	AC 200-240V 50-60Hz Approx. 3W (Sleep) Approx. 8W (standby), Approx. 700W (Max)
Acoustic Noise Levels	Approx. 30dB(A) max (standby), 50dB(A) max (Copy)

