

Speed, quality and productive performance in a compact, elegant design.

i-SENSYS
LBP6310dn

you can



A compact A4 mono laser printer with all the capabilities small and medium-sized businesses demand.

This network ready, compact mono laser printer with duplex printing keeps you productive and offers the performance that dynamic small and medium-sized businesses demand.

Key features

- Compact, 33ppm mono laser printer keeps you productive
- Efficient automatic double-sided printing
- Network ready for easy integration and operation
- Fast First Print Out Time of just 6 seconds or less
- No waiting with Quick First-Print technologies
- Up to 2400 x 600 dpi print resolution with Automatic Image Refinement
- Max. 800-sheet paper capacity (250-sheet cassette, 50-sheet multi-purpose tray, optional 500-sheet cassette)
- Energy efficient and silent in standby
- Maintenance-free All-in-One cartridge for continuous high quality output

What's in the box

Main unit, 719 cartridge, power cord, quick setup guide and warranty card with user software and manual CDs.

Dimensions (W x D x H)

400mm x 376mm x 263mm

Supported OS

Windows 7 (32/64bit) / Vista (32/64bit) / XP (32/64bit) / Server 2003 (32/64bit) / Server 2008 (32/64bit) / Server 2008 R2 (64bit)

Mac OS 10.5 and up
(Web distribution only)

Linux (Web distribution only)

Citrix



PRINT



COPY



FAX



SCAN

Canon



Specifications:

PRINTER ENGINE	Print speed 33ppm mono (A4) Printing method Monochrome laser beam printing Print quality Up to 2400 x 600 dpi with Automatic Image Refinement Print resolution Up to 600 x 600 dpi Warm-up time Approx. 10 seconds or less from power on First Page Out Time Approx. 6 seconds or less Duty cycle Max. 25,000 pages per month ¹ Print margins 5mm – top, bottom, left and right
MEDIA HANDLING	Paper input (Standard) 250-sheet cassette 50-sheet multi-purpose tray Paper input (Option) 500-sheet cassette Paper output 150-sheet face down Media types Plain paper, Heavy paper, Transparency, Label, Index card, Envelope Media sizes Cassette (Standard and optional): A4, B5, A5, A6, Legal, Letter, Executive, 16K, Custom sizes: Width: 105.0mm to 215.9mm; Length: 148.0mm to 355.6mm Multi-purpose tray: A4, B5, A5, A6, Legal, Letter, Executive, 16K, Envelope DL, Envelope COM10, Envelope C5, Envelope B5, Envelope Monarch, Index Card, Custom sizes: Width: 76.2mm to 215.9mm; Length: 127.0mm to 355.6mm Media weights Cassette (Standard and optional): 60 to 120 g/m ² Multi-purpose tray: 60 to 163 g/m ² Double sided printing Automatic
GENERAL FEATURES	Power requirements 220-240V (±10%) 50/60Hz (±2Hz) Power consumption Maximum: Approx. 1170 W or less Active: Approx. 540 W Standby: Approx. 9 W Sleep: 1 W Typical Electricity Consumption (TEC): 1.9 kWh/week Noise level Sound power ² : Active: 7.06 B or less Standby: Inaudible Sound pressure ² : Active: 54.2 dB(A) or less Standby: Inaudible Dimensions (W x D x H) 400mm x 376mm x 263mm Weight Approx. 11.2kg Operating environment Temperature: 10 to 30°C (50 to 86°F) Humidity 20 to 80% RH (no condensation) Control panel 4 LED indicators 1 Operation key

CONTROLLER	Memory 16 MB Printer languages CAPT (Canon Advanced Printing Technology) Interface and connectivity USB 2.0 High-Speed, 10BASE-T/100BASE-TX Software and printer management NetSpot Device Installer, Remote User Interface (RUI) Operating systems compatibility Windows 7 (32/64bit) / Vista (32/64bit) / XP (32/64bit) / Server 2003 (32/64bit) / Server 2008 (32/64bit) / Server 2008 / R2 (64bit) / Mac OS 10.5 and up ^{3,4,5} / Linux ^{3,4} / Citrix
CONSUMABLES	All-in-One cartridges Standard: Cartridge 719 (2,100 pages ⁶) High yield: Cartridge 719H (6,400 pages ⁶)
ACCESSORIES / OPTIONS	Items Paper Feeder PF-44 (500-sheet cassette)
Standard disclaimers. All specifications subject to change without notice. 1] Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product 2] Declared noise emission in accordance with ISO 9296 3] Web distribution only 4] English driver only 5] The driver will be released in February 2013 6] Based on ISO/IEC 19752	

