## Epson AcuLaser CX17 Series



The AcuLaser CX17 Series is Epson's most compact A4 colour laser-class all-in-one for small businesses. Every model in the series is neat, highly efficient and straightforward, without compromising performance or quality.

The series has everything a business user could require from a colour all-in-one. As well as it's multi-function print, copy and scan capabilities, the CX17NF¹ and CX17WF¹ models come with a faxing function.

Each model only takes up the space of a desktop printer, making it ideal for maximising valuable workspace while still offering professional-standard results. A print resolution of 600x600dpi produces high-quality images, combined with vibrant and realistic colours thanks to Epson's AcuBrite toners. Performance is enhanced with a standard memory of 128MB across all models.

Delivering up to 15 mono pages per minute and 12 colour pages per minute, the series has one of the fastest colour print speeds in its class. All models have USB connections and the CX17NF¹ comes with Ethernet connectivity for multiple users. Connectivity options are expanded to include Ethernet and Wi-Fi on the CX17WF¹.

This series has been developed with the business user in mind and provides low-maintenance, peace-of-mind printing. The toner cartridge is the only supply item requiring replacement, which also helps to keep the total cost of ownership down.

#### DATASHEET



#### **KEY FEATURES**

- Compact size
- Fast colour print speed
- Ethernet connectivity<sup>1-2</sup>
- 128MB memory
- ENERGY STAR-qualified power efficiency



The AcuLaser CX17 Series is Epson's most compact A4 colour laser-class all-in-one for small businesses.



#### PRODUCT SPECIFICATIONS

TECHNOLOGY Print resolution	LED 600x600dpi
PRINT Print speed mono/colour First page out mono/colour Maximum monthly volume	Up to 15ppm/12ppm 12.5 seconds/15 seconds or less Up to 20,000 pages
CONNECTIVITY Printer interface  Network printing protocols Network management protocols  Wireless security protocols	USB 2.0 compliant, AL-CX17NF¹: additional Ethernet (10Base-T/100Base-TX), fax RJ-11 AL-CX17WF¹: additional Ethernet (10Base-T/100Base-TX), wireless IEEE 802.11b/g, fax RJ-11 AL-CX17NF/WF¹: TCP/IP: LPD, WSD, Port9100 AL-CX17NF/WF¹: TCP/IP: TCP/IPv4, TCP/IPv6, DHCP, SNMP v1/v2, BOOTP, RARP, HTTP, SMTP/POP3, WSD (print), AutoIP, Bonjour, LLTD, DNS, SNMP/UDP AL-CX17WF¹: WEP (64/128bits), WPA-PSK (TKIP, AES), WPA-2PSK (AES)
SCAN & COPY Scan speed mono/colour Scan-to functions  Scan area / document size Compatibility Optical resolution Copy resolution Copy speed mono/colour Zoom	Up to 8spm/2.6spm Scan to PC (via USB), Scan to USB Memory, CX17NF/WF¹: scan to E-mail, scan to FTP, scan to SMB Flatbed: up to 215.9 x 297mm, ADF (CX17NF/WF only): up to 215.9 x 355.6mm TWAIN, WIA 1200x1200dpi 600x600dpi Up to 15cpm/12cpm 25%-400%
FAX (AL-CX17NF/WF)¹ Fax Protocol Transmission Speed Fax Receive memory Dialing Functions Fax Speed Dial Fax Functions PC Fax Functions	Up to 33.6Kbps, ECM, super G3 compliant 2MB 6 groups dial 99 numbers Address book, one-touch dial (8 keys), auto redial, auto receive mode Send fax from PC (local and network)
PAPER HANDLING Standard paper input Paper size  Duplex Paper weight Paper output Automatic document feeder	160 sheets A4, B5, A5, LT, EXE, US Folio, LGL, Com-10, Monarch, DL, C5, custom size: 76.2-215.9mm width to 127-355.6mm length, labels, envelopes Manual 60-163g/m² Up to 100 sheets (face-down) AL-CX17NF/WF¹: up to 15 sheets
POWER REQUIREMENTS Power consumption Voltage Current Frequency range	Max: 950W, printing: 350W/h, ready: 65W/h, sleep: 7W, power off: 0W AC 220V-240V ±10% 5A or less 50Hz/60Hz ±3Hz
DIMENSIONS (W x D x H)	CX17: 410 x 389 x 318mm, CX17NF/WF <sup>1</sup> : 410 x 389 x 338mm
WEIGHT (with consumables)	CX17: 14.3kg, CX17NF/WF1: 15kg
GENERAL Sound power Sound pressure Operating temperature Operating humidity Windows support Mac support Drivers	printing: 6.43B, ready: 4.30B Printing: 50dB(A), ready: 23dB(A) Operation: 10-32°C, storage: 0-35°C Operation: 10-35%RH, storage: 15-85%RH Windows XP (32bit/64bit), Vista (32bit/64bit), 7 (32bit/64bit), Server 2008 (32bit/64bit), Server 2008 R2 (64bit) Mac OS X 10.4.11 and later Printer driver (GDI), scanner driver, fax driver (AL-CX17NF/WF¹)
STANDARDS EMC standards Safety standards	EMI: EN55022, IEC61000-3-2, IEC61000-3-3, EMS: IEC61000-4-2, IEC61000-4-3, IEC61000-4-4, IEC61000-4-5, IEC61000-4-6, IEC61000-4-8, IEC61000-4-11 IEC60950-1 / EN60950-1, IEC60825-1 / EN60825-1
OTHER FEATURES Environmental measures Processor Printer control language emulations Memory LCD	ENERGY STAR-qualified 295MHz Host based 125MB 4 lines
WARRANTY Standard	1-vear on site

#### PRODUCT MODEL ORDER CODES

- AcuLaser CX17
- AcuLaser CX17NF<sup>1</sup>
- AcuLaser CX17WF<sup>1</sup>

#### WHAT'S IN THE BOX

- Printer
- Power cable
- Software CD
- Instruction and notice sheets
- Warranty sheet

### **SUPPLIES**

- Black Toner Cartridge High
   (0.000 pages)
  - (2.000 pages<sup>3</sup>) C13S050614
- Yellow Toner Cartridge High (1.400 pages³) C13S050611
- Magenta Toner Cartridge High
- (1.400 pages³) C13S050612
   Cyan Toner Cartridge High
- (1.400 pages<sup>3</sup>) C13S050613
- Black Toner Cartridge Standard
   (700 pages³)
   C13S050672
- Yellow Toner Cartridge Standard (700 pages³) C13S050669
- Magenta Toner Cartridge Standard
   (700 pages³) C13S050670
- Cyan Toner Cartridge Standard (700 pages³) C13S050671
- Initial Toner Cartridge CMYK (700 Pages<sup>3</sup>)

# TONER CARTRIDGE COLLECTION PROGRAM

This free service helps us to collect and recycle used Epson toner cartridges in a safe and environmentally-friendly way. There are three easy ways to dispose of your empty cartridges and take an active role in reducing waste:

- Put them in a toner cartridge collection box which will be picked up once full
- Return them free of charge by post
- Drop them off at an Epson Express Centre Please visit www.epson.com/recycle for more details about the program
- Some or all Wi-Fi/ fax products may not be available in certain countries. Wireless n standard is available in EU countries only.
- NF & WF models
- ISO/IEC19798 and ISO/IEC24712 yield test reports



Optional











1-year on site CX17: 3-year on site ECPGRP35, CX17NF/WF1: 3-year on site ECPGRP40









For more information please contact:

Telephone: 0871 222 6702 (UK)\*
01 436 7742 (Republic of Ireland)
E-mail: enquiries@epson.co.uk
Chat: etalk.epson-europe.com
Fax: 0871 222 6740

Web:

www.epson.co.uk www.epson.ie

