C610 Specifications





The C610 stands out from the rest delivering fast, versatile and affordable inhouse A4 colour and mono printing for the general office. With class-leading media handling that allows you to get more from your investment and environmental benefits that can reduce your organisations print related carbon footprint, this powerful printer is the ultimate solution for every small to medium business. It effortlessly supports workgroups of up to 10 users

Tackle the toughest deadlines

The C610 is built for speed making light work of the toughest deadlines.

- Outstanding print speeds of 34ppm in colour and 36ppm in black and white
- Delivering your first print in as little as 9 seconds colour and 8 seconds mono
- Ultra-reliable digital LED technology with fewer moving parts and a flat paper path

Print on the paper you want

Exceptional media flexibility means that business stationery, banners and marketing collateral are just as easy to print in-house as ordinary office documents.

- Prints on stock of up to 250gsm heavier than any comparable printer
- Handles any size from A6 to A4 through to 1.2 metre A4 banners
- With 2 optional paper trays available, paper capacity can be increased up to 1,460 sheets

Environmental efficiencies

The C610's significantly low power consumption reduces energy bills and your environmental impact.

- Low energy consumption, consuming just 1.2 watts in sleep mode
- Duplex printing (optional on C610n) reduces unnecessary paper usage and therefore costs
- All models are are Energy Star qualified products

Reduce and control your print costs

Taking care to keep costs to a minimum the C610 has an attractive price tag, high-yield toners and long life image drums. What's more, included in-the-box, are three cost and time saving utilities. No other colour printer offers so much for so little.

- Print Control software lets you track printer usage and control costs
- PrintSuperVision software lets you monitor, manage and report on your networked printers
- Colour Access Policy Manager lets you monitor and control colour usage for printed output
- Protected by an impressive 3 year warranty as standard (upon registration)

A4
Range of media handling
Colour, mono
Print
Up to 10 users

Variants available: C610n networked C610dn duplex, networked C610dtn duplex, 2nd tray, networked



C610 - Colour and Mono Printers

PRINTER		Typefaces	
Print speed	A4: 34ppm colour, 36ppm mono	Printer fonts	Scalable: 87 PCL fonts and 136 PostScript fonts; PCL Bitmap fonts. OCR-A/B; USPS ZIP Barcode
Time to first print	9 seconds colour, 8 seconds mono	Barcode	
Warm up time	up to 60 seconds from power on & up to 35 seconds from power save	GENERAL FEATURES	
Processor speed	533MHz		S. 1 12-12 2-12 1 2-12 2-12 1
PRINT QUALITY		Memory	Standard RAM: 256MB; Maximum RAM: 768MB; Optional SDHC Memory Card ⁵ : 16GB
Resolution	ProQ2400 Multi-level technology, 1200 x 600dpi, 600 x 600dpi		Temperature/Humidity: 10°C to 32°C (17°C to 27°C
Enhancements	Auto Colour Balance, Photo Enhance via driver (excludes Mac and PostScript drivers)	Operating conditions	recommendedy
			Storage: -10°C to 43°C, 10% to 90% RH
INTERFACE AND SOFTWARE		Power supply	Single phase 220-240VAC, frequency 50/60Hz +/-2%
Connectivity	Hi-Speed USB & 10/100-TX Ethernet	Power consumption	Typical: 600W; Max: 1300W; Idle: 100W (average); Power Save: <15W; Sleep: 1.2W
Printer languages	PCL 6 (XL3.0) and PCL5c, PostScript 3 (emulation), SIDM (IBM-PPR, EPSON-FX), PDF Direct Print v1.7, XPS	Noise level	Operating: 54dB(A); Standby: 37dB(A); Power save: Background Level
Network & protocols	All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IP: ARP, IPv4/v6, ICMPv4/v6, TCP, UDP, LPR, FTP, TELNET, HTTP(IPP), BOOTP, DHCP, SNMPv1/v3, DNS, DDNS, UPnP, Bonjour, WINS, SSL/TLS, SMTP, POP3, SNTP, WSDPrint, JetDirect protocols. NetBIOSoverTCP, NetWare 3.x, 4.x, 5.x and 6 with full NDS and NDPS support: PServer, RPrinter, NDPS supported via dedicated OKI NDPS Gateway. AppleTalk: ELAP, AARP, DDP, AEP, NBP, ZIP, RTMP, ATP, PAP. NetBEUI:- SMB, NetBIOS. Other:EAP	Dimensions (HxWxD)	C610n: 340 x 435 x 546 mm; C610dn: 340 x 435 x 604 mm; C610dtn: 476 x 435 x 604 mm
		Weight ⁴	C610n: 26kg; C610dn: 29kg; C610dtn: 35kg
		Duty cycle	Maximum: 75,000 pages/month; Average: 5,000 pages per month
		Warranty	3 years extended warranty upon registration within 30 days of purchase
		Product order numbers	C610n: 01269501; C610dn: 01268902; C610dtn: 01269002
OS Compatibility ¹	Windows 2000 / XP Home / XP Professional / XP Professional x64 / Server 2003 / Server 2003 for x64 / Server 2008 / Server 2008 x64 / Vista (32-bit) / Vista (64-bit) / Windows 7 (web download); Mac OS X 10.3.9 - 10.6.1	Accessories (Order Numb	ERS)
		2nd paper tray	44274502 (standard on C610dtn)
		3rd paper tray	44274502
Advanced networking and security	IPv6, 802.1x authentication, SNMPv3, SSL/TLS HTTPS encrpytion, Secure Print³, Secure Erase³, Data encrpytion³, MAC filtering, IP filtering, IPSec	Duplex	01272601
		Cabinet	01219302
		Memory	256MB: 01182907; 512MB: 01182908
Utility Suite ¹	Color Correct, OKI LPR ² , PrintSuperVision.net ² , Swatch Utility, Template Manager ² , Web Driver Installer ² , Print Control Server ² , Print Control Client, Storage Device Manager ²⁸ , Gamma Utility, Profile Assistant ³ , Colour Access Policy Manager ²	SDHC Memory Card ⁵ 16GB: 01272701 CONSUMABLES (ORDER NUMBERS)	
, , ,		Toner cartridges*	
PAPER HANDLING		(8,000 black & 6,000	Cyan: 44315307; Magenta: 44315306; Yellow: 44315305; Black: 44315308
Paper capacity	Tray 1: 300 sheets of 80gsm; Multi-purpose tray: 100 sheets of 80gsm	colour pages) Image drum** (20,000 pages)	Cyan: 44315107; Magenta: 44315106; Yellow: 44315105; Black: 44315108
Paper capacity optional trays	Tray 2: 530 sheets of 80gsm (standard on C610dtn); Tray 3: 530 sheets of 80gsm	Transfer Belt (60,000 pages)	44341902
Maximum paper capacity	1,460 sheets of 80gsm	Fuser Unit	
Paper sizes	Tray 1: A4, A5, B5, A6; Tray 2/3: A4, A5, B5; Multi-purpose tray: A4, A5, B5, A6, 10 Envelopes (Com-9, Com-10, DL, Monarch, C5), Labels (Avery 7162, 7664, 7666), Custom Size (up to 1,200mm length including banner); Duplex: A4, A5, B5, Custom Size: Width 148-215.9mm x Length 210-355.6mm	*Toner: A4 pages yield compliant with ISO/IEC 19798. Printer shipped with 2,000 A4 pages. **Drum: A4 pages average life.	
Paper weight	Tray 1/2/3: 64-220gsm; Multi-purpose tray: 64-250gsm; Duplex: 64-120gsm		
Duplex	Standard: C610dn & C610dtn; Optional: C610n		
Paper output	250 sheets face down, 100 sheets face up, 80gsm		

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI Printing Solutions toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

¹ Check local OKI Printing Solutions website for latest driver releases and OS compatibility; ²Windows only; ³SDHC Memory Card required; ⁴Including all consumables;

⁵ Secure Digital High Capacity (SDHC) Memory Card supports up to 32GB. OKI is not responsible for any compatibility risk using non-OKI genuine SDHC Memory Cards.

Simply Unique - 3 Year Warranty

YEAR WARRANTY

Our devices are manufactured to the highest standards of quality and technology, which has been confirmed by independent tests. We are so convinced of the high quality of our products that we are offering you an extension of the standard warranty period to 3 years – for free! Simply register your product within 30 days of purchase to be eligible for our

unique all inclusive offer. Fully covered by OKI! For further information please visit www.okiprintingsolutions.co.uk/warranty Without registration, the standard pan-European 1 year warranty applies.

OKI SYSTEMS (UK) LTD.

550 Dundee Road, Slough Berkshire, SL1 4LE United Kingdom T +44(0) 1753 819819 F +44(0) 1753 819899

WWW.OKIPRINTINGSOLUTIONS.CO.UK



