



## Microline Dot Matrix Printers

### ML3410 9-Pin Dot Matrix Printer

#### Power, reliability and versatility from a single printer

The ML3410 is a powerful dot matrix printer designed to handle the most data-intensive applications at very high speeds. Its copy capabilities are impressive producing up to eight multi-part copies at any one time.

#### Highlights:

- 136 column dot matrix printer
- Extremely durable 9-pin print head with Oki reliability built-in as standard
- Up to 550 characters per second print speed
- Multi-part paper-handling (original + 7 copies)
- Ideal for purchasing and distribution, and Accounts, Finance and IT departments that require high speed, high volume printouts



# ML3410

		ML3410
<b>General</b>	Number of pins	9
	No. of multi-part forms	8 (one original + 7 copies)
<b>Speed and throughput</b>	High speed draft (12cpi & 10cpi)	550cps
	Utility (12cpi & 10cpi)	417cps
	Near letter quality (12cpi & 10cpi)	104cps
	Fastest print speed (10cpi)	550cps
<b>Font &amp; print features</b>	Carriage width (10cpi)	136 columns
	Max. in compression mode	272 columns
	Character pitch	10/12/15/17.1/20 pitch & proportional
	Graphics resolution	Up to 240 x 216 dpi
	Typeface & Font	NLQ-Courier, NLQ-Gothic, OCR-B, High Speed Draft, Utility + Barcodes
	Typestyle	Emphasised, Enhanced, Double Width, Double Height, Italics, Bold, Superscript, Subscript, Underline, Overscore
<b>Emulations &amp; Interfaces</b>	Printer emulations	Epson FX, IBM ProPrinter XL or Oki Microline/PM (optional)
	Standard interfaces	Centronics Parallel, Serial RS 232C, dual interface
<b>Paper handling</b>	Continuous paper	76–406mm
	Continuous envelopes	239 x 102mm
	First printable line (from top of page)	Cut sheet: 25.4mm , Continuous: 23.3mm
	Standard	Autoload single sheet, Paper parking, Rear push tractors, Metal long-life tear-off bar
	Optional	Single/dual bin sheet feeder, Pull tractor, Bottom power push tractor
<b>Physical</b>	Dimensions (HxWxD)	180 x 570 x 417mm
	Weight	18kg
	Memory (Total RAM)	Standard buffer 28KB (reduced buffer)
	Noise level (ISO 7779)	<58dB(A)
<b>Power</b>	Power requirements	230V AC
	Frequency	50/60Hz
<b>Reliability</b>	Print head life	200 million characters
	Ribbon life	10 million characters
	MTBF	8,000 hours

**Consumables Information:** Only use genuine OKI Printing Solutions Original consumables to ensure the best quality and performance from your hardware. Non OKI Printing Solutions Original products may damage your printer's performance and invalidate your warranty. Specifications subject to change without notice. All trademarks acknowledged.

