







You know what it's like. You need one machine to copy. One machine to print. One machine to scan and so it goes on. Where will you find the space in a small or home office? Most importantly, how much will it cost you to buy all of these essentials? With Brother's new range of compact colour all-in-one printers, you'll get a fast, high quality machine that prints, copies, scans and also faxes without the fast lane price tag.

Super efficient

All the printers in our range will produce professional results time after time, in no time at all, thanks to features like the impressive 16 pages per minute colour and mono print speed and hi-speed fax. Which means you'll get things done faster.

Plus with extra features such as wireless and ethernet connectivity, direct USB printing, secure print and a range of f exible scanning options (to USB, PDF, FTP, network and email), there's certainly no compromise on quality.

Super savings

With printing, copying, scanning and even faxing all in just one handy machine, you'll save space in the office and money too, as you only need one machine instead of three or four. And, as they're network ready too, everyone in the office can share just one printer. To keep costs down further, each printer has a colour restrict feature, which means that only designated users can print in colour. Each machine also comes with a free 1000-sheet colour toner in the box, so you'll save money from the word go.

^{*} Fax not available on the DCP-9010CN

Make light work of office work with a range of handy features

The perfect solutions for small businesses. Our handy machines can take care of all your office needs with professional-quality results, low running costs and lots of other time-saving features.

Save time

with fast 16ppm colour and mono print speeds and direct printing from USB

Saves money

as one machine does it all. And as they're all network ready, everyone can share just one machine

Less refilling

with large 250 sheet paper tray and 35 sheet automatic feeder to handle multi-page documents

Go green

with a range of printers that meet Energy Star and Blue Angel environmental standards







Here are a few pointers to help you choose

You know what you need from your printer and what will be useful to you. While you can expect hi-spec features we're not here to blind you with science. So to help put you in the picture take a look at the handy table below, which will make it easy for you to choose the right one.

| Compact Colour All-in-One Printers | | | |
|---------------------------------------|------------|------------|------------|
| | DCP-9010CN | MFC-9120CN | MFC-9320CW |
| 16ppm colour and mono printing | • | • | • |
| Colour copy, scan | • | • | • |
| Hi-speed faxing | | • — | • |
| Network ready | • | • | • |
| Wireless network ready | | | • |
| USB host | | | • |
| 250 sheet paper tray | • | • | • |
| 35 sheet ADF | • | • | • |
| PCL & Postscript Emulation | • | • | • |
| Scan to FTP | | • | • |
| Scan to PDF | • | • | • |
| Scan to Network Location | | • | • |

Space-saving technology

The technology inside our 9000 series all-in-ones allows you to enjoy high-resolution laser-quality printing from a more compact, space-saving printer. Which makes them the ideal choice for small businesses.





Green and clean









Our models use non-hazardous materials and are designed to be recycling friendly to meet the renowned Energy Star and Blue Angel environmental standards. As a company our environmental and ethical standards are second to none. All Brother consumables can be recycled for free at our award-winning plant in North Wales. We were even awarded 100 out of 100 by the Ethical Company Organisation for the third year in a row – the only printer manufacturer to achieve this.

And our commitment to the environment now includes sponsoring 4 square kilometres of Amazon rainforest in partnership with Cool Earth, which protects endangered areas to help combat global warming.

Little extras to make you feel good

No one wants to feel 'stranded' so in the unlikely event of something going wrong with your printer we're happy to take control. You're covered by a 12 month warranty plus 24 hour online support and a dedicated helpline during office hours.

Cleverly designed consumables



Get the most from your Brother printers by using specifically designed consumables. When the toner runs out simply replace it with the one specially designed for use in your model – it's long-lasting, great value and knows exactly what your model needs to run at its very best.

Technical Specifications MFC-9120CN & MFC-9320CW

| elenhology Electrophotographic LED printer (Single Pass) Inter Speed M Inter Speed W | rinter | | Printer Driver Softwa | re |
|--|---------------|---|-------------------------|--|
| hite Speed A | Ele | lectrophotographic LED printer (Single Pass) | Windows® | Windows Vista®, Windows® XP Professional (32 & 6 |
| leseolution | | | | bit editions) / XP Home Edition, Windows Server+ 20 |
| Varm by Time 27 seconds (from sleep mode) 16 seconds (Golout), 15 seconds (Mone) 16 seconds (Golout), 15 seconds (Mone) PCL86-6 Scalable Fonts, 12 Bitmap Fonts, 13 Barcodes Postscripti39 - Compatible fonts: 66 H-Speed USB 2.0 Linux** Linux | | | | (32 & 64 bit editions), Windows Server [®] 2008®, |
| inst Print forts 60 seconds (Coloun), 15 seconds (Mono) PCL96, BR-Script 3 Printer Driver Functions Rup Printing Save paper reduc Ad page Poster Printing Ad page Poster Printing Ad page Poster Printing Save paper reduc Ad page Poster Printing Ad page Poster Printing Ad page Poster Printing Add page Poster Printing Add predefined te Adocuments and Booklet Printing Add predefined te Adocuments and Booklet Printing Add predefined te Add pager Print Colour Save pager reduc Ad page Poster Printing Save paper reduc Ad page Poster Printing Booklet Printing Add page Poster Printing Save paper reduc Add pager Print Colour Save page Poster Printing Booklet Printing Add page Poster Printing Save printing Save paper reduc Add pager Print Colour Save page Poster Printing Booklet Printing Add page Poster Printing Save paper reduc Add pager Printing Save pager reduc Add predefined te Add predefined te Poster Printing Booklet Printing Add pager Pri | | | | Windows® 2000 Professional |
| interface Interf | | | Masintash® | |
| lesident Ports PCL®6 - 66 Scalable Fonts, 12 Bitmap Fonts, 13 Barcodes Postscript®3 - Compatible fonts: 66 Hi-Speed USB 2.0 Lebwork 10/100 Base TX 2 line, 16 characters green back-lit LCD, 2 LEDs (error, data) 2 less than 24 seconds (Colour), 19 seconds (Mono) 60 x 600dpi instruction 60 x 600dpi instruction 7 leads and enlarge documents from 25% to 400% less than 24 seconds (Colour), 19 seconds (Mono) 1 less than 24 seconds (Colour, 19 seconds (Mono) 1 less than 24 seconds (Colour, 19 seconds (Mono) 1 less than 24 seconds (Colour) 1 less than 24 seconds (Colour less than 24 seconds (Colour less than 24 seconds (Colour less than 24 seconds (Mono) 1 less than 24 seconds (Colour less than 24 seconds (Mono) 1 less than 24 seconds (Colour less than 24 seconds (Mono) 1 less than 24 seconds (Mono) 1 less than 24 seconds (Colour less than 24 seconds (Mono) 1 less than 24 seconds (Colour less than 24 seconds (Mono) 1 less than 24 seconds (| | | | |
| tetraface Hi-Speed USB 2.0 compatible fonts: 66 Hi-Speed USB 2.0 line, 16 characters green back-lit LCD, 2 Lien, 2 line, 16 characters green back-lit LCD, 2 LEDs (error, data) volumer Copier voly Speed Al Up to 16cpm Colour & Mono 600 x 6000pi rist Copy Out Time Less than 24 seconds (Colour), 19 seconds (Mono) stack and sort multiple copied documents rist Copy Out Time Leduction / Reduce and enlarge documents from 25% to 400% using 1% increments volumer Fax footem Speed 3, 3,600bps (G3) Hatemaf Ex** Fax documents anywhere in the world over the Internet without the use of a telephone line aw/rel Switch here-Touch Dial Up to 200 speed locations and up to 20 groups Automatically redials number if line is busy listinctive Ring peed & Group Dial Up to 200 speed locations and up to 20 groups Automatically redials number if line is busy stacted and a manufaction of fax and telephone reception 8 (4 x x) locations Automatically redials number if line is busy staction (UK and Demmark only) with the certificated and for retrieve faxes to or from another location for retrieve faxes to or from another location for retrieve faxes to or from another location for Examer leterical remains in the fax of the | | | Linux*** | CUPS printing system (x86, x64 environment), LPD/ |
| Interface Hi-Speed USB 2.0 (Inc. 16 characters green back-lit LCD, 2 LEDs (error, data) (Inc. 16 characters green back-lit LCD, 2 LEDs (error, data) (Inc. 16 characters green back-lit LCD, 2 LEDs (error, data) (Inc. 16 characters green back-lit LCD, 2 LEDs (error, data) (Inc. 16 characters green back-lit LCD, 2 LEDs (error, data) (Inc. 16 characters green back-lit LCD, 2 LEDs (error, data) (Inc. 16 characters green back-lit LCD, 2 LEDs (error, data) (Inc. 16 characters green back-lit LCD, 2 LEDs (error, data) (Inc. 16 characters green back-lit LCD, 2 LEDs (error, data) (Inc. 16 characters green back-lit LCD, 2 LEDs (error, data) (Inc. 16 characters green back-lit LCD, 2 LEDs (error, data) (Inc. 16 characters green back-lit LCD, 2 LEDs (error, data) (Inc. 16 characters green back-lit LCD, 2 LEDs (error, data) (Inc. 16 characters green back-lit LCD, 2 LEDs (error, data) (Inc. 16 characters green back-lit LCD, 2 LEDs (error, data) (Inc. 16 characters green back-lit LCD, 2 LEDs (error, data) (Inc. 16 characters green back-lit LCD, 2 LEDs (error, data) (Inc. 16 characters green back-lit LCD, 2 LEDs (error, data) (Inc. 16 characters green back-lit LCD, 2 LEDs (error, data) (Inc. 16 characters green back-lit LCD, 2 LEDs (Inc. 16 characters gages for bioge pages for a | | | | LPRng printing system (x86, x64 environment) |
| letwork 10/1/00 Base-TX 2 line, 16 characters green back-lit LCD, 2 LEDs (error, data) 2 line, 16 characters green back-lit LCD, 2 LEDs (error, data) 2 line, 16 characters green back-lit LCD, 2 LEDs (error, data) 30 color Copier 30 y Seped 4A 30 Up to 16 cpm Colour & Mono 600 x 6000 x 6000 x 5000 x 6000 x 6000 x 5000 x 5000 x 6000 x 5000 x 6000 x 5000 x 6000 x 5000 x 6000 x 5000 x 5000 x 6000 x 5000 x 5000 x 6000 x 5000 x 500 | Ba | 3arcodes Postscript®3 - Compatible fonts: 66 | Printer Driver Function | ons |
| letwork 10/1/00 Base-TX 2 line, 16 characters green back-lit LCD, 2 LEDs (error, data) 2 line, 16 characters green back-lit LCD, 2 LEDs (error, data) 2 line, 16 characters green back-lit LCD, 2 LEDs (error, data) 2 line, 16 characters green back-lit LCD, 2 LEDs (error, data) 2 line, 16 characters green back-lit LCD, 2 LEDs (error, data) 2 line, 16 characters green back-lit LCD, 2 line, 16 characters green | Hi | li-Speed USB 2.0 | N-up Printing | Save paper reducing 2, 4, 9, 16 or 25 A4 pages to 1 |
| Poster Printing Poster Pri | | | | |
| 2 LEDs (error, data) avisiour Copier apges for a bigger avisiour Copier avisiour Copier avisiour Copier besolution avisiour Copier besolution avisiour Copier besolution avisiour Copier avisiour Copier avisiour Copier avisiour Copier besolution avisiour Copier a | | | Poster Printing | Enlarge 1 A4 page into a poster using 4, 9, 16 or 25 |
| add predefined the documents as a was solution (600 x 600dp) in the session of th | | | r oster r minnig | |
| opy Speed A | | LEDS (error, data) | | |
| assistion 600 x 600dpi trist to 500 your Ent t | | | Watermark Printing | Add predefined text or user-defined messages to yo |
| irist Copy Out Time Lass than 24 seconds (Colour), 19 seconds (Mono) tack & Sort atak & Sort atak & Sort seduction / Reduce and enlarge documents from 25% to 400% using 19% increments offour Fax Jagoment Ratio offour Ratio Management Diriver Deployment A quick and easy Jagoment Print Server Jagoment Ratio Management Diriver Deployment Management Diriver Beployment Manageme | | | | documents as a watermark |
| tack & Sort eduction / Reduce and enlarge documents from 25% to 400% using 1% increments obtainer Fax documents anywhere in the world over the Internet without the use of a telephone line feather without the use of a telephone line ax/Tel Switch herough (20 cations and up to 20 groups utbmatic Redial plot 20 cations and up to 20 groups utbmatic Redial ped & Group Dial ubmatic Redial sitentifies (UK and Denmark only) to 200 speed locations and up to 20 groups utbmatic Redial sitentifies (UK and Denmark only) forward or retrieve laxes to or from another location etrieval ansmit / Receive memory MMR) receive fetiled documents where sending fax shares ECM Personal (Receiving is for Windows® only) regression (Enhanced) 19,200 x 19,200dpi (from scanner glass) 1,200 x 600dpi (from ADF) gesolution (Enhanced) 19,200 x 19,200dpi (from scanner glass) 1,200 x 600dpi (from ADF) gesolution (Enhanced) 19,200 x 19,200dpi (from scanner glass) 1,200 x 600dpi (from ADF) gesolution (Enhanced) 19,200 x 19,200dpi (from scanner glass) 1,200 x 600dpi (from ADF) gesolution (Enhanced) 19,200 x 19,200dpi (from scanner glass) 1,200 x 600dpi (from ADF) gesolution (Enhanced) 19,200 x 19,200dpi (from scanner glass) 1,200 x 6,00dpi (from ADF) gesolution (Enhanced) 19,200 x 19,200dpi (from scanner glass) 1,200 x 6,00dpi (from Scanner glass) 1,200 x 6,00d | 60 | 00 x 600dpi | Booklet Printing | Print easy-to-read, professional documents in A5 box |
| tack & Sort eduction / Reduce and enlarge documents from 25% to 400% using 1% increments obtainer Fax documents anywhere in the world over the Internet without the use of a telephone line feather without the use of a telephone line ax/Tel Switch herough (20 cations and up to 20 groups utbmatic Redial plot 20 cations and up to 20 groups utbmatic Redial ped & Group Dial ubmatic Redial sitentifies (UK and Denmark only) to 200 speed locations and up to 20 groups utbmatic Redial sitentifies (UK and Denmark only) forward or retrieve laxes to or from another location etrieval ansmit / Receive memory MMR) receive fetiled documents where sending fax shares ECM Personal (Receiving is for Windows® only) regression (Enhanced) 19,200 x 19,200dpi (from scanner glass) 1,200 x 600dpi (from ADF) gesolution (Enhanced) 19,200 x 19,200dpi (from scanner glass) 1,200 x 600dpi (from ADF) gesolution (Enhanced) 19,200 x 19,200dpi (from scanner glass) 1,200 x 600dpi (from ADF) gesolution (Enhanced) 19,200 x 19,200dpi (from scanner glass) 1,200 x 600dpi (from ADF) gesolution (Enhanced) 19,200 x 19,200dpi (from scanner glass) 1,200 x 600dpi (from ADF) gesolution (Enhanced) 19,200 x 19,200dpi (from scanner glass) 1,200 x 6,00dpi (from ADF) gesolution (Enhanced) 19,200 x 19,200dpi (from scanner glass) 1,200 x 6,00dpi (from Scanner glass) 1,200 x 6,00d | rt Time Le | ess than 24 seconds (Colour), 19 seconds (Mono) | | format using manual duplex |
| largement Ratio using 1% increments of the control of the control of the colour set alour fax odden Speed and enlarge documents from 25% to 400% alour fax odden Speed Story Discourage colours of the colour fax and telephone line aw/fel switch the use of a telephone line Automatic recognition of fax and telephone reception 8 (4 x 2) locations 4 (4 x 2) locations and up to 20 groups ultimatic Redial butimatic Redial butimatic Redial butimatic Redial stitution of the colour set and provided for the colour set in the colour for the colour set in the set in the colour set in the set in the colour set in the colour set in the colour set in the set in the colour set in the colour set in the colour set in the set in the colour set in the set in the colour set in the | | | Secure Print | Protect your print jobs with a PIN number |
| accurate colours a colours and proper termet fax*** solour Fax documents anywhere in the world over the Internet without the use of a telephone line without the use of a telephone line at forup Dial ubmarts Redial procession of fax and telephone reception of (4 x 2) locations and up to 20 groups ubmarts Redial procession and up to 20 groups detection. Altomatic recognition of fax and telephone reception beed & forup Dial ubmarts Redial procession and up to 20 groups. Automatically redials number if line is busy istinctive Ring. Ability to detect different ring styles (UK and Denmark only) as forward and etrieval aromatic receive faxes to or from another location etrieval aromatic receive faxes from your PC using a phone line (Receiving is for Windows® only) ToP-Tax Send & receive faxes from your PC using a phone line (Receiving is for Windows® only) Resending of failed documents where sending fax shares ECM Send & receive faxes from your PC using a phone line (Receiving is for Windows® only) Resolution (Enhanced) 19,200 x 19,200dpi rety Scale 256 shades of grey are available for copying, faxing and scanning 36 bit internal, 24 bit external 256 san to E-mail / OCR / Image / File** Scan to E-mail Sever** Scan to F-mail Sever* Standard Paper Tray - Plain, Recycled Paper, Thin Paper, Manual Feed Slot - 90 to 163g/m2 (16 to 28lb) ADF - 64 - 90g/m2 (17 - 24lb) Manual Feed Slot - 60 to 163g/m2 (16 to 43lb) Standard Paper Tray - 44, Letter, ISOB5, A5, ISOB6, A6, Executive, Legal, Folio ADF - 49 - 49g/m2 (17 - 24lb) Manual Feed Slot - Width 76.2mm to 220mm, Length 116mm to 406.4mm (Width 3.0" to 8.66", Length 4.57" to 16") Manual Feed Slot - Width 76.2mm to 220mm, Length 116mm to 406.4mm (Width 3.0" to 8.66", Length 4.57" to 16") | | | | Edit the colour settings in the printer driver to get |
| colour Pax oblower Speed 33,600bps (G3) ternet Fax*** Fax documents anywhere in the world over the Internet without the use of a telephone line Automatic recognition of fax and telephone reception 8, (4 x 2) locations and up to 20 groups utomatic Redial Jutomatic Redial stinctive Ring Ability to detect different ring styles (UK and Denmark only) at Strinctive Ring of telephone line etheval ansmit/ Receive III Up to 500 pages (ITU-T Test Chart, Standard Resolution, Horris Seand & receive faxes form your PC using a phone line (Receiving is for Windows® only) flow x 2,400dpi (from scanner glass) 1,200 x 600dpi (from ADF) scan to F-mail Server** Scan to E-mail / COCR / Image / File** Scan to E-mail / COCR / Image / File** Scan to E-mail / COCR / Image / File** Scan to FTP / Network teldia Specifications etidia Weights Standard Paper Tray - A4, Letter, ISOB5, A5, ISOB6, A6, Executive, Legal, Folio ADF - 49 - 490/mc (17 - 24lb) Manual Feed Slot - 916 in 163g/mc (16 to 43lb) Standard Paper Tray - 44, Letter, ISOB5, A5, ISOB6, A6, Executive, Legal, Folio ADF - 40 scanner (Width 3.0" to 8.66", Length 4.57" to 16") Colour Portiting ca andemics addition the trevork Web Based Web based Web browser print Mean Bandwill Management Driver Deployment Wick and easy. Web Based Web browser print Bandwill Management Driver Deployment Wixard on a networked Wixard o | | | Colour Collino 1001 | |
| terner Fax*** Fax documents anywhere in the world over the Internet without the use of a telephone line Automatic recognition of fax and telephone reception 8 (4 x 2) locations Up to 200 speed locations and up to 20 groups utomatic Redial Automatic recognition of fax and telephone reception 8 (4 x 2) locations Up to 200 speed locations and up to 20 groups tetection Guite Kornup Dial Up to 200 speed locations and up to 20 groups tetection Guite Kornup Dial Up to 200 speed locations and up to 20 groups tetection Guite Kornup Dial Up to 200 speed locations and up to 20 groups tetection Guite Kornup Dial Up to 200 speed locations and up to 20 groups tetection Guite Kornup Dial Up to 200 speed locations and up to 20 groups tetection Guite Kornup Dial Up to 500 pages (ITU-T Test Chart, Standard Resolution, BRAdmin Light For LaN / WAN m Froftessional** Frot Lan / Wan m Froft | ratio us | sing 1% increments | | |
| ternet Fax*** Fax documents anywhere in the world over the Internet without the use of a telephone line without the use of a telephone line without the use of a telephone reception at Vertical Print the time & didocuments and the use of a telephone reception at Vertical Print the time & didocuments and the vision of the vi | | | | Colour printing can be restricted for individual users |
| without the use of a telephone line Automatic recognition of fax and telephone reception 8 (4 x 2) locations Up to 200 speed locations and up to 20 groups Automatically redials number if line is busy Ability to detect different ring styles (UK and Denmark only) ax Forward and etrieval Up to 500 pages (ITU-T Test Chart, Standard Resolution, MR) Resending of failed documents where sending fax shares ECM C-Fax Send & receive faxes from your PC using a phone line (Receiving is for Windows® only) olour Scanner seolution (Enhanced) 1,200 x 2,400dpi (from scanner glass) 1,200 x 600dpi (from ADF) scan to E-mail / OCR / Image / File* Scan to E-mail / OCR / Image / File* Scan to E-mail / OCR / Image / File* Scan to E-mail Ped Stot - 80 to 163g/m2 (16 to 43lb) Standard Paper Tray - Plain, Recycled Paper, Thin Paper, Thick Paper, Recycled, Paper, Bond, Label, Envelope, Thin Envelope Itelia Sizes Standard Paper Tray - Ad, Letter, ISOBS, A5, ISOB6, A6, Executive, Legal, Folio ADF - Width 147.3 to 215.9mm, Length 147.3 to 236.0mm (Width 3.0" to 8.66", Length 4.57" to 16") Web Based Management Mizard Web Drowser print Web Based Management Wizard Management Wizard Drow Polyoment Wizard Draw Print server manag 10.3.9 or greater BRAdmin Light Protocols TCP/IP (IPv4 & IP- Protocols TCP/IP (19v4 & IP- Protocols TCP/I | | | | an administrator to control costs |
| without the use of a telephone line Automatic recognition of fax and telephone reception Be (3 (4 x 2) locations Up to 200 speed locations and up to 20 groups Automatically redials number if line is busy Automatically redials number line in subsy Automatically redials number if line is busy Automatically redials number li line is busy | ** Fa | ax documents anywhere in the world over the Internet | Header and Footer | Print the time & date and/or the user ID on the |
| Nutrel Switch Automatic recognition of fax and telephone reception 8 (4 x 2) locations 8 (4 x 2) locations 8 (4 x 2) locations 1 Up to 200 speed locations and up to 20 groups Automatically redials number if line is busy stinctive Ring stenction (UK and Denmark only) Xiz Forward and betrieval Amsmit Receive Bradmin Forward or retrieve faxes to or from another location betrieval Amsmit Receive Bradmin For Lan / Wan m Ammit Receive Bradmin For Lan / Wan m Broward or retrieve faxes from your PC using a phone line (Receiving is for Windows® only) 1,200 x 2,400dpi (from scanner glass) 1,200 x 600dpi (from ADF) Scale Schades of grey are available for copying, faxing and scanning 1,200 x 2,400dpi (from scanner glass) 1,200 x 600dpi (from ADF) Scan to E-mail / Server** Scan to E-mail / Server * Scan to E-mail / Server * Scan to E-mail / Server * Scan to F-mail / Server * | | | | documents |
| me-Touch Dial 8 (4 x 2) locations cheed & Group Dial Up to 200 speed locations and up to 20 groups attended and the seed and speed locations and up to 20 groups attended and the state of | | | Notwork | documento |
| pied & Group Dial Up to 200 speed locations and up to 20 groups Albility to detect different ring styles (UK and Denmark only) at forward and strieval ansmit / Receive ansmit / Receive memory MMR) Forward or retrieve faxes to or from another location attrieval ansmit / Receive memory MMR) Up to 500 pages (ITU-T Test Chart, Standard Resolution, emory MMR) Forward or retrieve faxes from your PC using a phone line (Receiving is for Windows® only) Frotocols TCP/IP (IPv4 & IPv Supported Resolution (Receiving is for Windows® only) Frotocols TCP/IP (IPv4 & IPv Supported Resolution (Receiving is for Windows® only) App Supported Scan to E-mail Server** S | | | | Wah browner print conver management |
| Litomatic Redial Automatically redials number if line is busy sistinctive Ring Ability to detect different ring styles (UK and Denmark only) Ability ability of greater and the ring styles of great and styles (UK and Denmark only) Ability ability ability of great and Severy. TELN Branch on a networked Wilder Ability Print server mang 10.3.9 or greater | | | | Web browser print server management |
| istinctive Ring | | | | |
| etraction (UK and Denmark only) ax Forward and Forward or retrieve faxes to or from another location etrieval Forward or retrieve faxes to or from another location etrieval Forward or retrieve faxes to or from another location etrieval Forward or retrieve faxes to or from another location fetrieval Forward or retrieve faxes to or from another location fetrieval Forward or retrieve faxes from your PC using a phone line (Receiving is for Windows® only) Frotocols Forward Forwa | | | | A quick and easy way to deploy Brother printer drive |
| A Forward and etrieval and etrieval and etrieval exact to or from another location etrieval ansmit / Receive (lemory MMR) Up to 500 pages (ITU-T Test Chart, Standard Resolution, MR) Resending of failed documents where sending fax shares ECM Resending of failed documents where sending fax shares ECM Send & receive faxes from your PC using a phone line (Receiving is for Windows® only) alour Scanner 1,200 x 2,400dpi (from scanner glass) 1,200 x 600dpi (from ADF) sesolution (Enhanced) 19,200 x 2,400dpi (from scanner glass) 1,200 x 600dpi (from ADF) sesolution (Enhanced) 19,200 x 19,200dpi rey Scale 256 shades of grey are available for copying, faxing and scanning olour Depth 48 bit internal, 24 bit external can Functions Scan to E-mail Server: Scan to E-mail Geryer: scan to E-mail Server: Scan to E-mail Server: Scan to E-mail Server: Scan to E-mail Server: Manual Feed Slot - 1 Plain Paper, Thin Paper, Thin Paper, Recycled, Paper, Recycled, Paper, Recycled, Paper, Recycled, Paper, Recycled Paper, Thin Envelope than and Ered Slot - 60 to 163g/m2 (16 to 28lb) ADF - 64 - 90g/m2 (17 - 24lb) Manual Feed Slot - 50 to 163g/m2 (16 to 43lb) Standard Paper Tray - A4, Letter, ISOB5, A5, ISOB6, A6, Executive, Legal, Folio ADF - Witht 147.3 to 215.9mm, Length 147.3 to 356.0mm (Width 5.8" to 8.5", Length 5.8" to 14.0") Manual Feed Slot - Width 76.2mm to 220mm, Length 116mm to 406.4mm (Width 3.0" to 8.66", Length 4.57" to 16") With Carton 480W copying, faxing and scanning an | ing Ab | bility to detect different ring styles | Wizard | on a networked Windows® PC |
| 10.3.9 or greater | | | BRAdmin Light | Print server management for Windows® and Mac OS |
| strieval ansmit / Receive more of the control of th | | | | |
| ansmit / Receive Up to 500 pages (ITU-T Test Chart, Standard Resolution, Immory MMR) Professional*** Professional** Professional** Professional*** Professional*** Professional*** Professional** | unu 10 | orward or retrieve taxes to or from another location | DDAdmin. | |
| Improve the continuation Improve the continu | | 1 | | FOI LAIN / WAIN III aliagement |
| ror Correction Resending of failed documents where sending fax lobel (ECM) shares ECM shares ECM (Receiving is for Windows® only) 1,200 x 2,400dpi (from scanner glass) 1,200 x 600dpi (from ADF) (from ADF) (from ADF) (grow 19,200 x 19,200dpi (from scanner glass) 1,200 x 600dpi (from ADF) (grow 19,200 x 19,200dpi (from scanner glass) 1,200 x 600dpi (from ADF) (grow 19,200 x 19,200dpi (from scanner glass) 1,200 x 600dpi (fro | | | | |
| Protocols NetBIOS name reserved Protocols Prot | | | | |
| C-Fax Send & receive faxes from your PC using a phone line (Receiving is for Windows® only) 1,200 x 2,400dpi (from scanner glass) 1,200 x 600dpi (from ADF) esolution (Entanced) 19,200 x 19,200dpi rey Scale 256 shades of grey are available for copying, faxing and scanning olour Depth 48 bit internal, 24 bit external can Functions Scan to E-mail / CoR/ Image / File** Scan to E-mail / Score / Scan to FTP / Network ledia Specifications ledia Types Manual Feed Slot - Plain Paper, Thin Paper, Recycled, Paper, Bond, Label, Envelope, Thin Envelope Standard Paper Tray - 60 to 105g/m2 (16 to 28lb) ADF - 64 - 90g/m2 (17 - 24lb) Manual Feed Slot - 60 to 163g/m2 (16 to 43lb) ADF - 80 + 90g/m2 (17 - 24lb) Manual Feed Slot - 80 to 163g/m2 (16 to 43lb) ADF - 80 + 100 + 1 | ion Re | Resending of failed documents where sending fax | IPv4 Supported | ARP, RARP, BOOTP, DHCP, APIPA (Auto IP), WINS/ |
| (Receiving is for Windows® only) olour Scanner olour Scanner 1,200 x 2,400dpi (from scanner glass) 1,200 x 600dpi (from ADF) esolution (Enhanced) 19,200 x 2,400dpi (from scanner glass) 1,200 x 600dpi (from ADF) rery Scale 256 shades of grey are available for copying, faxing and scanning olour Depth 48 bit internal, 24 bit external can Functions Scan to E-mail / OCR / Image / File** Scan to E-mail / OCR / Image / File** Scan to E-mail Server** Scan to E-mail / OCR / Image / File** Scan to FTP / Network tedia Specifications tedia Types Standard Paper Tray - Plain, Recycled Paper, Thin Paper, Thick Paper, Recycled, Paper, Bond, Label, Envelope, Thin Envelope Standard Paper Tray - 60 to 105g/m2 (16 to 28lb) ADF - 64 - 90g/m2 (17 - 24lb) Manual Feed Slot - 60 to 163g/m2 (16 to 43lb) Standard Paper Tray - A4, Letter, ISOB5, A5, ISOB6, A6, Executive, Legal, Folio ADF - Witht 147.3 to 215.9mm, Length 147.3 to 356.0mm (Width 5.8" to 8.5", Length 5.8" to 14.0") Manual Feed Slot - Width 76.2mm to 220mm, Length 118mm to 406.4mm (Width 3.0" to 8.66", Length 4.57" to 16") With Carton Others Power Consumption 480W copying, Iss power Consumption 480W copying, Iss power Consumption A60W copying, Iss power Consumption A60W copying, Iss power Consumption Others Power Consumption A60W copying, Iss power Consumption Others Power Consumption A60W copying, Iss power Consumption A60W copying, Iss power Consumption Others Power Consumption A60W copying, Iss power Consumption A60W copying, Iss power Consumption Others Power Consumption A60W copying, Iss power Consumption A60W copying, Iss power Consumption A60W copying, Iss power Consumption Others Power Consumption A60W copying, Iss A60W copying, | sh | hares ECM | Protocols | NetBIOS name resolution, DNS Resolver, mDNS, LLI |
| (Receiving is for Windows® only) In PS, FTP Client I 1,200 x 2,400dpi (from scanner glass) 1,200 x 600dpi (from ADF) Iterosolution (Enhanced) 19,200 x 19,200dpi Iterosolution 10,200 x 19,200dpi Iterosolution 10,200 x 19,200dpi Iterosolution 10,200 x 19,200 x 19,200dpi Iterosolution 10,200 x 19,200 x 19, | Se | Send & receive faxes from your PC using a phone line | | responder, LPR/LPD, Custom Raw Port/Port9100, IF |
| icesolution (Enhanced) 19,200 x 2,400dpi (from scanner glass) 1,200 x 600dpi (from ADF) | | | | IPPS, FTP Client and Server, TELNET Server, HTTP/ |
| Lesolution 1,200 x 2,400dpi (from scanner glass) 1,200 x 600dpi (from ADF) (from ADF) | | teceiving is for willdows@ only) | | |
| (from ADF) lesolution (Enhanced) 19,200 x 19,200dpi rey Scale 265 shades of grey are available for copying, faxing and scanning 256 shades of grey are available for copying, faxing and scanning 48 bit internal, 24 bit external 52can to E-mail / OCR / Image / File** Scan to E-mail / OCR / Image / File** Scan to E-mail Sever*** Scan to FTP / Network Media Specifications Media Types Standard Paper Tray - Plain, Recycled Paper, Thin Paper, Manual Feed Slot - Plain Paper, Thin Paper, Thick Paper, Recycled, Paper, Bond, Label, Envelope, Thin Envelope 54 Standard Paper Tray - 60 to 105g/m2 (16 to 28lb) ADF - 64 - 90g/m2 (17 - 24lb) Manual Feed Slot - 60 to 163g/m2 (16 to 43lb) Manual Feed Slot - 60 to 163g/m2 (16 to 43lb) Manual Feed Slot - Voluth 147.3 to 215.9mm, Length 147.3 to 356.0mm (Width 147.3 to 215.9mm, Length 116mm to 406.4mm (Width 3.0" to 8.66", Length 4.57" to 16") Manual Feed Slot - Width 76.2mm to 220mm, Length 116mm to 406.4mm (Width 3.0" to 8.66", Length 4.57" to 16") NoDe Supplies Inbox Toners 1,000 pages Cn. More Tolour 1,400 pages* Cn. More Tolou | | | | HTTPS server, SSL/TLS, TFTP client and server, SM |
| Lesolution (Enhanced) 19,200 x 19,200dpi rirey Scale 256 shades of grey are available for copying, faxing and scanning 256 shades of grey are available for copying, faxing and scanning 256 shades of grey are available for copying, faxing and scanning 256 shades of grey are available for copying, faxing and scanning 256 shades of grey are available for copying, faxing and scanning 256 shades of grey are available for copying, faxing and scanning 256 shades of grey are available for copying, faxing and scanning 256 shades of grey are available for copying, faxing and scanning 256 shades of grey are available for copying, faxing and scanning 256 shades of grey are available for copying, faxing and scanning 256 shades of grey are available for copying, faxing and scanning 256 shades of grey are available for copying, faxing and scanning 256 shades of grey are available for copying, faxing and scanning 256 shades of grey are available for copying, faxing and scanning 256 shades of grey are available for copying, faxing and scanning 256 shades of grey are available for copying, faxing and scanning 256 shades of grey are available for copying, faxing and scanning 256 shades of grey are available for copying, faxing and scanning 256 shades of grey are available for copying, faxing and scanning 256 shades of grey are available for copying, faxing and scanning 256 shades of grey are available for copying, fexing and Server, TELNI T.S., TFTP client a before SMTP, SM LLTD responder, VS supplies Supplies Supplies Supplies Supplies Supplies Supplies Supplies Supplies Inbox Toner Black 2,200 pages* C, N noner Black 2,200 pages* C, N n | | | | Client, APOP, POP before SMTP, SMTP-AUTH, SNM |
| rery Scale 256 shades of grey are available for copying, faxing and scanning olour Depth 48 bit internal, 24 bit external can Functions Scan to E-mail / OCR / Image / File** Scan to E-mail / OCR / Image / File** Scan to E-mail / OCR / Image / File** Scan to E-mail Server** Scan to FTP / Network Iedia Specifications Iedia Types Standard Paper Tray - Plain, Recycled Paper, Thin Paper, Thick Paper, Recycled, Paper, Bond, Label, Envelope, Thin Envelope Standard Paper Tray - 60 to 105g/m2 (16 to 28lb) ADF - 64 - 90g/m2 (17 - 24lb) Manual Feed Slot - 60 to 163g/m2 (16 to 43lb) Standard Paper Tray - 44, Letter, ISOB5, A5, ISOB6, A6, Executive, Legal, Folio ADF - Width 147.3 to 215.9mm, Length 147.3 to 356.0mm (Width 3.0" to 8.66", Length 4.57" to 16") Width 3.0" to 8.66", Length 4.57" to 16") Power Consumption 48W Copying, faxing and scanning and Scannin | | | | v2c/v3, ICMP, LLTD responder, WebServicesPrint, C |
| scanning folour Depth 48 bit internal, 24 bit external can Functions Scan to E-mail / OCR / Image / File* Scan to E-mail Server** Scan to E-mail / OCR / Image / File* Scan to E-mail Server** Supplies Inbox Toners 1,000 pages* C, N Toner Slour 1,400 pages* C, N Toner Slo | nhanced) 19,3 | J,200 x 19,200dpi | | Client, SNTP |
| scanning folour Depth 48 bit internal, 24 bit external can Functions Scan to E-mail / OCR / Image / File* Scan to E-mail Server** Scan to E-mail / OCR / Image / File* Scan to E-mail Server** Supplies Inbox Toners 1,000 pages* C, N Toner Slour 1,400 pages* C, N Toner Slo | 25 | 56 shades of grey are available for copying, faxing and | IPv6 Supported | NDP, RA, DNS resolver, mDNS, LLMNR responder, L |
| colour Depth 48 bit infernal, 24 bit external can Functions Scan to E-mail / OCR / Image / File** Supples Inbox Toners 1.000 pages 'C, N Toner Black 2.200 pages' EM. Toner Bl | | | | LPD, Custom Raw Port/Port9100, IPP/IPPS, FTP Cli |
| can Functions Scan to E-mail J OCR / Image / File** Scan to E-mail Server** Scan to E-mail Server** Scan to E-mail Server** Scan to FTP / Network ledia Specifications ledia Types Standard Paper Tray - Plain, Recycled Paper, Thin Paper, Manual Feed Slot - Plain Paper, Thin Paper, Thick Paper, Recycled, Paper, Bond, Label, Envelope, Thin Envelope Standard Paper Tray - 60 to 105g/m2 (16 to 28lb) ADF - 64 - 90g/m2 (17 - 24lb) Manual Feed Slot - 60 to 163g/m2 (16 to 43lb) Standard Paper Tray - A4, Letter, ISOB5, A5, ISOB6, A6, Executive, Legal, Folio ADF - Width 147.3 to 215.9mm, Length 147.3 to 356.0mm (Width 5.8" to 8.5", Length 5.8" to 14.0") Manual Feed Slot - Width 76.2mm to 220mm, Length 116mm to 406.4mm (Width 3.0" to 8.66", Length 4.57" to 16") Noise Level Supplies ITLS, TFP client to before SMTP, SMT LLTD responder, V Supplies Inbox Toners 1,000 pages* C, M Toner Black 2,200 pages* BK Toner Colour 1,400 pages* (7, M Toner Slack 2,200 pages* Duruns 15,000 pages* (7, M Toner Slack | | | 110100010 | and Server, TELNET Server, HTTP/HTTPS server, SS |
| Scan to E-mail Server*** Scan to FETP / Network Scan to FTP / Network Manual Feed Siot - Plain Paper, Thin Paper, Thick Paper, Recycled, Paper, Bond, Label, Envelope, Thin Envelope Standard Paper Tray - 60 to 105g/m2 (16 to 28lb) ADF - 64 - 90g/m2 (17 - 24lb) Manual Feed Siot - 60 to 163g/m2 (16 to 43lb) ADF - 84, Letter, ISOB5, A5, ISOB6, A6, Executive, Legal, Folio ADF - With 147.3 to 215.9mm, Length 147.3 to 366.0mm (Width 5.8" to 8.5", Length 5.8" to 14.0") Manual Feed Siot - 40 to 163g/m2 (16 to 43lb) Maste Toner Box Waste Toner Box Dimensions / Weight With Carton Waste Toner Box Dimensions / Weight With Carton 743 (W) x 592 (D) Others Power Consumption 480W copying 75W ready 11W sleep Noise Level Sound Pressure - less than 30dB &i When copying, les Power Save - Cor Toner Save - Red. Recommended | | | | TIC TETP - I CMTD Client ADOD DO |
| Scan to FTP / Network Idedia Specifications Idedia Specifications Standard Paper Tray - Plain, Recycled Paper, Thin Paper, Recycled, Paper, Bond, Label, Envelope, Thin | | | | TLS, TFTP client and server, SMTP Client, APOP, PC |
| Idedia Types | | | | before SMTP, SMTP-AUTH, SNMPv1/v2c/v3, ICMPv |
| ledia Types Standard Paper Tray - Plain, Recycled Paper, Thin Paper Manual Feed Slot - Plain Paper, Think Paper Recycled, Paper, Bond, Label, Envelope, Thin Envelope Standard Paper Tray - 60 to 105g/m² (16 to 28lb) ADF - 64 - 90g/m² (17 - 24lb) Manual Feed Slot - 60 to 163g/m² (16 to 28lb) Standard Paper Tray - 44, Letter, ISOB5, A5, ISOB6, A6, Executive, Legal, Folio ADF - Width 147.3 to 215.9mm, Length 147.3 to 356.0mm (Width 5.8" to 8.5", Length 5.8" to 14.0") Manual Feed Slot - Width 76.2mm to 220mm, Length 116mm to 406.4mm (Width 3.0" to 8.66", Length 4.57" to 16") Width 247.0 to 25.00mm, Length 147.3 to 356.0mm (Width 3.0" to 8.66", Length 4.57" to 16") Width 247.0 to 25.00mm, Length 147.3 to 356.0mm (Width 3.0" to 8.66", Length 4.57" to 16") With Carton Others Power Consumption 480W copying, Its Videna Value 11W sleep Noise Level Ecology Noise Level Recommended Noise Level Recommended Noise Carter Recommended | | Scan to FTP / Network | | LLTD responder, WebServicesPrint, CIFS Client, SN |
| edia Types Standard Paper Tray - Plain, Recycled Paper, Thin Paper Manual Feed Slot - Plain Paper, Think Paper Recycled, Paper, Bond, Label, Envelope, Thin Envelope Standard Paper Tray - 60 to 105g/m² (16 to 28lb) ADF - 64 - 99g/m² (17 - 24lb) Manual Feed Slot - 60 to 163g/m² (16 to 28lb) Standard Paper Tray - 44, Letter, ISOB5, A5, ISOB6, A6, Executive, Legal, Folio ADF - With 147.3 to 215.9mm, Length 147.3 to 356.0mm (Width 5.8" to 8.5", Length 5.8" to 14.0") Manual Feed Slot - Width 76.2mm to 220mm, Length 116mm to 406.4mm (Width 3.0" to 8.66", Length 4.57" to 16") With Carton Others Power Consumption 480W copying, Its Others Power Consumption Noise Level Sound Pressure - less than 30dBå i when copying, Its Ecology Power Save - Cor Toner Save - Red. | fications | | Supplies | |
| Manual Feed Slot - Plain Paper, Think Paper, Thick Paper, Recycled, Paper, Bond, Label, Envelope, Thin Envelope Standard Paper Tray - 60 to 105g/m² (16 to 28lb) ADF - 64 - 90g/m² (17 - 24lb) Manual Feed Slot - 60 to 163g/m² (16 to 43lb) Manual Feed Slot - 60 to 163g/m² (16 to 43lb) Manual Feed Slot - 80 to 163g/m² (16 to 43lb) Manual Feed Slot - 80 to 163g/m² (16 to 43lb) Manual Feed Slot - Width 147.3 to 215.9mm, Length 147.3 to 356.0mm (Width 5.8" to 215.9mm, Length 147.3 to 356.0mm (Width 5.8" to 8.5", Length 5.8" to 14.0") Manual Feed Slot - Width 76.2mm to 220mm, Length 116mm to 406.4mm (Width 3.0" to 8.66", Length 4.57" to 16") Noise Level Sound Pressure - less than 30dBA it when copying, les Ecology Power Save - Con Toner Save - Red. Recommended Recommend | | Standard Paper Tray - Plain, Recycled Paper, Thin Paper | | 1,000 pages* C, M, Y |
| Recycled, Paper, Bond, Label, Envelope, Thin Envelope | | | | |
| Drums 15,000 pages (one Nath Carlot | | | | |
| ADF - 64 - 90g/m² (17 - 24lb) Manual Feed Slot - 60 to 163g/m² (16 to 43lb) Standard Paper Tray - A4, Letter, ISOB5, A5, ISOB6, A6, Executive, Legal, Folio ADF - Witth 147.3 to 215.9mm, Length 147.3 to 356.0mm (Width 5.8" to 8.5", Length 5.8" to 14.0") Manual Feed Slot - Width 76.2mm to 220mm, Length 116mm to 406.4mm (Width 3.0" to 8.66", Length 4.57" to 16") Witth Carton Others Power Consumption 480W copying 75W ready 11W sleep Noise Level Sound Pressure - less than 30dBA is when copying, less Ecology Power Save - Con Toner Save - Red. Recommended 300 to 1,500 page | | | | |
| Manual Feed Slot - 60 to 163g/m2 (16 to 43lb) Ideida Sizes Standard Paper Tray - A4, Letter, ISOB5, A5, ISOB6, A6, Executive, Legal, Folio ADF - Width 147.3 to 215.9mm, Length 147.3 to 356.0mm (Width 5.8" to 8.5", Length 5.8" to 14.0") Manual Feed Slot - Width 76.2mm to 220mm, Length 116mm to 406.4mm (Width 3.0" to 8.66", Length 4.57" to 16") With Carton 743 (W) x 592 (D) Without Carton 428 (W) x 491 (D) Others Power Consumption 480W copying 75W ready 11W sleep Noise Level Sound Pressure - less than 30dBA in when copying, less than 30dBA in the first of the second propring less than 30dBA in the first of the second propring less than 30dBA in the first of the second propring less than 30dBA in the first of the second propring less than 30dBA in the first of the second propring less than 30dBA in the first of the second propring less than 30dBA in the first of the second propring less than 30dBA in the first of the second propring less than 30dBA in the first of the second propring less than 30dBA in the secon | | | | 15,000 pages (one page per job) C, M, Y, BK |
| edia Sizes Standard Paper Tray - A4, Letter, ISOB5, A5, ISOB6, A6, Executive, Legal, Folio ADF - Width 147.3 to 215.9mm, Length 147.3 to 356.0mm (Width 5.8" to 8.5", Length 5.8" to 14.0") Manual Feed Slot - Width 76.2mm to 220mm, Length 116mm to 406.4mm (Width 3.0" to 8.66", Length 4.57" to 16") Without Carton 428 (W) x 491 (D): Others Power Consumption 480W copying 75W ready 11W sleep Noise Level Sound Pressure - less than 30dBA it when copying, less than 30dBA it when copying, less Ecology Power Save - Con Toner Save - Redu Recommended 300 to 1,500 page | | | | Up to 50,000 pages |
| Executive, Legal, Folio ADF - Width 147.3 to 215.9mm, Length 147.3 to 386.0mm (Width 5.8" to 8.5", Length 5.8" to 14.0") Manual Feed Slot - Width 76.2mm to 220mm, Length 116mm to 406.4mm (Width 3.0" to 8.66", Length 4.57" to 16") With Carton 428 (W) x 491 (D): Others Power Consumption 11W sleep Noise Level Sound Pressure - less than 30dBA is when copying, less Ecology Power Save - Cor Toner Save - Red. Recommended 300 to 1,500 page | | | | Up to 50,000 pages |
| ADF - Width 147.3 to 215.9mm, Length 147.3 to 356.0mm (Width 5.8" to 8.5", Length 5.8" to 14.0") Manual Feed Slot - Width 76.2mm to 220mm, Length 116mm to 406.4mm (Width 3.0" to 8.66", Length 4.57" to 16") Without Carton 428 (W) x 491 (D): Others Power Consumption 480W copying 75W ready 111W sleep Noise Level Sound Pressure - less than 30dBA it when copying, less than 30dBA it when copying, less Ecology Power Save - Cor Toner Save - Reduced Recommended 300 to 1,500 page | St | Standard Paper Tray - A4, Letter, ISOB5, A5, ISOB6, A6, | Dimensions / Weight | |
| ADF - Width 147.3 to 215.9mm, Length 147.3 to 356.0mm (Width 5.8" to 8.5", Length 5.8" to 14.0") Manual Feed Slot - Width 76.2mm to 220mm, Length 116mm to 406.4mm (Width 3.0" to 8.66", Length 4.57" to 16") Without Carton 428 (W) x 491 (D): Others Power Consumption 480W copying 75W ready 111W sleep Noise Level Sound Pressure - less than 30dBA it when copying, less than 30dBA it when copying, less Ecology Power Save - Cor Toner Save - Reduced Recommended 300 to 1,500 page | | | | 743 (W) x 592 (D) x 575 (H) mm / 29.0kg |
| 356.0mm (Width 5.8" to 8.5", Length 5.8" to 14.0") Manual Feed Slot - Width 76.2mm to 220mm, Length 116mm to 406.4mm (Width 3.0" to 8.66", Length 4.57" to 16") Noise Level Noise Level Sound Pressure - less than 30dBA is when copying, less Ecology Power Save - Con Toner Save - Red. Recommended 300 to 1,500 page | | | | 428 (W) x 491 (D) x 401 (H) mm / 22.9kg |
| Manual Feed Slot - Width 76.2mm to 220mm, Length 116mm to 406.4mm (Width 3.0" to 8.66", Length 4.57" to 16") Noise Level Sound Pressure - less than 30dBA i when copying, les Ecology Power Save - Cor Toner Save - Red Recommended 300 to 1,500 page | | | | 120 (11) X 101 (D) X 401 (H) HIIII / 22.0Kg |
| Length 116mm to 406.4mm (Width 3.0" to 8.66", Length 4.57" to 16") Noise Level Sound Pressure - less than 30dBA in when copying. Ecology Power Save - Con Toner Save - Red. Recommended 300 to 1,500 page | | | | 40014 |
| (Width 3.0" to 8.66", Length 4.57" to 16") 11W sleep Noise Level Sound Pressure - less than 30dBA is when copying, les Ecology Power Save - Cor Toner Save - Red Recommended 300 to 1,500 page | | | Power Consumption | |
| Noise Level Sound Pressure - less than 30dBA i when copying, les Ecology Power Save - Cor Toner Save - Red Recommended 300 to 1,500 page | | | | |
| Noise Level Sound Pressure - less than 30dBA i when copying, les Ecology Power Save - Cor Toner Save - Red Recommended 300 to 1,500 page | (W | Width 3.0" to 8.66", Length 4.57" to 16") | | 11W sleep |
| less than 30dBA in when copying, less Ecology Power Save - Con Toner Save - Recommended 300 to 1,500 Reg | | , , , | Noise Level | Sound Pressure - Less than 53dBA when copying, |
| when copying, les Ecology Power Save - Con Toner Save - Read Recommended 300 to 1,500 page | | | TOTOG EGYGT | less than 30dBA in ready. Sound Power - Less than |
| Ecology | | | | |
| Toner Save - Redu Recommended 300 to 1,500 page | | | | when copying, less than 4.8 in ready |
| Recommended 300 to 1,500 page | | | Ecology | Power Save - Consume less energy when not in use |
| Recommended 300 to 1,500 page | | | | Toner Save - Reduces toner usage |
| | | | Recommended | 300 to 1,500 pages |
| monany i fint volune | | | | |
| | | | montany i fint voidille | |
| -9320CW as above plus: | s above plus | s: | | |

| Colour LED printer | |
|----------------------|---|
| Network | 10/100 Base-TX, Wireless LAN IEEE802.11b/g (Infrastructure Mode/Adhoc Mode) |
| Colour Scanner | |
| Scan Functions | Scan to FTP / Network / USB Flash Memory Drive |
| USB Direct Interface | |
| USB Direct Print | Print images or files directly from a USB Flash Memory Drive. |
| File Formats - Print | PDF (version1.7), Microsoft XPS (version 10), JPEG, Exif + JPEG, PRN (created by MFC-9320CW series printer driver), TIFF (MH) (scanned by Brother model). |

Memory Drives File Formats - Scan PDF (version 1.3), Microsoft XPS (version 1.0), JPEG, TIFF Wireless Easy Setup Secure Easy Setup™ (SES), Wi-Fi Protected Setup™ (WPS), AirStation Power Consumption 12W sleep Wireless Network WEP 64/128bit, WPA-PSK (TKIP/AES), WPA2-PSK Security (TKIP&AES), LEAP(CKIP), EAP-FAST(TKIP/AES) Wireless Easy Setup Secure Easy Setup™ (SES), Wi-Fi Protected Setup™

(WPS), AirStation OneTouch Secure System™ (AOSS)

^{*} Declared yield value in accordance with ISO/IEC 19798 ** Requires Brother Software

^{***} Optional free downloads available from http://solutions.brother.com † Vertical x Horizontal Resolution +Network printing only

Technical Specifications DCP-9010CN

| Colour LED Printer | | |
|-------------------------|---|--|
| Technology | Electrophotographic LED printer (Single Pass) | |
| Print Speed A4 | Up to 16ppm Colour & Mono | |
| Resolution | Up to 2,400 x 600dpi† print resolution | |
| Warm Up Time | 27 seconds (from sleep mode) | |
| First Print Out Time | 16 seconds (Colour), 15 seconds (Mono) | |
| Emulation | PCL®6, BR-Script 3 | |
| Resident Fonts | PCL®6 - 66 Scalable Fonts, 12 Bitmap Fonts, 13 | |
| | Barcodes Postscript® 3 - Compatible fonts: 66 | |
| Interface | Hi-Speed USB 2.0 | |
| Network | 10/100 Base-TX | |
| Display | 2 line, 16 characters green back-lit LCD | |
| | 2 LEDs (error, data) | |
| Colour Copier | | |
| Copy Speed A4 | Up to 16cpm Colour & Mono | |
| Resolution | 600 x 600dpi | |
| First Copy Out Time | Less than 24 seconds (Colour), 19 seconds (Mono) | |
| Stack & Sort | Stack and sort multiple copied documents | |
| Reduction / | Reduce and enlarge documents from 25% to 400% | |
| Enlargement Ratio | using 1% increments | |
| Colour Scanner | | |
| Resolution | 1,200x2,400dpi (from scanner glass) 1,200x600dpi (from ADF) | |
| Resolution (Enhanced) | 19,200 x 19,200dpi | |
| Grey Scale | 256 shades of grey are available for copying and scanning | |
| Colour Depth | 48 bit internal, 24 bit external | |
| Scan Functions | Scan to E-mail / OCR / Image / File** | |
| Media Specifications | O | |
| Media Types | Standard Paper Tray - Plain Paper, Recycled Paper, | |
| | Thin Paper, Manual Feed Slot - Plain Paper, Thin Paper, | |
| | Thick Paper, Recycled, Paper, Bond, Label, Envelope, Thin Envelope | |
| Madia Waighta | Standard Paper Tray - 60 to 105g/m2 (16 to 28lb) | |
| Media Weights | ADF - 64 - 90g/m2 (17 - 24lb) | |
| | Manual Feed Slot - 60 to 163g/m2 (16 to 43lb) | |
| Media Sizes | Standard Paper Tray - A4, Letter, ISOB5, A5, ISOB6, | |
| Modia Oizos | A6, Executive, Legal, Folio. ADF - Width 147.3 to | |
| | 215.9mm, Length 147.3 to 356.0mm (Width 5.8" to | |
| | 8.5", Length 5.8" to 14.0") Manual Feed Slot - Width | |
| | 76.2mm to 220mm, Length 116mm to 406.4mm(Width | |
| | 3.0" to 8.66", Length 4.57" to 16") | |
| Printer Driver Software | | |
| Windows® | Windows Vista®, Windows® XP Professional (32 & | |
| | 64 bit editions) / XP Home Edition, Windows Server* | |
| | 2003® (32 & 64 bit editions), Windows Server+ 2008®, | |
| | Windows® 2000 Professional | |
| Macintosh® | Mac OS® X 10.3.9 or greater | |
| Linux*** | CUPS printing system (x86, x64 environment), LPD/ | |
| | LPRng printing system (x86, x64 environment) | |
| Printer Driver Function | | |
| N-up Printing | Save paper reducing 2, 4, 9, 16 or 25 A4 pages to 1 A4 page | |
| Poster Printing | Enlarge 1 A4 page into a poster using 4, 9, 16 or 25 A4 | |
| | pages for a bigger impact | |
| Watermark Printing | Add predefined text or user-defined messages to your | |
| | documents as a watermark | |
| Booklet Printing | Print easy-to-read, professional documents in A5 | |
| | booklet format using manual duplex | |
| Secure Print | Protect your print jobs with a PIN number | |
| Colour Control Tool | Edit the colour settings in the printer driver to get | |
| Outron Bushistian T. | accurate colours everytime | |
| Colour Restriction Tool | Colour printing can be restricted for individual users by | |
| | | |

an administrator to control costs Print the time & date and/or the user ID on the

documents

Header and Footer

| Network | |
|-----------------------------------|--|
| Driver Deployment Wizard | at Web browser print server management A quick and easy way to deploy Brother printer driver on a networked Windows® PC |
| BRAdmin Light | Print server management for Windows® and Mac OS X® 10.3.9 or greater |
| BRAdmin Professional [^] | For LAN / WAN management |
| Protocols | TCP/IP (IPv4 & IPv6) |
| IPv4 Supported Protocols | ARP, RARP, BOOTP, DHCP, APIPA (Auto IP), WINS/ NetBIOS name resolution, DNS Resolver, mDNS, LLMNR responder, LPRVLPD, Custom Raw Port/ Port9100, IPP/IPPS, FTP Client and Server, TELNET Server, HTTP/HTTPS server, SSL/TLS, TFIP Client ar server, SMTP Client, APOP, POP before SMTP, SMTP AUTH, SNMPV1/VzC/v3, ICMP, LLTD responder, WebServicesPrint, CIFS Client, SNTP |
| IPv6 Supported Protocols | NDP, RA, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port9100, IPP/IPPS, FTI Client and Server, TELNET Server, HTTP/HTTPS serv SSL/TLS, TFTP client and server, SMTP Client, APOF POP before SMTP, SMTP-AUTH, SNMPv1/v2c/v3, ICMPv6, LLTD responder, WebServicesPrint, CIFS Client, SMTP |
| Supplies | |
| Inbox Toners | 1,000 pages* C, M, Y |
| Standard Toner Black | 2,200 pages* BK |
| Standard Toner Colour | 1,400 pages* C, M, Y |
| Drums | 15,000 pages (one page per job) C, M, Y, BK |
| Belt Unit | Up to 50,000 pages |
| Waste Toner Box | Up to 50,000 pages |
| Dimensions / Weight | |
| With Carton | 743 (W) x 592 (D) x 575 (H) mm / 28.2kg |
| Without Carton | 428 (W) x 491 (D) x 401 (H) mm / 22.7kg |
| Others | |
| Power Consumption | 480W copying, 75W ready, 10W sleep |
| Noise Level | Sound Pressure - Less than 53dBA when copying, less than 30dBA in ready. Sound Power - Less than 6.5B when copying, less than 4.8B in ready |
| Ecology | Power Save - Consume less energy when not in use. Toner Save - Reduces toner usage |
| Recommended | 300 to 1,500 pages |
| | |

- * Declared yield in accordance with ISO/IEC 19752.
- ** Requires Brother Software
- *** Optional free downloads available from http://solutions.brother.com
- † Vertical and Horizontal resolution
- + Network printing only

Monthly Print Volume

Brother UK Ltd, Audenshaw, Manchester M34 5JD Telephone: 08444 999 444 Fax: 0870 830 4031 Website: www.brother.co.uk

Specification correct at time of going to print. Brother is a registered trademark of Brother Industries Ltd. Brand product names are registered trademarks or trademarks of their respective companies.

ZLFT9000SERIESU3 RAFT 10/09 V1













