



## The Brother MFC-7225N

A fully featured laser printer and fax machine, offering monochrome copying and scanning with the convenience of being network ready as standard.



Always at your side

[www.brother.co.uk](http://www.brother.co.uk)  
<http://solutions.brother.com/index-eu.html>

# Brother MFC-7225N

The MFC-7225N is a compact, easy to use machine with trouble free installation, offering high performance functions for the individual or small workgroup. It comes network ready as standard, making it simple to print, fax and scan over a network.

This machine offers high quality laser printing at speeds of up to 20ppm. A Super G3 fax modem, 10 one-touch dial locations and 200 speed dials provide speed and efficiency when communicating. A memory of up to 500 pages ensures reliable storage of received or ready-to-transmit fax messages.

- Up to 20ppm Printing speed
- HQ1200 Print resolution (2,400 x 600dpi)
- 32MB Memory as standard
- 33,600bps Super G3 fax modem
- 10 One-touch dial locations
- 200 Speed dial locations
- Up to 99 multicopies
- Stack and sort functions
- Up to 1,200dpi scanner resolution (Interpolated)
- Windows® and Macintosh® compatible

Copying and scanning on this machine is quick and easy. The ability to copy whilst at your desktop and scan to email, OCR, image and file (including PDF) makes the MFC-7225N the ideal professional partner.

Brother continues to save you money and help the environment. As with all laser machines from Brother, the MFC-7225N operates using a separate toner and drum, which means you only replace the toner or drum when necessary.



## Technical Specifications MFC-7225N

### General

Engine	Monochrome laser
Backlit LCD Display	1 line x 16 characters
Back-lit Function Keys	For easy selection of fax, copy or scan functions
Back-up for Clock	Keeps time and date backed up to 4 days
Memory Capacity	32MB standard
Automatic Document Feeder	Up to 20 sheets
Paper Handling Size	Up to A4
Paper Capacity	Up to 250 sheets
	Up to 100 sheets
Standard paper tray	
Output paper capacity	Receive a fax whilst copying a document

### Simultaneous Operation

### Print

Print Speed	Up to 20ppm monochrome print speed
Resolution	HQ1200 (up to 2,400 x 600dpi)
First Print Out Time	Less than 10 secs
Emulation	PCL® 6 & BR-Script 3

### Fax

Modem	33,600bps Super G3
Data Compression	Approx 2 seconds transmission
Automatic Redial	Mono: MH / MR / MMR / JBIG
One-touch Dials	Automatic redial if the recipient fax is busy
Group Dials	10
Speed Dials	200
Fax / Tel Switch	Up to 8 groups
	Automatic recognition of fax and telephone reception
Distinctive Ring Detection	Yes
Super Fine	Enables quality transmission and reception of very small print or line drawings
Grey Scale	64 levels
Delayed Timer	Yes - up to 50
Transit/Receive Memory	Up to 500 pages*
Broadcasting Locations	Send the same fax message to up to 260 locations
Batch Transmission	Stores documents for the same location in the memory for transmission in a single call
Auto Reduction	Automatically reduces a received fax to fit on to a single sheet of A4

Error Correction Mode	Where machines share the ECM feature, errors during transmission are corrected automatically ensuring received documents are error free
Fax Forwarding	Sends a fax received in memory to another pre-programmed fax number
Remote Access	Allows the user to remotely access their machine by using another touch tone phone
Fax Retrieval	Allows the user to retrieve fax messages using another touch tone machine
PC Fax	Send and Receive
Dual Access	Scan a fax for transmission whilst receiving a fax

### Copier

Speed	Up to 20cpm monochrome
Reduction / Enlargement Ratio	50% - 200% in 1% increments
Resolution	Up to 200 x 300dpi
Multi Copy	Produces up to 99 copies of each original
Stack & Sort	Stacks or sorts output copies as desired
N in 1	Compress 2 or 4 pages on to a single sheet of A4

### Scanner

Resolution	Up to 200 x 400dpi (optical)
Grey Scale	Up to 1,200 x 1,200dpi (interpolated)
Scan Key	256 shades of grey
	Scan to email, OCR, image or file

### Interface(s)

External TAD Interface	Interface for connecting external telephone answering device
USB	USB 2.0 Full Speed
Parallel	IEEE 1284 Parallel Port
Network Connection	Ethernet 10/100 Base-TX as standard

### Weights & Dimensions

Dimensions / Weight	With Carton	452 (w) x 496 (d) x 430 (h) mm / 11.4kg
	Without Carton	374 (w) x 374 (d) x 262 (h) mm / 7.25kg

### Supplies

Toner	TN2000	Up to 2,500 A4 pages @ 5% coverage
Drum	DR2000	Approx 12,000 A4 pages (1 page per job)

### Other Information

Power Consumption	Sleep	Less than 10W
	Standby	Less than 80W
	Peak	Less than 1032W

\*ITU-T Test Chart, Standard Resolution, JBIG

Contact:



### Brother UK Ltd

Audenshaw, Manchester M34 5JD  
Tel:0870 830 4000 (National Rate Call) Fax:0870 830 4031  
Web-site: www.brother.co.uk

Your calls to us may be monitored or recorded for training purposes.

Specification correct at time of going to print. Brother is a registered trademark of Brother Industries Ltd.

Brand product names are registered trademarks or trademarks of their respective companies.