

Portable Printers



PIXMA iP100

The PIXMA iP100 delivers the ultimate in convenient, portable printing. Connect via IrDA IR or an optional Bluetooth adaptor and get speedy photolab-quality photos wherever you are.

- Compact and portable document and photo printer
- 9600 x 2400dpi FINE print head with 1pl Micro-Nozzles
- 5 Single Inks with Photo Black Dye ink for enhanced photo quality
- Borderless 10 x 15cm photo prints in approximately 50 seconds
- ChromaLife100 for long-lasting, beautiful photos
- High speed document printing: 20ppm mono, 14ppm colour
- Pigment Black ink for crisp and sharp text
- Stylish silver finish with piano black panel detail
- Printing freedom with IrDA IR or optional Bluetooth
- iP100 also available with rechargeable battery



GENERAL ACCESSORIES



Bluetooth® Unit BU-30

Bluetooth® Unit provides support for wireless printing from Bluetooth® wireless technology enabled camera phones, PC's and PDA's.



Silex C-6700WG

Share your Canon PIXMA printer or All-in-One wirelessly using the silex C-6700WG print server. Easy to set up, the silex C-6700WG means you can share printing at the same time and print or scan from almost anywhere in the house.



LK-62 for PIXMA iP100


The rechargeable Li-ion battery and charger kit allows you to print on the move. The battery prints up to 290 pages on a single charge and also includes a charge level indicator, so you always know how much power you have left.



PU-200U for PIXMA iP100

The Automobile Power Unit allows you to charge the optional battery or run the printer from your car's cigarette lighter socket.

PIXMA Portable Printers Specifications Chart



	PIXMA iP100	PIXMA iP100 with battery
PORTABLE PRINTERS		
PRINTER FUNCTIONS		
Print Resolution	Up to 9600 ¹ x 2400 dpi	Up to 9600 ¹ x 2400 dpi
Print Engine	Inkjet 5-ink with minimum 1 pl Micro-Nozzles & FINE print head	Inkjet 5-ink with minimum 1 pl Micro-Nozzles & FINE print head
Photo Lab Quality Speed	Borderless 10 x 15cm: Approx. 50 seconds (Standard)	Borderless 10 x 15cm: Approx. 50 seconds (Standard)
Mono Print Speed	Up to 20ppm (Max), 15.6ppm (Standard)	Up to 20ppm (Max), 15.6ppm (Standard)
Colour Print Speed	Text & Graphics: Up to 14ppm (Max.), 11.2ppm (Standard)	Text & Graphics: Up to 14ppm (Max.), 11.2ppm (Standard)
Ink Cartridge Configuration	Cartridge - PGI-35 Black, CLI-36 Color	Cartridge - PGI-35 Black, CLI-36 Color
Ink Cartridge Life	Black: 191 pages, Colour: 249 pages ³ Black: 2080 photos*, Colour: 1111 photos*	Black: 191 pages, Colour: 249 pages ³ Black: 2080 photos*, Colour: 1111 photos*
Media Type	Plain Paper, Envelopes, Photo Paper Pro (PR-101), Photo Paper Plus Glossy (PP-101), PP-201), Photo Paper Plus Double Sided (PP-101D), Photo Paper Plus Semi-gloss (SG-201), Glossy Photo Paper (GP-401), Glossy Photo Paper "Everyday Use" (GP-501), Matte Photo Paper (MP-101), High Resolution Paper (HR-101N), T-shirt Transfer (TR-301), Photo Stickers (PS-101), Super White Paper (SW-201)	Plain Paper, Envelopes, Photo Paper Pro (PR-101), Photo Paper Plus Glossy (PP-101), PP-201), Photo Paper Plus Double Sided (PP-101D), Photo Paper Plus Semi-gloss (SG-201), Glossy Photo Paper (GP-401), Glossy Photo Paper "Everyday Use" (GP-501), Matte Photo Paper (MP-101), High Resolution Paper (HR-101N), T-shirt Transfer (TR-301), Photo Stickers (PS-101), Super White Paper (SW-201)
Media Input	Sheet Feeder: Max. 50 sheets	Sheet Feeder: Max. 50 sheets
Media Size	Sheet Feeder: A4, B5, A5, Letter, Legal, Envelopes (DL size or Commercial 10), 10 x 15cm, 13 x 18cm, 10x18cm (wide), 20x25cm, Credit Card (54 x 86mm)	Sheet Feeder: A4, B5, A5, Letter, Legal, Envelopes (DL size or Commercial 10), 10 x 15cm, 13 x 18cm, 10x18cm (wide), 20x25cm, Credit Card (54 x 86mm)
Media Weight	Sheet Feeder: 64 to 105 g/m ² and supported Canon special media up to 273 g/m ²	Sheet Feeder: 64 to 105 g/m ² and supported Canon special media up to 273 g/m ²
Two Sided Printing	Available by manual operation using Photo Paper Plus Double Sided, Super White Paper or plain paper in A4, B5, A5, Letter & 13 x 18cm sizes (Windows only)	Available by manual operation using Photo Paper Plus Double Sided, Super White Paper or plain paper in A4, B5, A5, Letter & 13 x 18cm sizes (Windows only)
Borderless Printing	Yes (A4, 13 x 18cm, 10 x 15cm & Credit Card sizes)	Yes (A4, 13 x 18cm, 10 x 15cm & Credit Card sizes)
INTERFACE AND CONNECTIVITY		
Interface Type - PC	USB 2.0 Hi-Speed ¹¹ IrDA IR v1.4Bluetooth v2.0: Max speed 1.44Mbps (optional, HCRP) ⁷ (with optional Bluetooth unit BU-30)	USB 2.0 Hi-Speed ¹¹ IrDA IR v1.4Bluetooth v2.0: Max speed 1.44Mbps (optional, HCRP) ⁷ (with optional Bluetooth unit BU-30)
Interface Type - Camera	Direct Print Port: Camera direct photo printing fromPictBridge compliant digital cameras & camcorders	Direct Print Port: Camera direct photo printing fromPictBridge compliant digital cameras & camcorders
Interface Type - Mobile Phone / PDA	IrDA IR v1.4 (JPEG/PNG only)Bluetooth v2.0: Max speed 1.44Mbps (optional, JPEG/PNG only, OPP, BIP, BPP) ⁵ (with optional Bluetooth unit BU-30).Direct Print Port: PictBridge	IrDA IR v1.4 (JPEG/PNG only)Bluetooth v2.0: Max speed 1.44Mbps (optional, JPEG/PNG only, OPP, BIP, BPP) ⁵ (with optional Bluetooth unit BU-30).Direct Print Port: PictBridge
DRIVERS AND SOFTWARE		
Supported Operating System	Windows Vista / Windows XP SP2 / Windows 2000 Professional SP4 Mac OS X v.10.3.9 - v.10.4 - v.10.5	Windows Vista / Windows XP SP2 / Windows 2000 Professional SP4 Mac OS X v.10.3.9 - v.10.4 - v.10.5
Minimum System Requirements	Windows [®] Vista™, XP, 2000 / Internet Explorer 6.0 / Pentium [®] II 300 MHz including compatible processors / 128 MB RAM / 800 MB Hard disk space / CD-ROM drive / Display XGA 1024 x 768 Mac OS X v.10.5 / Intel [®] processor, PowerPC G4 / 512 MB RAM Mac OS X v.10.4 / Intel [®] processor, PowerPC G3 / 256 MB RAM Mac OS X v.10.3.9 / PowerPC G3 / 128 MB RAM Safari / 650 MB Hard disk space / CD-ROM drive / Display XGA 1024x768	Windows [®] Vista™, XP, 2000 / Internet Explorer 6.0 / Pentium [®] II 300 MHz including compatible processors / 128 MB RAM / 800 MB Hard disk space / CD-ROM drive / Display XGA 1024 x 768 Mac OS X v.10.5 / Intel [®] processor, PowerPC G4 / 512 MB RAM Mac OS X v.10.4 / Intel [®] processor, PowerPC G3 / 256 MB RAM Mac OS X v.10.3.9 / PowerPC G3 / 128 MB RAM Safari / 650 MB Hard disk space / CD-ROM drive / Display XGA 1024x768
Driver Features	Windows: Photo Optimizer PRO, Image Optimizer, Photo Noise Reduction, Vivid Photo	Windows: Photo Optimizer PRO, Image Optimizer, Photo Noise Reduction, Vivid Photo
Software Included	Mac: Photo Optimizer PRO, Photo Noise Reduction, Vivid Photo	Mac: Photo Optimizer PRO, Photo Noise Reduction, Vivid Photo
GENERAL FEATURES		
Power Source	AC: 100-240V, 50/60HzCar adapter (optional): PU-200U, Input voltage 12-24V DC (negative ground)Battery & attachment: LK-62 Li-ion	AC: 100-240V, 50/60HzCar adapter (optional): PU-200U, Input voltage 12-24V DC (negative ground)Battery & attachment: LK-62 Li-ion
Power Consumption	Standby: 1.5 WOff: Approx. 0.4 WPrinting: Approx. 9 W ¹²	Standby: 1.5 WOff: Approx. 0.4 WPrinting: Approx. 9 W ¹²
Temperature Range	Operating environment: 5° - 35° C	Operating environment: 5° - 35° C
Humidity	Operating humidity: 10 - 90%RH (no condensation)	Operating humidity: 10 - 90%RH (no condensation)
Acoustic Noise Levels	Printing: Approx. 38.5 dB(A) in best quality mode	Printing: Approx. 38.5 dB(A) in best quality mode
Dimensions (W x D x H)	322 x 185 x 61.7mm	322 x 185 x 61.7mm
Weight	Approx. 2.0kg	Approx. 2.0kg
Options	Bluetooth [®] Unit BU-30, Rechargeable Battery & attachment LK-62, Automobile Power Unit PU-200U	Supplied as standard: Rechargeable Battery & attachment LK-62 Options: Bluetooth [®] Unit BU-30, Automobile Power Unit PU-200U

