

you can
Canon

PIXMA iP3600



Advanced 1pl and 9600dpi* performance for superior photo printing

A compact, affordable home photo printer with class-leading specification that delivers superior photolab-quality prints.

The PIXMA iP3600 is part of the Canon inkjet Photo & Document Home Printer range.

The Photo & Document Home Printer range consists of: PIXMA iP4600, **PIXMA iP3600**, PIXMA iP2600, PIXMA iP1900

Embargo Date: 26th August 2008
Sales Start Date: Mid-September 2008
Target Market: Young Player, Achievers, Creative Connectors

Key Features in Importance Order:

- 9600x2400dpi resolution for photolab-quality printing*
- Virtually grain-free prints with 1pl ink droplets
- Photolab-quality 10x15cm borderless print in approximately 41 seconds*
- Economical 5 Single Ink system
- Easy photo correction with Auto Photo Fix
- Versatile media handling: two-way paper feeding for different paper types
- No need for a PC: print directly from a digital camera with PictBridge
- Advanced ChromaLife100+ system for long-lasting, beautiful photos**
- Super-stylish, low-profile design
- Hi-speed USB connection

* See specifications

** See www.canon-europe.com/chromalife100

Product Name	Mercury Code	EAN Code	Recommended Retail Price
PIXMA iP3600	3021B008AA	4960999610993	£69.99 / €90.84

What's in the box:

PIXMA iP3600, Power cord, Print Head, Consumables PGI-520 Bk, CLI-521Bk, CLI-521 C, CLI-521M, CLI-521 Y, Multilingual set up guides, Setup software & User's manual CD including Easy-PhotoPrint EX, Media Sales Brochure, Sample Media PP-201 10x15cm (3 sheets), Warranty sheet

Consumables	Mercury Code	EAN Code	Recommended retail price
PGI-520 Bk	2932B001AA	4960999577456	£8.99 / €11.99
CLI-521 Bk	2933B001AA	4960999577470	£7.99 / €10.99
CLI-521 C	2934B001AA	4960999577494	£7.99 / €10.99
CLI-521 M	2935B001AA	4960999577517	£7.99 / €10.99
CLI-521 Y	2936B001AA	4960999577531	£7.99 / €10.99

Note: Blister packs with and without security are available for each of the inks listed above

you can
Canon

PIXMA iP3600



Technical Specifications

Printer functions Print Resolution Print Engine Photo Lab Quality Speed Mono Print Speed Colour Print Speed Ink Cartridge Configuration Black Ink Tank Life Colour Ink Tank Life Media Type Media Input Media Size Media Weight Two Sided Printing Borderless Printing	Up to 9600 ¹ x 2400 dpi InkJet 5-ink with minimum 1 pl ink droplets & FINE print head Borderless 10 x 15cm: Approx. 41 seconds (Standard) Up to 26ppm (Max.), 12.8ppm (Standard) Text & Graphics: Up to 17ppm (Max.), 10.5ppm (Standard) Single Ink technology - 5 separate ink tanks (PGI-520BK, CLI-521BK, CLI-521C, CLI-521M, CLI-521Y) Black: 324 pages (PGI-520BK), 3425 pages* (CLI-521BK) ² Black: 4520 photos* (PGI-520BK), 815 photos* (CLI-521BK) ³ *Estimated Supplemental Yield Cyan: 535 pages (CLI-521C), Magenta: 510 pages (CLI-521M), Yellow: 530 pages (CLI-521Y) ² Cyan: 241 photos (CLI-521C), Magenta: 236 photos (CLI-521M), Yellow: 220 photos (CLI-521Y) ³ Plain Paper, Envelopes, Photo Paper Pro Platinum (PT-101), Photo Paper Pro II (PR-201), Photo Paper Plus Glossy II (PP-201), Photo Paper Plus Semi-gloss (SG-201), Glossy Photo Paper "Everyday Use" (GP-501), Matte Photo Paper (MP-101), High Resolution Paper (HR-101N), T-shirt Transfer (TR-301), Photo Stickers (PS-101) Rear Tray: Max. 150 sheets Cassette: Max. 150 sheets Rear Tray: A4, B5, A5, Letter, Legal, Envelopes (DL size or Commercial 10), 10 x 15cm, 13 x 18cm, 20 x 25cm, Credit Card (54 x 86mm) Cassette: A4, B5, A5, Letter Rear Tray: Plain paper: 64 to 105 g/m ² and supported Canon special media up to 300 g/m ² Cassette: Plain paper: 64 to 105 g/m ² Available by manual operation using plain paper in A4, B5, A5, Letter & 13 x 18cm sizes (Windows only) Yes (A4, 20 x 25cm, 13 x 18cm, 10 x 18cm, 10 x 15cm)
Interface and software Interface Type - PC Interface Type - Camera Interface Type - Mobile Phone / PDA Supported Operating System Minimum System Requirements	Hi-Speed USB (B Port) Direct Print Port: Camera direct photo printing from PictBridge compliant digital cameras & camcorders Photo printing via PictBridge Windows Vista (32bit, 64bit) / Windows XP SP2 / Windows 2000 Professional SP4 Mac OS X v.10.3.9 - v.10.5 Windows: PC: Windows Vista™, XP, 2000 Professional / Internet Explorer 6.0 / CD-ROM drive / SVGA Display 800 x 600 Mac OS X v.10.3.9, v.10.4, v.10.5 / Safari / CD-ROM drive / XGA Display 1024x768
Interface and software (Continue) Driver Features Software Included	Photo Optimizer PRO (Windows only), Image Optimizer (Windows only), Photo Noise Reduction, Vivid Photo Windows: Easy-PhotoPrint EX, Mac: Easy-PhotoPrint EX
General features Power Source Power Consumption Temperature Range Humidity Acoustic Noise Levels Dimensions (W x D x H) Weight	AC 100-240V, 50/60Hz Standby: Approx. 1.3W Off: Approx. 0.5W Printing: 16.0W ⁴ Operating environment: 5°- 35° C Operating humidity: 10 - 90% RH (no condensation) Printing: Approx. 41 dB(A) When printing ISO/JIS-SCID N2 pattern on 10x15cm Photo Paper Plus Glossy II using default settings 431 x 296 x 153mm Approx. 5.6kg
	<ol style="list-style-type: none"> Ink droplets can be placed with a minimum pitch of 1/9600 inch Declared yield value in accordance with ISO/IEC 24711. Values obtained by continuous printing. When printing Canon standard photos continuously on 10x15cm Canon Photo Paper Plus Glossy II with the default settings, using Windows Vista printer driver in borderless printing mode and Windows Vista Home Premium Photo Gallery. Declared yield value determined based on Canon standard method referring to ISO/IEC 24711. When printing ISO/JIS-SCID N2 pattern bordered on A4 plain paper with the default settings. <p>All specifications subject to change without notice. Borderless 10x15cm photo lab quality print speed based on Standard driver setting using Canon Photo Paper Plus Glossy II media. PPM print speed is based on the highest speed mode setting using Canon standard patterns on plain paper. Photo print speed is based on the default setting using "ISO/JIS-SCID N2" on 10x15cm Photo Paper Plus Glossy II. Print speed measured as soon as first page begins to feed into printer and may vary depending upon a number of factors. Print speed does not take into account data processing time on host computer. Ink yield may vary depending on texts/photos printed, applications software used, print mode and type of paper used. For yield information see www.canon-europe.com/ink/yield All brand and product names are trademarks of their respective companies. Microsoft, Windows and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries. For more information on ChromaLife100 please visit www.canon-europe.com/chromalife100</p>