



**Embargo Date:** 19<sup>th</sup> August 2009  
**Sales Start Date:** 28<sup>th</sup> September 2009  
**Target Market:** Advanced / Home / Office

## Key Features in Importance Order:

- Superior photolab-quality printer with 9600x2400dpi, 1pl FINE print engine\*
- Canon uses ISO standard for realistic print speeds, document ESAT speed 9.2ipm mono, 8.1ipm colour
- Photolab-quality borderless 10x15cm print in approx. 20sec\*
- 5 Single Inks for efficient ink use
- Auto duplex for automatic double-sided printing
- Versatile media handling: two-way paper feeding for different paper types
- Print directly onto DVDs and CDs
- Easy-WebPrint EX to easily clip, combine, edit and print from the web
- ChromaLife100+ for longer lasting, beautiful photos\*\*
- Print directly from a camera or camera phone via PictBridge

\* See specifications

\*\* See [www.canon-europe.com/chromalife100](http://www.canon-europe.com/chromalife100)

### Superior quality and functionality for the best in home photo and document printing.

The PIXMA iP4700 is the ultimate A4 photo printer, offering superior photo quality and fast document printing alongside extra features: print straight onto a DVD or make double-sided prints with ease.

The PIXMA iP4700 is part of the A4 PIXMA Photo Printer range.

The A4 PIXMA Photo Printer range consists of: **PIXMA iP4700**, PIXMA iP3600, PIXMA iP2600

Product Name	Mercury Code	EAN Code	Recommended Retail Price
PIXMA iP4700	3742B008AA	4960999637600	£109.00

**What's in the box:** PIXMA iP4700 printer, power cord, print head, ink tanks (PGI-520BK, CLI-521C, CLI-521M, CLI-521Y, CLI-521BK), DVD/CD print tray, multilingual set-up guides, set-up software & user manual CD (including Easy-PhotoPrint EX, CD-LabelPrint, Easy-WebPrint EX downloader), warranty sheet, photo paper range leaflet, sample PP-201 10x15cm (3 sheets), MP-101 for head alignment, A4 (2 sheets).

Consumables	Mercury Code	EAN Code	Recommended Retail Price
PGI-520BK	2932B001AA	4960999577456	£8.99
CLI-521BK	2933B001AA	4960999577470	£7.99
CLI-521C	2934B001AA	4960999577494	£7.99
CLI-521M	2935B001AA	4960999577517	£7.99
CLI-521Y	2936B001AA	4960999577531	£7.99

Note: Blister packs with and without security are available for each of the inks listed above

# Technical Specifications

<b>PRINTER FUNCTIONS</b>	
Print Resolution	Up to 9600 x 2400 dpi <sup>1</sup>
Print Engine	InkJet 5-ink with minimum 1 pl ink droplets & FINE print head
Photo Lab Quality Speed	Borderless 10 x 15cm: Approx. 20 seconds (Standard)
Mono Print Speed	ESAT: Approx. 9.2 ipm
Colour Print Speed	ESAT: Approx. 8.1 ipm
Ink Cartridge Configuration	Single Ink technology - 5 separate ink tanks (PGI-520BK, CLI-521BK, CLI-521C, CLI-521M, CLI-521Y)
Black Ink Tank Life	Black: 350 pages (PGI-520BK), 1875 pages* (CLI-521BK) <sup>2</sup> Black: 5235 photos* (PGI-520BK), 670 photos* (CLI-521BK) <sup>3</sup> *Estimated Supplemental Yield
Colour Ink Tank Life	Cyan: 505 pages (CLI-521C), Magenta: 471 pages (CLI-521M), Yellow: 505 pages (CLI-521Y) <sup>2</sup> Cyan: 209 photos (CLI-521C), Magenta: 204 photos (CLI-521M), Yellow: 205 photos (CLI-521Y) <sup>3</sup>
Media Type	Plain Paper, Envelopes, Photo Paper Pro Platinum (PT-101), Photo Paper Pro II (PR-201), Photo Paper Plus Glossy II (PP-201), Photo Paper Plus Semi-gloss (SG-201), Glossy Photo Paper "Everyday Use" (GP-501), Matte Photo Paper (MP-101), High Resolution Paper (HR-101N), T-shirt Transfer (TR-301), Photo Stickers (PS-101)
Media Input	Rear Tray: Max. 150 sheets Cassette: Max. 150 sheets DVD/CD Tray: 1 printable DVD or CD
Media Size	Rear Tray: A4, B5, A5, Letter, Legal, Envelopes (DL size or Commercial 10), 10 x 15cm, 13 x 18cm, 20 x 25cm, Credit Card (54 x 86mm) Cassette: A4, B5, A5, Letter
Media Weight	Rear Tray: Plain paper: 64 to 105 g/m <sup>2</sup> and supported Canon special media up to 300 g/m <sup>2</sup> Cassette: Plain paper: 64 to 105 g/m <sup>2</sup>
DVD/CD Printing	Available as standard
Two Sided Printing	Available for plain paper in A4, B5, A5 & Letter
Borderless Printing	Yes (A4, Letter, 20 x 25cm, 13 x 18cm, 10 x 15cm)
<b>INTERFACE AND SOFTWARE</b>	
Interface Type - PC	Hi-Speed USB (B Port)
Interface Type - Camera	Direct Print Port: Camera direct photo printing from PictBridge compliant digital cameras & camcorders
Interface Type - Mobile Phone / PDA	Photo printing via PictBridge
Supported Operating System	Windows Vista, Vista SP1 / Windows XP SP2, SP3 / Windows 2000 Professional SP4 Mac OS X v.10.3.9 - v.10.5
Minimum System Requirements	Windows Vista, Vista SP1 (1GHz processor, 512MB RAM) / Windows XP SP2, SP3 and Windows 2000 Professional SP4 (300MHz processor, 128MB RAM) Internet Explorer 6- / CD-ROM drive / Hard disk space 450MB* / Display SVGA 800x600 * for bundled software installation Mac OS X v.10.5 (Intel processor, PowerPC G5, PowerPC G4, 867MHz or faster / 512MB), Mac OS X v.10.4 (Intel processor, PowerPC G5, PowerPC G4, PowerPC G3 / 256MB), Mac OS X v.10.3.9 (Intel processor, PowerPC G5, PowerPC G4, PowerPC G3 / 128MB) Mac OS Extended (Journaled), Mac OS Extended Safari / CD-ROM drive / Hard disk space 600MB* / Display XGA 1024x768 * for bundled software installation

<b>INTERFACE AND SOFTWARE (continued)</b>	
Driver Features	Photo Optimizer PRO (Windows only), Image Optimizer (Windows only), Photo Noise Reduction, Vivid Photo, Simulate Illustration, Monochrome effects
Software Included	Canon Easy-PhotoPrint EX, Canon Easy-WebPrint EX*, CD-LabelPrint *Canon Easy-WebPrint EX available as download from <a href="http://www.canon-europe.com">www.canon-europe.com</a> , Internet Explorer 7 or later is required
<b>GENERAL FEATURES</b>	
Power Source	AC 100-240V, 50/60Hz
Power Consumption	Standby (USB connection to PC): Approx. 0.9 W Off (USB connection to PC): Approx. 0.5 W Printing: 17 W <sup>4</sup>
Temperature Range	Operating environment: 5° - 35° C
Humidity	Operating humidity: 10 - 90%RH (no condensation)
Acoustic Noise Levels	Printing: Approx. 46.5 dB(A) <sup>4</sup>
Dimensions (W x D x H)	431 x 296 x 153mm
Weight	Approx. 5.7 kg

All specifications subject to change without notice.

Borderless 10x15cm photo lab quality print speed based on default driver setting using ISO/JIS-SCID N2 on Canon Photo Paper Plus Glossy II media

Document print speed (ipm) on plain paper is measured based on the office category test of ISO/IEC 24734.

Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used and does not take into account data processing time on host computer.

Ink yield may vary depending on texts/photos printed, applications software used, print mode and type of paper used. For yield information see [www.canon-europe.com/ink/yield](http://www.canon-europe.com/ink/yield)

All brand and product names are trademarks of their respective companies.

Microsoft, Windows and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.

For more information on ChromaLife100+ please visit [www.canon-europe.com/chromalife100](http://www.canon-europe.com/chromalife100)

<sup>1</sup> Ink droplets can be placed with a minimum pitch of 1/9600 inch

<sup>2</sup> When printing Canon standard patterns continuously with the default settings of testing paper using Windows Vista printer driver in borderless printing mode and Windows Vista Home Premium Photo Gallery. Declared yield value determined based

on Canon standard method referring to ISO/IEC 24711.

<sup>3</sup> Declared yield value in accordance with ISO/IEC 24711. Values obtained by continuous printing.

<sup>4</sup> When printing ISO/JIS-SCID N2 pattern on A4 size plain paper using default settings.