



**i-SENSYS**  
FAX-L160

This compact and stylish laser fax ensures productive and reliable, performance – to meet all of your everyday faxing needs with ease and efficiency. Ideal for medium and small sized enterprises, it can also be used as a professional laser printer.

- Super G3 fax modem (33.6kbps) – 3 seconds per page\* transmission
- Stylish, compact and robust design
- Ultra High Quality 256 greyscale imaging for faxing fine details
- 340-page\* transmit and receive fax memory
- 15 one-touch and 100 coded speed dials
- Easy to use All-in-One cartridge, ensures continuous high quality output
- 150-sheet paper capacity
- 30-page Automatic Document Feeder
- 2-line backlight display
- Printing: 14 pages per minute with Quick First-Print performance
- Copying: 12 copies per minute – zero warm up time from sleep mode
- Energy efficient – only 3 watts in sleep mode

\* Based on ITU-T Standard Chart No. 1



**i-SENSYS**  
FAX-L140

Get superb laser fax quality in a compact and stylish design with this affordable Super G3 fax. Easy to use, energy efficient and offering a range of professional fax features, it's the ideal solution for small and medium-sized businesses.

- Super G3 fax modem (33.6kbps) – 3 seconds per page\* transmission
- Stylish, compact and robust design
- Ultra High Quality 256 greyscale imaging for faxing fine details
- 340-page\* transmit and receive fax memory
- 15 one-touch and 100 coded speed dials
- Easy to use All-in-One cartridge, ensures continuous high quality output
- 150-sheet paper capacity
- 30-page Automatic Document Feeder
- 2-line backlight display
- Copying: 12 copies per minute – zero warm up time from sleep mode
- Energy efficient – only 3 watts in sleep mode

\* Based on ITU-T Standard Chart No. 1



# Inkjet Fax Specifications Chart



	i-SENSYS FAX-L3805	i-SENSYS FAX-L160	i-SENSYS FAX-L140
FAX UNIT TYPE			
Compatibility	Group 3	Group 3	Group 3
Applicable Line	PSTN	PSTN	PSTN
FAX SCANNING FEATURES			
Automatic Document Feeder	50 sheets	30 sheets (80 g/m <sup>2</sup> paper) A4	30 sheets (80 g/m <sup>2</sup> paper) A4
Effective Scanning Width	208mm	208mm	208mm
Scanning Speed	Approx. 2 sec./page Approx. 25 pages per minute	Approx. 3.5 sec. per page Approx. 15.5 pages per minute	Approx. 3.5 sec. per page Approx. 15.5 pages per minute
Fax Resolution	Standard, Fine, Super fine, Ultra fine	Standard, Fine, Superfine, Photo	Standard, Fine, Superfine, Photo
Image Processing System	UHQ (Ultra High Quality)	UHQ (Ultra High Quality)	UHQ (Ultra High Quality)
Halftone	256 shades of grey	256 shades of grey	256 shades of grey
FAX PRINTING FEATURES			
Printing Method	Mono Laser Beam Printing	Mono Laser Beam Printing	Mono Laser Beam Printing
Print Speed	18 pages per minute	12 pages per minute	12 pages per minute
Print Resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
Paper Capacity	250 sheets Auto Sheet Feeder, Manual Feed: 1 sheet	150 sheets Auto Sheet Feeder	150 sheets Auto Sheet Feeder
Print Cartridge	Cartridge T All-in-One cartridge	FX-10 All-in-One cartridge	FX-10 All-in-One cartridge
Yield	Approx. 3,500 pages based on ISO/IEC19752 (Approx. 5,250 pages with Toner Save on)	Approx. 2,000 pages based on 5% coverage (Approx. 3,000 pages with Toner Save on)	Approx. 2,000 pages based on 5% coverage (Approx. 3,000 pages with Toner Save on)
Toner/Ink Saver Mode	YES	YES	YES
Auto Image Reduction On Reception	YES (100 to 75%)	YES	YES
TRANSMISSION/RECEPTION FEATURES			
Transmission Speed	3 seconds per page with 33.6 Kbps modem (based on ITU-T Standard Chart No. 1)	3 seconds per page with 33.6 Kbps modem (based on ITU-T Standard Chart No. 1)	3 seconds per page with 33.6 Kbps modem (based on ITU-T Standard Chart No. 1)
Compression Method	MH, MR, MMR, JBIG	MH, MR, MMR	MH, MR, MMR
Memory Transmission/Reception	YES	YES	YES
Quick Memory Transmission	YES	YES	YES
Fax Memory	Memory Transmission: 510 pages (based on ITU-T Standard Chart No. 1), Memory Reception: 510 pages (based on ITU-T Standard Chart No. 1)	Memory Transmission: 340 pages (based on ITU-T Standard Chart No. 1), Memory Reception: 340 pages (based on ITU-T Standard Chart No. 1)	Memory Transmission: 340 pages (based on ITU-T Standard Chart No. 1), Memory Reception: 340 pages (based on ITU-T Standard Chart No. 1)
Memory Backup	YES (1 hour)	NO	NO
Optional Memory	NO	NO	NO
SECURITY AND MANAGEMENT FEATURES			
Dual Access	YES	YES	YES
Error Correction Mode (ECM)	YES	YES	YES
TELEPHONE FEATURES			
Delayed Transmission	YES (Max. 142 locations)	YES (Max. 50 locations)	YES (Max. 50 locations)
Sequential Broadcast	YES (Max. 142 locations)	YES (Max. 131 locations)	YES (Max. 131 locations)
Polling	YES	YES	YES
Reception	YES	YES	YES
Dept. ID Management	YES	YES	YES
System Administrator ID	YES	YES	YES
Reports	Activity Report, Transmission Report, Reception Report, Multi Transaction Report, Memory Clear Report, Doc. Memory/Speed Dial/Group Dial List	Activity Report, TX Report, RX Report, Lost Report, Memory Data/1 touch/Coded & Group Dial/Status List, Memory Image Print	Activity Report, TX Report, RX Report, Lost Report, Memory Data/1 touch/Coded & Group Dial/Status List, Memory Image Print
One-touch Dials	31 locations	15 (max. 50 locations)	15 (max. 50 locations)
Coded Dials	100 locations	100 locations	100 locations
Redial	YES (Automatic and Manual)	YES (Automatic and Manual)	YES (Automatic and Manual)
Built-in Answering Machine	NO	NO	NO
Fax/Tel. Auto Switch	YES	YES	YES
Answering Machine Hook-up	YES	YES	YES
Remote Reception	YES	YES	YES
Telephone Handset	Option	Option	Option
Other Features	Password user restriction	—	—
COPY FEATURE			
Copy Speed (Mono)	18 pages per minute	12 pages per minute	12 pages per minute
Multiple Copy	Up to 99 copies	Up to 99 copies	Up to 99 copies
Reduction/Enlargement	YES (Preset ratios 50% - 200%)	YES (Zoom 50% - 200%)	YES (Zoom 50% - 200%)
PC RELATED FEATURES			
PC Interface	USB 2.0	USB 2.0 Hi-Speed	—
Printer Function (Printer Language)	YES (CARPS)	YES (UFRIL-LT)	—
Supported OS	Windows 98/ME/2000/XP/Vista	Windows 2000/XP/Vista/ Mac OS X Version 10.2.x, 10.3.x, 10.4.x, 10.5.x (Available via web distribution only)	—
Print Speed	18 pages per minute	14 pages per minute	—
Print Resolution	600 x 600 dpi (1,200 x 600 dpi enhanced)	600 x 600 dpi (1,200 x 600 dpi enhanced)	—
NETWORK FEATURES			
Network Connectivity	With optional Axis 1650 Print server	—	—
Functionality	Network printing	—	—
Type	NO	—	—
Network protocols	NO	—	—
GENERAL FEATURES			
Dimensions Without Trays (W x D x H)	438 x 401 x 336mm	400 x 386 x 221mm	400 x 386 x 221mm
Weight	Approx. 11kg	Approx. 8kg	Approx. 8kg
Power Consumption	Max.: Approx. 800W, Standby: Approx. 10W	Max.: Approx. 700W, Standby: Approx. 8W Sleep: Approx. 3W	Max.: Approx. 700W, Standby: Approx. 8W Sleep: Approx. 3W