



i-SENSYS LBP3460

The compact Laser Shot i-SENSYS LBP3460 provides a complete out-of-the-box solution for professional quality laser printing. A fast 33 pages per minute print speed is combined with PCL5e/6 compatibility, built-in networking and duplexing and an extensive paper supply.

- 33 ppm heavy-duty Laser Printer
- PCL 5e/6 & UFR II* supported for maximum compatibility
- Built-in networking (TCP/IP) for sharing printer resources
- Built-in duplex unit to provide double sided printing
- No warm-up time and first print ready in 7.7 seconds or less
- Print quality: 600 x 600 dpi or 2400 x 600 dpi equivalent
- Maintenance-free All-in-One cartridge
- 250-sheet cassette and 100-sheet multi-purpose tray plus optional 500-sheet cassette
- USB2.0 Hi-Speed connection between printer and PC
- Stylish, space-saving design with full frontal operation

* Canon's own printer language



i-SENSYS LBP3360

Share productive, professional output with this solid and compact network-ready Laser Printer. Easy to use and maintain, it has a 21 ppm print speed, practical PCL5e/6 & UFR II* support, cost-saving automatic double-sided printing and an All-in-One cartridge.

- 21 pages per minute Laser Printer
- PCL 5e/6 & UFR II* supported for maximum compatibility
- Network ready: built-in interface card
- Built-in duplex unit for double-sided printing
- Virtually no warm-up time, first print out time in less than 9 seconds
- 2400 x 600 dpi enhanced print resolution
- All-in-One cartridge for consistent high quality output & maintenance-free operation. High yield replacement cartridge available.
- 250-sheet cassette + optional 250-sheet cassette (up to A4)
- Windows, Mac** & Linux** compatible; USB2.0 Hi-Speed
- Solid, stylish design with full frontal/top operation

* Canon's own printer language
** English only & web distribution only



Suzie Geenen – 'Luxemburg City'



i-SENSYS LBP3300

Benefit from a fast 21 pages per minute print speed and professional laser output with the Laser Shot i-SENSYS LBP3300. Productive features include standard double sided printing, a flexible paper supply and optional networking – in a space-saving and easy-to-use unit.

- High performance Laser Printer: 21 ppm
- Standard built-in duplex unit for double sided printing
- No warm-up time and first print ready in 9 seconds or less
- Print quality: 600 x 600 dpi or 2400 x 600 dpi equivalent
- Maintenance-free All-in-One cartridge
- Standard 250-sheet cassette plus optional 250-sheet cassette
- Superior processing speed due to CAPT* & SCoA**
- USB2.0 Hi-Speed connection between printer and PC
- Network printing with optional Canon Network Board NB-C2
- Stylish, space-saving design with full frontal operation

* CAPT = Canon Advanced Printing Technology
** SCoA = Smart Compression Architecture



i-SENSYS LBP3000

Get the print speed you need and the laser quality you expect, with the Laser Shot i-SENSYS LBP3000. Advanced Canon technologies ensure fast output, enhanced print quality and exceptional ease of use. Plus optional network printing makes it even more productive.

- Laser Printer with rapid print speed: 14 ppm
- No warm-up time or waiting with On-Demand Fixing Technology
- Fast first print out: under 9.3 seconds due to CAPT* & SCoA**
- All-in-One cartridge: easy to replace and ensures continuous high quality output
- High print quality: 600 x 600 dpi or 2400 x 600 dpi equivalent with Automatic Image Refinement
- Easy-to-use Windows graphical interface & 'sound assist' function
- Flexible paper handling and 150-sheet Multi Purpose Tray
- Optional network printing with AXIS 1650 Print Server
- Small, stylish and quiet in operation

* CAPT = Canon Advanced Printing Technology
** SCoA = Smart Compression Architecture



i-SENSYS LBP2900





The small, stylish Laser Shot i-SENSYS LBP2900 produces professional laser prints, quickly and quietly – without waiting and without any worries. Exceptionally easy to use, it delivers consistently high quality output thanks to Canon's convenient All-in-One cartridge.

- Affordable Laser Printer with fast print speed: 12 ppm
- No warm-up time or waiting with On-Demand Fixing Technology
- Fast first print out: under 9.3 seconds due to CAPT* & SCoA**
- All-in-One cartridge: easy to replace and ensures continuous high quality output
- High print quality: 600 x 600 dpi or 2400 x 600 dpi equivalent with Automatic Image Refinement
- Easy-to-use Windows graphical interface & 'sound assist' function
- Flexible paper handling and 150-sheet Multi Purpose Tray
- Optional network printing with AXIS 1650 Print Server
- Small, stylish and quiet in operation

* CAPT = Canon Advanced Printing Technology
** SCoA = Smart Compression Architecture



Laser Beam Printers Specifications Chart






				
PRINTING METHOD AND QUALITY				
Printing Method	Colour Laser beam printing with built-in duplex unit	Colour Laser beam printing with built-in duplex unit	Colour Laser beam printing with built-in duplex unit	Colour Laser beam printing
Printer Language	PCL5e/PCL6 and UFR II	CAPT (Canon Advanced Printing Technology)	CAPT (Canon Advanced Printing Technology)	CAPT (Canon Advanced Printing Technology)
Resolution	600 x 600 dpi (Max. 9600 x 600 dpi with AIR)	600 x 600 dpi (Max. 9600 x 600 dpi with AIR)	600 x 600 dpi (Max. 9600 x 600 dpi with AIR)	600 x 600 dpi (Max. 9600 x 600 dpi with AIR)
PRINT SPEED				
Mono Text	Mono: 21 ppm A4 Colour: 21 ppm A4	Mono: 21 ppm A4 Colour: 21 ppm A4	Mono: 12 ppm A4 Colour: 10 ppm A4	Mono: 8 ppm A4 Colour: 8 ppm A4
Duty Cycle	60,000 pages per month (Max.)	55,000 pages per month (Max.)	35,000 pages per month (Max.)	Note ¹
MEDIA HANDLING AND SUPPORT				
Paper Size	A4, B5, A5, Legal, Letter, Executive, Statement, 8.5 x 13, 16K, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 - 215.9mm, length 127.0 - 355.6mm)	A4, B5, A5, Legal, Letter, Executive, Statement, 8.5 x 13, 16K, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 - 215.9mm, length 127.0 - 355.6mm)	A4, B5, A5, Legal, Letter, Executive, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 - 215.9mm, length 127.0 - 355.6mm)	A4, B5, A5, Letter, Executive, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 - 215.9mm, length 127.0 - 355.6mm)
Media Weight	64 - 135g/m ²	64 - 135g/m ²	64 - 135g/m ²	64 - 135g/m ²
Media Handling	250 sheet paper cassette/ 100 sheets Multipurpose tray (64g/m ²) (+500 sheet optional cassette)	250 sheet paper cassette/ 100 sheets Multipurpose tray (64g/m ²) (+500 sheet optional cassette)	250 sheet paper cassette/ single sheet Multipurpose tray (+250 sheet optional cassette)	250 sheet paper cassette/ 1-sheet manual (+250-sheet optional cassette)
Paper Output	200 sheets	200 sheets	125 sheets (face-down)	125 sheets (face-down)
Memory	128MB SDRAM Standard (expandable up to 384MB)	16MB SDRAM + Hi-SCoA	16MB SDRAM + Hi-SCoA	8MB + SCoA
TONER CARTRIDGE INFORMATION				
Toner Cartridge Life	Cartridge 711 Blk: 6,000 pages (A4, at 5% coverage) Cartridge 711 C/M/Y: 6,000 pages (A4, at 5% coverage)	Cartridge 711 Blk: 6,000 pages (A4, at 5% coverage) Cartridge 711 C/M/Y: 6,000 pages (A4, at 5% coverage)	Cartridge 707 Blk: 2,500 pages (A4, at 5% coverage) Cartridge 707 C/M/Y: 2,000 pages (A4, at 5% coverage)	Cartridge 707 Blk: 2,500 pages (A4, at 5% coverage) Cartridge 707 C/M/Y: 2,000 pages (A4, at 5% coverage)
DEVICE CHARACTERISTICS				
Interface	Standard: USB 2.0 Hi-Speed, IEEE1284 (Parallel)	Standard: USB 2.0 Hi-Speed	Standard: USB 2.0 Hi-Speed	Standard: USB 2.0 Hi-Speed
Dimensions (W x D x H)	412 x 470.7 x 453mm	412 x 470.7 x 453mm	407 x 365 x 395mm	407 x 365 x 374mm
Weight	Approx. 22kg (without cartridge)	Approx. 22kg (without cartridge)	Approx. 18kg (without cartridge)	Approx. 16kg (without cartridge)
POWER				
Consumption	Standby Approx. 45W Printing Approx. 416W	Approx. 45W Approx. 415W	16W 340W	Approx. 18W Approx. 207W
Acoustic Noise Levels	Max. 53dB(A) or less (during operation) 35dB(A) or less (during standby)	Max. 53dB(A) or less (during operation)	During standby: background noise level, During operation: 50dB(A) or less	Max. 50dB(A) or less (during operation)
OPERATING ENVIRONMENT				
Temperature Range	10 - 30°C	10 - 30°C	10 - 30°C	10 - 30°C
Humidity	10 - 80% RH	10 - 80% RH	10 - 80% RH	10 - 80% RH
OPERATING SYSTEM REQUIREMENTS				
Operating Systems	Windows® 98/SE/ME/2000/XP/ Vista-/Server 2003/Win x64 bit/ Mac OS X 10.2.8-10.4.6 (online distribution only) and Linux (English and online distribution only) With Server-Based Computing Environment. Compatible Windows Terminal Server (Service): Microsoft Windows 2000 Server, Server 2003. Compatible Software: Citrix MetaFrame 1.8, Presentation server 3.0 and 4.0 Compatible Microsoft Cluster Server (MSCS): Microsoft Windows 2000 Advanced Server, Server 2003 Enterprise Edition	Windows® 98/ME/NT 4.0/2000/XP/ Vista-/Server 2003/ Mac OS X v10.3.9 or later (online distribution only)/Linux (English and online distribution only)	Windows® 98/ME/2000/Server 2003/XP/ Vista-/Mac OS version 10.4 or later (online distribution only), Linux (English and online distribution only)	Windows® 98/ME/2000/XP/ Vista-/Server 2003/Mac Power PC: OS X (Version v10.3.x, v10.4), Mac Intel: OS X/1.4.X, (English and online distribution only)/ Linux (English and online distribution only)
Network Connectivity	Canon 10Base-T/100Base-TX	Canon 10Base-T/100Base-TX	Optional Canon Network Board NB-C2	Optional Canon Network Board NB-C2

Standard disclaimer
a All specifications subject to change without notice

Footnotes
1 Specification not available at time of print
2 For details on Vista support check <http://www.canon-europe.com/vista>

3 Based on ITU-T Chart No.1
4 Cartridge 701 BLK 5,000 pages at 5% coverage
Cartridge 701L Cya/Mag/Yel - 2,000 pages at 5% coverage (Included with machine)
Cartridge 701 Cya/Mag/Yel - 4,000 pages at 5% coverage
Drum cartridge 701 - 20000 pages mono / 5000 pages colour

Laser Beam Printers Specifications Chart

					
PRINTING METHOD AND QUALITY					
Printing Method	Monochrome Laser beam printing with built-in duplex unit	Monochrome Laser beam printing with built-in duplex unit	Monochrome Laser beam printing with built-in duplex unit	Monochrome Laser beam printing	Monochrome Laser beam printing
Printer Language	PCL5e/PCL6 and UFR II	PCL5e/PCL6 and UFR II	CAPT (Canon Advanced Printing Technology)	CAPT (Canon Advanced Printing Technology)	CAPT (Canon Advanced Printing Technology)
Resolution	600 x 600 dpi (Max. 2400 x 600 dpi with AIR)	600 x 600 dpi (Max. 2400 x 600 dpi with AIR)	600 x 600 dpi (Max. 2400 x 600 dpi with AIR)	600 x 600 dpi (Max. 2400 x 600 dpi with AIR)	600 x 600 dpi (Max. 2400 x 600 dpi with AIR)
PRINT SPEED					
Mono Text	33 ppm A4	21 ppm A4	21 ppm A4	14 ppm A4	12 ppm A4
Duty Cycle	90,000 pages per month (Max.)	10,000 pages per month (Max.)	8,000 pages per month (Max.)	5,000 pages per month (Max.)	Note ¹
MEDIA HANDLING AND SUPPORT					
Paper Size	A4, B5, A5, Letter, Executive, Envelope C5/COM10/DL, Monarch, B5, Custom paper (width 76.2 - 215.9mm, length 127.0 - 355.6mm)	A4, B5, A5, Letter, Executive, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 - 215.9mm, length 127.0 - 355.6mm)	A4, B5, A5, LTR, Executive, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 - 215.9mm, length 127.0 - 355.6mm)	Multipurpose tray: A4, B5, A5, LTR, Executive, Envelope C5/COM10/DL, Monarch, Custom Paper (width 76.2 - 215.9mm, length 127.0 - 355.6mm) for Manual Feed only	Multipurpose tray: A4, B5, A5, LTR, Executive, Envelope C5/COM10/DL, Monarch, Custom Paper (width 76.2 - 215.9mm, length 127.0 - 355.6mm) for Manual Feed only
Media Weight	64 - 135g/m ²	64 - 135g/m ²	64 - 135g/m ²	64 - 163g/m ²	64 - 163g/m ²
Media Handling	250 sheet paper cassette/ 100 sheets Multipurpose tray (+500-sheet cassette optional)	250 sheet paper cassette/ 1-sheet manual sheet slot	250 sheet paper cassette/ 1-sheet manual sheet slot	Multipurpose tray: approx. 150 sheets	Multipurpose tray: approx. 150 sheets
Paper Output	250 sheets (face-down)	125 sheets (face-down) 1 sheet (+250-sheet optional cassette)	125 sheets (face-down) 1 sheet (face-up)	100 sheets (face-down)	100 sheets (face-down)
Memory	64MB SDRAM, Expandable up to 320MB	64MB	8MB + SCoA	2MB + SCoA	2MB + SCoA
TONER CARTRIDGE INFORMATION					
Toner Cartridge Life	Cartridge 710: 6,000 pages (A4, based on ISO/IEC19752)	Cartridge 708: 2,500 pages (A4, based on ISO/IEC19752)	Cartridge 708: 2,500 pages (A4, based on ISO/IEC19752)	Cartridge 703: 2,000 pages (A4, based on ISO/IEC19752)	Cartridge 703: 2,000 pages (A4, based on ISO/IEC19752)
DEVICE CHARACTERISTICS					
Interface	Standard: USB 2.0 Hi-Speed	Standard: USB 2.0 Hi-Speed	Standard: USB 2.0 Hi-Speed	Standard: USB 2.0 Hi-Speed	Standard: USB 2.0 Hi-Speed
Dimensions (W x D x H)	445 x 410 x 273mm	400 x 376 x 255mm	369.7 x 257.7 x 375.7mm	370 x 251 x 217mm	370 x 251 x 217mm
Weight	Approx. 16.1kg (without cartridge)	Approx. 12kg (without cartridge)	Approx. 11kg (without cartridge)	5.7kg (without cartridge)	5.7kg (without cartridge)
POWER					
Consumption	Standby Approx. 11W Printing Approx. 572W	Approx. 11W Approx. 400W	Approx. 4W Approx. 436W	Approx. 2W Approx. 259W	Approx. 2W Approx. 259W
Acoustic Noise Levels	Max. 52dB(A) or less (during operation)	Max. 50.9dB(A) or less (during operation)	Max. 52.8dB(A) or less (during operation)	Max. 48dB	Max. 48dB
OPERATING ENVIRONMENT					
Temperature Range	10 - 30°C	10 - 32°C	10 - 32°C	10 - 32.5°C	10 - 32.5°C
Humidity	10 - 80% RH	20 - 80% RH	20 - 80% RH	20 - 80% RH	20 - 80% RH
OPERATING SYSTEM REQUIREMENTS					
Operating Systems	Windows® 98/SE/ME/2000/XP/ Vista-/Server 2003/Win x64 bit/ Mac OS X 10.2.8-10.4.6 (online distribution only) and Linux (English and online distribution only) With Server-Based Computing Environment. Compatible Windows Terminal Server (Service): Microsoft Windows 2000 Server, Server 2003. Compatible Software: Citrix MetaFrame 1.8, Presentation server 3.0 and 4.0 Compatible Microsoft Cluster Server (MSCS): Microsoft Windows 2000 Advanced Server, Server 2003 Enterprise Edition (Netware option)	Windows® 98/SE/ME/2000/XP/ Vista-/Server 2003/Win x64 bit/ Mac OS X 10.2.8 or later (online distribution only) and Linux (English and online distribution only) With Server-Based Computing Environment. Compatible Windows Terminal Server (Service): Microsoft Windows 2000 Server, Server 2003. Compatible Software: Citrix MetaFrame 1.8, Presentation server 3.0 and 4.0 Compatible Microsoft Cluster Server (MSCS): Microsoft Windows 2000 Advanced Server, Server 2003 Enterprise Edition	Windows® 98/ME/2000 Professional/XP/ Vista-/ Server 2003/Linux (English and online distribution only)	Windows® 98/ME/2000 Professional/XP/ Vista-/ Linux (English and online distribution only)	Windows® 98/ME/2000 Professional/XP/ VISTA -/ Linux (English and online distribution only)
Network Connectivity	Canon 10Base-T/100Base-TX	Built-in 10Base-T/100Base-TX	Canon 10/100Base-TX Ethernet Board NB-C2 as option	Optional Axis 1650 10/100Base-TX Network Server	Optional Axis 1650 10/100Base-TX Network Server