

# Laser Beam Printers



**i-SENSYS**  
LBP5360

Designed for demanding workgroups, this compact, robust and quiet colour laser printer offers high specification performance. Network ready, PCL compatible and easy to use and maintain it delivers fast, professional output with automatic double-sided printing.

- Compact Colour Laser Printer: 21 ppm in colour & mono
- Automatic double-sided printing as standard
- PCL5c/6 & UFR II\* supported for maximum compatibility
- Quick First Print performance; no warm-up time from sleep mode
- Fast 10 second first print time
- Network ready
- 128MB standard, expandable up to 384MB. Optional 20GB hard disk drive
- 9600 x 600 dpi – print resolution
- Colour All-in-One cartridges
- 250-sheet cassette, 100-sheet multi-purpose tray and optional 500-sheet cassette (max. A4)
- Windows, Mac\*\* and Linux\*\* compatible

\* Canon's own printer language  
\*\* See specifications



**i-SENSYS**  
LBP5300

This quiet, network ready colour laser printer is designed for frequent, high-quality shared printing. The 21 ppm colour and mono output, large paper capacity, double-sided printing and maintenance-free colour All-in-One cartridges make it ideal for busy workgroups.

- Robust and compact Colour Laser Printer: 21 ppm in colour & mono
- Fast first colour print in approx. 10 seconds
- Maintenance free colour All-in-One cartridges containing S Toner for continuous professional quality
- 9600 x 600 dpi enhanced print resolution
- Zero warm-up time and quiet operation due to Colour On-Demand Fixing Technology
- Network ready with Remote User Interface (RUI)
- Automatic double-sided printing as standard
- Large paper capacity: 250-sheet cassette, 100-sheet multi-purpose tray and optional 500-sheet cassette (max. A4)
- USB2.0 Hi-Speed connection
- Windows, Mac\* and Linux\* compatible

\* See specifications



**i-SENSYS**  
LBP5100

This compact colour laser printer delivers high quality output and impressive print speeds with quiet, easy operation. Built-in automatic duplexing allows the creation of more professional double-sided documents – while cutting down on paper costs.

- Compact and quiet Colour Laser Printer
- Impressive print speeds: 10 ppm in colour, 12 ppm in mono
- Built-in automatic double-sided printing
- 9600 x 600 dpi print resolution and S Toner for professional output with vivid, contrasting colours and sharp text
- Quick first print, zero warm-up time from sleep mode
- Fast first print out in approx. 20 seconds
- Colour All-in-One cartridges
- 250-sheet paper cassette plus optional 250-sheet cassette (max. A4)
- Small footprint with full frontal operation
- Network printing with optional NB-C2 Network card



**i-SENSYS**  
LBP5000

The i-SENSYS LBP5000 brings speed, simplicity and style to colour laser printing – with convenient, maintenance-free colour All-in-One cartridges. Benefit from fast, professional colour output at 8 ppm, with this smart, quiet and space-saving printer.

- Robust, smart and stylish desktop Colour Laser Printer
- Print speed: 8 ppm in colour & mono
- Maintenance-free with colour All-in-One cartridges
- Print quality: 600 x 600 dpi or 9600 x 600 dpi equivalent
- No warm-up time with Colour On-Demand Fixing Technology plus fast first colour print in under 20 seconds
- Paper capacity: 250 sheets plus optional 250-sheet cassette
- Space-saving design with full frontal operation
- Easy-to-use Windows graphical interface
- USB2.0 Hi-Speed connection between printer and PC
- Network printing with optional Canon Network Board NB-C2



**i-SENSYS**  
LBP3460

The compact i-SENSYS LBP3460 provides a complete out-of-the-box solution for professional quality laser printing. A fast 33 pages per minute print speed is combined with PCL5e/6 compatibility, built-in networking and duplexing and an extensive paper supply.

- 33 ppm heavy-duty Laser Printer
- PCL 5e/6 & UFR II\* supported for maximum compatibility
- Built-in networking (TCP/IP) for sharing printer resources
- Built-in duplex unit to provide double sided printing
- No warm-up time and first print ready in 7.7 seconds or less
- Print quality: 600 x 600 dpi or 2400 x 600 dpi equivalent
- Maintenance-free All-in-One cartridge multi-purpose tray plus optional 500-sheet cassette
- USB2.0 Hi-Speed connection between printer and PC
- Stylish, space-saving design with full frontal operation

\* Canon's own printer language



## Laser Printers Specifications



	i-SENSYS LBP5360	i-SENSYS LBP5300	i-SENSYS LBP5100	i-SENSYS LBP5000
<b>PRINTING METHOD AND QUALITY</b>				
<b>Printing Method</b>	Colour Laser beam printing with built-in duplex unit	Colour Laser beam printing with built-in duplex unit	Colour Laser beam printing	Colour Laser beam printing
<b>Printer Language</b>	PCL5e/PCL6 and UFR II	CAPT (Canon Advanced Printing Technology)	CAPT (Canon Advanced Printing Technology)	CAPT (Canon Advanced Printing Technology)
<b>Resolution</b>	600 x 600 dpi (Max. 9600 x 600 dpi with AIR)	600 x 600 dpi (Max. 9600 x 600 dpi with AIR)	600 x 600 dpi (Max. 9600 x 600 dpi with AIR)	600 x 600 dpi (Max. 9600 x 600 dpi with AIR)
<b>PRINT SPEED</b>				
<b>Mono Text</b>	Mono: 21 ppm A4 Colour: 21 ppm A4	Mono: 21 ppm A4 Colour: 21 ppm A4	Mono: 12 ppm A4 Colour: 10 ppm A4	Mono: 8 ppm A4 Colour: 8 ppm A4
<b>Duty Cycle</b>	Up to 60,000 pages per month	Up to 55,000 pages per month	Up to 35,000 pages per month	Note <sup>1</sup>
<b>MEDIA HANDLING AND SUPPORT</b>				
<b>Paper Size</b>	A4, B5, A5, Legal, Letter, Executive, Statement, 8.5 x 13, 16K, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 - 215.9mm, length 127.0 - 355.6mm)	A4, B5, A5, Legal, Letter, Executive, Statement, 8.5 x 13, 16K, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 - 215.9mm, length 127.0 - 355.6mm)	A4, B5, A5, Legal, Letter, Executive, Statement, 8.5 x 13, 16K, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 - 215.9mm, length 127.0 - 355.6mm)	A4, B5, A5, Legal, Letter, Executive, Statement, 8.5 x 13, 16K, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 - 215.9mm, length 127.0 - 355.6mm)
<b>Media Weight</b>	64 - 220g/m <sup>2</sup>	64 - 220g/m <sup>2</sup>	64 - 163g/m <sup>2</sup>	64 - 163g/m <sup>2</sup>
<b>Media Handling</b>	250 sheet paper cassette/ 100 sheets Multipurpose tray (+500 sheet optional cassette)	250 sheet paper cassette/ 100 sheets Multipurpose tray (+500 sheet optional cassette)	250 sheet paper cassette/single sheet Multipurpose slot (+250 sheet optional cassette)	250 sheet paper cassette/single sheet Multipurpose slot (+250 sheet optional cassette)
<b>Paper Output</b>	200 sheets	200 sheets	125 sheets face-down	125 sheets face-down
<b>Memory</b>	128MB SDRAM Standard (expandable up to 384MB)	16MB with CAPT & Hi-SCoA technology	16MB with CAPT & Hi-SCoA technology	8MB with CAPT & Hi-SCoA technology
<b>TONER CARTRIDGE INFORMATION</b>				
<b>Toner Cartridge Life</b>	Cartridge 711 Blk: 6,000 pages Cartridge 711 C/M/Y: 6,000 pages (A4, at 5% coverage)	Cartridge 711 Blk: 6,000 pages Cartridge 711 C/M/Y: 6,000 pages (A4, at 5% coverage)	Cartridge 707 Blk: 2,500 pages (A4, at 5% coverage) Cartridge 707 C/M/Y: 2,000 pages (A4, at 5% coverage)	Cartridge 707 Blk: 2,500 pages Cartridge 707 C/M/Y: 2,000 pages (A4, at 5% coverage)
<b>DEVICE CHARACTERISTICS</b>				
<b>Interface</b>	Standard: USB 2.0 Hi-Speed, IEEE1284, 10Base-T/100Base-TX	Standard: USB 2.0 Hi-Speed, 10Base-T/ 100Base-TX	Standard: USB 2.0 Hi-Speed, Optional: 10Base-T/100Base-TX	Standard: USB 2.0 Hi-Speed, Optional: 10Base-T/100Base-TX
<b>Dimensions (W x D x H)</b>	412mm x 453mm x 470.7mm	412mm x 453mm x 470.7mm	407mm x 365mm x 395mm	407mm x 365mm x 374mm
<b>Weight</b>	Approx. 22kg (without cartridge)	Approx. 22kg (without cartridge)	Approx. 18kg (without cartridge)	Approx. 16kg (without cartridge)
<b>POWER</b>				
<b>Consumption</b>				
	<b>Sleep</b>	Approx. 15W	Approx. 13W	Approx. 8W
	<b>Standby</b>	Approx. 45W	Approx. 45W	Approx. 16W
	<b>Operation</b>	Approx. 416W	Approx. 415W	Approx. 340W
<b>Acoustic Noise Levels</b>	Max. 53dB(A) or less (during operation) 35dB(A) or less (during standby)	Max. 53dB(A) or less (during operation)	Max. 50dB(A) or less (during operation) 25dB(A) or less (during standby)	Max. 50dB(A) or less (during operation) 25dB(A) or less (during standby)
<b>OPERATING ENVIRONMENT</b>				
<b>Temperature Range</b>	10 - 30°C	10 - 30°C	10 - 30°C	10 - 30°C
<b>Humidity</b>	10 - 80% RH	10 - 80% RH	10 - 80% RH	10 - 80% RH
<b>OPERATING SYSTEM REQUIREMENTS</b>				
<b>Operating Systems</b>	Windows®98/SE/ME/2000/XP/Vista/Server 2003/Mac OS X v10.3.x, v10.4.x, v10.5.x (English driver only and online distribution only) / Linux (English driver only and online distribution only) With Server-Based Computing Environment. Compatible Windows Terminal Server (Service): Microsoft Windows 2000 Server, Server 2003. Compatible Software: Citrix MetaFrame 1.8, Presentation server 3.0 and 4.0 Compatible Microsoft Cluster Server (MSCS): Microsoft Windows 2000 Advanced Server, Server 2003 Enterprise Edition	Windows® 98/ME/2000/ XP/Vista (32 bit only)/Server 2003/Mac OS X v10.3.x, v10.4.x, v10.5.x (English driver only and online distribution only) / Linux (English driver only and online distribution only)	Windows® 98/ME/2000/ XP/Vista (32 bit only)/Server 2003/Mac OS X v10.3.x, v10.4.x, v10.5.x (English driver only and online distribution only) / Linux (English driver only and online distribution only)	Windows® 98/ME/2000/ XP/Vista (32 bit only)/Server 2003/Mac OS X v10.3.x, v10.4.x, v10.5.x (English driver only and online distribution only) / Linux (English driver only and online distribution only)

Standard disclaimer  
\*All specifications subject to change without notice

Footnotes  
<sup>1</sup> Specification not available at time of print

## Laser Printers Specifications



	i-SENSYS LBP3460	i-SENSYS LBP3370	i-SENSYS LBP3360	i-SENSYS LBP3310
<b>PRINTING METHOD AND QUALITY</b>				
<b>Printing Method</b>	Monochrome Laser beam printing	Monochrome Laser beam printing	Monochrome Laser beam printing	Monochrome Laser beam printing
<b>Printer Language</b>	PCL5e/PCL6 and UFR II	PCL5e/PCL6 and UFR II	PCL5e/PCL6 and UFR II	CAPT (Canon Advanced Printing Technology)
<b>Resolution</b>	600 x 600 dpi (Max. 2400 x 600 dpi with AIR)	600 x 600 dpi (Max. 2400 x 600 dpi with AIR)	600 x 600 dpi (Max. 2400 x 600 dpi with AIR)	600 x 600 dpi (Max. 2400 x 600 dpi with AIR)
<b>PRINT SPEED</b>				
<b>Mono Text</b>	33 ppm A4	26 ppm A4	21 ppm A4	26 ppm A4
<b>Duty Cycle</b>	Up to 90,000 pages per month	Up to 15,000 pages per month	Up to 10,000 pages per month	Up to 10,000 pages per month
<b>MEDIA HANDLING AND SUPPORT</b>				
<b>Paper Size</b>	A4, B5, A5, Legal, Letter, Executive, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 - 215.9mm, length 127.0 - 355.6mm)	A4, B5, A5, Legal, Letter, Executive, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 - 215.9mm, length 127.0 - 355.6mm)	A4, B5, A5, Legal, Letter, Executive, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 - 215.9mm, length 127.0 - 355.6mm)	A4, B5, A5, Legal, Letter, Executive, Envelope C5/COM10/DL, Monarch, B5, Index Card, Custom paper (width 76.2 - 215.9mm, length 127.0 - 355.6mm)
<b>Media Weight</b>	64 - 199 g/m <sup>2</sup>	64 - 163 g/m <sup>2</sup>	64 - 163 g/m <sup>2</sup>	64 - 163 g/m <sup>2</sup>
<b>Media Handling</b>	250 sheet paper cassette, 100 sheets Multi-purpose tray, 500-sheet optional cassette	250 sheet paper cassette, 50 sheets Multi-purpose tray, 250-sheet optional cassette	250 sheet paper cassette, single sheet Multi-purpose slot, 250-sheet optional cassette	250 sheet paper cassette, 50 sheets Multi-purpose tray, 250-sheet optional cassette
<b>Paper Output</b>	250 sheets (face-down), 50 sheets (face-up)	125 sheets (face-down), 1 sheet (face-up)	125 sheets (face-down), 1 sheet (face-up)	125 sheets (face-down), 1 sheet (face-up)
<b>Memory</b>	64MB SDRAM, Expandable up to 320MB	64MB	64MB	8MB with CAPT & Hi-SCoA technology
<b>TONER CARTRIDGE INFORMATION</b>				
<b>Toner Cartridge Life</b>	Cartridge 710: 6,000 pages Cartridge 710H: 12,000 pages (A4, based on ISO/IEC19752)	Cartridge 715: 3,000 pages Cartridge 715H: 7,000 pages (A4, based on ISO/IEC19752)	Cartridge 708: 2,500 pages Cartridge 708H: 6,000 pages (A4, based on ISO/IEC19752)	Cartridge 715: 3,000 pages Cartridge 715H: 7,000 pages (A4, based on ISO/IEC19752)
<b>DEVICE CHARACTERISTICS</b>				
<b>Interface</b>	Standard: USB 2.0 Hi-Speed, 10Base-T/100Base-TX	Standard: USB 2.0 Hi-Speed, 10Base-T/100Base-TX	Standard: USB 2.0 Hi-Speed, 10Base-T/100Base-TX	Standard: USB 2.0 Hi-Speed, Optional 10/100Base-TX
<b>Dimensions (W x D x H)</b>	445 x 410 x 273mm	399.7 x 378.6 x 267mm	399.7mm x 375.7mm x 267mm	399.7 x 378.6 x 258mm
<b>Weight</b>	Approx. 16.1kg (without cartridge)	Approx. 11.4kg (without cartridge)	Approx. 12kg (without cartridge)	Approx. 11.2kg (without cartridge)
<b>POWER</b>				
<b>Consumption</b>				
	<b>Standby</b>	Approx. 11W (6W in sleep mode)	Approx. 9W (5W in sleep mode)	Approx. 11W (4W in sleep mode)
	<b>Printing</b>	Approx. 572W	Approx. 403W	Approx. 400W
<b>Acoustic Noise Levels</b>	Max. 52dB(A) or less (during operation) Background noise only (during standby)	Max. 55dB(A) or less (during operation) Background noise only (during standby)	Max. 50.9dB(A) or less (during operation) Background noise only (during standby)	Max. 55dB(A) or less (during operation) Background noise only (during standby)
<b>OPERATING ENVIRONMENT</b>				
<b>Temperature Range</b>	10 - 80% RH	20 - 80% RH	20 - 80% RH	20 - 80% RH
<b>OPERATING SYSTEM REQUIREMENTS</b>				
<b>Operating Systems</b>	Windows®98/ME/2000/XP/SERVER 2003/Vista/Mac OS X Version 10.2.x, 10.3.x, 10.4.x, 10.5.x (Online distribution only)/Linux (English driver and online distribution only) / With Server-Based Computing Environment. Compatible Windows Terminal Server (Service): Microsoft Windows 2000 Server, Server 2003. Compatible Software: Citrix MetaFrame 1.8, Presentation server 3.0 and 4.0 Compatible Microsoft Cluster Server (MSCS): Microsoft Windows 2000 Advanced Server, Server 2003 Enterprise Edition / Netware option	Windows®2000/XP/SERVER 2003/ Vista/Mac OS X Version 10.2.x, 10.3.x, 10.4.x, 10.5.x (Online distribution only)/Linux (English driver and online distribution only) / With Server-Based Computing Environment. Compatible Windows Terminal Server (Service): Microsoft Windows 2000 Server, Server 2003. Compatible Software: Citrix MetaFrame 1.8, Presentation server 3.0 and 4.0 Compatible Microsoft Cluster Server (MSCS): Microsoft Windows 2000 Advanced Server, Server 2003 Enterprise Edition	Windows®98/ME/2000/XP/SERVER 2003/Vista/Mac OS X Version 10.2.x, 10.3.x, 10.4.x, 10.5.x (Online distribution only)/Linux (English driver and online distribution only) / With Server-Based Computing Environment. Compatible Windows Terminal Server (Service): Microsoft Windows 2000 Server, Server 2003. Compatible Software: Citrix MetaFrame 1.8, Presentation server 3.0 and 4.0 Compatible Microsoft Cluster Server (MSCS): Microsoft Windows 2000 Advanced Server, Server 2003 Enterprise Edition	Windows 2000/XP/SERVER 2003/ Vista/Mac OS X Version 10.2.x, 10.3.x, 10.4.x, 10.5.x (Online distribution only) / Linux (English driver and online distribution only)

Standard disclaimer  
\*All specifications subject to change without notice

Footnotes  
<sup>1</sup> Specification not available at time of print