The compact printer that's perfect for personal use

i-SENSYS LBP6020 i-SENSYS LBP6020B

you can

Compact, energy-efficient desktop mono laser printer

A space saving, affordable mono laser printer that's perfect for personal use. Delivering quality, maintenance-free prints, this energy-saving device is easy to use and exceptionally quiet.

Key features

- Compact design making it ideal for even the smallest desk spaces
- Productive 18ppm mono laser printing
- Quick warm-up time from sleep mode
- First Print Out Time of only 7.8 seconds or less
- Up to 2400 x 600 dpi resolution for high quality prints with Automatic Image Refinement
- Highly efficient 0.8W power consumption in sleep mode
- Quiet operation and inaudible in Standby mode
- Convenient, easy to use All-in-One cartridge

What's in the box

Main unit, starter cartridge 725, power cord, setup sheet and warranty card – with user software and manual CDs.

Dimensions (W x D x H)

359mm x 249mm x 198mm

Supported OS

Windows 7 (32 / 64bit) / XP (32 / 64bit) / Vista (32 / 64bit) / 2000 / Server 2003 (32 / 64bit) / Server 2008 (32 / 64bit) / Server 2008 R2 (64bit)
Mac OS Version 10.4.9 and up (Web distribution only)
Linux (Web distribution only)

PRINT COPY FAX SCAN

Canon

i-SENSYS LBP6020 i-SENSYS LBP6020B

1 150-sheet tray
2 Cartridge 725

Specifications:

PRINTER ENGINE	
Print speed	18ppm mono (A4)[1]
Printing method	Monochrome laser beam printing
Print quality	Up to 2400 x 600 dpi with Automatic Image Refinement
Print resolution	Up to 600 x 600 dpi
Warm-up time	0.5 seconds from Sleep Approx. 10 seconds or less from power on
First Print Out Time	Approx. 7.8 seconds or less
Duty cycle	Max 5000 pages per month
Print margins	5mm – top and bottom, 5mm – left and right
MEDIA HANDLING	
Paper input (Standard)	150-sheet multi-purpose tray
Paper output	100-sheet face down
Media types	Plain paper, Heavy paper, Transparency, Label, Envelope
Media sizes	A4 / B5 / A5 / LGL / LTR / EXE / 16K / Custom size COM10 / Monarch / C5 / DL / ISO-B5 width 76.2-215.9mm x length 188-355.6mm
Media weights	Multi-purpose tray: 60 to 163 g/m²
GENERAL FEATURES	
Power requirements	AC 220 – 240V (±10%), 50/60Hz (±2Hz)
Power consumption	Maximum: Approx. 910W or less Active: Average approx. 295W Standby: Average approx. 1.8W or less Sleep: Average approx. 0.8W or less Typical Electricity Consumption (TEC): 0.5 kWh/week
Noise level	Sound power [2]: Active: 6.34B or less Standby: Inaudible Sound pressure [2]: Active: 50dB (A) Standby: Inaudible
Dimensions (W x D x H)	359mm x 249mm x 198mm
Weight	Approx. 5.0 kg
Operating environment	Temperature:10-30°c Humidity: 20-80% RH (no condensation)
Control panel	1 LED indicator, 1 operation key

CONTROLLER	
Memory	8MB
Printer languages	Canon Advanced Printing Technology (CAPT)
Interface and connectivity	USB 2.0 Hi-Speed
Operating systems compatibility	Windows 7 (32 / 64bit) / XP (32 / 64bit) / Vista (32 / 64bit) / 2000 / Server 2003 (32 / 64bit) / Server 2008 (32 / 64bit) / Server 2008 R2 (64bit) / Mac OS 10.4.9 and up[3] / Linux[3]
CONSUMABLES	
All-in-One cartridges	Standard: Cartridge 725 (1600 pages[4])[5]
ACCESSORIES / OPTIONS	
Items	TELEPHONE KIT 6

Standard disclaimers. All specifications subject to change without notice.

1] The print speed may drop depending on the printer driver settings, paper size, paper type and number of pages printed
2] Declared noise emission in accordance with ISO 9296
3] Web distribution only
4] Based on ISO/IEC 19752
5] Printer ships with 700 pages starter cartridge

Canon

Canon Electronics Inc
canon.com

Canon Europe
canon-europe.com

European Edition 0000
© Canon Europa N.V., 2012 (0000)