

Mono Laser Printer

i-SENSYS
LBP6650dn

you can



Packs powerful print performance in a compact unit

This high performance, compact mono laser printer offers productive auto duplexing and extensive network connectivity for seamless integration into IT print workflows.

33 PPM MONO LASER PRINTING
PAPER CAPACITY MAX. 800-SHEET
QUICK FIRST-PRINT
UP TO 2400 X 600 DPI PRINT RESOLUTION
AUTOMATIC DOUBLE-SIDED PRINTING
PCL5e/6 & OPTIONAL POSTSCRIPT 3

Key features

- High performance, 33 ppm mono laser printer
- Productive automatic double-sided printing
- Network ready with Remote User Interface (RUI)
- PCL5e/6 and UFR II support, optional PostScript Level 3
- Fast First Print Out Time: 6 seconds or less
- No waiting with Quick First-Print technologies
- Up to 2400 x 600 dpi print resolution with AIR (Automatic Image Refinement)
- Max. 800-sheet paper capacity (250-sheet cassette, 50-sheet multi-purpose tray, optional 500-sheet cassette)
- Energy efficient and silent in standby
- Maintenance-free All-in-One cartridge for continuous high quality output

What's in the Box

Main unit, Cartridge 719, power cord, quick setup guide and warranty card - with user software and manual CDs.

Dimensions (W x D x H)

400 x 376 x 267 mm

Supported OS

Windows 2000/ Server 2003/
Server 2008/ XP/ Vista/ 7



PRINT



COPY



FAX



SCAN

Canon



- 1 50-sheet multi-purpose tray
- 2 250-sheet cassette
- 3 Optional 500-sheet cassette
- 4 Cartridge 719 All-in-One
- 5 Optional Cartridge 719 H All-in-One

<p>PRINTER ENGINE</p> <p>Print speed Printing method Print quality Print resolution Warm-up time First Page Out Time Duty cycle Print margins</p>	<p>33 ppm mono (A4) Monochrome laser beam printing Up to 2400 x 600 dpi with Automatic Image Refinement Up to 600 x 600 dpi Approx. 10 seconds or less from power on Approx. 6 seconds or less Max. 50,000 pages per month 5 mm-top, bottom, left and right</p>
<p>MEDIA HANDLING</p> <p>Paper input (Standard) Paper input (Option) Paper output Media types Media sizes</p> <p>Media weights Double sided printing</p>	<p>250-sheet cassette 50-sheet multi-purpose tray 500-sheet cassette 150-sheet face down Plain paper, Heavy Paper, Transparency, Label, Index card, Envelope Cassette (Standard and optional): A4, B5, A5, A6, Legal, Letter, Executive, 16K, Custom sizes: Width 105 mm to 215.9 mm; Length 148.0 mm to 355.6 mm</p> <p>Multi-purpose tray: A4, B5, A5, A6, Legal, Letter, Executive, 16K, Envelope DL, Envelope COM10, Envelope C5, Envelope Monarch, Index Card 76.2 mm x 127 mm, Custom sizes: Width 76.2 to 215.9 mm; Length 127.0 to 355.6mm Cassette (Standard and optional): 60 to 120 g/m² Multi-purpose tray: 60 to 163 g/m² Automatic</p>
<p>GENERAL FEATURES</p> <p>Power requirements Power consumption</p> <p>Noise level</p>	<p>220-240V (±10%) 50/60Hz (±2Hz) Maximum: Approx. 1170 W or less Active: Approx. 580 W Standby: Approx. 11 W Sleep: Approx. 10 W (Panel sleep), Approx. 6 W (Deep sleep) Typical Electricity Consumption (TEC): 2.52kWh/week Sound power¹: Active: 7.06 B or less Standby: 4.3 B or less</p> <p>Sound pressure¹: Active: 54.9 dB(A) or less Standby: Inaudible</p>


<p>Dimensions (W x D x H) Weight Operating environment Control panel</p>	<p>400 mm x 376 mm x 267 mm Approx. 12.4 kg Temperature: 10 to 30°C (50 to 86°F) Humidity 20 to 80% RH (no condensation) LCD 16 characters x 1 line 8 LED indicators 8 operations keys</p>
<p>CONTROLLER</p> <p>Processor Speed Memory Printer languages Fonts Interface and connectivity Software and printer management Operating systems compatibility</p>	<p>333 MHz 64 MB expandable up to 320 MB UFR II (Ultra Fast Rendering), PCL5e, PCL6, PostScript Level 3 Emulation (optional)² 45 Scalable fonts, 10 Bitmap fonts USB 2.0 High-Speed, 10BASE-T/100BASE-TX</p> <p>NetSpot Device Installer, Remote User Interface (RUI)</p> <p>Windows 2000/ Server 2003/ Server 2008/ XP/ Vista/ 7</p>
<p>CONSUMABLES</p> <p>All-in-One cartridges</p>	<p>Standard: Cartridge 719 (2,100 pages³) High yield: Cartridge 719 H (6,400 pages³)</p>
<p>ACCESSORIES/ OPTIONS</p> <p>Items</p>	<p>PAPER FEEDER PF-44 (500-sheet cassette) ER-64 (64 MB RAM) ER-128 (128 MB RAM) ER-256 (256 MB RAM) PS ROM A-44 (PostScript 3 Emulation ROM module)</p>
<p>All specifications subject to change without notice</p> <p>¹ Declared noise emission in accordance with ISO 9296 ² PostScript Level 3 Emulation support requires PS ROM A-44 ³ Based on ISO/IEC 19752</p>	



Mono Laser Printer

i-SENSYS
LBP6650dn

you can



Packs powerful print performance in a compact unit

The i-SENSYS LBP6650dn is part of the Canon Mono Laser Printer Range

Sales Start Date: **March 2010**

The whole range consists of:

Mono: LBP3460, **LBP6650dn**,
LBP3370, LBP6300dn,
LBP3310, LBP3250,
LBP3100, LBP3010

Box Dimensions (W x D x H)

452 x 517 x 369 mm

Box weight

Approx. 15.5 kg

Packet style

Pallet

Quantity

12

MERCURY CODES

PRODUCT Name	Mercury Code	EAN Code
LBP6650dn	3549B006AA	8714574546919
OPTIONS		
Accessories		
PAPER FEEDER PF-44	3439B001AA	4960999630540
PS ROM A-44	3927B001AA	4960999643922
ER-64 (64 MB RAM)	0646A038AA	4960999356976
ER-128 (128 MB RAM)	0646A039AA	4960999356990
ER-256 (256 MB RAM)	0646A040AA	4960999356983
CONSUMABLES		
Toner		
Cartridge 719 (2,100 pages*)	3479B002AA	4960999650289
Cartridge 719 H (6,400 pages*)	3480B002AA	4960999650319
EASY SERVICE PLAN		
Details		
3 year return to base service-S3	093ZZ322	8714574979724
3 year on site next day service-S3	093ZZ335	8714574979823
Installation Service-N1	093ZZ324	8714574979748

* Based on ISO/IEC 19752



PRINT



COPY



FAX



SCAN

Canon