
Epson AcuLaser M2400D series

DATASHEET





Increase your company's efficiency with the Epson AcuLaser M2400D A4 mono laser series. Designed for small-to-medium workgroups, it gets the job done fast with a first-page-out time of 7 seconds and a print speed of 35 pages per minute. There's no compromise on quality with a print resolution of 1200 x 1200dpi.

The AcuLaser M2400D series has the flexibility to perfectly match the needs of your workgroups – with expandable RAM. Paper handling is adjustable too, with automatic double-sided printing and a choice of one or two optional additional paper trays to increase capacity up to 800 sheets.

Seamlessly integrating into IT environments, the AcuLaser M2400D series supports PCL5e, PCL6, ESC/Page, Genuine PostScript 3[™] and PDF 1.3. It features a parallel port (D model) or an Ethernet interface (DN model) for easy connectivity.

Your company's cost per page is optimised thanks to high-capacity toner cartridges. The series' ENERGY STAR® qualified power efficiency and Epson's toner cartridge return programme further reduce bills and minimise environmental impact.

KEY FEATURES

- Compact monochrome laser printer
- Efficient print speed of up to 35ppm in A4
- Fast first-page-out time of 7 seconds
- Superior output quality with 1200 x 1200dpi support
- Duplex printing as standard
- Versatile paper handling from 300 sheets to 800 sheets



AL-M2400DN's paper capacity can be extended to 800 sheets with two optional additional paper trays.



PRODUCT SPECIFICATIONS

TECHNOLOGY Print technology Print resolution Up to 1200 x 1200dpi PRINT Print speed Up to 35ppm (monochrome A4) First page out Maximum monthly volume Up to 50,000 pages per month D model: USB 2.0 compliant, Parallel (IEEE1284 compliant) DN model: Ethernet (10/100Base-T), USB 2.0 compliant Printer interface Network printing protocols DN model: TCP/IP: LPR, FTP, IPP, PORT2501, PORT9100, WSD (Web Services Dynamic Discovery), Microsoft Network: Net BIOS over TCP/IP, Net BIOS over NetBEUI, AppleTalk DN model: TCP/IP: SNMP, HTTP, TELNET, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SNTP, SSDP, SLP, WSD, LLTD (Link Layer Topology Discovery). Microsoft Network: Auto-IP, SSDP. MS Network management protocols Network (NetBEUI): SNMP. Apple Talk: SNMP PAPER HANDLING Standard paper input Up to 300 sheets Paper size A4, A5, A6, B5, LT, HLT, LGL, GLT, GLG, EXE, F4, Label, Envelope (C5, C6, DL, Com10, Monarch, ISO-B5), Custom size: from 70~216mm to 148~356mm Paper weight 60~220q/m² Paper output Up to 250 sheets (face down) Optional paper handling Optional 250-sheet paper tray (maximum two) 800 sheets (50-sheet MP tray + 250-sheet paper tray + two optional 250-sheet paper tray) Maximum paper input POWER REQUIREMENTS Power consumption Max: 840W; Printing: 505W; Ready: 9W; Sleep: 4W; Power Off: 0W, TEC value: 2501 Voltage Current 220-240V ±10% Frequency range 50Hz ±2% DIMENSIONS (W x D x H) 378 x 390 x 255mm WEIGHT (without consumables) 11.5kg **GENERAL** Printing mode: 68dB(A) Standby mode: 47dB(A) Sound power Printing mode: 55dB. Standby mode: 4/10b/A)
Printing mode: 55dB. Standby mode: 30dB
Operation mode: 10~32.5°C / Storage: 0~35°C
Operation mode: 15~80%RH / Storage: 15~80%RH
Windows 7 (32/64bit) / Vista (32/64bit) / XP (32/64bit) / Windows 2000 / Server 2008 (32/64bit) / Sound pressure Operating temperature Operating humidity Windows support Server 2008 R2 / Server 2003 (32/64bit) Mac OS X 10.4.11 or later Mac support Operating system For compatibility details relating to Linux, Unix, Novell, SAP, etc. please refer to http://www.business-solutions.epson.co.uk/Compatible.htm Options 250-sheet paper tray (C12C802641) OTHER FEATURES Environmental measures ENERGY STAR® compliant D model: 32MB as standard, up to 288MB Memory DN model: 64MB as standard, up to 320MB PCL6, PCL5e, Genuine PostScript 3™, PDF 1.3, ESC/Page(B/W), FX, ESCP2, I239X Printer control language emulations Resident typefaces Scalable: 84 ESC/Page, 95 PCL5c, 80 PCL6, 17 PS3. Bitmap: 7 ESC/Page, 5 PCL5c, 1 PCL6. Typeface: 10 ESC/P2, 8 FX, 8 I239X WARRANTY

Epson AcuLaser M2400D series

PRODUCT MODEL ORDER CODES

- AcuLaser M2400D
- AcuLaser M2400DT (with one additional paper tray)
- AcuLaser M2400DN (with network connectivity)
- AcuLaser M2400DTN (with one additional paper tray and network connectivity)

WHAT'S IN THE BOX

- Printer
- Power cable
- Software CD
- Instruction and notice sheets
- Warranty sheet

SUPPLIES

- Black High Capacity Toner Cartridge (8,000 pages*) C13S050582
- Black Standard Capacity Toner Cartridge (3,000 pages*) C13S050583
- Black Return High Capacity Toner Cartridge (8,000 pages*) C13S050584
- Black Return Standard Capacity Toner Cartridge (3,000 pages*) C13S050585
- Maintenance Unit (100,000 pages**)

C13S051206

- Initial Toner Cartridge (2,000 pages*)
- * According to ISO/IEC 19752 yield measurement
- ** Yield may vary depending on printing variables and conditions including toner and page coverage, continuous or intermittent

OPTIONAL ACCESSORIES

C12C802641 250-sheet paper tray

RETURN AND RECYCLE INCENTIVE

Return toner cartridges provide customers with a lower priced toner cartridge on the agreement that the empty cartridge will be returned via Epson's free toner collection programme. Toner cartridge return is available only in countries where Epson collection is available. Please visit www.epson.com/recycle for more details about products and availability.



Standard







1-vear on-site warranty





For more information please contact

Telephone: 0871 222 6702 (UK)* 01 436 7742 (Republic of Ireland) E-mail: enquiries@epson.co.uk Chat: etalk.epson-europe.com Fax: 0871 222 6740

Web: www.epson.co.uk

www.epson.ie

