HP LaserJet P4014 Printer series





A fast, affordable and highly reliable black-and-white printer which enables higher productivity. Experience professional quality printing, exceptional ease of use and expandability plus flexible connectivity options for shared print environments.

Ideal for workgroups of 5 – 10 users in small and medium-sized businesses who need to produce high volume, professional quality documents.



HP LaserJet P4014 Printer



HP LaserJet P4014n Printer



HP LaserJet P4014dn Printer

Get reliable, fast, and affordable black and white printing for your workgroup.

Help your workgroup operate at peak efficiency with print speeds of up to 43 ppm, a 540 MHz processor and Gigabit networking¹. Get consistent results and optimal performance with the printer's new toner technology. Legendary HP reliability means worry-free printing that stands up to the demands of your office environment. No time is lost waiting for the printer to warm up as Instant-on technology² ensures the first page prints out as fast as 8.5 seconds from Ready mode.

Enjoy exceptional ease of use with this simple, intuitive printer.

Operate and maintain your printer without assistance from IT. Printer configuration and troubleshooting is easy with "Show-Me-How" features on the control panel. Avoid interruptions and increase productivity: HP Easy Printer Care software³ lets you monitor around 15 HP LaserJet printers and MFPs simultaneously. Use a single driver—the HP Universal Print Driver⁴ communicates directly with each HP device on your network and customises the user interface to show available features.

Expand your printer's performance and capabilities as your business needs grow.

Experience fewer interruptions and streamline workflows with optional paper handling accessories, including additional 500-sheet trays or 1,500-sheet input tray, an automatic duplexer for two sided printing⁵, an envelope feeder, and output options such as a 5 bin mailbox, stacker, or stapler/stacker. Print on a variety of media types and sizes to produce the output that meets your specific business needs. Improve performance and increase storage capacity with an optional EIO hard disk.

- ¹ Optional on HP LaserJet P4014 and standard on HP LaserJet P4014n and P4014dn
- ² Instant-on Technology provides up to 50 percent energy savings over traditional fusing while providing a first page-out in seconds
- ³ Download free at www.hp.com/go/easyprintercare
- 4 To download the free HP Universal Print Driver Series for Windows, visit www.hp.com/go/upd
- ⁵ Cut paper consumption in half with optional automatic two-sided printing, standard on HP LaserJet P4014dn.

Product walkaround

HP LaserJet P4014n Printer shown with optional 500-sheet 5-bin mailbox, optional 500-sheet input trays 3 and 4, optional 1,500-sheet high capacity input tray, optional printer stand, optional duplexer

- 1. Control panel simultaneously displays up to four lines of text and animated graphics
- 2. Optional 500-sheet 5-bin mailbox with sorting capability 3. 500-sheet top output bin
- 4. Adjustable 100-sheet multipurpose input tray 1 for special media
- 5. 500-sheet input tray 2
- 6. Optional 500-sheet input tray 3
- 7. Optional 500-sheet input tray 4
- 8. Optional 1,500 sheet high capacity input tray
- 9. HP Jetdirect Gigabit Ethernet embedded print server for easy network sharing
- 10. A powerful 540 MHz processor and up to 128 MB memory, upgradeable to 640 MB
- 11. EIO expansion slot supports an optional parallel card, hard disk, or Jetdirect print server
- 12. One external and two internal Host USB 2.0 like ports for third party connections
- 13. Security lock slot
- 14. Hi-Speed USB 2.0 port for direct connection to printer
- 15. 100-sheet rear output bin
- 16. Optional duplexer for automatic two-sided printing
- 17. Optional printer stand enables printer mobility



Series at a glance



HP LaserJet P4014 Printer

- Print speed of up to 43 ppm
- 96 MB RAM (max 608 MB)
- 540 MHz processor
- Standard input capacity of 600-sheets with 1x100 sheet tray and 1x500-sheet input tray
- Expandable to 3600 pages with optional 3x500-sheet input trays and a 1500-sheet high-capacity input tray
- Recommended monthly print volume 3000 to 12000 pages
- Duty cycle up to 175000 pages



HP LaserJet P4014n Printer

- As base model with:
- additional 32 MB RAM (max 640 MB)
- HP Jet Direct Gigabit Ethernet Print server



HP LaserJet P4014dn Printer

- As base model with:
- additional 32 MB RAM
- embedded Gigabit networking
- automatic duplexer for two-sided printing

Recommended accessories





Feeder/Tray The HP 500-sheet input tray and feeder increases flexibility by providing one additional paper tray, increasing output capacity and decreasing user intervention.

CB523A HP LaserJet 1500-sheet High-capacity Input Tray Ideal for handling large high volume print jobs, the HP 1500-sheet high capacity input tray helps to increase productivity and minimise user interventions.



CB519A HP LaserJet Automatic Duplexer for Two-sided Printing Accessory

The automatic duplexer for two-sided printing enables you to cut paper consumption by up to 50% and save money.



CB520A

HP LaserJet 500-sheet 5-bin Mailbox Find your printed output quickly and easily with the HP LaserJet 500-sheet 5-Bin Mailbox. Assign each mailbox bin to an individual, workgroup or department for easy job retrieval. It can also

be used as a sorter/collator,

stacker or job separator.



CB524A HP LaserJet 75-sheet Envelope Feeder

The HP LaserJet 75-sheet Envelope Feeder enables simple and efficient business mailing and eliminates the need for manual loading as you can print up to 75 envelopes at a time.



CB522A HP LaserJet 500-sheet Stapler/Stacker

This stapler/stacker offers an additional 500-sheets output capacity and an automatic stapling capability (up to 15 pages), enabling simple, convenient and efficient finishing of documents with automatic offset.

HP Global Solutions Catalogue

HP Global Solutions partners deliver and integrate a wide range of business printing solutions: Products can be mixed, matched and customized. Solutions include: E-forms and stationery, Barcodes and cheque printing (OCR and MICR), Printing from SAP R/3 and ERP packages, Secure printing, Host printing, Cost-controlled printing and copying, Print job accounting and special industry solutions. Go to www.hp.com/eur/gsc for more information.

Ordering information



HP LaserJet P4014 Printer (CB506A)

Printer, right-angled power cord, control panel overlay, software and documentation on CD-ROM, print cartridge, Getting Started Guide, support flyer



HP LaserJet P4014n Printer (CB507A)

Printer, right-angled power cord, control panel overlay, software and documentation on CD-ROM, print cartridge, Getting Started Guide, support flyer



HP LaserJet P4014dn Printer (CB512A) Printer, right-angled power cord, control panel overlay, software and documentation on CD-ROM, print cartridge, Getting Started Guide, support flyer

Accessories, Supplies and Support

Accessories	
CB518A	HP LaserJet 500-sheet Feeder/Tray
CB523A	HP LaserJet 1500-sheet High-capacity Input Tray
CB519A	HP LaserJet Automatic Duplexer for Two-sided Printing
	Accessory
CB520A	HP LaserJet 500-sheet 5-bin Mailbox
CB524A	HP LaserJet 75-sheet Envelope Feeder
CB522A	HP LaserJet 500-sheet Stapler/Stacker
Q3216A	HP 1000-staple Cartridge
CB521A	HP LaserJet 500-sheet Stacker
CB525A	HP LaserJet P4010/P4510 Series Printer Stand
CB527A	HP LaserJet 400-sheet Custom Media Tray
J8019A	HP Secure High Performance EIO Hard Disk
J7972G	HP 1284B Parallel Card
CC413A	HP 64 MB 144-pin x32 DDR2 DIMM
CC414A	HP 128 MB 144-pin x32 DDR2 DIMM
CE483A	HP 512 MB 144-pin x32 DDR2 DIMM
CB389A	HP 220-volt User Maintenance Kit

Supplies	
CC364A	HP LaserJet CC364A Black Print Cartridge Average cartridge yields 10000 standard pages. Declared yield value in accordance with ISO/IEC 19752*
Connectivity	
17934G	HP letdirect 620n East Ethernet Print Server

J/934G	HP jetairect 020h Fast Ethernet Print Server
J7961G	HP Jetdirect 635n IPv6/IPsec Print Server
J8007G	HP Jetdirect 690n IPv6/IPSec 802.11g Wireless Print Server

J8021A HP Jetdirect ew2500 802.11b/g Wireless Print Server

Service & support

UK523A/E HP Care Pack, Next Business Day On-site, 3 years UK652E HP Care Pack, Same Business Day On-site within 4 hours 13x5, 3 years

UK524E HP Care Pack, Next Business Day On-site, 4 years UK525E HP Care Pack, Next Business Day On-site, 5 years UK656PE HP Care Pack, Post Warranty Next Business Day On-site,

UK658PE HP Care Pack, Post Warranty Same Business Day On-site within 4 hours 13x5, 1 year

UK662E HP Care Pack, Next Business Day On-site, 3 years (3 kits limit)

UC742E HP Care Pack Installation and Network configuration for 1 network printer

For a complete list of supplies, accessories and services, please refer to http://www.hp.com



Technical specifications

Print technology	Monochrome Lo	aser				
Print speed	A4 black: Up to 43 ppm					
	First page out Black: As fast as 8.5 sec (from ready mode)					
	Exact speed va	ries depending on the system configuration,	, software program, and document complexity			
Processor	540 MHz, Motorola ColdFire® V5e					
Memory	P4014: 96 MB; P4014n: 128 MB; P4014dn: 128 MB; P4014: Expandable to 608 MB through One 144-pin DDR2 DIMM slot; P4014n: Expandable to 640					
	One 144-pin D	DR2 DIMM slot ; P4014dn: Expandable to	640 MB through One 144-pin DDR2 DIMM slo	ot		
Print resolution	Up to 1200 x 1	200 dpi				
Print quality	HP REt, HP Fast	Res 1200, HP ProRes 1200, HP 600 dpi, H	HP 300 dpi			
Printer languages	HP PCL 6, HP P	CL 5e, HP Postscript level 3 emulation, dire	ct PDF (v 1.4) printing (Printer memory 128 MB	required, 192 MB recommended)		
Economical printing	Return to Power	Save mode after print job due to instant-on	fuser technology (saves electricity), N-up printing	g and two-sided printing (saves paper), Draftmode (saves toner)		
Typefaces/fonts	80 HP font set (plus Greek, Hebrew, Cyrillic, Arabic)				
Recommended Monthly Page Volume	3000 to 12000)				
Duty cycle (monthly, A4)	Up to 175000	pages				
Print margins		5 mm, right: 5 mm, bottom: 6 mm				
Media handling	Input	Capacity	Weight	Size		
	Tray 1	sheets: 100, envelopes: 10	60 to 200 g/m ²	A4, A5, B5 (JIS), letter, legal, executive, statement, 16K, Dpostcard (JIS), Executive (JIS), envelope (Com10, Monarch #7-3/4, DL ISO, C5 ISO, B5 ISO), 76 x 127 mm to 216 x 356 mm		
	Tray 2	sheets: 500	60 to 120 g/m ²	A4, A5, B5 (JIS), letter, legal, executive, statement, 16K, Executive (JIS), 148 x 210 to 216 x 356 mm		
	Tray 3	sheets: 500	60 to 120 g/m ²	A4, A5, B5 (JIS), letter, legal, executive, statement, 16K, Executive (JIS), 148 x 210 to 216 x 356 mm		
	Output: Duplex printing	Output: Sheets: Up to 600. Envelopes: Up to 10. Transparencies: Up to 600; 100-sheet rear output bin, 500-sheet top output bin Duplex printing: P4014: Automatic (optional); P4014n: Automatic (optional); P4014dn: Automatic (standard)				
Media types	Paper (bond, colour, letterhead, plain, preprinted, prepunched, recycled, rough, light), envelopes, labels, cardatock, transparencies					
Interface and connectivity	P4014: 1 Hi-Sp	beed USB 2.0, 1 EIO slot, 1 external and 2	internal Host USB 2.0-like ports for 3rd party co	nnection; P4014n: Embedded Jetdirect (Gigabit Ethernet) print		
	P4014: 1 Hi-Sp server, 1 Hi-Spe server, 1 Hi-Spe external print se available HP ne	weed USB 2.0, 1 EIO slot, 1 external and 2 wed USB 2.0, 1 EIO slot, 1 external and 2 i wed USB 2.0, 1 EIO slot, 1 external and 2 i ervers; HP wireless print servers; HP Secure etworking solutions visit http://www.hp.com	internal Host USB 2.0-like ports for 3rd party co nternal Host USB 2.0-like ports for 3rd party con nternal Host USB 2.0-like ports for 3rd party con High Performance EIO Hard Disk J8019A (CPE n/go/jetdirect	onnection; P4014n: Embedded Jetdirect (Gigabit Ethernet) print anection; P4014dn: Embedded Jetdirect (Gigabit Ethernet) print anection; optional: HP Jetdirect internal print servers; HP Jetdirect OZ firmware of 10.1 or higher required). For more information of		
Interface and connectivity Operating systems compatibility	P4014: 1 Hi-Sp server, 1 Hi-Spe server, 1 Hi-Spe external print se available HP ne Microsoft® Wir Optional: Mac	eed USB 2.0, 1 EIO slot, 1 external and 2 eed USB 2.0, 1 EIO slot, 1 external and 2 i eed USB 2.0, 1 EIO slot, 1 external and 2 i revers; HP wireless print servers; HP Secure etworking solutions visit http://www.hp.con indows® 2000, XP Home, XP Professional; 3	internal Host USB 2.0-like ports for 3rd party co nternal Host USB 2.0-like ports for 3rd party co nternal Host USB 2.0-like ports for 3rd party con High Performance EIO Hard Disk J8019A (CPE n/go/jetdirect Server 2003; Certified for Windows Vista®; Ma iVMS, Most recent printer drivers and software for	nnection; P4014n: Embedded Jetdirect (Gigabit Ethernet) print nnection; P4014dn: Embedded Jetdirect (Gigabit Ethernet) print nnection; optional: HP Jetdirect internal print servers; HP Jetdirect OZ firmware of 10.1 or higher required). For more information of c OS X v10.2, v10.3 or higher		
	P4014: 1 Hi-Sp server, 1 Hi-Spe external print se available HP ne Microsoft® Wir Optional: Mac http://www.hp Via an HP Jetdii compatible with SUSE Linux 8.x	beed USB 2.0, 1 EIO slot, 1 external and 2 and USB 2.0, 1 EIO slot, 1 external and 2 ared USB 2.0, 1 EIO slot, 1 external and 2 i prvers; HP wireless print servers; HP Secure atworking solutions visit http://www.hp.con indows® 2000, XP Home, XP Professional; S OS X v10.5, OS/2, UNIX, Linux, HP Oper .com/support; if no access to the Internet, s rect print server: Microsoft® Windows® 2003, XP, and W Microsoft® Windows® 2003, XP, and W and later; HP-UX 10.20, 11.x, 11.i; Solari	internal Host USB 2.0-like ports for 3rd party con nternal Host USB 2.0-like ports for 3rd party con nternal Host USB 2.0-like ports for 3rd party con High Performance EIO Hard Disk J8019A (CPE n/go/jetdirect Server 2003; Certified for Windows Vista®; Ma iVMS, Most recent printer drivers and software for see support flyer that came in printer box 100, Server 2003, XP, 2003 64-bit, XP 64-bit; V indows Vista®); Novell® 5.1 and later; Mac OS s® 2.5 and later (SPARC® systems only); IBM®	nnection; P4014n: Embedded Jetdirect (Gigabit Ethernet) print unection; P4014dn: Embedded Jetdirect (Gigabit Ethernet) print unection; optional: HP Jetdirect internal print servers; HP Jetdirect OZ firmware of 10.1 or higher required). For more information of c OS X v10.2, v10.3 or higher or all supported operating systems available at Vindows Vista®, Windows Vista® 64-bit (For Microsoft® IPv6 S X v10.2, v10.3, v10.4 and later; RED HAT Linux 7.x and later, AIX 3.2.5 and later 1; MPE-iX; Citrix® MetaFrame Server;		
Operating systems compatibility Network operating systems compatibility Minimum system requirements	P4014: 1 Hi-Sp server, 1 Hi-Spe external print se available HP ne Microsoft® Wir Optional: Mac http://www.hp Via an HP Jetdi compatible with SUSE Linux 8.x Microsoft® Wir CD-ROM drive; GHz processor, bidirectional pa	beed USB 2.0, 1 EIO slot, 1 external and 2 and USB 2.0, 1 EIO slot, 1 external and 2 ared USB 2.0, 1 EIO slot, 1 external and 2 i arvers; HP wireless print servers; HP Secure tworking solutions visit http://www.hp.con ndows® 2000, XP Home, XP Professional; S OS X v10.5, OS/2, UNIX, Linux, HP Oper .com/support; if no access to the Internet; or rect print server: Microsoft® Windows® 2003, XP, and W and later; HP-UX 10.20, 11.x, 11.i; Solari adows® Terminal Services, optional: Microsoft® Windows® 2000: 133 MHz processor, 64 MI Microsoft® Windows® Server 2003: 550 512 MB RAM (Windows Vista® Ready, cl rarallel port, USB (compatible with USB 1.1	internal Host USB 2.0-like ports for 3rd party con nternal Host USB 2.0-like ports for 3rd party con nternal Host USB 2.0-like ports for 3rd party con nternal Host USB 2.0-like ports for 3rd party con High Performance EIO Hard Disk J8019A (CPE n/go/jetdirect Server 2003; Certified for Windows Vista®; Ma IVMS, Most recent printer drivers and software for see support flyer that came in printer box J00, Server 2003, XP, 2003 64-bit, XP 64-bit; V indows Vista®); Novell® 5.1 and later; Mac OS s@ 2.5 and later (SPARC® systems only); IBM® soft® Windows® 2000, XP Home, XP Profession B RAM, CD-ROM drive; Microsoft® Windows® MHz processor, 128 MB RAM (standard editior heck user guide for minimum hard drive space);	nnection; P4014n: Embedded Jetdirect (Gigabit Ethernet) print unection; P4014dn: Embedded Jetdirect (Gigabit Ethernet) print unection; optional: HP Jetdirect internal print servers; HP Jetdirect OZ firmware of 10.1 or higher required). For more information of c OS X v10.2, v10.3 or higher or all supported operating systems available at Vindows Vista®, Windows Vista® 64-bit (For Microsoft® IPv6 5 X v10.2, v10.3, v10.4 and later; RED HAT Linux 7.x and later, AIX 3.2.5 and later 1; MPE-iX; Citrix® MetaFrame Server; ial, Server 2003; Apple Mac OS X v10.2, v10.3, v10.4, v10.5 XP Home and Professional: 233 MHz processor, 64 MB RAM, 1), 220 MB of free hard disk space for Microsoft® Windows®, 1 CD-ROM drive or Internet connection, IEEE 1284-compliant er; PowerPC G3, G4, G5, or Intel® Core processor; 160 MB free		
Operating systems compatibility Network operating systems compatibility Minimum system requirements	P4014: 1 Hi-Sp server, 1 Hi-Spe external print se available HP ne Microsoft® Wir Optional: Mac http://www.hp Via an HP Jetdii compatible with SUSE Linux 8.x Microsoft® Wir CD-ROM drive; GHz processor, bidirectional pa hard disk space	beed USB 2.0, 1 EIO slot, 1 external and 2 and USB 2.0, 1 EIO slot, 1 external and 2 ared USB 2.0, 1 EIO slot, 1 external and 2 is arvers; HP wireless print servers; HP Secure tworking solutions visit http://www.hp.con ndows® 2000, XP Home, XP Professional; 3 OS X v10.5, OS/2, UNIX, Linux, HP Oper .com/support; if no access to the Internet, s rect print server: Microsoft® Windows® 2003, XP, and W and later; HP.UX 10.20, 111.x, 11.i; Solari ndows® Terminal Services, optional: Microsoft® Windows® 2000: 133 MHz processor, 64 MI Microsoft® Windows® server 2003: 550 512 MB RAM (Windows Vista® Ready, cl urallel port, USB (compatible with USB 1.1 a; CD-ROM drive, USB port or IEEE 1284-B	internal Host USB 2.0-like ports for 3rd party con nternal Host USB 2.0-like ports for 3rd party con nternal Host USB 2.0-like ports for 3rd party con htigh Performance EIO Hard Disk J8019A (CPE n/go/jetdirect Server 2003; Certified for Windows Vista®; Ma iVMS, Most recent printer drivers and software for see support Hyer that came in printer box 1000, Server 2003, XP, 2003 64-bit, XP 64-bit; V indows Vista®); Novell® 5.1 and later; Mac CS so 2.5 and later (SPARC® systems only); IBM® soft® Windows® 2000, XP Home, XP Profession B RAM, CD-ROM drive; Microsoft® Windows® MHz processor, 128 MB RAM (standard editior heck user guide for minimum hard drive space); or 2.0 specifications), Mac OS X v10.2 or highe compliant parallel port (via HP1284B Parallel C	nnection; P4014n: Embedded Jetdirect (Gigabit Ethernet) print unection; P4014dn: Embedded Jetdirect (Gigabit Ethernet) print unection; optional: HP Jetdirect internal print servers; HP Jetdirect OZ firmware of 10.1 or higher required). For more information of c OS X v10.2, v10.3 or higher or all supported operating systems available at Vindows Vista®, Windows Vista® 64-bit (For Microsoft® IPv6 5 X v10.2, v10.3, v10.4 and later; RED HAT Linux 7.x and later, AIX 3.2.5 and later 1; MPE-iX; Citrix® MetaFrame Server; ial, Server 2003; Apple Mac OS X v10.2, v10.3, v10.4, v10.5 XP Home and Professional: 233 MHz processor, 64 MB RAM, 1), 220 MB of free hard disk space for Microsoft® Windows®, 1 CD-ROM drive or Internet connection, IEEE 1284-compliant er; PowerPC G3, G4, G5, or Intel® Core processor; 160 MB free		
Operating systems compatibility Network operating systems compatibility Minimum system requirements Software	P4014: 1 Hi-Sp server, 1 Hi-Spe external print se available HP ne Microsoft® Wir Optional: Mac http://www.hp Via an HP Jetdii compatible with SUSE Linux 8.x Microsoft® Wir CD-ROM drive; GHz processor, bidirectional pa hard disk space Print drivers and	weed USB 2.0, 1 EIO slot, 1 external and 2 and USB 2.0, 1 EIO slot, 1 external and 2 and USB 2.0, 1 EIO slot, 1 external and 2 and USB 2.0, 1 EIO slot, 1 external and 2 and 2 is the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream of the stream stream of the stream of the stream of the stream of the stream stream of the stream	internal Host USB 2.0-like ports for 3rd party con nternal Host USB 2.0-like ports for 3rd party con nternal Host USB 2.0-like ports for 3rd party con nternal Host USB 2.0-like ports for 3rd party con High Performance EIO Hard Disk J8019A (CPE n/go/jetdirect Server 2003; Certified for Windows Vista®; Ma iVMS, Most recent printer drivers and software for see support flyer that came in printer box 1000, Server 2003, XP, 2003 64-bit, XP 64-bit; V indows Vista®); Novell® 5.1 and later; Mac OS soft® Windows® 2000, XP Home, XP Profession B RAM, CD-ROM drive; Microsoft® Windows® MHz processor, 128 MB RAM (standard editior heck user guide for minimum hard drive space); or 2.0 specifications), Mac OS X v10.2 or high compliant parallel port (via HP1284B Parallel C 5e, HP PCL 6, Postscript, Postscript Printer Descr	nnection; P4014n: Embedded Jetdirect (Gigabit Ethernet) print unection; P4014dn: Embedded Jetdirect (Gigabit Ethernet) print unection; p4014dn: Embedded Jetdirect (Gigabit Ethernet) print or cost in the servers; HP Jetdirect or all supported operating systems available at Vindows Vista®, Windows Vista® 64-bit (For Microsoft® IPv6 5 X v10.2, v10.3, v10.4 and later; RED HAT Linux 7.x and later, AIX 3.2.5 and later 1; MPE-iX; Citrix® MetaFrame Server; ad, Server 2003; Apple Mac OS X v10.2, v10.3, v10.4, v10.5 XP Home and Professional: 233 MHz processor, 64 MB RAM, n), 220 MB of free hard disk space for Microsoft® Windows®, 1 CD-ROM drive or Internet connection, IEEE 1284-compliant r; PowerPC G3, G4, G5, or Intel® Core processor; 160 MB free Card J7972G)		
Operating systems compatibility Network operating systems compatibility Minimum system requirements Software Control panel	P4014: 1 Hi-Sp server, 1 Hi-Spe external print se available HP ne Microsoft® Wir Optional: Mac http://www.hp Via an HP Jetdi compatible with SUSE Linux 8.x Microsoft® Wir CD-ROM drive; GHz processor, bidirectional pa hard disk space Print drivers and 2.29 x 5.33 cm No numeric key	weed USB 2.0, 1 EIO slot, 1 external and 2 and USB 2.0, 1 EIO slot, 1 external and 2 and USB 2.0, 1 EIO slot, 1 external and 2 and USB 2.0, 1 EIO slot, 1 external and 2 and 2 is the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream and stream of the stream of the stream of the stream of the stream stream of the stream of the stream of the stream of the stream stream of the stream	internal Host USB 2.0-like ports for 3rd party con nternal Host USB 2.0-like ports for 3rd party con Not state to the state of the state of the state of the see support flyer that came in printer box 100, Server 2003, XP, 2003 64-bit, XP 64-bit; V indows Vista®); Novell® 5.1 and later; Mac OS s@ 2.5 and later (SPARC® systems only); IBM® soft@ Windows@ 2000, XP Home, XP Profession B RAM, CD-ROM drive; Microsoft® Windows@ MHz processor, 128 MB RAM (standard editior heck user guide for minimum hard drive space); or 2.0 specifications), Mac OS X v10.2 or highe compliant parallel port (via HP1284B Parallel C 5e, HP PCL 6, Postscript, Postscript Printer Descr (LED) indicator lights (Ready, Data, Attention), 5	nnection; P4014n: Embedded Jetdirect (Gigabit Ethernet) print unection; P4014n: Embedded Jetdirect (Gigabit Ethernet) print unection; p4014dn: Embedded Jetdirect (Gigabit Ethernet) print unection; optional: HP Jetdirect internal print servers; HP Jetdirect OZ firmware of 10.1 or higher required). For more information of c OS X v10.2, v10.3 or higher or all supported operating systems available at Vindows Vista®, Windows Vista® 64-bit (For Microsoft® IPv6 S X v10.2, v10.3, v10.4 and later; RED HAT Linux 7.x and later, AIX 3.2.5 and later 1; MPE-iX; Citrix® MetaFrame Server; tal, Server 2003; Apple Mac OS X v10.2, v10.3, v10.4, v10.5 XP Home and Professional: 233 MHz processor, 64 MB RAM, 1), 220 MB of free hard disk space for Microsoft® Windows®, 1 CD-ROM drive or Internet connection, IEEE 1284-compliant r; PowerPC G3, G4, G5, or Intel® Core processor; 160 MB free Card J7972G) iption files, HP LaserJet Utility (Mac), Macintosh software		
Operating systems compatibility	P4014: 1 Hi-Sp server, 1 Hi-Spe external print se available HP ne Microsoft® Wir Optional: Mac http://www.hp Via an HP Jetdi compatible with SUSE Linux 8.x Microsoft® Wir CD-ROM drive; GHz processor, bidirectional pa hard disk space Print drivers and 2.29 x 5.33 cm No numeric key HP Web Jetadm Requirements: In (active/printing	weed USB 2.0, 1 EIO slot, 1 external and 2 and USB 2.0, 1 EIO slot, 1 external and 2 and USB 2.0, 1 EIO slot, 1 external and 2 and USB 2.0, 1 EIO slot, 1 external and 2 and 2 is 2000, XP Home, XP professional; SOS X v10.5, OS/2, UNIX, Linux, HP Oper acom/support; if no access to the Internet, and ther; HP-UX 10.20, 11.x, 11.; Solari andows® 2000: 133 MHz processor, 64 MI Microsoft® Windows® 2003, XP, and W and later; HP-UX 10.20, 11.x, 11.; Solari adows® 2000: 133 MHz processor, 64 MI Microsoft® Windows® Server 2003: 550 512 MB RAM (Windows Vista® Ready, cl and cles; HP-UX 10.20, 11.x, 11.; Solari atolses and the state of the state of the state and state of the state of the state of the state and the state of the state of the state of the state and the state of the state of the state of the state and the state of the state of the state of the state state of the state state of the state of	internal Host USB 2.0-like ports for 3rd party con nternal Host USB 2.0-like ports for 3rd party con n/go/jetdirect Server 2003; Certified for Windows Vista®; Ma VMS, Most recent printer drivers and software for see support flyer that came in printer box 1000, Server 2003; XP, 2003 64-bit; XP indows Vista®); Novell® 5.1 and later; Mac OS s@ 2.5 and later (SPARC® systems only); IBM® soft® Windows® 2000, XP Home, XP Profession B RAM, CD-ROM drive; Microsoft® Windows® MHz processor, 128 MB RAM (standard edition heck user guide for minimum hard drive space); or 2.0 specifications), Mac OS X v10.2 or highe compliant parallel port (via HP1284B Parallel C 5e, HP PCL 6, Postscript, Postscript Printer Descr (LED) indicator lights (Ready, Data, Attention), 5 Server, HP Easy Printer Care 50/60 Hz (+/- 3 Hz); 220 to 240 VAC (+/- 107 ximum (sleep), Typical Electricity Consumption (L	nnection; P4014n: Embedded Jetdirect (Gigabit Ethernet) print innection; P4014dn: Embedded Jetdirect (Gigabit Ethernet) print innection; p4014dn: Embedded Jetdirect (Gigabit Ethernet) print innection; optional: HP Jetdirect internal print servers; HP Jetdirect OZ firmware of 10.1 or higher required). For more information or c OS X v10.2, v10.3 or higher or all supported operating systems available at Vindows Vista®, Windows Vista® 64-bit (For Microsoft® IPv6 S x v10.2, v10.3, v10.4 and later; RED HAT Linux 7.x and later, AIX 3.2.5 and later 1; MPEiX; Citrix® MetaFrame Server; ial, Server 2003; Apple Mac OS X v10.2, v10.3, v10.4, v10.5 XP Home and Professional: 233 MHz processor, 64 MB RAM, n), 220 MB of free hard disk space for Microsoft® Windows®, 1 CD-ROM drive or Internet connection, IEEE 1284-compliant r; PowerPC G3, G4, G5, or Intel® Core processor; 160 MB free ard J7972G) iption files, HP LaserJet Utility (Mac), Macintosh software buttons (Information, Return, Stop/Cancel, OK, Toggle up/down) (6), 50/60 Hz (+/- 3 Hz). Consumption: 800 watts maximum (EC): 4.11 kVM/Week		
Operating systems compatibility Network operating systems compatibility Minimum system requirements Software Control panel Printer management	P4014: 1 Hi-Sp server, 1 Hi-Spe external print se available HP ne Microsoft® Wir Optional: Mac http://www.hp Via an HP Jetdi compatible with SUSE Linux 8.x Microsoft® Wir Microsoft® Wir CD-ROM drive; GHz processor, bidirectional pa hard disk space Print drivers and 2.29 x 5.33 cm No numeric key HP Web Jetadm Requirements: In (active/printing Out of package	eed USB 2.0, 1 EIO slot, 1 external and 2 eed USB 2.0, 1 EIO slot, 1 external and 2 eed USB 2.0, 1 EIO slot, 1 external and 2 eed USB 2.0, 1 EIO slot, 1 external and 2 eed USB 2.0, 1 EIO slot, 1 external and 2 revers; HP wireless print servers; HP Secure etworking solutions visit http://www.hp.con ndows® 2000, XP Home, XP Professional; COM Support; if no access to the Internet, ecom/support; if no access to the Internet, ndicrosoft® Windows® 2003, XP, and W and later; HP-UX 10.20, 11.x, 11.i; Solari ndows® Terminal Services, optional: Microso ndows® 2000: 133 MHz processor, 64 MI Microsoft® Windows® Server 2003: 550 512 MB RAM (Windows Vista® Ready, cl ratel port, USB (compatible with USB 1.1- ; CD-ROM drive, USB port or IEEE 1284-B d installation software on CD-ROM: HP PCL i 4-line ICD display, 3 light-emitting diode las nput voltage 100 to 127 VAC (+/- 10%), 5 , 17 watts maximum (ready), 12 watts ma e: P4014: 419 x 450 x 393 mm; P4014n:	internal Host USB 2.0-like ports for 3rd party con nternal Host USB 2.0-like ports for 3rd party con nternal Host USB 2.0-like ports for 3rd party con nternal Host USB 2.0-like ports for 3rd party con High Performance EIO Hard Disk J8019A (CPE n/go/jetdirect Server 2003; Certified for Windows Vista®; Ma IVMS, Most recent printer drivers and software for see support flyer that came in printer box 1000, Server 2003, XP, 2003 64-bit, XP 64-bit; W indows Vista®; Novell® 5.1 and later; Mac OS s® 2.5 and later (SPARC® systems only); IBM® soft® Windows® 2000, XP Home, XP Profession B RAM, CD-ROM drive; Microsoft® Windows® MHz processor, 128 MB RAM (standard edition heck user guide for minimum hard drive space); or 2.0 specifications), Mac OS X v10.2 or higher compliant parallel port (via HP1284B Parallel C 5e, HP PCL 6, Postscript, Postscript Printer Descr (LED) indicator lights (Ready, Data, Attention), 5 Server, HP Easy Printer Care 50/60 Hz (+/- 3 Hz); 220 to 240 VAC (+/- 109)	nnection; P4014n: Embedded Jetdirect (Gigabit Ethernet) print innection; P4014dn: Embedded Jetdirect (Gigabit Ethernet) print innection; p4014dn: Embedded Jetdirect (Gigabit Ethernet) print innection; optional: HP Jetdirect internal print servers; HP Jetdirect OZ firmware of 10.1 or higher required). For more information or or oll supported operating systems available at Vindows Vista®, Windows Vista® 64-bit (For Microsoft® IPv6 5 X v10.2, v10.3, v10.4 and later; RED HAT Linux 7.x and later, AIX 3.2.5 and later 1; MPEiX; Citrix® MetaFrame Server; ial, Server 2003; Apple Mac OS X v10.2, v10.3, v10.4, v10.5 XP Home and Professional: 233 MHz processor, 64 MB RAM, n), 220 MB of free hard disk space for Microsoft® Windows®, 1 CD-ROM drive or Internet connection, IEEE 1284-compliant erad J7972G) iption files, HP LaserJet Utility (Mac), Macintosh software buttons (Information, Return, Stop/Cancel, OK, Toggle up/down) (6), 50/60 Hz (+/- 3 Hz). Consumption: 800 watts maximum IEC): 4.11 kWh/Week 394 mm		
Operating systems compatibility Network operating systems compatibility Minimum system requirements Software Control panel Printer management Power	P4014: 1 Hi-Sp server, 1 Hi-Spe external print se available HP ne Microsoft® Wir Optional: Mac http://www.hp Via an HP Jetdi compatible with SUSE Linux 8.x Microsoft® Wir CD-ROM drive; GHz processor, bidirectional pa hard disk space Print drivers and 2.29 x 5.33 cm No numeric key HP Web Jetadan Requirements: II (active/printing Out of packaged: P40 Out of packaged	eed USB 2.0, 1 EIO slot, 1 external and 2 eed USB 2.0, 1 EIO slot, 1 external and 2 eed USB 2.0, 1 EIO slot, 1 external and 2 eed USB 2.0, 1 EIO slot, 1 external and 2 eed USB 2.0, 1 EIO slot, 1 external and 2 revers; HP wireless print servers; HP Secure etworking solutions visit http://www.hp.con ndows® 2000, XP Home, XP Professional; COM Support; if no access to the Internet, ecom/support; if no access to the Internet, ndicrosoft® Windows® 2003, XP, and W and later; HP-UX 10.20, 11.x, 11.i; Solari ndows® Terminal Services, optional: Microso ndows® 2000: 133 MHz processor, 64 MI Microsoft® Windows® Server 2003: 550 512 MB RAM (Windows Vista® Ready, cl ratel port, USB (compatible with USB 1.1- ; CD-ROM drive, USB port or IEEE 1284-B d installation software on CD-ROM: HP PCL i 4-line ICD display, 3 light-emitting diode las nput voltage 100 to 127 VAC (+/- 10%), 5 , 17 watts maximum (ready), 12 watts ma e: P4014: 419 x 450 x 393 mm; P4014n:	internal Host USB 2.0-like ports for 3rd party con nternal Host USB 2.0-like ports for 3rd party con 100, Server 2003; Certified for Windows Vista®; Ma VMS, Most recent printer drivers and software for see support flyer that came in printer box 100, Server 2003, XP, 2003 64-bit, XP 64-bit; V indows Vista®; Novell® 5.1 and later; Mac OS s® 2.5 and later (SPARC® systems only); IBM® soft® Windows® 2000, XP Home, XP Profession B RAM, CD-ROM drive; Microsoft® Windows® MHz processor, 128 MB RAM (standard editor heck user guide for minimum hard drive space); or 2.0 specifications), Mac OS X v10.2 or highe compliant parallel port (via HP1284B Parallel C 5e, HP PCL 6, Postscript, Postscript Printer Descr (LED) indicator lights (Ready, Data, Attention), 5 Server, HP Easy Printer Care 50/60 Hz (+/- 3 Hz); 220 to 240 VAC (+/- 109 ximum (sleep), Typical Electricity Consumption (1 419 x 450 x 393 mm; P4014dn: 419 x 538 x 535 x 500 mm; P4014dn: 790 x 600 x 540 m 4014dn: 28.28 kg	nnection; P4014n: Embedded Jetdirect (Gigabit Ethernet) print innection; P4014dn: Embedded Jetdirect (Gigabit Ethernet) print innection; p4014dn: Embedded Jetdirect (Gigabit Ethernet) print innection; optional: HP Jetdirect internal print servers; HP Jetdirect OZ firmware of 10.1 or higher required). For more information or or oll supported operating systems available at Vindows Vista®, Windows Vista® 64-bit (For Microsoft® IPv6 5 X v10.2, v10.3, v10.4 and later; RED HAT Linux 7.x and later, AIX 3.2.5 and later 1; MPEiX; Citrix® MetaFrame Server; ial, Server 2003; Apple Mac OS X v10.2, v10.3, v10.4, v10.5 XP Home and Professional: 233 MHz processor, 64 MB RAM, n), 220 MB of free hard disk space for Microsoft® Windows®, 1 CD-ROM drive or Internet connection, IEEE 1284-compliant erad J7972G) iption files, HP LaserJet Utility (Mac), Macintosh software buttons (Information, Return, Stop/Cancel, OK, Toggle up/down) (6), 50/60 Hz (+/- 3 Hz). Consumption: 800 watts maximum IEC): 4.11 kWh/Week 394 mm		
Operating systems compatibility Network operating systems compatibility Minimum system requirements Software Control panel Printer management Power Dimensions (w x d x h)	P4014: 1 Hi-Sp server, 1 Hi-Spe server, 1 Hi-Spe external print se available HP ne Microsoft® Wir Optional: Mac http://www.hp Via an HP Jetdi compatible with SUSE Linux 8.x Microsoft® Wir Microsoft® Wir CD-ROM drive; GHz processor, bidirectional pa hard disk space Print drivers and 2.29 x 5.33 cm No numeric key HP Web Jetadm Requirements: In (active/printing) Out of package Packaged: P40 Objecting temp 80% RH. Storage	seed USB 2.0, 1 EIO slot, 1 external and 2 seed USB 2.0, 1 EIO slot, 1 external and 2 is duSB 2.0, 1 EIO slot, 1 external and 2 i prvers; HP wireless print servers; HP Secure tworking solutions visit http://www.hp.con ndows® 2000, XP Home, XP Professional; S OS X v10.5, OS/2, UNIX, Linux, HP Oper .com/support; if no access to the Internet; s rect print server: Microsoft® Windows® 2003, XP, and W Microsoft® Windows® 2003, XP, and W and later; HP-UX 10.20, 11.x, 11.i; Solari adows® 2000: 133 MHz processor, 64 Mi Microsoft® Windows® Server 2003: 550 512 MB RAM (Windows Vista® Ready, cl urallel port, USB (compatible with USB 1.1 s; CD-ROM drive, USB port or IEEE 1284-B d installation software on CD-ROM: HP PCL 4-line ICD display, 3 light-emitting diode I s. in, HP LaserJet Utility, HP Embedded Web mput voltage 100 to 127 VAC (+/- 10%), 5), 17 watts maximum (ready), 12 watts ma a: P4014: 419 x 450 x 393 mm; P4014n: 570 x 535 x 500 mm; 24014n: 25.82 kg; P4014n: 27 kg; P4014n: 27 kg; F4014n: 27 kg; P4014n: 27 kg; P4014dn: 29, verature: 15 to 32.5° C. Recommended op	internal Host USB 2.0-like ports for 3rd party con nternal Host USB 2.0-like ports for 3rd party con n/go/jetdirect Server 2003; Certified for Windows Vista®; Ma VMS, Most recent printer drivers and software for see support flyer that came in printer box 1000, Server 2003; XP, 2003 64-bit; XP 64-bit; V indows Vista®); Novell® 5.1 and later; Mac OS s® 2.5 and later (SPARC® systems only); IBM® soft® Windows® 2000, XP Home, XP Profession B RAM, CD-ROM drive; Microsoft® Windows® mHz processor, 128 MB RAM (standard edition heck user guide for minimum hard drive space); or 2.0 specifications), Mac OS X v10.2 or highe compliant parallel port (via HP1284B Parallel C 56, HP PCL 6, Postscript, Postscript Printer Descr (LED) indicator lights (Ready, Data, Attention), 5 Server, HP Easy Printer Care 50/60 Hz (+/- 3 Hz); 220 to 240 VAC (+/- 109; ximum (sleep), Typical Electricity Consumption [1 419 x 450 x 393 mm; P4014dn: 419 x 538 x 535 x 500 mm; P4014dn: 790 x 600 x 540 m 4014dn: 28.28 kg 6 kg errating temperature: 10 to 32° C. Operating hui ity: 10 to 95% RH. Noise level per ISO 9296: S	nnection; P4014n: Embedded Jetdirect (Gigabit Ethernet) print innection; P4014dn: Embedded Jetdirect (Gigabit Ethernet) print innection; p4014dn: Embedded Jetdirect (Gigabit Ethernet) print innection; optional: HP Jetdirect internal print servers; HP Jetdirect OZ firmware of 10.1 or higher required). For more information or or oll supported operating systems available at Vindows Vista®, Windows Vista® 64-bit (For Microsoft® IPv6 5 X v10.2, v10.3, v10.4 and later; RED HAT Linux 7.x and later, AIX 3.2.5 and later 1; MPEiX; Citrix® MetaFrame Server; ial, Server 2003; Apple Mac OS X v10.2, v10.3, v10.4, v10.5 XP Home and Professional: 233 MHz processor, 64 MB RAM, n), 220 MB of free hard disk space for Microsoft® Windows®, 1 CD-ROM drive or Internet connection, IEEE 1284-compliant erad J7972G) iption files, HP LaserJet Utility (Mac), Macintosh software buttons (Information, Return, Stop/Cancel, OK, Toggle up/down) (6), 50/60 Hz (+/- 3 Hz). Consumption: 800 watts maximum IEC): 4.11 kWh/Week 394 mm		
Operating systems compatibility Network operating systems compatibility Minimum system requirements Software Control panel Printer management Power Dimensions (w x d x h) Weight	P4014: 1 Hi-Sp server, 1 Hi-Spe external print se available HP ne Microsoft® Wir Optional: Mac http://www.hp Via an HP Jetdi compatible with SUSE Linux 8.x Microsoft® Wir CD-ROM drive; GHz processor, bidirectional pa hard disk space Print drivers and 2.29 x 5.33 cm No numeric key HP Web Jetadm Requirements: Ih (active/printing Out of package Packaged: P40 Out of package Packaged: P40 Operating temp 80% RH. Storag Sound pressure: Safety certificat	seed USB 2.0, 1 EIO slot, 1 external and 2 and USB 2.0, 1 EIO slot, 1 external and 2 and USB 2.0, 1 EIO slot, 1 external and 2 i and 25 2.0, 1 EIO slot, 1 external and 2 i and 25 2.0, 1 EIO slot, 1 external and 2 i and 25 2.0, 1 EIO slot, 1 external and 2 i and 25 2.0, 1 EIO slot, 1 external and 2 i and 25 2.0, 1 EIO slot, 1 external and 2 i and 05 2.0, 1 EIO slot, 1 external and 2 i and 05 2.0, 1 EIO slot, 1 external and 2 i and 05 2.0, 1 EIO slot, 1 external and 2 i and later; HP windows® 2003, XP, and W and later; HP-UX 10.20, 11.x, 11.i; Solari adows® 2000: 133 MHz processor, 64 MI Microsoft® Windows® Server 2003: 550 512 MB RAM (Windows® Server 2003: 550 512 MB RAM (Windows® Server 2003: 550 512 MB RAM (Windows Vista® Ready, cl arallel port, USB (compatible with USB 1.1 e; CD-ROM drive, USB port or IEEE 1284-B d installation software on CD-ROM: HP PCL 1 e4-line LCD display, 3 light-emitting diode (s an, HP LaserJet Utility, HP Embedded Web poput voltage 100 to 127 VAC (+/- 10%), 5), 17 watts maximum (ready), 12 watts ma a: P4014: 419 x 450 x 393 mm; P4014n: 570 x a: P4014: 25.82 kg; P4014n: 25.82 kg; P4 14: 27 kg; P4014n: 27 kg ; P4014dn: 29, perature: 15 to 32° C. Storage humid ispam 58 dB(A) (active/printing), 27 dB(A ions: IEC 60950-1 (International), EN 609	internal Host USB 2.0-like ports for 3rd party con nternal Host USB 2.0-like ports for 3rd party con 100, Server 2003; Certified for Windows Vista®; Ma VMS, Most recent printer drivers and software for see support flyer that came in printer box 100, Server 2003; XP, 2003 64-bit; Y 64-bit; V indows Vista®; Novell® 5.1 and later; Mac OS s® 2.5 and later (SPARC® systems only); IBM® soft@ Windows@ 2000, XP Home, XP Profession B RAM, CD-ROM drive; Microsoft® Windows@ MHz processor, 128 MB RAM (standard editior heck user guide for minimum hard drive space); or 2.0 specifications), Mac OS X v10.2 or highe compliant parallel port (via HP1284B Parallel C 5e, HP PCL 6, Postscript, Postscript Printer Descr (IED) indicator lights (Ready, Data, Attention), 5 Server, HP Easy Printer Care 50/60 Hz (+/- 3 Hz); 220 to 240 VAC (+/- 109 ximum (sleep), Typical Electricity Consumption (I 119 x 450 x 393 mm ; P4014dn: 419 x 538 x 505 x 500 mm; P4014dn: 790 x 600 x 540 m 4014dn: 28.28 kg 6 kg erating temperature: 10 to 32° C. Operating hu ity: 10 to 95% RH. Noise level per ISO 9296: S) (ready) 50-1+A11 (EU), IEC 60825-1+A1+A2, UL/cUL	nnection; P4014n: Embedded Jetdirect (Gigabit Ethernet) print unection; P4014dn: Embedded Jetdirect (Gigabit Ethernet) print unection; optional: HP Jetdirect internal print servers; HP Jetdirect OZ firmware of 10.1 or higher required). For more information or c OS X v10.2, v10.3 or higher or all supported operating systems available at Vindows Vista®, Windows Vista® 64-bit (For Microsoft® IPv6 S X v10.2, v10.3, v10.4 and later; RED HAT Linux 7.x and later, AIX 3.2.5 and later 1; MPE-iX; Citrix® MetaFrame Server; ral, Server 2003; Apple Mac OS X v10.2, v10.3, v10.4, v10.5 XP Home and Professional: 233 MHz processor, 64 MB RAM, n), 220 MB of free hard disk space for Microsoft® Windows®, 1 CD-ROM drive or Internet connection, IEEE 1284-compliant er; PowerPC G3, G4, G5, or Intel® Core processor; 160 MB free ard J7972G) iption files, HP LaserJet Utility (Mac), Macintosh software buttons (Information, Return, Stop/Cancel, OK, Toggle up/down) 6), 50/60 Hz (+/- 3 Hz). Consumption: 800 watts maximum IEC): 4.11 kWh/Week 394 mm m		

http://www.hp.com/uk



© Copyright 2008 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

