

FS-1350DN

A4 MONOCHROME DESKTOP PRINTER

► print ► copy ► scan ► fax

PERFORMANCE DESKTOP PRINTING

The new KYOCERA FS-1350DN comes complete with a high printing speed of up to 30 pages per minute, an LCD display, network connectivity, as well as a USB host port, allowing direct printing. By incorporating Kyocera's environmentally-sustainable ECOSYS design principles the FS-1350DN makes a perfect addition to the family of mono laser printers.

- Up to 30 pages per minute monochrome printing
- Double-sided printing and network connectivity as standard
- 250-sheet internal paper cassette
- 50-sheet multi-purpose tray
- Maximum paper capacity of 800 sheets from 4 sources
- 2-year warranty (Return-To-Base)
- PCL6 and PostScript 3 compatible
- 1200 dpi hardware resolution
- Warm-up time: 6.0 seconds

The highest security standards prevent data interception or misuse.



USB host enables users to printout PDF files directly from a USB stick.



FS-1350DN

A4 MONOCHROME DESKTOP PRINTER

ECOSYS stands for ECOlogy, ECOlogy and SYStem-printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflow-enhancing functions and a wide variety of paper handling capabilities as required. Integrated system software provides long-term cross-network compatibility. Kyocera's long-life components cost you and the environment less.

General

Technology

Kyocera ECOSYS, Laser

Engine speed

Up to 30 pages per minute A4

Resolution

1,200 x 1,200 dpi

Time to first page

6 seconds or less

Warm-up time from sleep

14 seconds

Warm-up time off-on

19 seconds

Duty cycle

Max. 20,000 pages per month,
average 2,000 pages per month

Power source

AC 220 ~ 240 V, 50/60 Hz

Power consumption

Printing: 484 W
Stand-by: 12 W
Power-Saving (ECOpower): 7.1 W

Noise (ISO 7779)

Printing: 54 dB(A)
Stand-by: 30 dB(A)

Power-Saving (ECOpower)

Immeasurably low

Dimensions (W x D x H)

375 x 393 x 267 mm

Weight

Main unit incl. toner: Approx. 12 kg

Certifications

TÜV/GS, CE
This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

Paper Handling

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity

250-sheet universal paper cassette, 60-120 g/m², A4, A5, A6, B5, Letter, Legal, Custom (148 x 210 mm to 216 x 297 mm)
50-sheet multi-purpose tray, 60-220 g/m², A4, A5, A6, B5, Letter, Custom (70 x 148 mm to 216 x 356 mm)

PRESCRIBE II[®]

With the KYOCERA page design and control language PRESCRIBE II[®], even complex graphics, logos and forms (including multipart forms) can be created independently on the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

The KM NetViewer

The KM NetViewer enables complete monitoring and control of all ECOSYS printers and digital Kyocera multifunctional units from any Windows[®] PC and thus provides ideal network administration. It also supports the standardised SNMP protocol.

Status Monitor and Command Center

The Status Monitor shows the current printers condition and gives direct access to the Command Center for the modification of settings that are not contained in the drivers (e.g. network settings, adjustment of sleep mode or blocking of the control panel).

USB Host Interface for USB Flash Memory

PDF files can be printed directly from a USB Flash Memory (e.g. USB stick) via the USB host interface. Documents are selected directly via the printer's control panel. No computer is required.

Max. paper capacity incl. options: 800 sheets

Duplex as standard

Output capacity

250 sheets face-down

Controller

Processor

PowerPC-440F5-500 MHz

Memory

Standard 128 MB + ECOMemory, max. 1,152 MB in 1 DDRII SDRAM DIMM slot

Standard interface

USB 2.0 (Hi-Speed), Fast Ethernet 10Base-T/100Base-TX, KUIO/W interface slot, USB Host - USB 1.1, Slot for optional CompactFlash[®]-Card

Emulations

PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible) with automatic emulation switching, Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630, PDF - 1.5, XPS Printing

Controller language

Prescribe II[®]

Fonts

101 outline fonts accessible in all emulations, 1 bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode PDF-417

Downloadable fonts

Kyocera, PCL + TrueType format, Type 1 + 3 format

Print features

Automatic duplex unit enables booklet Printing

Consumables

TK-130 Toner-kit

Microfine toner for 7,200 pages in accordance with ISO/IEC 19752*

*Capacity of starter toner is 3,600 pages in accordance with ISO/IEC 19752

Options

PF-100 Paper feeder (max. 2 units)

250 sheets, 60-120 g/m², A4, A5, A6, B5, Letter, Legal, Custom (148 x 210 mm to 216 x 356 mm)

CB-100 Cabinet

Wooden desk with storage capacity, including castors (wheels)

Memory upgrade

MDDR2-128: 128 MB; MDDR2-256: 256 MB;
MDDR2-512: 512 MB, MDDR2-1024: 1,024 MB

KYO LIFE



Your KYOCERA Business Partner:

KYOCERA MITA (UK) Ltd, 8 Beacontree Plaza, Gillette Way, Reading RG2 0BS
Tel 0118 931 1500, Fax 0118 931 1108
www.kyoceramita.co.uk, info@kyoceramita.co.uk

* KYOCERA does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged. KYOcount is a trademark of KYOCERA MITA Europe B.V.

