



Sometimes lots of colour
means lots to do.

Sometimes it doesn't.

Lexmark C530dn

Lexmark's most affordable
duplex colour printer ever!

Two-sided savings

Make considerable cost savings and help the environment at the same time with automatic duplex printing, now standard.

Up to 22 ppm mono,
21 ppm colour

Duplex as standard

PCL 6, PostScript 3 Emulation

Attractive yet fast

Reach up to 21 ppm in colour and produce professional documents with vivid 4800 Colour Quality and emulation support for PCL6 and PS3.

Easy on your workgroup

Compact, quiet and network-ready, the C530dn is easy to set up, and includes an intuitive operator panel for simplified operation.

LEXMARKTM

Lexmark C530dn

Save time. Save money. Save the environment!

Now's the perfect time to liven up your documents with brilliant colour laser printing. Very attractively priced and easy to use, the Lexmark C530dn brings big surprises to small, budget-sensitive workgroups. That includes outstanding colour, rapid print speeds, full network compatibility and automatic duplex printing – a real rarity for such a compact, exceptionally priced printer!

With duplex everyone wins

How much of your profit is heading straight for the waste bin? By printing on both sides of a page, you can now reduce paper waste and drive down costs considerably. Of course, that also means less adding paper into the drawer and therefore less user intervention. This makes it an intelligent solution for you, your budget, your workgroup and the environment.

Speed and quality unite!

With Lexmark's rich, vibrant 4800 Colour Quality you can make an impact on everything from spreadsheets to graphics to marketing presentations. But enjoying brilliant colour should never mean compromising productivity. Backed by a rapid processor and 128MB of memory, the C530dn reaches up to 21 ppm in colour, 22 ppm in monochrome.

Print Technology

Colour Laser

Print Speed (A4 mono)

Up to 22 ppm

Print Speed (Letter, Colour)

Up to 22 ppm

Print Speed (A4 colour)

Up to 21 ppm

Print Speed (Letter mono)

Up to 24 ppm

Time to First Page (Black)

as fast as < 11 seconds

Time to First Page (Colour)

as fast as < 11 seconds

Print Resolution, Black

1200 x 1200 dpi

4800 Color Quality (2400 x 600 dpi)

Print Resolution, Colour

1200 x 1200 dpi, 4800 Color Quality (2400 x 600 dpi)

Processor

375 MHz

Memory, standard

128 MB

Memory network model, maximum

640 MB

Expandable Memory Options

Yes

Apple Macintosh Operating Systems Supported

Mac OS X, Mac OS 9.x

Citrix MetaFrame

Citrix, MetaFrame and MetaFrame XP are registered trademarks or trademarks of Citrix Systems, Inc. in the U.S. and other countries., Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0., Microsoft Windows Server 2003 running Terminal Server with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0, Microsoft Windows Server 2003 running Terminal Server with Citrix Presentation Server 4.0

Linux Operating Systems Supported

Red Flag Linux Desktop 4.0, 5.0, Linpus Linux Desktop 9.2, 9.3, Red Hat Enterprise Linux WS 3.0, 4.0, SUSE Linux Enterprise Server 8.0, 9.0, SUSE Linux Professional 9.1, 9.2, 9.3, Debian GNU/Linux 3.0, 3.1, Linspire Linux 4.5, 5.0, SUSE Linux 10.0, 10.1

Microsoft Windows Operating Systems Supported

2000, NT (4.0/4.00 Server), Me, XP, Server 2003, 98 2nd Edition, XP x64, Server 2003 running Terminal Services, 2000 Server running Terminal Services, Server 2003 x64 Edition, Vista

Novell Operating Systems Supported

Open Enterprise Server for Netware with NDS, iPrint or Novell Distributed Print Services (NDPS), NetWare 5.x, 6.x with iPrint or Novell Distributed Print Services (NDPS)

UNIX Operating Systems Supported

Sun Solaris SPARC 7, 8, 9, 10, HP-UX 11.00, 11.11, IBM AIX 5.1, 5.2, 5.3, Sun Solaris x86 10

Other Operating Systems Supported

IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform, Virtually any platform supporting TCP/IP

Paper Handling (Standard)

250-Sheet Output Bin, Integrated Duplex, 100-Sheet Multipurpose Feeder, 250-Sheet Input Tray

Paper Input Capacity (Standard)

350 pages at 80 gsm bond

Paper Input Capacity (Maximum)

350 pages at 80 gsm bond

Paper Output Capacity (Standard)

250 pages at 80 gsm bond

Paper Output Capacity (Maximum)

250 pages at 80 gsm bond

Envelope Capacity

10

Finishing Option

No

Number of Paper Inputs

2

Number of Paper Inputs, Maximum

2

Media Types Supported

Card Stock, Envelopes, Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide

Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal

Standard Ports

Ethernet 10/100BaseTX (RJ-45), USB Compatible with USB 2.0 Specification

Optional Network Ports

Lexmark N4050e 802.11g Wireless Print Server (Print Only), External MarkNet™ N7020e Gigabit Ethernet, External MarkNet™ N7000e Fast Ethernet (USB)

Network Printing Methods

LPR/LPD, Direct IP (Port 9100), Socket (Raw TCP/IP), IPP (Internet Printing Protocol), HTTP, Enhanced IP (Port 9400),

FTP, TFTP

Network Protocol Support

TCP/IP IPv4, AppleTalk™, TCP/IP IPv6

Printable Area

4.2 mm of the top, bottom, right and left edges (within)

Printer Languages (Standard)

PCL 5c Emulation, PCL 6 Emulation (and PostScript 3 Emulation on E250dn), Personal Printer Data Stream (PPDS), PostScript 3 Emulation, PDF 1.5, xHTML

Packaged Size (mm - H x W x D)

570 x 633 x 553 mm

Size (mm - H x W x D)

484 x 440 x 512 mm

Weight (kg)

25.9 kg

Noise Level, Idle

31 dBA

Noise Level, Operating

53 dBA

Product Guarantee

One Year Onsite Repair, Next Business Day response time

Product Certifications

Energy Star, CSA, ICES Class B, BSMI Class B, VCCI Class B, FCC Class B, UL 60950 3rd Edition, IEC 320-1, CE Class B, CB IEC 60950, IEC 60825-1, GS (TÜV), SEMKO, UL AR, CS, TÜV Rh, C-tick mark Class B, CCC Class B, CISPIR 22 Class B, MIC Mark

Duty Cycle

Up to 65,000 one-time maximum Pages

Specified Operating Environment

Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80%

Relative Humidity, Altitude: 0 - 3048 Meters (10,000 Feet)

Cartridges

Ships with 1.5K* Black and 1.5K** CMY Return Programme Toner Cartridges

Aftermarket cartridges available :
3K* and 1.5K** CMY Return Programme Toner Cartridges.
4K* and 1.5K* Black Return Programme Toner Cartridges.

Regular Cartridges also available.

20K pages Black Photoconductor unit,
4 Pack Photoconductor (K,C,M,Y)

*Up to this number of Standard pages. Average continuous black declared cartridge yield in accordance with ISO/IEC 19798 (FDIS).

**Up to this number of Standard pages. Average continuous composite CMY declared cartridge yield in accordance with ISO/IEC 19798 (FDIS).

Cost saving & environmental features

Energy Star compliant - Integrated duplex printing, print and hold (verify print), multi-up printing and quality printing on recycled paper help reduce paper consumption - Selectable toner-saving modes help reduce the amount of toner used on a page - Return Programme cartridges and end-of-life product management help reduce landfill.

Models available

C530dn — Duplex, Network



Lexmark believes that the environment is a critical component of responsible business management and clearly demonstrates it by implementing the "4R" strategy: Reduce, Recover, Reuse and Recycle. To learn more about these programmes please visit www.lexmark.com/recycle



With our innovative solutions and services, we help you PRINT smarter, MOVE information faster and MANAGE output more efficiently across your enterprise. Ask your local Lexmark representative for more information.

Specifications are subject to change without notice. Lexmark, Lexmark with diamond design is trademark of Lexmark International, Inc. registered in the United States and/or other countries. All other trademarks are the properties of their respective owners.

www.lexmark.co.uk

LEXMARK
TM