



Watch productivity flourish with Lexmark multifunction.



print



copy



scan



fax
(X502n)



colour

Lexmark **X500n** and **X502n**

A brighter new way to simplify your office!




- Colour laser multifunction device
- Up to 31 ppm mono, 8 ppm colour
- 1200 x 600 dpi enhanced print quality
- Network-ready and easy to use

X500n

X502n

LEXMARK[™]

Lexmark **X500n and X502n**



Do it all, do it better,
do it in colour.

One colour device that does it all

You don't have to be a large organisation to tap into the benefits of brilliant colour and true multifunction productivity. Lexmark's compact and affordable X500n and X502n MFPs let you consolidate all your document functions into a single, high-performance colour device that includes printing, copying and scanning (plus faxing on the X502n). In addition to their small footprint, both devices offer you a rich range of features to boost productivity and work more efficiently than ever before.

Scan, send and save

Gone are the days of having to ship piles of hardcopies to various recipients via post or courier. Lexmark's new X500n and X502n MFPs combine fast, high-quality scanning with intuitive workflow software, which allows you to digitise documents and send them to multiple destinations in different formats. By scanning directly to PC, fax, email, application or network folder, you can streamline your business processes – and reap a world of savings too!

Lexmark X500n and X502n

Shift into high gear!

Now nothing can slow you down. Armed with a powerful host-based driver, these MFPs zip through print runs as fast as 31 ppm in mono. The 35-sheet Automatic Document Feeder makes copying large presentations a breeze – just load your stack of originals and watch them go! Of course, speed isn't the only thing you need. When you want to liven up documents with outstanding colour, you can count on Lexmark's advanced colour technology for sharp, consistent print quality every time.



Easy to install, easy to use

No one wants to waste time scratching their head over confusing set-up manuals and diagrams. With these MFPs there's no need to! Fully network-ready, both devices include auto-IP discovery, which means you can configure them in four simple mouse clicks. Once you're set-up, operating and maintenance is just as easy. The front-loading toner cartridges take seconds to replace. And the operator panel is extremely intuitive, featuring simple navigation buttons to switch between functions easily.

Which model is perfect for your needs?



Lexmark X500n

- Affordable network colour laser MFP
- Printing, copying and scanning
- Up to 31 ppm mono, 8 ppm colour



Model shown:
Lexmark X502n plus
second drawer

Lexmark X502n

- High-speed 4-function device
- Includes the added benefit of faxing
- Up to 70 speed-dial and/or speed e-mail shortcuts

Lexmark's guarantee to you : At Lexmark, we're always working hard to ensure you achieve maximum productivity and minimum downtime. Our X500n and X502n MFPs include our solid service guarantee of One-year On Site Repair, with a response time of next business day (in serviceable areas). For an even greater level of peace of mind, you can opt for one of our extended-guarantee service offerings. For more information on any of these offerings, just contact your local dealer or visit us today at www.lexmark.co.uk.

Lexmark X500n

High-performance colour printing, copying and scanning

Compact and affordable, Lexmark's X500n colour laser MFP delivers big advantages to small workgroups. These include outstanding colour output, as well as high-performance printing, copying and scanning.

Print Technology

Colour Laser

Print Speed (A4 mono)

Up to 31 ppm

Print Speed (A4 colour)

Up to 8 ppm

Print Speed (Letter mono)

Up to 31 ppm

Print Speed (Letter, Colour)

Up to 8 ppm

Time to First Page (Black)

as fast as 13 seconds

Time to First Page (Colour)

as fast as 19 seconds

Copy Speed (A4, Black)

Up to 31 cpm

Time to First Copy (Black)

as fast as 25 seconds

Print Resolution, Black

1200 x 600 dpi

Print Resolution, Colour

1200 x 600 dpi

Processor

366 MHz

Memory, standard

128 MB

Memory network model, maximum

128 MB

Expandable Memory Options

No

Apple Macintosh Operating Systems Supported

Mac OS X

Microsoft Windows Operating Systems Supported

2000, XP, Server 2003, XP x64, Server 2003 x64 Edition, Vista, Vista x64

Paper Handling (Standard)

250-Sheet Output Bin, 250-Sheet Input Tray

Paper Handling Optional

530-Sheet Drawer

Paper Input Capacity (Standard)

250 pages at 80 gsm bond

Paper Input Capacity (Maximum)

780 pages at 80 gsm bond

Paper Output Capacity (Standard)

250 pages at 80 gsm bond

Paper Output Capacity (Maximum)

250 pages at 80 gsm bond

Envelope Capacity

15

Finishing Option

No

Number of Paper Inputs

1

Number of Paper Inputs, Maximum

2

Media Types Supported

Card Stock, Envelopes, Glossy paper, Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide

Media Sizes Supported

10 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Letter, Statement, Universal, Legal with Optional Legal Tray

Standard Ports

Fast Ethernet, USB 2.0 Specification Hi-Speed Certified

Network Printing Methods

LPR/LPD, Direct IP (Port 9100), IPP (Internet Printing Protocol), HTTP

Network Protocol Support

TCP/IP IPv4, AppleTalk™

Printable Area

5.0 mm of the top, bottom, right and left edges (within)

Printer Languages (Standard)

Host-Based Printing

Reduce / Enlarge Range

25 - 400 %

Scan Area, Maximum

215.9 x 355.6 mm

Supplies Yield

1,500*-page colour Toner Cartridges (CMY), 2,500*-page black Toner Cartridge, 3,000*-page colour High Yield Toner Cartridges (CMY), 5,000*-page black High Yield Toner Cartridge, Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798., Ships with 1,500*-page CMY Toner Cartridges, Ships with 2,500*-page Black Toner Cartridge

Packaged Size (mm - H x W x D)

760 x 595 x 575 mm

Size (mm - H x W x D)

534 x 482 x 437 mm

Weight (kg)

35 kg

Noise Level, Idle

34 dBA

Noise Level, Operating

54 dBA

Copier Noise Level, Operating

54 dBA

Scanner Noise Level, Operating

44 dBA

Product Guarantee

One Year OnSite Repair

Product Certifications

FCC Class B, UL 60950-1, U.S. FDA, IEC 60320-1, CAN/CSA-C22.2 60950-00, ICES Class B, CE Class B, CB IEC 60320, IEC 60825-1, GS (TÜV), SEMKO, UL AR, CS, TÜV R, ACA C-tick mark Class B, BSMI Class B, CCC Class B, EK, MIC

Duty Cycle

Up to 35000 one-time maximum pages per month

Specified Operating Environment

Altitude: 0 - 2500 Meters (8,200 Feet), Humidity: 15 to 80% Relative Humidity, Temperature: 10 to 32°C (50 to 90°F)



Lexmark believes that the environment is a critical component of responsible business management and clearly demonstrates it by implementing the "4R" strategy: Reduce, Recover, Reuse and Recycle. To learn more about these programmes please visit www.lexmark.com/recycle



With our innovative solutions and services, we help you PRINT smarter, MOVE information faster and MANAGE output more efficiently across your enterprise. Ask your local Lexmark representative for more information.

Specifications are subject to change without notice. Lexmark, Lexmark with diamond design is trademark of Lexmark International, Inc. registered in the United States and/or other countries. All other trademarks are the properties of their respective owners.

LEXMARK

Lexmark X502n

A complete 4-in-1 solution, including advanced faxing

The Lexmark X502n offers high quality and multifunction performance, plus the added benefit of advanced faxing. Among many of its features, it boasts rapid transmission speeds to send off your faxes in as little as three seconds.

Print Technology

Colour Laser

Print Speed (A4 mono)

Up to 31 ppm

Print Speed (A4 colour)

Up to 8 ppm

Print Speed (Letter mono)

Up to 31 ppm

Print Speed (Letter, Colour)

Up to 8 ppm

Time to First Page (Black)

as fast as 13 seconds

Time to First Page (Colour)

as fast as 19 seconds

Copy Speed (A4, Black)

Up to 31 cpm

Time to First Copy (Black)

as fast as 25 seconds

Print Resolution, Black

1200 x 600 dpi

Print Resolution, Colour

1200 x 600 dpi

Processor

366 MHz

Memory, standard

128 MB

Memory network model, maximum

128 MB

Expandable Memory Options

No

Apple Macintosh Operating Systems Supported

Mac OS X

Microsoft Windows Operating Systems Supported

2000, XP, Server 2003, XP x64, Server 2003 x64 Edition, Vista

Paper Handling (Standard)

250-Sheet Output Bin, 250-Sheet Input Tray

Paper Handling Optional

530-Sheet Drawer

Paper Input Capacity (Standard)

250 pages at 80 gsm bond

Paper Input Capacity (Maximum)

780 pages at 80 gsm bond

Paper Output Capacity (Standard)

250 pages at 80 gsm bond

Paper Output Capacity (Maximum)

250 pages at 80 gsm bond

Copy/Fax/Scan (ADF) Paper Input Capacity

Up to 35 pages at 80 gsm bond

Envelope Capacity

15

Finishing Option

No

Number of Paper Inputs

1

Number of Paper Inputs, Maximum

2

Media Types Supported

Card Stock, Envelopes, Glossy paper, Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide

Media Sizes Supported

10 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Letter, Statement, Universal, Legal with Optional Legal Tray

Standard Ports

Fast Ethernet, USB 2.0 Specification Hi-Speed Certified

Network Printing Methods

LPR/LPD, Direct IP (Port 9100), HTTP, IPP 1.1 (Internet Printing Protocol)

Network Protocol Support

TCP/IP IPv4, AppleTalk™

Printable Area

5.0 mm of the top, bottom, right and left edges (within)

Printer Languages (Standard)

Host-Based Printing

Reduce / Enlarge Range

25 - 400 %

Scan Area, Maximum

215.9 x 355.6 mm

Modem Speed

33.6 Kbps

Supplies Yield

1,500*-page colour Toner Cartridges (CMY), 2,500*-page black Toner Cartridge, 3,000*-page colour High Yield Toner Cartridges (CMY), 5,000*-page black High Yield Toner Cartridge, Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798., Ships with 1,500*-page CMY Toner Cartridges, Ships with 2,500*-page Black Toner Cartridge

Packaged Size (mm - H x W x D)

760 x 595 x 575 mm

Size (mm - H x W x D)

534 x 482 x 437 mm

Weight (kg)

35 kg

Noise Level, Idle

34 dBA

Noise Level, Operating

54 dBA

Copier Noise Level, Operating

59 dBA

Scanner Noise Level, Operating

51 dBA

Product Guarantee

One Year OnSite Repair

Product Certifications

FCC Class B, UL 60950-1, U.S. FDA, IEC 60320-1, CAN/CSA-C22.2 60950-00, ICES Class B, CE Class B, CB IEC 60320, IEC 60825-1, GS (TÜV), SEMKO, UL AR, CS, TÜV R, ACA C-tick mark Class B, BSMI Class B, CCC Class B, EK, MIC

Duty Cycle

Up to 35000 one-time maximum pages per month

Specified Operating Environment

Altitude: 0 - 2500 Meters (8,200 Feet), Humidity: 15 to 80% Relative Humidity, Temperature: 10 to 32°C (50 to 90°F)



Lexmark believes that the environment is a critical component of responsible business management and clearly demonstrates it by implementing the "4R" strategy: Reduce, Recover, Reuse and Recycle. To learn more about these programmes please visit www.lexmark.com/recycle



With our innovative solutions and services, we help you PRINT smarter, MOVE information faster and MANAGE output more efficiently across your enterprise. Ask your local Lexmark representative for more information.

Specifications are subject to change without notice. Lexmark, Lexmark with diamond design is trademark of Lexmark International, Inc. registered in the United States and/or other countries. All other trademarks are the properties of their respective owners.

LEXMARK