



More colour. More options. More productivity.



print



copy



scan



fax



finishing  
optional



colour

## Lexmark **Colour Laser MFPs**

High-quality colour meets high-power multifunction!



- High-performance colour-laser multifunctions in A4 and A3
- Up to 45 ppm mono, 40 ppm colour printing
- State-of-the-art security features
- Wide range of input and finishing options

X782e

X940e

X945e

**LEXMARK**  
™

# Lexmark **Colour Laser MFPs**

Expand your horizons.



## **The ultimate multifunction solution**

In today's competitive business world, it's more important than ever to ensure your workgroups are armed with all the tools they need to stay productive. One of the most effective ways to achieve this is by integrating Lexmark's highperformance colour MFPs, which consolidate all your critical document functions into a single space-saving device. In addition to brilliant colour output and ultra-fast print speeds, you'll benefit from advanced scanning, copying, faxing and much, much more!

### **Attractive yet affordable colour**

Lexmark has mastered the art of colour, as well as the art of controlling it! With our newly enhanced toner, you can liven up your business documents with crisp text, rich flesh tones and consistent images from first page to last. And you can also control colour-output costs effectively at every level of your workflow. These devices come equipped with a complete range of colour-costcontrol tools, such as colour-print permissions and a coverage estimator to assess the cost of a job before printing.

# Lexmark **Colour Laser MFPs**

## A big touch of simplicity

Now, performing workflow tasks is extraordinarily simple for any type of user. That's because Lexmark's colour-laser MFPs are designed with a super-intuitive, award-winning touch-screen interface. Incredibly large, vivid and fully customisable, it makes working a breeze. Whether you want to scan documents, print in duplex, pull up email addresses or preview documents as you scan, it's all as easy as a couple of touches of the screen. A world of possibilities at your fingertips!



## Total security for true peace of mind

Corporate information is one of your most valuable assets, and protecting it is absolutely critical. Lexmark's colour MFPs come equipped with the most sought-after security features to ensure this information always stays safe and sound. In addition to advanced user-access restriction tools, you'll benefit from a wide range of datasecurity features too, from disk wiping and encryption to secure data transmission (Secure Socket Layer) and confidential printing.



# Lexmark **Colour Laser MFPs**

## Save time, money and paper

If you're still printing, shipping and processing piles of hardcopies, this may be eating into your profits on a daily basis. Lexmark's colour-laser MFPs provide the ideal platform to benefit from Lexmark's enterprise workflow solutions, which include distributed capture, electronic document distribution, on-demand forms and many others. Whether embedded or server-based, these solutions help you print less, lower costs, reduce waste and streamline your business processes dramatically.

## Ready for anything!

With such a versatile range of options, your possibilities are practically endless! Thanks to the multiple input drawers, you can run diverse paper types or heavy print runs. Then polish off your documents with professional finishing, including stapling (alternative configuration required for X782e). Want to create a banner with your logo, or a special promo on outdoor media? The X782e makes it easy. Want to produce your own catalogues in-house? The A3 models offer a Booklet Finisher, which lets you create dazzling colour booklets in-house.

Which model is perfect for your needs?



### Lexmark X782e

- A4 colour MFP for high-volume needs
- Printing up to 38 ppm mono, 33 ppm colour
- ColorCare cost-control tools
- State-of-the-art security features



### Lexmark X940e

- Wide-format printing up to A3
- Advanced copy and scan functions
- Printing up to 40 ppm mono, 30 ppm colour
- 1,140-sheet standard input capacity



Fully configured

### Lexmark X945e

- Wide-format printing up to A3
- Adapted to higher-volume output needs
- Printing up to 45 ppm mono, 40 ppm colour
- 3,140-sheet standard input capacity

**Lexmark's guarantee to you :** At Lexmark, we're always working hard to ensure you achieve maximum productivity and minimum downtime. Our colour-laser MFPs include our solid service guarantee of One-year On Site Repair, with a response time of next business day (in serviceable areas). For an even greater level of peace of mind, you can opt for one of our extended-guarantee service offerings. For more information on any of these offerings, just contact your local dealer or visit us today at [www.lexmark.com](http://www.lexmark.com).

# Lexmark X782e

## Outstanding colour and intuitive interface – a brilliant combination

The Lexmark X782e offers brilliant colour output and a rich range of multifunction features – all in a single high-performance, space-saving A4 device. And it will boost your productivity with rapid print speeds up to 38 ppm in mono, 33 ppm in colour.

### Print Technology

Color Laser

### Function

Color Copying, Color Printing, Color Scanning, Faxing, Color Network Scanning

### Print Speed (A4, Black)

Up to 38 ppm

### Print Speed (Letter, Colour)

Up to 35 ppm

### Print Speed (A4, Colour)

Up to 33 ppm

### Print Speed (A4, Black) Duplex

Up to 38 spm

### Print Speed (Letter, Black)

Up to 40 ppm

### Print Speed (Letter, Black) Duplex

Up to 40 spm

### Time to First Page (Black)

As fast as 11 seconds

### Time to First Page (Colour)

As fast as 13 seconds

### Copy Speed (A4, Black)

Up to 38 cpm

### Time to First Copy (Black)

as fast as < 14 seconds

### Print Resolution, Black

1200 x 1200 dpi

4800 Color Quality (2400 x 600 dpi)

### Print Resolution, Colour

1200 x 1200 dpi, 4800 Color Quality

(2400 x 600 dpi)

### Scanning Resolution

300 X 300 dpi (colour), 600 X 600 dpi

(mono)

### Processor

800 MHz

### Memory, Standard

768 MB

### Memory, Maximum

768 MB

### Expandable Memory Options

No

### Apple Macintosh Operating Systems Supported

Mac OS X, Mac OS 9.x

### Citrix MetaFrame

Citrix, MetaFrame and MetaFrame XP are registered trademarks or trademarks of Citrix Systems, Inc. in the U.S. and other countries., Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0., Microsoft Windows Server 2003 running Terminal Server with Citrix MetaFrame XP Presentation Server or

Citrix MetaFrame Presentation Server

3.0, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0, Microsoft Windows Server 2003 running Terminal Server with Citrix Presentation Server 4.0, Microsoft Windows Server 2003 x64 Edition (Standard, Enterprise) running Terminal Server with Citrix Presentation Server 4.0

### Linux Operating Systems Supported

Red Flag Linux Desktop 4.0, 5.0, Linpus Linux Desktop 9.2, 9.3, Red Hat Enterprise Linux WS 3.0, 4.0, 5.0, SUSE Linux Enterprise Server 8.0, 9.0, 10.0, Debian GNU/Linux 3.1, Linspire Linux 5.0, SUSE Linux 10.0, 10.1, 10.2

### Microsoft Windows Operating Systems Supported

2000, NT (4.00/4.00 Server), XP, Server 2003, XP x64, Server 2003 running Terminal Server, 2000 Server running Terminal Services, Server 2003 x64 Edition, Server 2003 x64 Edition running Terminal Services, Vista, Vista x64

### Novell Operating Systems Supported

Open Enterprise Server for Netware with NDS, iPrint or Novell Distributed Print Services (NDPS), NetWare® 3.2, 4.2 (bindery), NetWare 4.2, 5.x and 6.x (NDS), NetWare 5.x, 6.x with iPrint or Novell Distributed Print Services (NDPS)

### UNIX Operating Systems Supported

Sun Solaris SPARC 7, 8, 9, 10, HP-UX 11.00, 11.1, IBM AIX 5.1, 5.2, 5.3, Sun Solaris x86 10

### Other Operating Systems Supported

IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform, Virtually any platform supporting TCP/IP

### Paper Handling Standard

250-Sheet Output Bin, 500-Sheet Drawer, 500-Sheet Input Tray, Duplex Unit, Second 500-Sheet Drawer, 100-Sheet Multipurpose Feeder

### Paper Handling Optional

Banner Media Tray

### Paper Input Capacity (Standard)

1600 pages 20 lb or 75 gsm bond

### Paper Input Capacity (Maximum)

1600 pages 20 lb or 75 gsm bond

### Paper Output Capacity (Standard)

250 pages 20 lb or 75 gsm bond

### Paper Output Capacity (Maximum)

250 pages 20 lb or 75 gsm bond

### Copy/Fax/Scan (ADF) Paper Input Capacity

Up to 50 pages 20 lb or 75 gsm bond

### Envelope Capacity

10

### Finishing Option

No

### Number of Paper Inputs

4

### Number of Paper Inputs, Maximum

4

### Media Types Supported

Card Stock, Envelopes, Glossy paper, Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide, Banner Paper

### Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Banner

### Connectivity (standard)

Fast Ethernet, USB Compatible with USB 2.0 Specification, USB Direct interface on Operator Panel

### Connectivity (optional)

Lexmark N4050e 802.11g Wireless Print Server (Print Only), External MarkNet™ N7020e Gigabit Ethernet

### Network Printing Methods

LPR/LPD, Direct IP (Port 9100), Socket (Raw TCP/IP), IPP (Internet Printing Protocol), HTTP, NDS Queue-based Printing, NDPS/NEPS (Novell Distributed Print Services), Novell Netware Enterprise Print Services, Enhanced IP (Port 9400)

### Network Protocol Support

TCP/IP IPv4, IPX/SPX, AppleTalk™, LexLink (DLC), TCP/IP IPv6

### Network Security

SSL Enabled Embedded Web Server, SNMPv3, TCP/IP port access control, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPSec

### Printable Area

4.2 mm of the top, bottom, right and left edges (within)

### Printer Languages (Standard)

PCL 5c Emulation, PCL 6 Emulation, PPDS, PostScript 3 Emulation, PDF 1.5 Emulation, xHTML, Direct Image

### Reduce / Enlarge Range

25 - 400 %

### Scan Area, Maximum

216 x 355.6 mm

### Modem Speed

33.6 Kbps

### Packaged Size (mm - H x W x D)

810 x 795 x 650: 1245 x 1219 x 1016 mm

### Size (mm - H x W x D)

1410 x 679 x 584 mm

### Weight (kg)

97.5 kg

### Acoustics/Noise level (Idle mode)

31 dBA

### Acoustics/Noise level (Operating mode)

50 dBA

### Copy Noise Level, Operating

49 dBA

### Scan Noise Level, Operating

49 dBA

### Product Guarantee

One Year Onsite Repair

### Product Certifications

CSA, ICES Class A, BSMI Class A, VCCI Class A, FCC Class A, UL 60950-1, IEC 60320-1, CE Class A, CB IEC 60950-1, IEC 60825-1, GS (TÜV), SEMKO, UL AR, CS, TÜV Rh, C-tick mark Class A, CCC Class A

### Duty Cycle

Up to 150,000 (one-time monthly usage) Pages per month (one-time monthly usage)

### Specified Operating Environment

Temperature:

16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 3048 Meters (10,000 Feet)

### Supplies Yield

6,000\*-page (CMYK) Print Cartridges, 10,000\*-page (CMYK) High Yield Print Cartridges, 15,000\*-page (CMYK) Extra High Yield Print Cartridges, Ships with 10,000\*-page black and colour High Yield Return Program Print Cartridges, \*Average continuous black or continuous composite CMY declared cartridge yield up to this # of standard pages in accordance with ISO/IEC 19798.



Lexmark believes that the environment is a critical component of responsible business management and clearly demonstrates it by implementing the "4R" strategy: Reduce, Recover, Reuse and Recycle. To learn more about these programmes please visit [www.lexmark.com/recycle](http://www.lexmark.com/recycle)



With our innovative solutions and services, we help you PRINT smarter, MOVE information faster and MANAGE output more efficiently across your enterprise. Ask your local Lexmark representative for more information.

Specifications are subject to change without notice. Lexmark, Lexmark with diamond design is trademark of Lexmark International, Inc. registered in the United States and/or other countries. All other trademarks are the properties of their respective owners.

# LEXMARK

# Lexmark X940e

## Competitive colour MFP for all your wide-format needs

Network-ready, competitive and easy to use, the Lexmark X940e is the ideal solution for mid-sized workgroups with regular A3 colour needs. Benefit from brilliant colour output and zip through print runs as fast as 40 ppm in mono, 30 ppm in colour.

### Print Technology

Color Laser

#### Function

Color Copying, Color Printing, Faxing, Color Network Scanning

#### Print Speed (A4, Black)

Up to 40 ppm

#### Print Speed (Letter, Colour)

Up to 30 ppm

#### Print Speed (A4, Colour)

Up to 30 ppm

#### Print Speed (A4, Black) Duplex

Up to 37 spm

#### Print Speed (Letter, Black)

Up to 40 ppm

#### Print Speed (Letter, Black) Duplex

Up to 37 spm

#### Time to First Page (Black)

As fast as 5 seconds

#### Time to First Page (Colour)

As fast as 10 seconds

#### Copy Speed (A4, Black)

Up to 40 cpm

#### Time to First Copy (Black)

as fast as 6.6 seconds

#### Print Resolution, Black

2400 Image Quality

#### Print Resolution, Color

2400 Image Quality

#### Scanning Resolution

600 X 300 dpi (colour), 600 X 600 dpi (mono)

#### Memory, Standard

512 MB

#### Memory, Maximum

1,024 MB

#### Expandable Memory Options

Yes

#### Apple Macintosh Operating Systems Supported

Mac OS X, Mac OS 9.x, Mac OS X (10.4 Intel), Mac OS X (10.4 Power PC)

#### Citrix MetaFrame

Citrix, MetaFrame and MetaFrame XP are registered trademarks or trademarks of Citrix Systems, Inc. in the U.S. and other countries., Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0., Microsoft Windows Server 2003 running Terminal Server with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0, Microsoft

Windows Server 2003 running Terminal Server with Citrix Presentation Server 4.0, Microsoft Windows Server 2003 x64 Edition (Standard, Enterprise) running Terminal Server with Citrix Presentation Server 4.0

#### Linux Operating Systems Supported

Red Flag Linux Desktop 4.0, 5.0, Linpus Linux Desktop 9.2, 9.3, Red Hat Enterprise Linux WS 3.0, 4.0, 5.0, SUSE Linux Enterprise Server 8.0, 9.0, 10.0, SUSE Linux Professional 9.1, 9.2, 9.3, Debian GNU/Linux 3.1, Linspire Linux 5.0, SUSE Linux 10.0, 10.1, 10.2

#### Microsoft Windows Operating Systems Supported

2000, NT (4.00/4.00 Server), XP, Server 2003, XP x64, Server 2003 running Terminal Server, 2000 Server running Terminal Services, Server 2003 x64 Edition, Server 2003 x64 Edition running Terminal Services, Vista, Vista x64

#### Novell Operating Systems Supported

Open Enterprise Server for Netware with NDS, iPrint or Novell Distributed Print Services (NDPS), NetWare® 3.2, 4.2 (bindery), NetWare 4.2, 5.x and 6.x (NDS), NetWare 5.x, 6.x with iPrint or Novell Distributed Print Services (NDPS)

#### UNIX Operating Systems Supported

Sun Solaris SPARC 7, 8, 9, 10, HP-UX 11.00, 11.1, IBM AIX 5.1, 5.2, 5.3, Sun Solaris x86 10

#### Other Operating Systems Supported

IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform, Virtually any platform supporting TCP/IP

#### Paper Handling Standard

Integrated Duplex, 100-Sheet Multipurpose Feeder, 520-Sheet Input Tray, 520-Sheet Drawer Stand with Cabinet

#### Paper Handling Optional

3,500-Sheet Finisher

#### Paper Input Capacity (Standard)

1140 pages 20 lb or 75 gsm bond

#### Paper Input Capacity (Maximum)

1140 pages 20 lb or 75 gsm bond

#### Paper Output Capacity (Standard)

400 pages 20 lb or 75 gsm bond

#### Paper Output Capacity (Maximum)

3500 pages 20 lb or 75 gsm bond

#### Copy/Fax/Scan (ADF) Paper Input

### Capacity

Up to 75 pages 20 lb or 75 gsm bond

#### Finishing Option

Yes

#### Number of Paper Inputs

3

#### Number of Paper Inputs, Maximum

3

#### Media Types Supported

Card Stock, Envelopes, Glossy paper, Paper Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide

#### Media Sizes Supported

10 Envelope, A3, A4, A5, C5 Envelope, DL Envelope, Executive, Folio, JIS-B4, JIS-B5, Ledger, Legal, Letter, Statement, Universal

#### Connectivity (standard)

One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified, USB Direct interface on Operator Panel, Gigabit Ethernet (10/100/1000), USB port (Type A) compatible with USB 2.0 Specification

#### Connectivity (optional)

Lexmark N4050e 802.11g Wireless Print Server (Print Only), Internal MarkNet™ N8050 802.11g Wireless, Internal MarkNet™ N8030 Fiber Fast Ethernet

#### Network Printing Methods

LPR/LPD, Direct IP (Port 9100), Socket (Raw TCP/IP), IPP (Internet Printing Protocol), HTTP, NDS Queue-based Printing, NDPS/NEPS (Novell Distributed Print Services, Novell Netware Enterprise Print Services), Enhanced IP (Port 9400), FTP, TFTP, IPP 1.1 (Internet Printing Protocol)

#### Network Protocol Support

TCP/IP IPv4, IPX/SPX, AppleTalk™, LexLink (DLC), TCP/IP IPv6

#### Network Security

SSL Enabled Embedded Web Server, SNMPv3, TCP/IP port access control, Authenticated and encrypted MarkVision Professional communication, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPsec

#### Printable Area

4.0 mm of the top, bottom, right and left edges (within)

#### Printer Languages (Standard)

PCL 5c Emulation, PCL 6 Emulation,

PPDS, PostScript 3 Emulation, xHTML, PDF 1.6, Direct Image

#### Reduce / Enlarge Range

25 - 400 %

#### Scan Area, Maximum

297 x 432 mm

#### Modem Speed

33.6 Kbps

#### Packaged Size (mm - H x W x D)

1480 x 740 x 925 mm

#### Size (mm - H x W x D)

1153 x 660 x 810 mm

#### Weight (kg)

173.7 kg

#### Acoustics/Noise level (Idle mode)

34 dBA

#### Acoustics/Noise level (Operating mode)

52 dBA

#### Copy Noise Level, Operating

53 dBA

#### Scan Noise Level, Operating

54 dBA

#### Product Guarantee

One Year Onsite Repair

#### Network Certifications

Energy Star, CSA, ICES Class A, BSMI Class A, VCCI Class A, FCC Class A, UL 60950-1, IEC 60320, CE Class A, CB IEC 60950-1, IEC 60825-1, CISPR 22 Class A, GS (TUV), SEMKO, UL AR, CS, TÜV Rh, A-tick mark Class A, CCC Class A

#### Duty Cycle

Up to 150,000 one-time maximum Pages per month (one-time monthly usage)

#### Specified Operating Environment

Temperature:

16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 2500 Meters (8,200 Feet)

#### Supplies Yield

\*Average continuous black or continuous composite CMY declared cartridge yield up to this # of standard pages in accordance with ISO/IEC 19798., Ships with 13,000\*-page black and 12,000\*-page colour Toner Cartridges, 22,000\*-page colour (CMY) Toner Cartridges, 36,000\*-page Black Toner Cartridge



Lexmark believes that the environment is a critical component of responsible business management and clearly demonstrates it by implementing the "4R" strategy: Reduce, Recover, Reuse and Recycle. To learn more about these programmes please visit [www.lexmark.com/recycle](http://www.lexmark.com/recycle)



With our innovative solutions and services, we help you PRINT smarter, MOVE information faster and MANAGE output more efficiently across your enterprise. Ask your local Lexmark representative for more information.

Specifications are subject to change without notice. Lexmark, Lexmark with diamond design is trademark of Lexmark International, Inc. registered in the United States and/or other countries. All other trademarks are the properties of their respective owners.

# LEXMARK

# Lexmark X945e

## Wide-format colour MFP ideal for high-volume printing

The ultimate high-power workhorse, the Lexmark X945e gives you the quality, speed and versatility you need to keep all your production runs in-house. That includes print speeds up to 45 ppm in mono, 40 ppm in colour, and standard input capacity up to 3,140 sheets.

### Print Technology

Color Laser

#### Function

Color Copying, Color Printing, Faxing, Color Network Scanning

#### Print Speed (A4, Black)

Up to 45 ppm

#### Print Speed (Letter, Colour)

Up to 40 ppm

#### Print Speed (A4, Colour)

Up to 40 ppm

#### Print Speed (A4, Black) Duplex

Up to 37 spm

#### Print Speed (Letter, Black)

Up to 45 ppm

#### Print Speed (Letter, Black) Duplex

Up to 37 spm

#### Time to First Page (Black)

As fast as 5.2 seconds

#### Time to First Page (Colour)

As fast as 10 seconds

#### Copy Speed (A4, Black)

Up to 45 cpm

#### Time to First Copy (Black)

as fast as 6.7 seconds

#### Print Resolution, Black

2400 Image Quality

#### Print Resolution, Color

2400 Image Quality

#### Scanning Resolution

600 X 300 dpi (colour), 600 X 600 dpi (mono)

#### Memory, Standard

512 MB

#### Memory, Maximum

1,024 MB

#### Expandable Memory Options

Yes

#### Apple Macintosh Operating Systems Supported

Mac OS X, Mac OS 9.x, Mac OS X (10.4 Intel), Mac OS X (10.4 Power PC)

#### Citrix MetaFrame

Citrix, MetaFrame and MetaFrame XP are registered trademarks or trademarks of Citrix Systems, Inc. in the U.S. and other countries., Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0., Microsoft Windows Server 2003 running Terminal Server with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0, Microsoft

Windows Server 2003 running Terminal Server with Citrix Presentation Server 4.0, Microsoft Windows Server 2003 x64 Edition (Standard, Enterprise) running Terminal Server with Citrix Presentation Server 4.0

#### Linux Operating Systems Supported

Red Flag Linux Desktop 4.0, 5.0, Linpus Linux Desktop 9.2, 9.3, Red Hat Enterprise Linux WS 3.0, 4.0, 5.0, SUSE Linux Enterprise Server 8.0, 9.0, 10.0, SUSE Linux Professional 9.1, 9.2, 9.3, Debian GNU/Linux 3.1, Linspire Linux 5.0, SUSE Linux 10.0, 10.1, 10.2

#### Microsoft Windows Operating Systems Supported

2000, NT (4.00/4.00 Server), XP, Server 2003, XP x64, Server 2003 running Terminal Services, Server 2003 x64 Edition, Server 2003 x64 Edition running Terminal Services, Vista, Vista x64

#### Novell Operating Systems Supported

Open Enterprise Server for Netware with NDS, iPrint or Novell Distributed Print Services (NDPS), NetWare® 3.2, 4.2 (bindery), NetWare 4.2, 5.x and 6.x (NDS), NetWare 5.x, 6.x with iPrint or Novell Distributed Print Services (NDPS)

#### UNIX Operating Systems Supported

Sun Solaris SPARC 7, 8, 9, 10, HP-UX 11.00, 11.1, IBM AIX 5.1, 5.2, 5.3, Sun Solaris x86 10

#### Other Operating Systems Supported

IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform, Virtually any platform supporting TCP/IP

#### Paper Handling Standard

Integrated Duplex, 100-Sheet Multipurpose Feeder, 520-Sheet Input Tray, 2520-Sheet High Capacity Feeder Stand

#### Paper Handling Optional

3,500-Sheet Finisher, Booklet Finisher

#### Paper Input Capacity (Standard)

3140 pages 20 lb or 75 gsm bond

#### Paper Input Capacity (Maximum)

3140 pages 20 lb or 75 gsm bond

#### Paper Output Capacity (Standard)

400 pages 20 lb or 75 gsm bond

#### Paper Output Capacity (Maximum)

3500 pages 20 lb or 75 gsm bond

#### Copy/Fax/Scan (ADF) Paper Input

### Capacity

Up to 75 pages 20 lb or 75 gsm bond

#### Envelope Capacity

not define

#### Finishing Option

Yes

#### Number of Paper Inputs

5

#### Number of Paper Inputs, Maximum

5

#### Media Types Supported

Card Stock, Envelopes, Glossy paper, Paper Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide

#### Media Sizes Supported

10 Envelope, A3, A4, A5, C5 Envelope, DL Envelope, Executive, Folio, JIS-B4, JIS-B5, Ledger, Legal, Letter, Statement, Universal

#### Connectivity (standard)

One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified, USB Direct interface on Operator Panel, Gigabit Ethernet (10/100/1000), USB port (Type A) compatible with USB 2.0 Specification

#### Connectivity (optional)

Lexmark N4050e 802.11g Wireless Print Server (Print Only), Internal MarkNet™ N8050 802.11g Wireless, Internal MarkNet™ N8030 Fiber Fast Ethernet

#### Network Printing Methods

LPR/LPD, Direct IP (Port 9100), Socket (Raw TCP/IP), IPP (Internet Printing Protocol), HTTP, NDS Queue-based Printing, NDPS/NEPS (Novell Distributed Print Services, Novell Netware Enterprise Print Services), Enhanced IP (Port 9400), FTP, TFTP, IPP 1.1 (Internet Printing Protocol)

#### Network Protocol Support

TCP/IP IPv4, IPX/SPX, AppleTalk™, LexLink (DLC), TCP/IP IPv6

#### Network Security

SSL Enabled Embedded Web Server, SNMPv3, TCP/IP port access control, Authenticated and encrypted MarkVision Professional communication, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPsec

#### Printable Area

4.0 mm of the top, bottom, right and left edges (within)

### Printer Languages (Standard)

PCL 5c Emulation, PCL 6 Emulation, PPDS, PostScript 3 Emulation, xHTML, PDF 1.6, Direct Image

#### Reduce / Enlarge Range

25 - 400 %

#### Scan Area, Maximum

297 x 432 mm

#### Modem Speed

33.6 Kbps

#### Packaged Size (mm - H x W x D)

1480 x 740 x 925 mm

#### Size (mm - H x W x D)

1153 x 660 x 810 mm

#### Weight (kg)

173.7 kg

#### Acoustics/Noise level (Idle mode)

34 dBA

#### Acoustics/Noise level (Operating mode)

52 dBA

#### Copy Noise Level, Operating

53 dBA

#### Scan Noise Level, Operating

54 dBA

#### Product Guarantee

One Year Onsite Repair

#### Product Certifications

Energy Star, CSA, ICES Class A, BSMI Class A, VCCI Class A, FCC Class A, UL 60950-1, IEC 60320, CE Class A, CB IEC 60950-1, IEC 60825-1, CISPR 22 Class A, GS (TÜV), SEMKO, UL AR, CS, TÜV Rh, A-tick mark Class A, CCC Class A

#### Duty Cycle

Up to 200,000 one-time maximum Pages per month (one-time monthly usage)

#### Specified Operating Environment

Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 2500 Meters (8,200 Feet)

#### Supplies Yield

\*Average continuous black or continuous composite CMY declared cartridge yield up to this # of standard pages in accordance with ISO/IEC 19798., Ships with 13,000\*-page black and 12,000\*-page colour Toner Cartridges, 22,000\*-page colour (CMY) Toner Cartridges, 36,000\*-page Black Toner Cartridge



Lexmark believes that the environment is a critical component of responsible business management and clearly demonstrates it by implementing the "4R" strategy: Reduce, Recover, Reuse and Recycle. To learn more about these programmes please visit [www.lexmark.com/recycle](http://www.lexmark.com/recycle)



With our innovative solutions and services, we help you PRINT smarter, MOVE information faster and MANAGE output more efficiently across your enterprise. Ask your local Lexmark representative for more information.

Specifications are subject to change without notice. Lexmark, Lexmark with diamond design is trademark of Lexmark International, Inc. registered in the United States and/or other countries. All other trademarks are the properties of their respective owners.

# LEXMARK