



Sometimes you're ready  
to spend it all.

Sometimes you don't have to.

# Lexmark X850e

An affordable path  
to workgroup efficiency!

A3

Up to 35 ppm

Low volume duty cycle

3100 sheets standard  
input capacity

## The perfect fit for your budget

Affordably priced, the X850e MFP offers a rich range of innovative features to help you work more easily and productively than ever before.

## Now showing on the 'big screen'

The incredibly large, customisable touch-screen gives you fast access to a number of easy-to-use functions, including duplex colour scanning.

## Faster and more robust

The X850e delivers 35 ppm print speeds, rapid time to first page, advanced finishing, and large standard input capacity of 3,100 sheets.

We make printing easy

**LEXMARK**<sup>TM</sup>

# Lexmark X850e

## Down with heavy costs. Up with productivity!

Ideal for small to mid-size businesses with wide-format mono needs, the Lexmark X850e takes care of all your printing, copying, scanning and faxing in just one compact device. Offering rapid 35 ppm print speeds and plenty of innovative features, it saves you time, money, floor space, and even electricity.

### Touch the future

It doesn't take long to see why the X850e will be a welcome addition to your office. Its huge LCD touch-screen offers a visually attractive – and extremely practical – way to access all the features you need. Intuitive, adjustable and fully customisable, it's your gateway to greater business efficiency.

### Scan and copy with ease

The large flatbed colour scanner is great for scanning and copying big reports. You can even preview scans on the LCD screen, or scan straight to a USB key. And if it's a big stack of 2-sided originals you need copied, no problem. Just place it into the 75-page Automatic Document Feeder, touch the screen and go!

### Print Technology: Monochrome Laser

**Function:** Copying, Faxing, Network Scanning, Printing

### Time to First Page (Black)

as fast as 6.8 seconds

### Copy Speed (Ltr, Black): Up to 35 cpm

### Time to First Copy (Black)

as fast as 10 seconds

### Simplex Scan Speed (Ltr, Black)

Up to 55 Sides per minute

### Simplex Scan Speed (Ltr, Colour)

Up to 27.5 Sides per minute

### Duplex Scan Speed (Ltr, Black)

Up to 50 Sides per minute

### Duplex Scan Speed (Ltr, Colour)

Up to 18 Sides per minute

### Print Resolution, Black

1200 Image Quality, 1200 x 1200 dpi, 2400 Image Quality, 600 x 600 dpi

### Scanning Resolution

600 X 600 dpi, 600 X 300 dpi (colour)

### Processor: 625 MHz

**Memory, Standard:** 256 MB

**Memory, Maximum:** 768 MB

**Expandable Memory Options:** Yes

### Apple Macintosh Operating Systems Supported

Apple Mac OS X, Apple Mac OS 9.x

### Citrix MetaFrame

### Linux Operating Systems Supported

### Microsoft Windows Operating Systems Supported

Microsoft Windows 2000, (Professional/Server/Advanced Server), Microsoft Windows NT (4.00/4.00 Server), Microsoft Windows Me, Microsoft Windows XP (Home, Professional), Microsoft Windows XP Professional x64, Microsoft Windows Server 2003 (Standard, Enterprise) running Terminal Server, Microsoft Windows 2000 Server running Terminal Services, Microsoft Windows Server 2003 (Standard, Enterprise) x64 Edition, Microsoft Windows Server 2003

x64 Edition (Standard, Enterprise) running Terminal Services

### Novell Operating Systems Supported

Novell® Open Enterprise Server for Netware with NDS, iPrint or Novell Distributed Print Services (NDPS), Novell NetWare® 3.2, 4.2 (bindery), Novell NetWare 4.2, 5.x and 6.x (NDS), Novell NetWare 5.x, 6.x with iPrint or Novell Distributed Print Services (NDPS)

### UNIX Operating Systems Supported

HP-UX 11.00, 11.11, IBM AIX 5.1, 5.2, 5.3, Sun Solaris x86 10

### Other Operating Systems Supported

IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform, Virtually any platform supporting TCP/IP

### Paper Handling Standard

500-Sheet Output Bin

### Duplex Unit

Two 500-Sheet Trays, 100-Sheet Multipurpose Feeder, 2,000-Sheet Dual Input

### Paper Handling Optional

2,000-Sheet High-capacity Feeder, 3,500-Sheet Finisher

### Paper Input Capacity (Standard)

3100 pages 75 gsm bond

### Paper Input Capacity (Maximum)

5100 pages 75 gsm bond

### Paper Output Capacity (Standard)

500 pages 75 gsm bond

### Paper Output Capacity (Maximum)

3800 pages 75 gsm bond

### Copy/Fax/Scan (ADF) Paper Input Capacity

Up to 75 pages 20 lb or 75 gsm bond

### Envelope Capacity: 10

### Finishing Option? Yes

### Number of Paper Inputs: 5

### Number of Paper Inputs, Maximum: 6

### A boost in performance

Maximise uptime and get your documents in your hands faster!

Combining rapid output speeds with a standard 3,100-sheet input capacity, and an optional finisher for stapling, stacking and hole-punch, the X850e delivers the uninterrupted performance you need to stay productive.

### Solutions-ready

Take workflow efficiency to new levels. The X850e is equipped with Lexmark's new Embedded Solutions framework, offering you network-friendly, native support for Lexmark's wide range of enterprise solutions, such as Optra Forms, ImageQuick, DLE applications and many others.

### Media Types Supported

Card Stock, Envelopes, Paper Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide

### Media Sizes Supported

10 Envelope, 7 3/4 Envelope, A3, A4, A5, C5 Envelope, DL Envelope, Executive, Folio, JIS-B4, JIS-B5, Ledger, Legal, Letter, Statement

### Standard Ports

Centronics IEEE 1284 Bidirectional Parallel, Ethernet 10/100BaseTX (RJ-45), One Internal Card Slot, USB Compatible with USB 2.0 Specification, USB Direct interface on Operator Panel, Optional Local Ports, Internal RS-232C serial, Internal 1284-B Bidirectional Parallel

### Optional Network Ports

Lexmark N4050e 802.11g Wireless Print Server (Print Only), External 802.11g Wireless

### Network Printing Methods

LPR/LPD, Direct IP (Port 9100), Socket (Raw TCP/IP), IPP (Internet Printing Protocol), HTTP, NDS Queue-based Printing, NDPS/NEPS (Novell Distributed Print Services, Novell Netware Enterprise Print Services), Enhanced IP (Port 9400), FTP, TFTP

### Network Protocol Support

TCP/IP IPv4, IPX/SPX, AppleTalk™, LexLink (DLC), TCP/IP IPv6

TCP/IP Set of Application Services

### Zero configuration, DDNS, mDNS, NTP:

Network Time Protocol, ping, finger, telnet, TFTP

### Network Management Protocols

HTTP, HTTPS (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, SLPv1, IGMP, BOOTP, RARP, AIPPA (AutolP), DHCP, ICMP, DNS

### Network Security

SSL Enabled Embedded Web Server, SNMPv3, TCP/IP port access control, Authenticated and encrypted MarkVision Professional communication, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPSec

### Printable Area (metric)

4 mm of the top, bottom, right and left edges (within)

### Printer Languages (Standard)

PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, PDF 1.5

### Reduce / Enlarge Range: 25 - 400 %

### Scan Area, Maximum (mm): 297 x 432 mm

### Modem Speed: 33.6 Kbps

### Packaged Size (mm - H x W x D)

1380 x 890 x 850 mm

### Size (mm - H x W x D)

1095 x 640 x 700 mm

### Weight (kg): 105.7 kg

### Noise Level, Idle: 32 dBA

### Copy Noise Level, Operating: 52 dBA

### Copy Noise Level, Operating: 56 dBA

### Scan Noise Level, Operating: 54 dBA

### Product Guarantee: One Year or 600,000 impressions - OnSite Repair

### Product Certifications

Energy Star, CSA, ICES Class A, BSMI Class A, VCCI Class A, FCC Class A, UL 60950-1, IEC 320-1, ECMA-74, CE Class A, CB IEC 60950 1, IEC 61000-3-2 and -3-3, EN 55022, EN 55024, CISPIR 22 Class A, GS (TÜV)-EN 60950-1, SEMKO, UL AR, CS, TÜV Rh, N Mark, C-tick Class A, CCC Class A, RPC, PSB, MIC, EK - K60950

### Duty Cycle: Up to 150,000 one-time maximum Impressions per month

### Specified Operating Environment

Temperature: 16 to 32°C (60 to 90°F) Humidity: 8 to 80% Relative Humidity Altitude: 0 - 3048 Meters (10,000 Feet)



### Supplies

Ships with 30K\* pages Return toner cartridge  
Ships with 60K Photoconductor Kit  
30K\* pages High Yield toner cartridge (aftermarket).  
48K pages Photoconductor Kit

- Printers and supplies are designed for use in Europe, Middle East and Africa only

\* Average cartridge yield. Declared yield value in accordance with ISO/IEC 19752.

### Model available

- X850e



Lexmark believes that the environment is a critical component of responsible business management and clearly demonstrates it by implementing the "4R" strategy: Reduce, Recover, Reuse and Recycle. To learn more about these programmes please visit [www.lexmark.com/recycle](http://www.lexmark.com/recycle)



With our innovative solutions and services, we help you PRINT smarter, MOVE information faster and MANAGE output more efficiently across your enterprise. Ask your local Lexmark representative for more information.

Specifications are subject to change without notice. Lexmark, Lexmark with diamond design is trademark of Lexmark International, Inc. registered in the United States and or other countries. All other trademarks are the properties of their respective owners.

[www.lexmark.co.uk](http://www.lexmark.co.uk)

**LEXMARK**  
TM