



Sometimes big ambition  
means big spending.



Sometimes it doesn't.

# Lexmark X854e

A complete solution for your  
heaviest departmental needs!

A3

Up to 55 ppm

High-volume duty cycle

Finishing capabilities

## Tireless performance

With output as fast as 55 ppm, and a very robust monthly duty cycle, the X854e has the speed and stamina to power your business growth.

## Big-screen simplicity

The incredibly large, customisable touch-screen gives you fast, hassle-free access to all the functions you need to stay productive.

## Ready for big jobs

Benefit from optional stapling, stacking and hole punch, as well as stackable input drawers to reach a tremendous capacity of up to 5,100 sheets.

We make printing easy

**LEXMARK**<sup>TM</sup>

# Lexmark X854e

## Designed to do it all!

Large enterprises with heavy and complex workloads will find the answer to all their document needs in the Lexmark X854e A3 MFP. Robust, reliable and lightning-fast – reaching output speeds of up to 55 ppm – this powerful multifunction device makes light work of your highest-volume tasks.

### Seeing is believing

It doesn't take long to see why the X854e will be a welcome addition to your office. Its huge LCD touch-screen offers a visually attractive – and extremely practical – way to access all the features you need. Intuitive, adjustable and fully customisable, it's your gateway to greater business efficiency.

### Scanning and copying made easy

The large flatbed colour scanner is great for scanning and copying big reports. You can even preview scans on the LCD screen, or scan straight to a USB key. And if it's a big stack of 2-sided originals you need copied, no problem. Just place it into the 75-page Automatic Document Feeder, touch the screen and go!

#### Print Technology: Monochrome Laser Function

Copying, Faxing, Network Scanning, Printing

**Print Speed (Letter, Black):** Up to 55 ppm

**Print Speed (Letter, Black) Duplex**  
Up to 50 spm

**Time to First Page (Black)**

as fast as 6.8 seconds

**Copy Speed (Ltr, Black):** Up to 55 cpm

**Time to First Copy (Black)**

as fast as 10 seconds

**Simplex Scan Speed (Ltr, Black)**

Up to 55 Sides per minute

**Simplex Scan Speed (Ltr, Colour)**

Up to 27 Sides per minute

**Duplex Scan Speed (Ltr, Black)**

Up to 50 Sides per minute

**Duplex Scan Speed (Ltr, Colour)**

Up to 18 Sides per minute

**Print Resolution, Black**

1200 Image Quality, 1200 x 1200 dpi

2400 Image Quality, 600 x 600 dpi

**Scanning Resolution**

600 X 600 dpi, 600 X 300 dpi (colour)

**Processor:** 625 MHz

**Memory, Standard:** 256 MB

**Memory, Maximum:** 768 MB

**Expandable Memory Options:** Yes

**Apple Macintosh Operating Systems Supported**

Apple Mac OS X

Apple Mac OS 9.x

**Citrix MetaFrame**

**Linux Operating Systems Supported**

**Microsoft Windows Operating Systems Supported**

Microsoft Windows 2000

(Professional/Server/Advanced Server)

Microsoft Windows NT (4.00/4.00 Server)

Microsoft Windows Me, Microsoft Windows

XP (Home, Professional) Microsoft Windows

Server 2003 (Standard, Enterprise), Microsoft

Windows 98 2nd Edition, Microsoft Windows

XP Professional x64, Microsoft Windows

Server 2003 (Standard, Enterprise) running

Terminal Server, Microsoft Windows 2000

Server running Terminal Services, Microsoft Windows Server 2003 (Standard, Enterprise) x64 Edition, Microsoft Windows Server 2003 x64 Edition (Standard, Enterprise) running Terminal Services

**Novell Operating Systems Supported**

Novell® Open Enterprise Server for Netware

with NDS, iPrint or Novell Distributed Print

Services (NDPS), Novell NetWare® 3.2, 4.2

(bindery), Novell NetWare 5.x, 5.x and 6.x

(NDS), Novell NetWare 5.x, 6.x with iPrint or

Novell Distributed Print Services (NDPS)

**UNIX Operating Systems Supported**

Sun Solaris 7, 8, 9, 10, HP-UX 11.00, 11.11,

IBM AIX 5.1, 5.2, 5.3, Sun Solaris x86 10

**Other Operating Systems Supported**

IBM iSeries or IBM AS/400® Systems with

TCP/IP with OS/400® V3R1 or later using

OS/400 Host Print Transform, Virtually any

platform supporting TCP/IP

**Paper Handling Standard**

500-Sheet Output Bin

**Duplex Unit**

Two 500-Sheet Trays

100-Sheet Multipurpose Feeder

2,000-Sheet Dual Input

**Paper Handling Optional**

2,000-Sheet High-capacity Feeder

3,500-Sheet Finisher

**Paper Input Capacity (Standard)**

3100 pages 75 gsm bond

**Paper Input Capacity (Maximum)**

5100 pages 75 gsm bond

**Paper Output Capacity (Standard)**

500 pages 75 gsm bond

**Paper Output Capacity (Maximum)**

3800 pages 75 gsm bond

**Copy/Fax/Scan (ADF) Paper Input**

**Capacity :**

Up to 75 pages 75 gsm bond

**Envelope Capacity:** 10

**Finishing Option?** Yes

**Number of Paper Inputs:** 5

**Number of Paper Inputs, Maximum:** 6

### Enterprise security

The X854e ensures you total peace of mind, offering you cutting-edge features for secure management, network communication and information storage. These include disk wiping and encryption, IPsec, SSL, SNMPv3, secure wireless transmission, user authentication, lockout modes and more.

### Solutions-ready

Take workflow efficiency to new levels. The X854e is equipped with Lexmark's new Embedded Solutions framework, offering you network-friendly, native support for Lexmark's wide range of enterprise solutions, such as Forms Card, ImageQuick, DLE applications and many others.

#### Media Types Supported

Card Stock, Envelopes, Paper Labels, Plain Paper, Transparencies

Refer to the Card Stock & Label Guide

**Media Sizes Supported**

10 Envelope, 7 3/4 Envelope, A3, A4, C5

Envelope, DL Envelope, Executive, Folio,

JIS-B4, JIS-B5, Ledger, Legal, Letter,

Statement, Universal

#### Standard Ports

Centronics IEEE 1284 Bidirectional Parallel

Ethernet 10/100BaseTX (RJ-45)

One Internal Card Slot

USB Compatible with USB 2.0 Specification

USB Direct interface on Operator Panel

**Optional Local Ports**

Internal RS-232C serial

Internal 1284-B Bidirectional Parallel

**Optional Network Ports**

Lexmark N4050e 802.11g Wireless Print

Server (Print Only)

External 802.11g Wireless

**Network Printing Methods**

LPR/LPD, Direct IP (Port 9100)

Socket (Raw TCP/IP), IPP (Internet Printing

Protocol), HTTP, NDS Queue-based Printing

NDPS/NEPS (Novell Distributed Print Services,

Novell Netware Enterprise Print Services)

Enhanced IP (Port 9400), FTP, TFTP

**Network Protocol Support**

TCP/IP IPv4, IPX/SPX, AppleTalk™, LexLink

(DLC), TCP/IP IPv6

**TCP/IP Set of Application Services**

Zero configuration, DDNS, mDNS, NTP:

Network Time Protocol, ping, finger, telnet,

TFTP

**Network Management Protocols**

HTTP, HTTPs (SSL/TLS), SNMPv1, SNMPv2c,

SNMPv3 WINS, SLPv, 1IGMP, BOOTP, RARP,

APIPA (AutoIP), DHCP, ICMP DNS

**Network Security**

SSL Enabled Embedded Web Server,

SNMPv3, TCP/IP port access control

Authenticated and encrypted MarkVision

Professional communication

802.1x Authentication: MD5, MSCHAPv2,

LEAP, PEAP, TLS, TTLS, IPSec

**Printable Area (metric)**

4 mm of the top, bottom, right and left edges

(within)

**Printer Languages (Standard)**

PCL 6 Emulation, Personal Printer Data

Stream (PPDS), PostScript 3 Emulation,

PDF 1.5

**Reduce / Enlarge Range:** 25 - 400 %

**Scan Area, Maximum (mm)**

297 x 432 mm

**Modem Speed:** 33.6 Kbps

**Packaged Size (mm - H x W x D)**

1380 x 890 x 850 mm

**Size (mm - H x W x D)**

1095 x 640 x 700 mm

**Weight (kg):** 105.7 kg

**Noise Level, Idle:** 32 dBA

**Print Noise Level, Operating:** 53 dBA

**Copy Noise Level, Operating:** 56 dBA

**Scan Noise Level, Operating:** 54 dBA

**Product Guarantee**

One Year or 600,000 Impressions - OnSite

Repair

**Product Certifications**

Energy Star, CSA, ICES Class A, BSMI Class

A, VCCI Class A, FCC Class A, UL 60950-1,

IEC 320-1, ECMA-74, CE Class A, CB IEC

60950 1, IEC 61000-3-2, -3-3, EN 55022, EN

55024, CISPIR 22 Class A, GS (TUV)-EN

60950-1, SEMKO, UL AR, CS, TÜV Rh, N

Mark, C-tick Class A, CCC Class A, RPC,

PSE, MIC, EK - K60950

**Duty Cycle**

Up to 300,000 one-time maximum

Impressions per month

**Specified Operating Environment**

Temperature: 16 to 32°C (60 to 90°F)

Humidity: 8 to 80% Relative Humidity

Altitude: 0 - 3048 Meters (10,000 Feet)



#### Supplies

Ships with 30K\* pages Return toner

cartridge

Ships with 60K Photoconductor Kit

30K\* pages High Yield toner cartridge

(aftermarket).

70K pages Photoconductor Kit

- Printers and supplies are designed for use

in Europe, Middle East and Africa only

\* Average cartridge yield. Declared yield

value in accordance with ISO/ IEC 19752.

#### Model available

• X854e

re  
reduce  
recover  
reuse  
recycle

Lexmark believes that the environment is a critical component of responsible business management and clearly demonstrates it by implementing the "4R" strategy: Reduce, Recover, Reuse and Recycle. To learn more about these programmes please visit [www.lexmark.com/recycle](http://www.lexmark.com/recycle)



With our innovative solutions and services, we help you PRINT smarter, MOVE information faster and MANAGE output more efficiently across your enterprise. Ask your local Lexmark representative for more information.

Specifications are subject to change without notice. Lexmark, Lexmark with diamond design is trademark of Lexmark International, Inc. registered in the United States and in other countries. All other trademarks are the properties of their respective owners.

[www.lexmark.co.uk](http://www.lexmark.co.uk)

LEXMARK