



Sometimes nice colours don't  
last very long.

Sometimes they do.

# Lexmark **C770n**

Get brilliant colour and  
performance at a competitive  
price!

## **A colourful impact on your business**

Liven up everything from office memos to spreadsheets to marketing reports with Lexmark's rich, vibrant colour output.

**Up to 24 ppm  
mono/colour A4**

**Network ready**

**Intelligent use of colour**

## **Effortless operation**

The large, 4-line backlit display offers clear instructions to coach your end-users through printing and maintenance tasks easily.

## **Leading cost-control tools**

Experience the most comprehensive range of cost-control tools on the market with Lexmark's exclusive ColorCare technology.

**LEXMARK**  
TM

# Lexmark C770n

## A brighter future for your document workflow

Combining superior print quality with a highly competitive price/performance ratio, the Lexmark C770n offers outstanding value for your busy workgroup. What's more, it's network-ready and easy on everyone in the office!

### No more brainteasers

Working is now simpler than ever thanks to a range of new user-friendly features, like a USB Direct interface for convenient PC-free printing, and a 10-digit numeric pad for effortless operation. You also benefit from a simplified driver interface, easy-to-load consumables and more.

### Total cost control

From toner-coverage estimators to IT-administered password controls, Lexmark's industry-leading ColorCare technology lets you manage costs effectively at every level of your workflow. Now you have the tools to decide who can print what, when, where and how much!

#### Print Technology

Color Laser

#### Print Speed (A4, Black)

Up to 24 ppm

#### Print Speed (Letter, Color)

Up to 25 ppm

#### Print Speed (A4, Color)

Up to 24 ppm

#### Print Speed (Letter, Black)

Up to 25 ppm

#### Time to First Page (Black)

as fast as < 13 seconds

#### Time to First Page (Color)

as fast as < 15 seconds

#### Print Resolution, Black

1200 x 1200 dpi

4800 Color Quality (2400 x 600 dpi)

#### Print Resolution, Color

1200 x 1200 dpi, 4800 Color Quality (2400 x 600 dpi)

#### Processor

800 MHz

#### Memory, Standard

256 MB

#### Memory, Maximum

768 MB

#### Expandable Memory Options

Yes

#### Apple Macintosh Operating Systems Supported

Mac OS X, Mac OS 9.x

#### Citrix MetaFrame

Citrix, MetaFrame and MetaFrame XP are registered trademarks or trademarks of Citrix Systems, Inc. in the U.S. and other countries., Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0., Microsoft Windows Server 2003 running Terminal Server with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0, Microsoft Windows Server 2003 running Terminal Server with Citrix Presentation Server 4.0, Microsoft Windows Server 2003 x64 Edition (Standard, Enterprise) running Terminal Server with Citrix Presentation Server 4.0

#### Linux Operating Systems Supported

Red Hat Linux 4.0, Linpus Linux 9.2, Red Hat Enterprise Linux WS 3.0, 4.0, SuSE Linux Enterprise Server 8.0, 9.0, SuSE Linux Professional 9.1, 9.2, Debian GNU/Linux 3.0, Linspire Linux 4.5

#### Microsoft Windows Operating Systems Supported

2000 (Professional/Server/Advanced Server), NT (4.00/4.00 Server), Me, XP (Home, Professional), Server 2003 (Standard, Enterprise), 98 2nd Edition, XP Professional x64, Server 2003 (Standard, Enterprise) running Terminal Server, 2000 Server running Terminal Services, Server 2003 (Standard, Enterprise)

x64 Edition, Server 2003 x64 Edition (Standard, Enterprise) running Terminal Services

#### Novell Operating Systems Supported

Open Enterprise Server for Netware with NDS, iPrint or Novell Distributed Print Services (NDPS), NetWare® 3.2, 4.2 (bindery), NetWare 4.2, 5.x and 6.x (NDS), NetWare 5.x, 6.x with iPrint or Novell Distributed Print Services (NDPS)

#### UNIX Operating Systems Supported

Sun Solaris 7, 8, 9, 10, HP-UX 11.00, 11.11, IBM AIX 5.1, 5.2, 5.3, Sun Solaris x86 10

#### Other Operating Systems Supported

IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform, Virtually any platform supporting TCP/IP

#### Paper Handling Standard

250-Sheet Output Bin, 500-Sheet Input Tray, 100-Sheet Multipurpose Feeder

#### Paper Handling Optional

Duplex Unit, 500-Sheet Drawer

#### Paper Input Capacity (Standard)

600 pages 20 lb or 75 gsm bond

#### Paper Input Capacity (Maximum)

1100 pages 20 lb or 75 gsm bond

#### Paper Output Capacity (Standard)

250 pages 20 lb or 75 gsm bond

#### Paper Output Capacity (Maximum)

250 pages 20 lb or 75 gsm bond

#### Envelope Capacity

10

#### Finishing Option

No

#### Number of Paper Inputs

2

#### Number of Paper Inputs, Maximum

3

#### Media Types Supported

Card Stock, Envelopes, Glossy paper, Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide

#### Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal (98 x 191 mm - 216 x 355 mm)

#### Connectivity (standard)

Fast Ethernet, One Internal Card Slot, USB Compatible with USB 2.0 Specification, USB Direct interface on Operator Panel

#### Connectivity (optional)

MarkNet N8030 Fibre Ethernet, Lexmark N4050e 802.11g Wireless Print Server (Print Only), MarkNet N8020 Gigabit Ethernet, MarkNet N8050 802.11g Wireless, External Gigabit

#### Ethernet

#### Network Printing Methods

LPR/LPD, Direct IP (Port 9100), Socket (Raw TCP/IP), IPP (Internet Printing Protocol), HTTP, NDS Queue-based Printing, NDPS/NEPS (Novell Distributed Print Services, Novell Enterprise Print Services), Enhanced IP (Port 9400)

#### Network Protocol Support

TCP/IP IPv4, IPX/SPX, AppleTalk™, LexLink (DLC), TCP/IP IPv6

#### Network Security

SSL Enabled Embedded Web Server, SNMPv3, TCP/IP port access control, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPsec

#### Printable Area

4.2 mm of the top, bottom, right and left edges (within)

#### Printer Languages (Standard)

PCL® 6 Emulation, PPDS Migration Tool, PostScript® 3 Emulation, PDF v1.5 emulation

#### Packaged Size (mm - H x W x D)

810 x 795 x 650 mm

#### Size (mm - H x W x D)

528 x 604,5 x 470 mm

#### Weight (kg)

47,7 kg

#### Acoustics/Noise level (Idle mode)

30 dBA

#### Acoustics/Noise level (Operating mode)

52 dBA

#### Product Guarantee

One Year Onsite Repair, Next Business Day response time.

#### Product Certifications

Energy Star, CSA, ICES Class A, BSMI Class A, VCCI Class A, FCC Class A, UL 60950-1, IEC 60320-1, CE Class A, CB IEC 60950-1, IEC 60825-1, GS (TÜV), SEMKO, UL AR, CS, TÜV Rh, C-tick mark Class A, CCC Class A

#### Duty Cycle

Up to 100 000 Impressions per month (one-time monthly usage)

#### Specified Operating Environment

Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 3048 Meters (10,000 Feet)

#### Supplies

Ships with 6K Pages\* Black, Cyan, Magenta, Yellow Return Program Print Cartridges.

Aftermarket cartridges available:

10K\* High Yield CMYK Return Programme Print Cartridges. Regular cartridges also available.

6K\* CMYK Return Programme Print Cartridges. Regular cartridges also available.

\* at 5% coverage.

#### Cost saving & environmental features

Compliant with Energy Star, WEEE marking and RoHS. Chemical Emissions meeting Blue Angel Requirements. Toner darkness control saves toner. Multi-up printing & Quality printing on recycled paper save paper. Power saver mode reduces energy consumption. End-of-Life product management reduces landfill.

#### Models available

C770n — Network  
C770dn — Duplex, Network  
C770dtn — Duplex, Tray, Network



Lexmark believes that the environment is a critical component of responsible business management and clearly demonstrates it by implementing the "4R" strategy: Reduce, Recover, Reuse and Recycle. To learn more about these programmes please visit [www.lexmark.com/recycle](http://www.lexmark.com/recycle)



With our innovative solutions and services, we help you PRINT smarter, MOVE information faster and MANAGE output more efficiently across your enterprise. Ask your local Lexmark representative for more information.

Specifications are subject to change without notice. Lexmark, Lexmark with diamond design is trademark of Lexmark International, Inc. registered in the United States and/or other countries. All other trademarks are the properties of their respective owners.

[www.lexmark.com](http://www.lexmark.com)

**LEXMARK**  
TM