



Sometimes high quality  
is hard to reach.

Sometimes it's not.

# Lexmark T640

High quality, low cost for  
your heavy output needs

Up to 35 ppm

As fast as 6 seconds time  
to first page

Direct PDF printing

## Exceptional value

Enjoy professional print quality and outstanding performance at a price that suits your budget.

## Painless operation

Scale new heights in productivity with a full range of user-friendly features, including a USB direct interface for PC-free printing.

## Total reliability

Achieve greater peace of mind thanks to a new robust design, heavy output capacity and Lexmark's solid one-year on site repair guarantee!

We make printing easy

**LEXMARK**<sup>TM</sup>

# Lexmark T640/n/dn/dtn

Make life easier on your workgroup - and your budget!

Reconcile excellence and value with an affordable distributed mono printer, built to keep up with the demanding requirements of your enterprise. Priced to suit most budgets, the Lexmark T640 uses easy-to-install supplies and offers a wide range of paper-handling options too.

### Built for simplicity

Equipped with a USB direct interface, the T640's user-friendly operating panel gives you PC-free printing of PDF, JPG, TIFF files and many other document types (1). Plus, its numeric pad with 4-line display coaches users through printing and maintenance functions with ease.

### A perfect fit for your business

With its sleek new design and very low acoustics, the T640 integrates seamlessly into your professional environment. And when you need big results, you can count on its outstanding print quality, powerful performance and lightning-fast time to first page of only 6 seconds!

### Dependability, at your service

Focus on your core business and leave the printing to Lexmark. Reliable and very robust, the T640 requires minimal intervention. Best of all, it comes with Lexmark's worry-free on site repair guarantee of one year.

#### Models available

T640 - Standalone  
T640n - T640 + network  
T640dn - T640n + duplex  
T640dtn - T640dn + 500-sheet drawer



Lexmark believes that the environment is a critical component of responsible business management and clearly demonstrates it by implementing the "4R" strategy: Reduce, Recover, Reuse and Recycle. To learn more about these programmes please visit [www.lexmark.com/recycle](http://www.lexmark.com/recycle)



With our innovative solutions and services, we help you PRINT smarter, MOVE information faster and MANAGE output more efficiently across your enterprise. Ask your local Lexmark representative for more information.



<b>Technology</b>	Laser
<b>Product class</b>	Small workgroup laser printer
<b>Speed</b>	Up to 35 ppm
<b>Time to first page</b>	As fast as 6 seconds
<b>Processor</b>	400 MHz
<b>Memory</b>	Standard: 64 MB Maximum: 576 MB
<b>Print quality</b>	Up to 1200 x 1200 dpi, 2400 Image Quality
<b>Duty cycle</b>	Up to 200K pages (one time monthly maximum usage)

<b>Paper input</b>	Standard: T640, T640n, T640dn: 250 sheets + 100 (multipurpose feeder) T640dtn: 250 sheets + 500 sheets + 100 (multipurpose feeder) Maximum: 3850 sheets Optional: 250-sheet drawer, 500-sheet drawer, 2000-sheet drawer, 250-sheet universally adjustable drawer, 400-sheet universally adjustable drawer, 250-sheet duplex unit, 85-envelope feeder
<b>Paper output</b>	Standard: 250 sheets Maximum: 2750 sheets Optional: 650-sheet output expander, 1850-sheet high-capacity output stacker, StapleSmart finisher, 5-bin mailbox
<b>Media types supported</b>	Plain Paper, Envelopes, Card Stock, Transparencies, Paper Labels (4), Dual-Web Labels (4), Polyester Labels (4), Vinyl Labels (4)
<b>Media sizes supported</b>	A4, A5, JIS B5, Letter, Legal, Statement, Executive, Folio Universal (69.85 x 127mm to 215.9 x 355.6mm) Envelopes (7 3/4, 9, 10, DL, C5, B5, other)

<b>Connectivity (standard)</b>	Standalone: IEEE 1284 Bidirectional Parallel, One Internal Card Slot, USB Compatible with USB 2.0 Specification, USB Direct interface on Operator Panel Network: IEEE 1284 Bidirectional Parallel, One Internal Card Slot, USB Compatible with USB 2.0 Specification, USB Direct interface on Operator Panel and Fast Ethernet
--------------------------------	---

<b>Connectivity (optional)</b>	<b>Internal Print Servers:</b> N8000 Fast Ethernet, N8020 Gigabit Ethernet, N8030 Fibre 10/BaseFX, N8050 802.11g Wireless <b>External Print Servers:</b> X2011e Fast Ethernet (2), X2012e Ethernet 10/100BaseTX/10Base2 (2), X2031e Fast Ethernet (3 ports) (2), X2030t Token-Ring (3 ports) (2), N4000e Fast Ethernet (3), N4050e 802.11g Wireless Print Server (3) <b>Other Attachment Options:</b> Coax/Twinax Adapter for SCS, 802.11g Wireless Print Adapter, Parallel 1284-B Interface Card, RS-232C Serial Interface Card
<b>Network management software</b>	MarkVision Professional
<b>Printer languages</b>	Postscript Level 3 and PCL6 emulations, PPDS Migration tool, PDF 1.5, ImageQuick (1) (JPEG, JPG, TIFF, BMP, GIF, PNG, PCX and DCX)
<b>Operating systems supported</b>	<b>Microsoft Windows:</b> Windows 9x, Me, NT, 2000, XP, Server 2003 <b>Apple Macintosh:</b> Mac OS 9.x, X (10.2 or later) <b>Novell, Linux:</b> Please visit our website <a href="http://www.lexmark.com">www.lexmark.com</a> for a complete list of supported versions
<b>Application solutions</b>	Bar Code Card, Card for IPDS and SCS/Tne, Prescribe Card, PrintCryption Card, Forms Card

<b>Guarantee</b>	Base guarantee: 1 year on site repair, response time next business day Service offerings: 2 years extended guarantee on site repair, response time next business day ; 1 year renewal guarantee on site repair, response time next business day
------------------	--

<b>Optional services</b>	Installation service, de-installation service, hardware and software training, trade-in of old products
--------------------------	---

<b>Supplies</b>	Ships with 6K-page Return Programme Print Cartridge (5) 21K-page High Yield Return Programme Print Cartridge (5) 21K-page High Yield Return Programme Print Cartridge for Label Applications (5) 6K-page Return Programme Print Cartridge (5) 21K & 6K-page Regular Print Cartridges also available (5)
-----------------	---

- Printers and supplies are designed for use in Europe, Middle East and Africa only

<b>Size (H x W x D)</b>	345 mm x 424 mm x 498 mm (T640/T640n)	<b>Cost saving &amp; environmental features</b>
<b>Weight</b>	17 kg (T640/T640n)	Energy Star Compliant
<b>Noise level</b>	Standby mode: 30 dBA Simplex printing mode: 53 dBA	High yield toner cartridges available Optional duplex printing (standard on T640dn & T640dtn) Power saver mode Selectable "print darkness" levels Print and Hold (Verify Print) Multi-up printing WEEE
<b>Power &amp; electric specifications</b>	Printing mode: 675 Watts Standby mode: 90 Watts Power Saver mode: 20 Watts	

(1) network models only ; (2) requires external parallel connection ; (3) requires USB connection ; (4) printing label applications requires a special fuser cleaner included in the cartridge for labels ; (5) average cartridge yield. Declared yield value in accordance with ISO/IEC 19752

Specifications are subject to change without notice. Lexmark, Lexmark with diamond design is trademark of Lexmark International, Inc. registered in the United States and or other countries. All other trademarks are the properties of their respective owners.

[www.lexmark.co.uk](http://www.lexmark.co.uk)

**LEXMARK**  
TM