

The high performance C5950 is the perfect solution for businesses wanting to work more productively, print more professionally and keep a tight control over costs.

The C5950 model is intended specifically for those who print mostly colour. Enhance product performance as needed with user installable options such as an extra paper tray, auto duplex unit or hard disk dive for advanced colour matching and print security.

The C5950 offers the operating system flexibility and advanced features provided by PCL/PostScript emulation. This enables printing from a greater range of applications and easier printing of PDF's.

High performance colour workgroup printing.

- Class-leading print speeds of 26ppm colour and 32ppm mono.
- Fast time to first print at just 9 seconds for a colour page or 8 seconds for mono.
- OKI's single pass digital LED technology which features flat paper path and unrivalled media flaxibility in this class of product. The printer easily handles paper weights of up to 203gsm and banners up to 1.2metres long.

- Easy to read front panel toner gauges allow walk up users to instantly see the status of the printer.
- Automatic duplex for professional double-sided documents, enabling booklet printing, reduced paper use and space saving.
- Scalable barcode printing (with checksum).
- Colour Access Manager allows control and management of colour printing.
- The optional hard disk drive can be installed to give advance colour matching and enable printing security functions.

Outstanding quality print. Low running costs

- ProQ2400 Multi-level technology and High Definition Toner have been developed in unison. Together they give a higher level of detail, greater colour depth, reduced grain and a high gloss feel.
- Auto Colour Balance ensures consistent results throughout the life of the printer.
- Photo Enhance provides stunning photo-like quality on ordinary office paper.
- High capacity colour and mono toner cartridges reduce running costs and user intervention.

Unique in-box software lets you take control

- Print Control is a powerful network tool to manage colour usage and costs.
- PrintSuperVision allows network administrators to remotely monitor all printers on their network and verify toner status.
- Template Manager helps you professionally design and print on a range of non-standard media – and to do so with ease. It even manages the printer settings automatically. From business cards, to CD labels, address labels and banners.
- Web Print makes printing web-pages easier.
 It adjusts text and images to fit on the printed page without cutting off information, saving you paper and hassle.
- Ask OKI dedicated online support, accessed easily via the printer driver.
- Plus powerful, professional colour management tools that allow you to accurately adjust and match colours.

THE C5950 FEATURES AT A GLANCE

	C5950n	C5950dn	C5950dtn	C5900cdtn
Colour speed (A4)	26ppm			
Mono speed (A4)	32ppm			
Printer language	PCL/PostScript			
Print quality	ProQ2400 Multi-level technology & High Definition Toner			
Memory	256MB			
10/100 networking	•			
Duplex (for double-sided printing)	0		•	
2nd paper tray (for 930 sheet max paper capacity)	0		•	
Cabinet	•			
Hard Disk Drive	○40GB			



The C5950 Colour and Mono Printers

		C5950n	C5950dn	C5950dtn	C5950cdtn	
Order number		01213101	01213201	01213301	01213401	
Speed & throughput	A4 Print speed	26ppm colour, 32ppm mono				
	Time to first print	9 seconds colour , 8 seconds mono				
	Warm up time	up to 60 seconds from power on & up to 45 seconds from power save				
	Processor speed	500MHz				
Print quality	Resolution	ProQ2400 Multi-level technology, 1200 x 600dpi				
	Enhancements	Auto Colour Balance, Photo Enhance via driver (excludes Mac and PostScript drivers)				
Typefaces	Printer fonts	Scalable: 87 PCL fonts and 136 PostScript fonts; PCL Bitmap fonts. OCR-A/B; USPS ZIP Barcode				
Compatibility	Printer languages	PCL 6 (XL3.0) and PCL5c, PostScript 3 (clone). SIDM (IBM-PPR, EPSON-FX), PDF Direct Print v1.5				
, ,	Connectivity	Hi-Speed USB, 10/100-TX Ethernet & IEEE 1284 Bi-directional Parallel				
	OS Compatibility	Windows 2000 / XP Home / XP Professional / XP Professional x64 / Server 2003 / Server 2003 for x64 / Vista (32-bit) / Vista (64-bit) /				
	oo companizatiy	Williams 2000 / Ar nollie / Ar Froisessolial / Ar Froisessolial X84 / Servet 2005 / Se				
	Barcode Support	Barcode with Checksum support				
Utility Suite		Color Correct, Oki LPR (Windows only), PrintSuperVision.net (Windows only), Swatch Utility, Template Manager (Windows only), Web Driver				
,		Installer (Windows only), WebPrint (Windows only), Print Control Server (Windows only), Print Control Client,				
			Storage Device Manager² (Windows o	nly), Gamma Utility, Profile Assistant	t ²	
Memory	Std RAM	256MB				
	Max RAM	768MB				
	Hard Disk Drive	40GB (Optional)				
Paper handling	Paper capacity tray 1	300 sheets of 80gsm. Paper sizes: A4, A5, A6, B5				
	Paper capacity	530 sheets of 80gsm. Paper sizes: A4, A5, B5,				
	optional 2nd tray	9 1 1 1				
	Paper capacity of	100 sheets of 80gsm. Paper sizes: A4, A5, A6, B5 10 Envelopes (Com-9, Com-10, DL, Monarch, C5), Labels (Avery 7162, 7664, 7666),				
	multi-purpose tray	Custom Size (up to 1200mm length including Banner), 50 transparencies				
	Standard tray paper weight	64 – 120gsm				
	Optional 2nd tray paper weight	64 – 176gsm				
	Multi-purpose tray paper weight	75 – 203gsm				
	Duplex	Optional Standard				
	Duplex paper sizes	Supported paper sizes: A4, A5, B5. Supports Custom Size: Width 148 – 215.9mm Length 210 – 355.6mm				
	Duplex paper weight	75 – 105gsm				
	Paper output	250 sheets face down, 100 sheets face up, 80gsm				
Operating conditions	Temperature/Humidity	10°C to 32°C (17°C to 27°C recommended) / 20% to 80% RH (50% to 70% RH recommended)				
	Storage	-10°C to 43°C, 10% to 90% RH				
Power requirements	Power supply	Single phase 220–240VAC, frequency 50/60Hz +/-2%				
	Power consumption	Typical 490W, Peak 1200W, Idle 100W (average), Power save <17W				
Noise level		Operating: Up to 55.6 dB(A), Standby: 37 dB(A), Power Save: Background Level				
Dimensions (HxWxD)		339.5mm x 400mm (max 435mm) x 528mm (max 563.5mm)	339.5mm x 400mm (max 435mm) x 621mm	486.5mm x 400mm (max 435mm) x 621mm	911.5 x 400mm (max 533mm x 621mm	
Weight ³		Approx 26kg	Approx 29kg	Approx 36kg	Approx 51kg	
Duty cycle	Printer duty (max)		60,000 pa	,,, -	1	
, -,	Printer duty (max) Printer duty (average)		1,500 – 6,00 0	<u> </u>		
Warranty	22., (210.050)	31	year onsite extended warranty upon r	1 0 1	se ⁴	
Accessories	Duplex					
Accessories		Optional (43347502) Standard				
	Memory	256MB (01182901) or 512MB (01182902)				
	2nd tray	Optional (43347602) Standard				
	Hard Disk Drive	40GB (01184501)				
	Cabinet	Optional (09004619) Standard			G: 1 1	

¹ Check local OKI Printing Solutions website for latest driver releases & OS compatibility.

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI Printing Solutions toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible," and if it does work, your printer's performance and print quality may be degraded.

Description	Life*	Order Numbers	
Black toner	8,000 pages	43865724	
Colour toner	6,000 pages	Cyan: 43865723 / Magenta: 43865722 / Yellow: 43865721	
Image drum	20,000 A4 pages @ 3 pages/job	Black: 43870024 Cyan: 43870023 Magenta: 43870022 Yellow: 43870021	
Transfer belt	60,000 A4 pages @ 3 pages/job	43363412	
Fuser unit	60,000 pages @ A4	43853103	

^{*}All toners: A4 pages @ 5%, Printer shipped with 1500 pages @ 5%.

Colour Printers Mono Printers MFPs

Fax

Dot Matrix

OKI PRINTING SOLUTIONS 550 Dundee Road, Slough

Berkshire, SL1 4LE United Kingdom T+44(0) 1753 819819

F+44(0) 1753 819899

WWW.OKIPRINTINGSOLUTIONS.CO.UK









² Hard Disk Drive required.

³ Includes all consumables.

⁴To qualify for the extended 3 year warranty, register your product online at www.okiprintingsolutions.co.uk/warranty. Without registration, the standard pan-European 1 year warranty applies.

 $Specification\ subject\ to\ change\ without\ notice.\ All\ trademarks\ acknowledged.$