

ML280 ELITE DOT MATRIX PRINTER



❖❖❖ ML280 ELITE

❖❖❖ 9-PIN DOT MATRIX PRINTER

THE RELIABLE AND AFFORDABLE PRINTER FOR INDUSTRIAL AND POINT OF SALE APPLICATIONS

The new Microline 280 Elite has been greatly improved from its popular predecessor, the Microline 280. Not only does the Microline 280 Elite have faster print speeds; 333 cps in high speed draft mode at 10cpi, it also offers greater flexibility, supporting a host of emulations, USB as standard and is ideal for continuous data processing. High reliability and very compact dimensions make it especially suited for front/back office applications and industrial environments (multipart forms, labels etc.)

MAIN FEATURES OF THE ML280 ELITE PRINTER

- ❖❖❖ Fast and durable Oki 9 pin narrow carriage impact printer
- ❖❖❖ Oki's unique, high durability 9-pin print head
- ❖❖❖ Handles up to 4 part forms (original + 3 copies)
- ❖❖❖ Fast 333 characters per second (10cpi high speed draft)
- ❖❖❖ Versatile top, bottom and rear paper feed
- ❖❖❖ Parallel/USB as standard, serial version also available



OKI

ML280 ELITE DOT MATRIX PRINTER

PRODUCT SPECIFICATION

| | | ML280 ELITE |
|------------------------------------|---|---|
| General | Number of pins | 9 |
| | No. of multi-part forms | 4 (one original + 3 copies) |
| Speed & throughput | Super speed (12cpi) | 375cps |
| | High speed draft (10cpi) | 333cps |
| | Utility (12cpi & 10cpi) | 250cps |
| | Near letter quality (12cpi & 10cpi) | 62.5cps |
| | Fastest print speed | 375cps |
| Font & print features | Carriage width (10cpi) | 80 columns |
| | Max. in compressed mode | 160 columns |
| | Character pitch | 10/12/15/17.1/20 pitch |
| | Graphics resolution | Up to 240 x 216 dpi |
| | Typeface & Font | Utility, High Speed, Draft, NLQ, Barcodes |
| | Typestyle | Emphasised, Enhanced, Double Width, Italics |
| Emulations & interfaces | Printer emulations | Epson FX, IBM Graphics or Oki MICROLINE |
| | Standard interfaces | Centronics Parallel/USB |
| | Optional interfaces | Serial RS 232C/RS 422/Current Loop |
| Paper-handling | Continuous paper | 76.2 – 241.3mm |
| | First printable line (from top of page) | Cut sheet: 15mm Continuous: 16.9mm |
| | Standard | Autoload single sheet, Platen pin feed, Low tear-off, Paper end detection |
| | Optional | Roll paper stand, Pull tractor feed, Single bin sheet feeder |
| Physical | Dimensions (HxWxD) | 80 x 360 x 275mm |
| | Weight | 4.5kg |
| | Memory | 128KB |
| | Noise level | 51dB (quiet mode) |
| Power | Power requirements | 220V - 240V AC |
| | Frequency | 50/60Hz |
| Reliability | Print head life | 200 million characters |
| | Ribbon life | 3 million characters (re-inking cartridge) |
| Supplies life | MTBF | 20,000 hours |

OKI

Only use genuine Oki Original consumables to ensure the best quality and performance from your hardware. Non Oki Original products may damage your printer's performance and invalidate your warranty. Specifications subject to change without notice. All trademarks acknowledged.

*Oki, Network Solutions
for a Global Society*

OKI SYSTEMS (UK) LTD, PART OF OKI ELECTRIC

OKI SYSTEMS (UK) LTD,
550 DUNDEE ROAD,
SLOUGH, BERKSHIRE
SL1 4LE
UNITED KINGDOM

TEL: +44 (0)1753 819819
FAX: +44 (0)1753 819899

WWW.OKI.CO.UK



As an ENERGY STAR Partner, Oki Europe Ltd has determined that this product meets the ENERGY STAR guidelines for energy efficiency

09400944
© 2003 Oki Europe Ltd.