



Samsung Mono Laser MFPs SCX-4833FD/SCX-5737FW



Key Features:

- Print Speeds up to 31ppm/35ppm in A4
- First Print Out Time 6.5 seconds (from Ready Mode)
- Improved Print Quality with up to 1,200 x 1,200dpi
- Maximum Monthly Duty Cycle 50,000/80,000 sheets
- Quiet Operation at less than 52/53dBA (printing)
- Standard Cartridge Yield of 2,000/5,000 pages
- 250-sheet Input Capacity, 50-sheet Multi-Purpose tray
- Instant Wireless at the touch of a button with the Wi-Fi Protected Set up (WPS) button¹

The simple business workflow solution.

Recent trends have shown that businesses are looking at their print environment as a way of driving efficiency throughout their business. By replacing out-dated inefficient printers and copiers with energy efficient multifunction devices they can achieve productivity gains, improved device availability and significantly reduced costs and carbon footprint.

Introducing the Samsung SCX-4833FD/SCX-5737FW mono laser multifunction printers. These intelligently designed devices offer reliable and fast performance alongside ease of use for maximum usability across the organisation. Their high ECO credentials make them an ideal option for businesses that are looking to reduce their environmental impact as well as reduce costs, increase productivity, improve workflow and boost overall competitiveness.

¹ SCX-5737FW only ² SCX-4833FD only

Top 3 Reasons to Buy:

- 1 User-Friendly and Reliable:**
 - Handy 4.3" touch screen¹ for access to a wide array of features and settings on the SCX-5737FW
- 2 Value for Money:**
 - Easily switch to Toner Save Mode for economical printing
 - Lower cost per page and fewer toner replacements with extra high yield toner cartridges.
- 3 Productivity Boosting Performance:**
 - Save time with the built-in 50 sheet duplex¹ Automatic Document Feeder (ADF) and a Duplex feeder (DADF) on the SCX-5737FW
 - 600MHz dual-core processor², Gigabit network connectivity² and up to 768 MB memory² for fast output
 - Fast printout speeds of up to 35ppm¹.

Product Configurations

SCX-4833FD (front)

Control Panel

Output Tray

Multi-Purpose Tray

Standard Tray

Optional Tray

Paper Level Indicator

ADF Document Feeder

SCX-4833FD (back)

- Network Cable
- Hi-Speed USB 2.0 Port for Direct Connection
- 5v Output for Parallel Port Option
- Power Cord

SCX-5737FW

Output Tray

- DADF Duplex Document Feeder
- LCD Menu Screen

- Multi-Purpose Tray
- Paper Level Indicator

Product Datasheet

Samsung Mono Laser MFPs SCX-4833FD/SCX-5737FW

Product Specifications

| | SCX-4833FD | SCX-5737FW |
|-----------------------------|--|--|
| Print | | |
| Speed (Mono) | Up to 31ppm in A4 (33ppm in Letter) | Up to 35ppm in A4 (37ppm in Letter) |
| First Print Out Time (Mono) | 6.5 Seconds | |
| First Print Out Time | Up to 1,200 x 1,200dpi effective output | |
| Emulation | PCL5e/6, PS3, Epson/IBM Pro, PDF, TIFF | PCL5e/6, PS3, XPS, Epson/IBM Pro, PDF, TIFF |
| Duplex | Built-in | |
| Copy | | |
| Speed | Up to 31ppm in A4 (33ppm in Letter) | Up to 35ppm in A4 (37ppm in Letter) |
| Resolution | Up to 1200 x 1200dpi effective output | |
| First Copy Out Time (Mono) | 12 Seconds | 10 Seconds |
| Zoom Rate | 25~400% (platen), 25~100% (ADF) | |
| Multi Copy | 1~99 pages | |
| Duplex Copy | Standard (1:1, 1:2) | |
| Copy Features | ID Copy, 2-up, 4-up, Poster Copy, Clone Copy, Collation Copy, Auto-fit | |
| Scan | | |
| Scan Speed(B/W) | 20ipm | 24ipm |
| Scan Size Document | Platen: Width (~216mm, 8.5"), Length (~297mm, 11.69"). ADF: Width (142~216mm, 5.6" ~ 8.5"), Length (148 ~ 356mm, 5.8" ~ 14") | |
| Compatibility | TWAIN Standard, WIA Standard | |
| Method | Colour CIS | |
| Resolution (Optical) | 1200 x 1200dpi | |
| Resolution (Enhanced) | Up to 4,800 x 4,800dpi | |
| Scan to | PC, Email, USB Memory | PC, Email, USB Memory, FTP, SMB, Internal Flash Drive |
| FAX | | |
| Compatibility | ITU-T G3 | |
| Modem Speed | 33.6Kbps | |
| Resolution | Standard: 203 x 98dpi, Fine/Photo: 203 x 196dpi, Super Fine: 300 x 300dpi, Colour: Up to 200 x 200dpi | |
| Memory | 5MB (Max. 445 Pages) | 50MB (Max. 4,000 Pages) |
| Auto Dial | Speed dial: 200 Locations | |
| Fax Feature | On hook Dial, Auto Redial, Last Number Redial, Auto Reduction, Multi-Send, Delayed Send, Fax Forwarding (Email/Fax), Broadcasting up to 209 locations | |
| Paper Handling | | |
| Input Capacity and Types | 250-sheet Cassette, 50-sheet Multi Purpose Tray | |
| Output Capacity and Type | 150-sheet Face Down, 1-sheet Face Up | |
| Media Size | 76 x 127mm (3" x 5") ~ 216 x 356mm (8.5" x 14") | |
| Media Type | Plain, Thin, Thick, Thicker, Cotton, Coloured, Envelope, Transparency, Pre-Printed, Recycled, Labels, Bond, Card stock, Archive | |
| ADF Capacity | 50-sheet | |
| ADF Document Size | Width: 142 ~ 216mm (5.6" ~ 8.5") / Length: 148 ~ 356mm (5.8" ~ 14.0") | |
| Envelope Capacity | 5 sheets | |
| General | | |
| Processor | Samsung 360Mhz | Samsung 600 Mhz |
| LCD | 2-line LCD | 4.3" Colour Touch-Screen LCD |
| Memory/Storage | 128MB (Max 384MB) | 256MB (Max 768MB) / 4GB Internal Flash Drive |
| OS Compatibility | Microsoft Windows: 2000/XP (32/64 bit), Vista (32/64 bit), 2003 Server (32/64 bit), 2008 Server (32/64 bit), Windows 7 (32/64 bit), 2008 Server R2 (64 bit); Various Linux OS: RedHat Enterprise Linux WS 4, 5 (32/64 bit), Fedora 5 to 13 (32/64 bit), SuSE Linux 10.1 (32 bit), OpenSuSE 10.2, 10.3, 11.0, 11.1, 11.2 (32/64 bit), Mandriva 2007 to 2010 (32/64 bit), Ubuntu 6.06, 6.10, 7.04, 7.10, 8.04, 8.10, 9.04, 9.10, 10.04 (32/64 bit), SuSE Linux Enterprise Desktop 10, 11 (32/64 bit), Debian 4.0, 5.0 (32/64 bit). | |
| Interface | Hi-Speed USB 2.0, Ethernet 10/100 Base TX | Hi-Speed USB 2.0, Ethernet 10/100/1000 Base TX, IEEE 802.11 b/g/n Wireless Network |
| Noise Level | Less than 52dBA (Printing); Less than 54dBA (Copying); Less than 26dBA (Standby) | Less than 53dBA (Printing); Less than 54dBA (Copying); Less than 26dBA (Standby) |
| Duty Cycle, Monthly | Up to 50,000 pages | Up to 80,000 pages |
| Dimension (WxDxH) | 424 x 382 x 407mm | 469 x 438 x 447mm |
| Weight | 14.37kg | 16.55kg |
| Power Consumption | 550W(Active)/50W(Ready)/8W(Sleep) | 600W(Active)/65W(Ready)/10W(Sleep) |

Consumables

| | | |
|----------------|--|---|
| Yield | Standard: Average Cartridge Yield 2,000 standard pages. High Yield: Average Cartridge Yield 5,000 standard pages. Ships with 2,000 pages Starter Toner Cartridge. Declared Cartridge Yield in accordance with ISO/IEC 19752. | Standard: Average Cartridge Yield 2,000 standard pages. High Yield: Average Cartridge Yield 5,000 standard pages. Extra High Yield: Average Cartridge Yield 10,000 standard pages. Ships with 5,000 pages Starter Toner Cartridge. Declared Cartridge Yield in accordance with ISO/IEC 19752. |
| Type | 1-piece Cartridge | |
| Codes | MLT-D205S/ELS - 2,000 Pages, MLT-D205L/ELS - 5,000 Pages | MLT-D205S/ELS - 2,000 Pages, MLT-D205L/ELS - 5,000 Pages, MLT-D205E/ELS - 10,000 Pages |
| Options | | |
| Options | -520-sheet Cassette Tray - ML-S3710A/SEE -Memory (256MB) - ML-PAR100/SEE -IEEE 1284B Parallel Connector - ML-PAR100/SEE | -520-sheet Cassette Tray - ML-S3050A/SEE -Memory (512MB) - ML-MEM170/SEE -IEEE 1284B Parallel Connector - ML-PAR100/SEE |



For more information, please visit www.samsung.com/uk/printer