

SunAngel 32 Series

SPECIFICATION

The SunAngel 32 Series printers are based on OKI C321dn machines and have been modified to allow SunAngel functionality. Printer hardware specification is as follows.

PRINTER

Maximum Print speed A4:	20ppm
Time to first print (TTFP):	9 seconds
Warm up time:	Up to 60 seconds
Processor speed:	532MHz

INTERFACE

Connectivity:	USB 2.0 High Speed, 10/100 TX Ethernet
Printer language:	PCL6 (XL3.0 & PCL5c) PostScript 3 emulation
OS Compatibility:	Windows XP Home / XP Professional (32-bit & 64-bit) / Server 2003 (32-bit & 64-bit) / Server 2008 (32-bit & 64-bit) / Server 2008 R2 (64-bit) / Vista (32-bit & 64-bit) / Windows 7 (32-bit & 64-bit); Mac OS X 10.3.9 to 10.7

PAPER

Paper capacity:	Multi-purpose tray: approx 100 sheets of 80gsm
Paper sizes:	Multi-purpose tray: A4, A5, B5, A6, Envelopes (C5, DL, Com-9, Com-10, Monarch), Index Card (3" x 5") (75 x 125mm), Photo Size (4" x 6", 5" x 7") (100 x 150mm, 125 x 175mm), Custom Size (up to 1320mm length including banners)

GENERAL

Memory (RAM) Standard:	128MB; Maximum: 640MB
Power supply:	Single phase 220-240VAC, frequency 50/60Hz +/-2%
Power consumption:	Typical: 480W; Max: 1170W; Idle: 90W; Power Save: <14W; Deep Sleep: <1.1W; Auto-Off: <0.5W
Noise level:	Operating: <52dB(A); Standby: 37dB(A); Power save: Inaudible
Dimensions (HxWxD):	242 x 410 x 504mm
Weight:	22kg

PRINTERS

32WB:	Standard White and Black prints
32SC:	Standard Cyan, Magenta, Yellow and Black prints
32DW:	Fluorescent White and Standard Black prints
32DC:	Fluorescent Cyan, Magenta, Yellow and Standard Black prints