

SunAngel 33SW

SPECIFICATION

The SunAngel 33SW Series printers are based on OKI C322dn machines and have been modified to allow SunAngel functionality. Printer hardware specification is as follows.

PRINTER

Maximum Print speed A4:	30ppm
Time to first print (TTFP):	9 seconds
Warm up time:	Up to 60 seconds
Processor speed:	533MHz

INTERFACE

Connectivity:	USB 2.0 High Speed, 10/100 TX Ethernet
Printer language:	PCL6 (XL3.0 & PCL5c) PostScript 3 emulation
OS Compatibility:	Windows XP Home / XP Professional (32-bit & 64-bit) / Server 2003 (32-bit & 64-bit) / Server 2008 (32-bit & 64-bit) / Server 2008 R2 (64-bit) / Vista (32-bit & 64-bit) / Windows 7 (32-bit & 64-bit); Mac OS X 10.3.9 to 10.7

PAPER

Paper capacity:	Multi-purpose tray: approx 100 sheets of 80gsm
Paper sizes:	Multi-purpose tray: A4, A5, B5, A6, Envelopes (C5, DL, Com-9, Com-10, Monarch), Index Card (3" x 5") (75 x 125mm), Photo Size (4" x 6", 5" x 7") (100 x 150mm, 125 x 175mm), Custom Size (up to 1320mm length including banners)

GENERAL

Memory (RAM) Standard:	1GB Memory
Power supply:	Single phase 220-240VAC, frequency 50/60Hz +/-2%
Power consumption:	Typical: 480W; Max: 1170W; Idle: 90W; Power Save: <14W; Deep Sleep: <1.1W; Auto-Off: <0.5W
Noise level:	Operating: <52dB(A); Standby: 37dB(A); Power save: Inaudible 242
Dimensions (HxWxD):	x 410 x 504mm
Weight:	22kg

