

WG7550F

IDEAL FOR SMBs, THIS RAPID- PRINTING A3 COLOUR MFP INKJET PRINTER DELIVERS HIGH- YIELDS WITH LOWER COSTS

With high-speed copy, print, scan and fax capabilities, this A3 printer is ideal for demanding offices. Few replaceable parts, lower power usage and higher-yield consumables cut running costs and simplify maintenance while a small footprint makes it the perfect fit for an office tight on space.



- Achieve a high printing yield with exceptional print speeds of up to 80ppm (300 dpi draft)
- Create seamless wireless LAN connections and print with smartphones or tablets via Mopria (Android), Apple AirPrint or the Canon PRINT Business mobile app
- Transfer scans to and print direct from a USB
- Take advantage of high-speed copying and scanning with ADF functionality, which produces a 2-sided scan in just one pass
- Deliver clear document transfers with the printer's high-speed fax capability
- Maximise office space and efficiency with the MFP's compact space-saving design
- Maintain with ease and print faster with the static FINE Line Head, which reduces the number of replacement parts
- Cut unnecessary down time with a maximum paper supply of 2,250 sheets (including optional cassette) and high-yield XL ink cartridges (20,000 pages with dedicated XL black ink and 16,500 pages with the XL colour ink)
- Reduce reliance on service teams - fewer replacement parts and smooth and easy recovery from paper jams allow easy user maintenance
- Enjoy easy operation thanks to the 5-inch colour touchscreen with on-screen keyboard
- Reduce costs with lower power consumption - just TEC 1.4kwh in sleep mode
- Work towards sustainability goals thanks to the printer's design - a portion of recycled plastic is used in each one

PRODUCT RANGE



WG7550Z



WG7550F



WG7550

Canon

TECHNICAL SPECIFICATIONS

WG7550F

PRINTER	
MAXIMUM PRINTING RESOLUTION	1200 x 1200dpi
PRINT HEAD/ INK	
Type	Line Head w/FINE Technology
Ink Tank	Black/Cyan/Magenta/Yellow
Ink Tank Series (EUR)	PGI-7500
Estimated Page Yield	XL = 20,000 pages BK XL - 16,500 pages C/M/Y
PRINT SPEED	
Document : Col, B/W ^{*1} Simplex, General Mode (600dpi), Cassette 1	Up to 50ppm
Document : Col, B/W ^{*2} Simplex, Office Document Mode (300dpi), Cassette 1	Up to 80ppm
Document : Col, B/W ^{*1} Duplex, General Mode (600dpi), Cassette 1	Up to 25 ppm
Document : Col, B/W ^{*3} FPOT Ready/simplex, Cassette 1	Approx. 6.5 sec
Document : Col, B/W ^{*3} FPOT Sleep/simplex, Cassette 1	Approx. 12.5 sec
MAXIMUM MEDIA SIZE (WXL) Default setting of Long Paper is OFF [*] This is supported by firmware 1.0 or 1.1	Cassette : 297 x 431.8 mm (11.7"x17") Multi-Purpose Tray: 330.2 mm x 482.6 mm (13"x19") ^{*4}
SUPPORTED MEDIA SIZE [*] Depending on regions, custom size specification may be different. Please refer to "Maximum Media Size".	A5, A4, A3, B5, B4, Statement, Executive, Letter, Legal, 11x17, 12x18, SRA3, 13x19, K8, K16, Foolscap/Folio, Oficio, G-Letter, A-Letter, G-Legal, A-Foolscap, B-Oficio, M-Oficio, E-Oficio, A-Oficio, F4A, FS(Indian Legal), 4x6", 5x7", 8x10", 10x12", 13x19", COM10, Monarch, ISO-C5, DL, Custom size (Up to 330.2mm x 711.2mm or 330.2 mm x 482.6 mm)
PRINTING MARGIN Bordered Printing Bordered Auto Duplex Printing	Top, Bottom, Left, Right: 4mm each ^{*5}
SUPPORTED MEDIA TYPE AND SIZE PER CASSETTE -CASSETTE 1:	
Thin Paper (52-63g/m ²) Plain Paper (64-105g/m ²) Thick Paper (106-220g/m ²) Colored Paper (64-82g/m ²) Recycled Paper (64-105g/m ²) Bond Paper (83-99g/m ²)	A5, A4, B5, Statement, Executive, Letter, K16, G-Letter
Envelope (75-105g/m ²) Canon Matte Photo Paper Label (118-185g/m ²)	COM10, Monarch, ISO-C5, DL Not Available Not Available
SUPPORTED MEDIA TYPE AND SIZE PER CASSETTE -CASSETTE 2, 3:	
Thin Paper (52-63g/m ²) Plain Paper (64-105g/m ²) Thick Paper (106-220g/m ²) Colored Paper (64-82g/m ²) Recycled Paper (64-105g/m ²) Bond Paper (83-99g/m ²)	A5, A4, A3, B5, B4, Statement, Executive, Letter, Legal, 11x17, K16, K8, Foolscap/Folio, Oficio, G-Letter, A-Letter, G-Legal, A-Foolscap, B-Oficio, M-Oficio, E-Oficio, A-Oficio, F4A, FS(Indian Legal)
Envelope (75-105g/m ²) Canon Matte Photo Paper Label (118-185g/m ²)	Not Available Not Available Not Available
SUPPORTED MEDIA TYPE AND SIZE PER CASSETTE -CASSETTE 4: [*] Cassette 2 & 3 support thick paper (106-220g/m ²) but cassette 4 supports 106-163g/m ² only	
Thin Paper (52-63g/m ²) Plain Paper (64-105g/m ²) Thick Paper (106-163g/m ²) Colored Paper (64-82g/m ²) Recycled Paper (64-105g/m ²) Bond Paper (83-99g/m ²) Envelope (75-105g/m ²)	A5, A4, A3, B5, B4, Statement, Executive, Letter, Legal, 11x17, K16, K8, Foolscap/Folio, Oficio, G-Letter, A-Letter, G-Legal, A-Foolscap, B-Oficio, M-Oficio, E-Oficio, A-Oficio, F4A, FS(Indian Legal) Not Available
Canon Matte Photo Paper Label (118-185g/m ²)	Not Available Not Available

SUPPORTED MEDIA TYPE AND SIZE -MULTI-PURPOSE TRAY:	
Thin Paper (60-63g/m ²) Plain Paper (64-105g/m ²) Thick Paper (106-256g/m ²) Colored Paper (64-82g/m ²) Recycled Paper (64-105g/m ²) Bond Paper (83-99g/m ²)	A5, A4, A3, B5, B4, Statement, Executive, Letter, Legal, 11x17, 12x18, SRA3, 13x19, K16, K8, Foolscap/Folio, Oficio, G-Letter, A-Letter, G-Legal, A-Foolscap, B-Oficio, M-Oficio, E-Oficio, A-Oficio, F4A, FS(Indian Legal), 4x6
Envelope (75-105g/m ²) Canon Matte Photo Paper Label (118-185g/m ²)	COM10, Monarch, ISO-C5, DL 4x6", 5x7", 8x10", 10x12", A4/LTR, A3, 13x19" A4, B4, Letter
PAPER CASSETTE CAPACITY (80G/M²)	
Cassette 1, 2, 3, 4 Multi-Purpose Tray	550 sheets each 50 sheets
MAXIMUM OUTPUT TRAY CAPACITY (80G/M²)	A3: 100 sheets, A4/LTR:250 sheets
SUPPORTED MEDIA TYPE FOR DOUBLE SIDE PRINTING	
Type	Thin Paper, Thick Paper, Plain Paper, Colored Paper, Recycled Paper, Bond Paper
Size/Weight	A5 - 12x18", 52-220g/m ²
PRINT HEAD ALIGNMENT	Automatic Adjustment
SCAN ^{*6}	
SCANNER TYPE	Flatbed & ADF
SCANNER SENSOR	CISx2 sensors
DUPLEX SCANNING	Available (Single Pass)
OPTICAL RESOLUTION ^{*7}	600 x 600 dpi
SELECTABLE RESOLUTION ^{*8}	9600 x 9600 dpi
SCANNING BIT DEPTH (INPUT/OUTPUT)	
Grayscale Color	10bit/8bit 30bit/24bit (RGB10bit/8bit each)
SCANNING SPEED ^{*9}	
Document(ADF) : Simplex Col Document(ADF) : Simplex B/W Document(ADF) : Duplex Col Document(ADF) : Duplex B/W	Approx. 40 ipm Approx. 40 ipm Approx. 65 ipm Approx. 65 ipm
MAXIMUM PAPER CAPACITY (80G/M²)	100 sheets
MAXIMUM DOCUMENT SIZE	
Flatbed ADF	A3/ 11"x17" A3/ 11"x17"
COPY	
MAXIMUM DOCUMENT SIZE SUPPORTED MEDIA SIZE	A3/ 11"x17" A5, A4, A3, B5, B4, Statement, Executive, Letter, Legal, 11x17, 12x18, SRA3, 13x19, K8, K16, Foolscap/Folio, Oficio, G-Letter, A-Letter, G-Legal, A-Foolscap, B-Oficio, M-Oficio, E-Oficio, A-Oficio, F4A, FS (Indian Legal), 4x6", 5x7", 8x10", 10x12", 13x19", COM10, Monarch, ISO-C5, DL, Custom size (Up to 330.2mm x 711.2mm or 330.2 mm x 482.6 mm)
COPY EXPOSURE	9 Levels
COPY SPEED ^{*10}	
Document (A4/LTR) Canon Original Method/ Simplex	50 ppm (Col, B/W)
FIRST-COPY-OUT TIME ^{*11}	
Document : Color sFCOT/Simplex	Approx. 5.8 sec
MAGNIFICATION	25-400% (1% Increments)
MULTIPLE COPY	Up to 999 copies
FAX	
APPLICABLE LINE	PSTN (Public Switched Telephone Network)
MODEM SPEED	Super G3 (Up to 33.6Kbps) / G3 (Up to 14.4Kbps)
TRANSMISSION SPEED	
B/W Color	Approx. 3 sec/page (33.6kbps) Not Available
COMPRESSION METHOD ^{*12}	
B/W Color	MH,MR,MMR,JBIG Not Available
GRADATION	
Black Color	256 Levels Not Available

TECHNICAL SPECIFICATIONS

WG7550F

FAX RESOLUTION	8dots/mm × 3.85 lines/mm (Standard) 8dots/mm × 7.7 lines/mm (Fine) 8dots/mm × 15.4 lines/mm (Super Fine) 16dots/mm × 15.4lines/mm (Ultra Fine)
MEDIA SIZE	
Sending	11 x 17, LGL, LTR, A3, B4, A4, B5*3, A5*4
Receiving	11 x 17, LGL, LTR, A3, B4, A4, B5, A5, 8K, and 16K
FAX MEMORY ^{*13}	Up to 512 pages
AUTOMATIC DIALING	
One-touch Dialing	Up to 19 (Best Member)
Coded Dialing	Up to 281
Group Dialing	Up to 199
SEND COMMUNICATION PROTOCOL	FTP (TCP/IP), SMB (TCP/IP), SMTP
MAXIMUM DOCUMENT SIZE	(Same as Copy function)
ADDRESS BOOK	300 addresses
SEND RESOLUTION	204dpi x 196 dpi, 300dpi x 300dpi
FILE FORMAT	
Single Page	TIFF (MMR), PDF, JPEG
Multi-Pages	TIFF (MMR), PDF
NETWORK	
WIRED LAN	
Network Type	1000 Base-T/ 100Base-TX/ 10Base-T
Data Rate	1Gbps(1000Mbps)/100Mbps/10Mbps
WIRELESS LAN	
Network Type	IEEE 802.11 b/g/n
Frequency Band	2.4 GHz
Range	Indoor 50m ^{*14}
Security	Infrastructure Mode; 128 (104)/ 64 (40) bit WEP, WPA-PSK(TKIP/AES), WPA2-PSK(TKIP/AES) Access Point Mode; WPA2-PSK (AES-CCMP)
DIRECT CONNECTION (WIRELESS LAN)	Available
OPERATING SYSTEM	
SUPPORTED OPERATING SYSTEMS	Windows: Windows 7 - Starter / Home Basic / Home Premium / Professional / Enterprise / Ultimate Windows 8.1 - 8.1 / Pro / Enterprise Windows 10 - Home / Pro / Enterprise Windows Server 2008 - Standard (x86/x64) / Enterprise Edition (x86/x64) / Datacenter (x86/x64) Windows Server 2008 R2 Windows Server 2012 Windows Server 2012 R2 Windows Server 2016 Mac: V10.16.0: OS10.8 to 10.13 (incompatible with 10.14) V10.17.0: OS10.8 to 10.14 (incompatible with 10.15)
PRINTING SOLUTIONS	
CANON PRINT BUSINESS	Available
CANON PRINT SERVICE	Available
MOPRIA	Available
APPLE AIR PRINT	Available ^{*14}
GOOGLE CLOUD PRINT	Available ^{*14}
NFC	NOT Available
MEDIA DIRECT PRINT (USB MEMORY)	
Compatible Format	USB 2.0 compatible
File Format	JPEG/TIFF/PDF
OTHERS	
OPERATION PANEL	
Display	LCD (5.0 inch/TFT color)
Language	35 Languages Selectable: Japanese/English/ German/ French/Italian/Spanish/Dutch/Portuguese/Norwegian/ Swedish/Danish/Finnish/Russian/Czech/Hungarian/ Polish/Slovene/Turkish/Greek/Simplified Chinese/ Traditional Chinese/Korean/Slovak/Estonian/Latvian/ Lithuanian/Romanian/Bulgarian/Croatian/Catalan/ Arabic/Malay/Basque/Thai/Vietnamese
INTERFACE	
USB Port for USB Memory	USB 2.0 Hi-Speed
USB Port for PC	USB 2.0 Hi-Speed

For Phone	Available
For Phone Line	Available
FINISHING OPTIONS	-
OPERATING ENVIRONMENT ^{*15}	Temperature; 5 to 35C (41 to 96F) Humidity: 20 to 90% RH (w/o condensation)
RECOMMENDED OPERATING ENVIRONMENT ^{*15}	Temperature; 15 to 30C (59 to 86F) Humidity: 20 to 85% RH (w/o condensation)
POWER	AC 100-240V 50/60Hz
POWER CONSUMPTION	
Copy/Print ^{*16}	Approx. 110W
Ready ^{*16}	Approx. 55W
Sleep ^{*16}	Approx. 1.9W
Off ^{*16}	Approx. 0.1W
Maximum Power Consumption	Approx. 300W
TEC (TYPICAL ELECTRICITY CONSUMPTION) ^{*17}	Approx. 1.25kWh/week
ENVIRONMENTAL REGULATION	Energy Star*, Blue Angel*, Eco Mark*, EPEAT* *To be officially announced
DUTY CYCLE	100,000 pages
RECOMMENDED MONTHLY PRINTING VOLUME	1,000 to 5,000 pages
DIMENSION (WxDxH)	
Standard Configuration (WxDxH)	560mm(W) x 590mm(D) x 880mm(H) 22.1"(W) x 23.3"(D) x 34.7"(H)
With Optional Pedestal (WxDxH)	588mm(W) x 590mm(D) x 1,133mm(H) 23.2"(W) x 23.3"(D) x 44.7"(H)
Maximum Space (WxDxH)	925mm(W)x1,208mm(D) x 1,487mm(H) 36.5"(W) x 47.6"(D) x 58.6"(H) (*ADF is opened to 60°)
WEIGHT (INC. PRINT HEAD)	Approx. 82.1 kg (Approx. 180.2lb)
(OPTIONAL) CASSETTE FEEDING UNIT CF10 (CASSETTE 3, 4)	
MEDIA SIZE	Refer to "Supported Media Type and Size per Cassette 3, 4: " above.
MEDIA WEIGHT	
MEDIA CAPACITY	
POWER	Supplied from Main Unit
DIMENSION/WEIGHT	560mm x 590mm x 253 mm (WxDxH) 22.1"(W) x 23.3"(D) x 10.0"(H), Approx. 19kg, Approx. 41.2lb

FOOTNOTES

- ^{*1} Print Speed is based on ISO/IEC 24734. Measured in default mode (General Mode: 600dpi) and calculated by Canon original methodology.
Print speed varies depending on system configuration, interface, software, content of document, print mode, media type, weight and used cassette etc.
- ^{*2} Print Speed is based on ISO/IEC 24734. Measured in fast mode (Office Document Mode: 300dpi) and calculated by Canon original methodology.
Print speed varies depending on system configuration, interface, software, content of document, print mode, media type, weight and used cassette etc.
- ^{*3} Print Speed (FPOT) is based on ISO/IEC17629. Print speed varies depending on system configuration, interface, software, content of document, print mode, media type, weight and used cassette etc.
- ^{*4} With Custom setting, cassette 1 supports 90.0 x 190.0 mm to 216.0 x 297.0 mm. cassette 2, 3 and 4 supports 139.7 x 210.0 mm to 297.0 x 431.8 mm
- ^{*5} Depending on the driver software, this margin varies.
- ^{*6} TWAIN driver (ScanGear) is based on TWAIN Specifications V 1.6.
- ^{*7} Optical Resolution is based on ISO/IEC 14473. This is the maximum sampling rate when scanning the original.
- ^{*8} When scanning in high resolution, scanning area size may be limited.
- ^{*9} Average copy time from ADF. Set the original on ADF and measure time from pushing the scanning button to output the copied paper.
- ^{*10} Copy Speed is based on Canon original Method. With Canon original chart, execute the continuous copy and calculate copy pages per minute.
- ^{*11} First-Copy-Out Time is based on ISO/IEC 29183.
- ^{*12} Data transfer speed is measured in default mode with Canon original FAX testing chart. Actual speed varies depending on content of document, receiving settings at the destination, transfer line status and etc.
- ^{*13} Fax memory is measured with Canon original FAX testing chart. This number varies depending on the available memory size, content of document and etc.
- ^{*14} Some early stage units may require firmware update to make Air Print available.
- ^{*15} Print quality might be lower depending on the operating environment.
- ^{*16} Reference value measured by Canon original method based on operation modes in International ENERGY STAR Program. Depending on your environment, this may vary.
- ^{*17} Typical Electricity Consumption (TEC) value: TEC value was calculated assuming the unit will be constantly switched among operational mode, sleep mode, and power-off mode for 5 days, and that it will be either in sleep or power-off mode for the remaining 2 days within the same week. The TEC value of this product is calculated by Canon on their own accord using TEC measurement procedure regulated in International ENERGY STAR Program.
Specifications may be changed without notice.

Canon Inc.
canon.com

Canon Europe
canon-europe.com

English edition
© Canon Europa N.V., 2019

