TECHNICAL **SPECIFICATIONS**

Canon PIXMA G4511

GENERAL SPECIFICATIONS

Functions

PRINTER SPECIFICATIONS

Print Resolution Print Technology

Mono Print Speed Colour Print Speed Photo Print Speed **Borderless Printing**

CARTRIDGES AND YIELDS Standard Ink Bottles

Cartridge Yield (Plain paper)

Cartridge Yield (Photo print)

PAPER SUPPORT Paper Types

Maximum Paper Input

Paper Sizes

Paper Weight

Wi-Fi, Print, Copy, Scan, Fax, Cloud Link

Up to 4800 [1] x 1200 dpi

2 FINE Cartridges (Black and Colour) Refillable ink tank printer Approx. 8.8 ipm [2]

Approx. 5.0 ipm ^[2]

Borderless 10x15cm: Approx. 60 seconds [3] Yes (A4, Letter, 20x25cm, 13x18cm, 13x13cm, 10x15cm)

GI-590 < PGBK> GI-590 <C>

GI-590 <M> GI-590 <Y>

A4 colour documents printing [4]

Black: 6000 pages* Colour: 7000 pages* Estimated supplemental yield 10x15cm colour photo printing ^[5] Colour: 2000 Photos*

* Estimated supplemental yield

Plain Paper High Resolution Paper (HR-101N) Photo Paper Plus Glossy II (PP-201) Photo Paper Pro Luster (LU-101) Photo Paper Plus Semi-gloss (SG-201) Glossy Photo Paper "Everyday Use" (GP-501)

Matte Photo Paper (MP-101)

Envelope

Rear tray: Max. 100 sheets (plain paper)

ADF: Max. 20 sheets (plain paper)
A4, A5, B5, 10x15cm, 13x13cm, 13x18cm, 20x25cm,

Envelopes (DL, COM10), Letter, Legal

Plain paper: 64 - 105 g/m²

Canon photo paper: up to 275 g/m²

SCANNER SPECIFICATIONS

Scanner Type Scanner Resolution (Optical) A4 Scan Speed Scanning Depth

(fugtuo / tugni) Maximum Document Size

COPIER SPECIFICATIONS

Copy Speed

ADF Colour Copy Speed ADF B/W Copy Speed Multiple Copy Copy Functions

Copy Zoom

Copy Quality Settings

FAX SPECIFICATIONS

Fax Type Fax Resolution

Fax Speed

Fax Memory

Group Dial

INTERFACE Display Type & Size

Display Languages

Interface Type - PC / Mac

Interface Type - Other

CIS flatbed photo and document scanner

Approx. approx. 19 sec [7] Colour: 48 bit / 24 bit Greyscale: 16 bit / 8 bit A4/LTR (216 x 297 mm) ADF: A4, LTR, LGL

sFCOT: Approx. 24 sec [8] sESAT: Approx. 3.5 ipm [8] ESAT: Approx 2.5 ipm^[8]

ESAT: Approx 8.0 ipm^[8]

99 copies (max.)

Document copying (plain paper), Borderless Copy, 2-on-1 copy, 4-on-1 copy, Collated copy (ADF only), Frame erase copy (Flatbed only), Copy job

reservation, ID copy 25-400%. Fit to Page Draft, Standard, High

Super G3 / Colour

Mono: up to 300 x 300dpi Colour: 200 x 200 dpi

Mono: approx. 3 sec. (33.6kbps) [7] Colour: approx. 1 min. (33.6kbps) [7]

Up to 50 pages

Max. 19 locations

Full dot I CD

32 Languages Selectable: Japanese/English (mm & inch)/German/French/Italian/Spanish/ Dutch/Portuguese/Norwegian/Swedish/Danish/ Finnish/Russian/Czech/Hungarian/Polish/Slovene/ Turkish/Greek/Simplified Chinese/Traditional Chinese/Korean/Indonesian/Slovakian/Estonian/ Latvian/Lithuanian/Ukrainian/Romanian/Bulgarian/

Croatian/Vietnamese Hi-Speed USB (B Port)

Wi-Fi: IEEE802.11 b/g/n Wireless LAN Frequency Band: 2.4GHz Wi-Fi Security: WPA-PSK, WPA2-PSK, WEP

PIXMA Cloud Link (from smartphone or tablet) Canon PRINT Inkjet/SELPHY app

Mopria (Android) Apple AirPrint Google Cloud Print Wireless Direct

Message In Print app



TECHNICAL SPECIFICATIONS

Canon PIXMA G4511

SOFTWARE

Supported Operating Systems

Supported Mobile Systems Minimum System Requirements

Software Included

PHYSICAL FEATURES Weight Dimensions (W x D x H) Operatina Temperature Operating Humidity Power Consumption

Windows 10 , Windows 8.1, Windows 7 SP1 .NET Framework 4.5.2 or 4.6 is required OS X 10.10.5~OS X 10.11, macOS 10.12

iOS, Android, Windows 10 Mobile

Windows: 3.1GB disk space, Internet Explorer 8 Mac: Internet connection, 1.5GB disk space, Safari 5 Display: 1024 x 768 XGA

MP Driver including Scanning Utility My Image Garden with Full HD Movie Print [9] Quick Menu Easy-WebPrint EX (download) [10]

approx. 7.3kg

approx. 445 x 330 x 197 mm approx. 45.5dB(A) [11]

5-35°C

10-90%RH (no dew condensation)

AC 100-240V, 50/60Hz

Off: Approx. 0.2W Standby (connected to PC via USB): Approx. 0.9W (scannina lamp off) Standby (all ports connected): Approx. 1.6W

(scanning lamp is off) Time to enter Standby mode: 10minutes 48sec Copying: Approx. 10W [12]

Footnotes

[1] Ink droplets can be placed with a minimum pitch of 1/4800 inch

- [2] A4 document print speed on plain paper is measured based on average of ESAT in Office Category Test of ISO/IEC 24734 standard.
- $^{\hbox{\tiny{[3]}}}$ Photo print speed is based on default driver setting using ISO/JIS-SCID N2 standard on Canon Photo Paper Plus Glossy II and does not take into account data processing time on host computer.
- $^{[4]}$ Page Yield is the estimated value based on Canon individual test method using the ISO/IEC 24712 chart and continuous printing simulation with the replacement after initial setup.
- $^{[5]}$ Page Yield is the estimated value based on Canon individual test method using the ISO/IEC 29103 chart and continuous printing simulation with the replacement after initial setup.
- [6] Optical resolution is a measure of maximum hardware sampling resolution based on ISO 14473 standard. When scanning in high resolution, the maximum scan size is
- $^{[7]}$ Color document scan speed is measured with ISO/IEC 29183 Target A. Scan speed indicates the time measured between pressing the scan button of the scanner driver and the on-screen status display turns off. Scan speed may vary depending on system configuration, interface, software, scan mode settings and document
- [8] Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming up time.
- [9] "Full HD Movie Print" is available from movie files created by the Canon digital cameras or Canon digital video cameras. Requires installation of the following software available for the Canon camera from which the movie was captured for Windows Vista. Canon ZoomBrowser EX (version 6.5 or later) or Canon ImageBrowser (version 6.5 or later) : MOV format only. Canon ImageBrowser EX (version 1.0 or later) software : MOV format and MP4 format
- [10] Easy-Web Print EX: Internet Explorer 8, 9, 10 and 11*(for Windows) is required.
- [11] When printing ISO/JIS-SCID N2 pattern on 10x15cm Photo Paper Plus Glossy II using
- [12] When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings

- All specifications subject to change without notice.
- Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
- Ink yield may vary depending on texts/photos printed, applications software used, print mode and type of paper used. For yield information see www.canon-europe.com/ink/yield
- Scan speed may vary depending on system configuration, interface, software, scan mode settings and document size etc.
- Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming
- All brand and product names are trademarks of their respective companies.
- Microsoft, Windows and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.



Canon Inc. canon.com Canon Europe canon-europe.com English edition Canon Europa NV 2019