PIXMA GM4050

BLACK & **WHITE** MEGATANK 3-IN-1 WITH **ADF**

Up productivity and cut costs with an 18,000-page yield from 3 black ink bottles¹. Boost scanning and copying with a 35-sheet ADF and top-up with no-squeeze ink bottles, ideal for small or home offices wanting smooth production and superb auality.







Cut the cost-per-page

Enjoy superb yields of up to 18,000 pages from 3 black ink bottles¹ and a low cost-per-page from the refillable ink tank. Top up with no-squeeze, mess-free ink bottles.

Fast-track productivity

Keep up momentum with auto two-sided printing and a large 350-sheet plain paper capacity via a two-way feed, and boost multipage scanning and copying with a 35sheet ADF.

Flexible connectivity

Link up with Wireless Connect and print, scan, copy, check ink levels and run maintenance via the Canon PRINT app. For fast local connections, use the Ethernet link.

Quality and speed

Work fast with print speeds of up to 13ipm mono² without sacrificing quality - enhanced pigment black ink keeps text sharp, crisp and clear for professional results.

Business-friendly

Use the two-line mono LCD for in-house control or keep track of ink levels, print usage and status out of house with remote management tools.









Connectivity

PRODUCT RANGE



Plain Paper Capacity

PIXMA GM4050



PIXMA G5050



PIXMA G6050

PIXMA GM2050 PIXMA GM4050 PIXMA G5050 PIXMA G6050 PIXMA G7050



Live for the story

TECHNICAL SPECIFICATIONS

PIXMA GM4050

GENERAL SPECIFICATIONS

Functions

PRINTER SPECIFICATIONS

Print Resolution Print Technology

Mono Print Speed Colour Print Speed (with optional colour cartridge)

Two Sided Printing

CARTRIDGES AND YIELDS

Standard Ink Cartridaes Optional Colour Ink . Cartridges

Cartridge Yield (Plain paper)

PAPER SUPPORT Paper Types

Maximum Paper Input

Automatic Document Feeder

Paper Sizes

Paper Weight

SCANNER SPECIFICATIONS Scanner Type Scanner Resolution (Optical)

A4 Scan Speed

Scanning Depth (Input / Output) Maximum Document Size Wi-Fi, Ethernet, Black & White Print, Copy, Scan, Cloud Link

Up to $600 \times 1200 \, \mathrm{dpi}^{\,[1]}$

1 FINE Cartridge (Black) with Optional Colour

Cartridge Refillable ink tank printer Approx. 13.0 ipm Approx. 6.8 ipm [2]

Auto Duplex Print (A4, A5, B5, Letter - Plain Paper)

GI-50 <PGBK> CI-541XI

A4 monochrome documents printing [3]

Black: 6,000 pages Colour (CL-541): 180 pages [4] Colour (CL-541XL): 400 pages [4]

* Estimated supplemental yield

Plain Paper

High Resolution Paper (HR-101N) Envelope

Rear Tray: Max. 100 sheets (plain paper) Cassette: Max. 250 sheets (plain paper)

Up to 35 Sheets (1-sided)

Rear Tray: A4, A5, B5, LTR, LGL

Envelopes (DL, COM10), Card Size (91 x 55mm) [Custom size] width 55mm - 215.9 mm,

length 89mm - 676mm Cassette: A4, A5, B5, LTR

[Custom size] width 148.0 mm - 215.9 mm. length 210mm - 297mm

ADF: A4 LTR LGL

Rear Tray/Cassette: Plain paper: 64 - 105 g/m²

Flatbed, ADF and CIS colour scanner

1200 x 2400 dpi [10]

Colour: 3.5 ms/line(300dpi) Greyscale: 1.5 ms/line(300dpi) [8] Colour: RGB each 16bit / 8bit Greyscale: 16 bit / 8 bit A4/LTR (216 x 297 mm) ADF: A4, LTR, LGL

COPIER SPECIFICATIONS

Copy Speed

Multiple Copy Copy Functions

Copy Zoom

INTERFACE Display Type & Size

Display Languages

Interface Type - PC / Mac

Interface Type - Other

SOFTWARE

Supported Operating Systems

Supported Mobile Systems Minimum System

Software Included

Requirements

sFCOT/Simplex (black): Approx. 12 sec [9] sESAT/Simplex (black): Approx. 10.7 ipm ^[9] ESAT/Simplex ADF (black): Approx. 11.5 ipm ^[9]

99 copies (max.)

Document Copying, Photo Copying,

Borderless copy, 2-sided copy, 2-on-1 and 4-on-1 copy, Frame erase copy, ID copy

25 - 400% (in 1% increments)

Fit to page A5 to A4, B5 to A4, A4 to A5 and A4 to B5

Full Dot LCD

32 Languages Selectable: Japanese/English (mm & inch)/German/French/Italian/Spanish/Dutch/ Portuguese/Norwegian/Swedish/Danish/Finnish/ Russian/Czech/Hungarian/Polish/Slovene/Turkish/ Greek/Simplified Chinese/Traditional Chinese/ Korean/Indonesian/Slovakian/Estonian/Latvian/ Lithuanian/Ukrainian/Romanian/Bulgarian/

Croatian/Vietnamese

Hi-Speed USB (B Port) Ethernet: 10/100Mbps (auto switchable)

Wi-Fi: IEEE802.11 b/g/n Wi-Fi Security: WPA-PSK, WPA2-PSK, WEP,

Administration password Wireless LAN Frequency Band: 2.4GHz

Canon PRINT Inkjet/SELPHY app

PIXMA Cloud Link

Canon Print Service Plugin (Android)

Wireless Direct Access Point Mode

Windows 10, Windows 8.1, Windows 7 SP1

Operation can only be guaranteed on a PC with pre-installed Windows 7 or later.
Printer driver and IJ Network Device Setup Utility are

available with following OS. Windows Server 2008 R2 SP1,

Windows Server 2012 R2, Windows Server 2016

Windows Server 2019 iOS, Android (via Canon PRINT Inkjet/SELPHY app)

Windows: 2.0GB or more

Note: for bundled software installation.

The necessary amount of hard disk space required. Display: 1024 x 768 XGA

MP Driver

IJ Printer Assistant Tool

TECHNICAL SPECIFICATIONS

PHYSICAL FEATURES Weiaht Dimensions (W x D x H) Acquistic Noise Levels Operating Temperature **Operating Humidity** Power Source Power Consumption

Typical Electricity Consumption (TEC) approx. 9.2kg approx. 403 x 369 x 234 mm approx. 50.5dB(A) [5] 5-35°C

0.14kWh [7]

10-90%RH (no dew condensation)

AC 100-240V, 50/60Hz Off: Approx. 0.3W Standby (connected to PC via USB): Approx. 0.8W Standby (all ports connected): Approx. 1.7W Time to enter Standby mode: 11min 9sec Printing (USB connection to PC): Approx. 10W [6]

Footnotes

- [1] Ink droplets can be placed with a minimum pitch of 1/4800 inch
- 21 Ad document print speed on plain paper is measured based on average of ESAT in Office Category Test of ISO/IEC 24734 standard.

PIXMA GM4050

- Yield is the estimated value based on Canon individual test method using the ISO/IEC 19752 monochrome chart and continuous printing simulation with the replacement after initial setup.
- [4] Print colour document with optional colour cartridge. This product is a monochrome inkjet printer.

 - Although colour printing can be done by purchasing a compatible colour cartridge, quickly using up the ink in the installed cartridge is recommended. Once the installed colour cartridge is empty, please replace with the contact protector or a new colour cartridge.
- [5] Plain Paper(A4, B/W). Acoustic Noise is measured based on ISO7779 standard.
- $^{\text{[6]}}$ Copy: When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.
- 77 Typical Electricity Consumption (TEC) value: TEC value was calculated assuming the unit will be constantly switched among operational mode, sleep mode, and power-off mode for 5 days, and that it will be either in sleep or power-off mode for the remaining 2 days within the same week. The TEC value of this product is calculated by Canon on their own accord using TEC measurement procedure regulated in International ENERGY STAR Program.
- [8] The fastest speed in Hi-Speed USB on Windows PC. Transfer time to computer is not
- [9] Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183. Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC 24735. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming up
- [10] Optical resolution is a measure of maximum hardware sampling resolution based on ISO 14473 standard.

All specifications subject to change without notice.

Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc. Ink yield may vary depending on texts/photos printed, applications software used, print mode and type of paper used. For yield information see www.canon-europe.com/ink/yield

All brand and product names are trademarks of their respective companies. Microsoft, Windows and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.

> Canon Inc. canon.com Canon Europe canon-europe.com English edition Canon Europa NV 2019



BLACK & WHITE MEGATANK 3-IN-1 WITH ADF

PIXMA GM4050

Up productivity and cut costs with an 18,000-page yield from 3 black ink bottles¹. Boost scanning and copying with a 35-sheet ADF and top-up with no-squeeze ink bottles, ideal for small or home offices wanting smooth production and superb quality.

Sales Start Date: TBC



PRODUCT DETAILS:

Product Name	Mercury Code	EAN Code		
PIXMA GM4050	3111C008AA	4549292152562		

CONSUMABLES:

Product Name	Mercury Code	EAN Code		
GI-50 (PGBK)	3386C001AA	4549292134155		

OPTIONAL CONSUMABLES:

Product Name	Mercury Code	EAN Code			
CL-541	5227B005AA	8714574572581			
CL-541XL	5226B005AA	8714574572604			



BLACK & WHITE MEGATANK 3-IN-1 WITH ADF

PIXMA GM4050

Up productivity and cut costs with an 18,000-page yield from 3 black ink bottles¹. Boost scanning and copying with a 35-sheet ADF and top-up with no-squeeze ink bottles, ideal for small or home offices wanting smooth production and superb quality.



MEASUREMENT / LOGISTIC INFORMATION:

Product Name	Mercury Code	Pack description	Quantity per pack	Length (mm)	Width (mm)	Height (mm)	Gross Weight (kg)	Net Weight (kg)
PIXMA GM4050	3111C008AA	Individual	1	500	538	333.8	12.98	10.3
		Pallet (Upper)	12	1003	1089	1059	157.80	123.6
		Pallet (Bottom)	16	1003	1089	1339.7	209.70	165

What's in the box?

- Multifunctional black and white refillable ink tank printer – PIXMA GM4050
- 3 high-yield ink bottles (3x Black)
- · Power cord
- Setup CD-ROM
- Manuals and other documents

