

SPEEDY A4 SINGLE-FUNCTION COLOUR LASER PRINTER FOR ENHANCED PRODUCTIVITY.

i-SENSYS LBP673Cdw II



Single-function A4 colour devices for smooth and speedy printing processes, designed for ease of use in smaller workspaces.

HIGH-QUALITY PRINTING

Produce high-quality output from toners with a wide range of colours and achieve bright, vibrant prints with excellent reproduction of both light and dark tones in high print quality.

SMOOTH USER EXPERIENCE

Easily carry out a range of print tasks and quickly reach relevant parts of the online manual via a QR code.

360-DEGREE SECURITY

A Security Settings Navigator recommends appropriate security settings to protect against security leaks and cyber threats.

IMPROVE SUSTAINABILITY EFFORTS

Increase your sustainability efforts by embracing devices that use recycled plastic and cardboard packaging for toner cartridges.

TECHNICAL SPECIFICATIONS

i-SENSYS LBP673Cdw II

PRINTER ENGINE		Power consumption
Print speed	Single sided : Up to 33 ppm (A4) Up to 60 ppm(A5-Landscape) Double sided : Up to 29.5 ipm (A4)	Maximum: Approx. 1,380W or less Active printing: Approx. 700 W Standby: Approx. 24.0W or less Sleep: Approx. 1.0 W or less Typical Electricity Consumption (TEC): 0.31 kWh/week ⁶ For detailed information relating to Lot26 regulation, please go to: http://www.canon-europe.com/For_Work/Lot26/index.aspx
Printing method	Colour laser beam printing	
Print quality	Up to 1200 x 1200 dpi	
Warm-up time	Approx. 16.6 seconds or less from power on	
Print margins	5 mm-top, bottom, left and right	
Advanced printing features	Encrypted Secure Print Secure Print Print from USB memory key (JPEG/TIFF/PDF) Microsoft Universal Print support iOS: AirPrint, Canon PRINT app Android; Mopria certified, Canon Print Service Plug-in, Canon PRINT app, IPP everywhere	
MEDIA HANDLING		
Paper input (Standard)	250 sheets 50 sheets multi-purpose tray	Dimensions (W x D x H)
Paper input (Option)	550 sheets cassette	Weight
Maximum paper input capacity	850 sheets	Operating environment
Paper output	150 sheets	Control panel
Media types	Plain paper, Recycled paper, Heavy Paper, Thin paper, Colour paper, Coated paper, Pre-punched, Label, Post card, Envelope	CONTROLLER
Media sizes	<p>Cassette (Standard): A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Post card, Envelop (COM10, DL, C5, Monarch), Custom sizes: Min. 98 x 148 mm Max. 216.0 x 356.0 mm.</p> <p>Multi-purpose tray: A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Post card, Indexcard, Envelope (COM10, DL, C5, Monarch), Custom sizes: Min. 76 x 127 mm Max. 216.0 x 356.0 mm.</p> <p>Cassette (Optional): A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Post card, Custom sizes: Min. 100 x 148 mm Max. 216.0 x 356.0 mm.</p>	Processor Speed 1200MHz Memory 1GB Storage 4GB Printer Languages UFRII, PCL5c ² , PCL6, Adobe® PostScript3 Fonts 45 PCL fonts, 136 PS fonts Interface and connectivity USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection
Media weights	Cassette (standard and optional): 60 to 163 g/m ² (Up to 200 g/m ² with Coated paper) Multi-purpose tray: 60 to 176 g/m ² (Up to 200 g/m ² with Coated paper)	Network Protocol Print: TCP/IP (LPD/Port9100/IPP/IPPS/WSD) Management: SNMPv1, SNMPv3 (IPv4,IPv6) Security: TLS1.3, IPsec, IP/Mac address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS, IPPS) Security (wireless): Infrastructure Mode: WPA-PSK(AES), WPA2-PSK(AES), WPA3-SAE (AES), WPA-EAP(AES), WPA2-EAP(AES), WPA3-EAP(AES) Access Point Mode: WPA2-PSK(AES), WPA3-SAE (AES)
Double sided printing	Automatic Cassette: A4, A5, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K Custom size - Min. 148 x 148 mm Max. 216.0 x 356.0 mm 60 to 200 g/m ²	Software and Printer Management Remote User Interface (RUI), Department ID Management, Toner Status Tool, iW Enterprise Management Console: Server-based software for centralised management of a fleet of devices Cooperating with External Security Audit System (Security Information and Event Management) eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics.
GENERAL FEATURES		
Power requirements	220-240V (±10%) 50/60Hz (±2Hz)	

TECHNICAL SPECIFICATIONS

i-SENSYS LBP673Cdw II

Operating Systems Compatibility	Windows® 11 / Windows® 10 / Server® 2025 / Server® 2022 / Server® 2019 / Server® 2016 Mac OS X version 10.15 & up Linux ³
CONSUMABLES	
All-in-One cartridges	Cartridge 069 Black (2,100 pages ⁴) ⁵ Cartridge 069H Black (7,600 pages ⁴) ⁵ Cartridge 069 Cyan (1,900 pages ⁴) ⁵ Cartridge 069H Cyan (5,500 pages ⁴) ⁵ Cartridge 069 Magenta (1,900 pages ⁴) ⁵ Cartridge 069H Magenta (5,500 pages ⁴) ⁵ Cartridge 069 Yellow (1,900 pages ⁴) ⁵ Cartridge 069H Yellow (5,500 pages ⁴) ⁵
ACCESSORIES/ OPTIONS	
Items	PAPER FEEDER PF-K1 (550-sheet cassette)

Footnotes

^[1] Declared noise emission in accordance with ISO 7779. Based on ISO9296, below figure is different. Active: 62dB or less

^[2] Commands supported only. Third party driver or direct printing from application required.

^[3] Web distribution only

^[4] Based on ISO/IEC 19798

^[5] Printer ships with Black: 1,200 pages, C/M/Y: 1,100 pages starter cartridges

^[6] As per US ENERGY STAR® version3.2

i-SENSYS LBP673Cdw II

Canon

Canon Inc.
Canon.com

Canon Europe
canon-europe.com

English Edition
© Canon Europa N.V. 2025