imagePROGRAF PRO-4000

Large format reliable and consistent print for photography, fine art and proofing. For the very best photographic quality, the imagePROGRAF PRO-4000 can produce images up to 44" with the best print quality, outstanding speed and reliability.







- Using LUCIA PRO 12 inks, colours are richer and blacks are deeper, producing prints that are faithful to your images.
- A new 1.28" wide print head enables faster printing while maintaining high print quality.
- Optional dual roll unit supports continuous paper feed or automatic take-up of the printed output.
- An attractive black body hardware design with an accentuated red line denoting the link with Canon EOS digital cameras.
- Ergonomic design with a flat top surface for print checking and 3.5" colour LCD touch screen operation panel.

- Fast and easy printing directly for PDF and JPEG file formats from USB memory stick.
- Wi-Fi functionality for easy connection and quick setup to wireless networks.
- Guaranteed colour consistency between jobs and different production sites.
- High-capacity "hot swap" ink tanks for uninterrupted printing.
- The Print Studio Pro plug-in lets you print effortlessly from professional editing software such as Adobe Lightroom®, Adobe Photoshop® and Canon's Digital Photo Professional.



Technical Specifications

imagePROGRAF PRO-4000

TECHNOLOGY

Print Technology

per print head x 1 print head)

Number of Nozzles Print Resolution 2,400 dpi x 1200 dpi

Nozzle Pitch

Ink Droplet Size minimum 4 pl per colour Sales Ink: 160ml/330ml/700ml Bundled Starter Ink: 190ml Ink Capacity

Pigment inks - Black, Matte Black, Cyan, Magenta, Yellow, Photo Cyan, Photo Magenta, Grey, Photo Grey, Red, Blue, Chroma Ink Type

OS Compatability

Printer Languages

USB A Port: USB Memory Direct Print for JPEG/PDF files USB B Port: Built-in Hi-Speed USB 2.0 Ethernet: 10/100/1000 base-T Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b

MEMORY

Standard memory **Hard Drive**

Standard Interfaces

PRINTING PAGE SIZE/ PRINT SPEED

Plain Paper Coated Paper Photo Glossy Paper

MEDIA HANDLING

Media Feed and Output

Media Width

Minimum Printable Length

Maximum Printable Length

Maximum Media Roll Diameter

Media Core Size

Margins Recommended area

Canon Bubblejet on Demand 12 colours integrated type (12 chips

18,432 nozzles (1536 nozzles x 12 colour)

 $600\ dpi\ x\ 2$ includes Non-firing nozzle detection and compensation system

User adjustments necessary. Printing environment and media must match those used for the adjustments.

CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only

Microsoft Windows 32 Bit: Vista, 7, 8, 8.1, 10, Server 2008, 64 Bit: Vista, 7, 8, 8.1, 10, Server 2008/R2, Server 2012/R2 Apple Macintosh: OSX 10.7.5 - 10.11

SG Raster (Swift Graphic Raster)

1 GB

320 GB

Roll Paper: One Roll, Front-loading, Front Output Optional Roll Paper: One Roll, Front-loading, Front Output Cut Sheet: Front-loading, Front Output (Manual feed using

media locking lever)

Roll paper: 203.2 ~ 1118 mm Cut sheet: 203.2 ~ 1118 mm

Roll/Cut: 0.07 ~ 0.8 mm

203.2 mm Roll paper: 18 m (Varies according to the OS and application) Cut sheet: 1.6 m $\,$

Internal diameter of roll core: 2"/3"

Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm

Margins Printable area

Media Take-up roll unit

Borderless Printing Width (Roll Only)

Maximum number of delivered prints

DIMENSIONS AND WEIGHT

Physical Dimensions WxDxH (mm) & Weight (Kg)

Packaged Dimensions WxDxH (mm) & Weight (Kg)

POWER AND OPERATING REQUIREMENTS

Power Supply

Power Consumption

Operating Environment

Accoustic Noise (Power/ Pressure)

Regulations

WHAT'S INCLUDED

What's in the Box?

Software Included

WHAT'S INCLUDED

Optional Items

User Replaceable Items

Roll paper: Top: 3 mm, Bottom: 3 mm, Side: 3 mm Roll paper (borderless): Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut sheet: Top: 3 mm, Bottom: 20 mm, Side: 3 mm

Roll Paper: One roll. If second option is added then automatic

Optional - Dual direction roll take up unit allowing print surface to be wound inside or outside of the roll

515 mm(JIS B20, 728 mm(JIS BI), 1030 mm(JIS B0), 594 mm(JIS AI), 1030 mm(JIS B0), 594 mm(JIS AI), 841 mm(JIS O AO), 10", 14", 17", 24", 36", 42", 44", 257 mm(JIS B4)*, 297 mm(JIS O A3)*, 329 mm(JIS O A3)*, 42", 44", 420 mm(JIS O A2)*, 8", 16", 30", 300 mm* "Some environmental conditions may not produce the desired result

Standard position: 1 sheet Flat position: A2 landscape, glossy paper less than 10 sheets, Coated paper less than 20 sheets (excludes strong curled condition)

1593 x 984 x 1168 (Basket Opened)

1593 x 766 x 1168 (Basket Closed) Weight approx 123 kg (including Roll Holder Set, excluding ink

and print heads)

Printer: (Main unit and stand with pallet): 1818 x 913 x 1012 mm.

Weight approx: 166 kg

AC 100-240V (50-60Hz)

Operation: 112 W or less Standby: 1.8 W or less Power off: 0.5 W or less

Temperature: 15~30°C, Humidity: 10~80% RH

(no dew condensation)

Operation: TBD dB (A) (Glossy paper, Print priority: Standard)

Operation: TBD dB (A) or less Operation: TBD Bels or less Operation: TBD Bels or less (Glossy paper, Image, Print priority: Standard) (Measured on ISO7779 standard)

Europe: CE mark, Germany: TUV mark, Russia: EAC, Other countries: CB certification International Energy Star Program (WW), RoHS

Printer, 1x print head, 3" paper core attachment, EU & UK Power Cable, 1 set of starter ink tanks, Set up guide, Safety/Standard Environment leaflet, User software CD-ROM (OSX/Windows), PosterArtist Lite CD-ROM, EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet, Quick Guide and Printhead Alignment Sheet

imagePROGRAF PRO Printer Driver, Print Plug-In for Office,

Quick Utility Toolbox and PosterArtist Lite Other software available as Download from Web.

Roll Unit: RU-41 2/3" Roll Holder: RH2-45

Ink Tank: PFI-1100(160ml), PFI-1300(330ml), PFI-1700(700ml) Print Head: PF-10 Cutter Blade: CT-07 Maintenance Cartridge: MC-30





Crystal-fidelity



