Canon i-SENSYS LBP151dw
Specification

PRINTER ENGINE

Print speed	Single sided: Up to 27 ppm (A4) Double sided: Up to 15 ipm (A4)
Printing method	Monochrome laser beam printing
Print quality	Up to 1200 x 1200 dpi
Print resolution	Up to 600 x 600 dpi
Warm-up time	Approx. 15 seconds or less from power on
First Page Out Time	Approx. 8 seconds
Recommended Monthly Print Volume	500 - 2,000 pages per month
Duty cycle	Max. 15,000 pages per month[1]
Print margins	5 mm-top, bottom, left and right
Advanced printing features	Google Cloud Print Ready iOS: Canon PRINT Business app Android; Mopria certified, Canon Print Service Plug-in, Canon PRINT Business app

MEDIA HANDLING

Paper input (Standard)	250-sheet cassette 1-sheet multi-purpose tray
Paper input (Option)	-
Paper output	100-sheet face down, 1 sheet face up
Media types	Plain paper, Recycled Paper, Heavy Paper, Label, Envelope, Transparecy
Media sizes	Cassette (Standard and optional) A4,B5,A5,LGL,LTR,EXECUTIVE,STATEMENT,FOOLSCAP,16K,OFFICIO,B-OFFICIO,M-OFFICIO,GLTR,GLGL,AFLS,Envelop: COM10,Monarch,C5,DL Custom sizes (Width:76.2 to 216mm Length: 210 to 356mm) Multi-purpose tray: A4,B5,A5,LGL,LTR,EXECUTIVE,STATEMENT,FOOLSCAP,16K,OFFICIO,B-OFFICIO,M-OFFICIO,GLTR,GLGL,AFLS,Envelop: COM10,Monarch,C5,DL Custom sizes (Width:76.2 to 216mm Length: 127 to 356mm)
Media weights	Cassette: 60 to 163 g/m² Multi-purpose tray: 60 to 163 g/m²
Double sided printing	Automatic (A4/LTR/LGL/OFFICIO/B-OFFICIO/M-OFFICIO/FLS, 60 to 105 g/m²)

GENERAL FEATURES

Power requirements	220-240V (±10%) 50/60Hz (±2Hz)
Power consumption	Maximum: Approx. 1120W or less Active: Approx. 260W or less Standby: Approx. 2.6W or less Sleep: Approx.1.1W or less[1] Power switch off: 0.5W or less Typical Electricity Consumption (TEC): 0.7kWh/week Idle time required to enter sleep mode: 1-30 min (default: 1 min) Idle time required to enter Auto Shutdown: 4 hours (default)
Noise level	Sound power[1] Active: 66 dB or less Standby: Inaudible Sound pressure[1] Active: 52 dB Standby: Inaudible
Dimensions (W x D x H)	390 mm x 365 mm x 245 mm
Weight	Approx. 8.6 kg
Operating environment	Temperature: 10 to 30ºC (50 to 86ºF) Humidity 20 to 80% RH (no condensation)
Control panel	5 LED indicators, 4 operation keys

CONTROLLER

Processor Speed	400MHz
Memory	512MB
Printer Languages	UFRII (Ultra Fast Rendering), PCL5e, PCL6
Fonts	45 PCL fonts
Interface and connectivity	USB 2.0 High-Speed, 10BASE-T/100 BASE-TX, Wireless 802.11b/g/n
Software and Printer Management	Remote User Interface (RUI), SSID Tool, Toner Status Tool, iW Management Console: Server-based software for centralised management of a fleet of devices
Operating Systems Compatibility	Windows® 10 / Windows® 8.1 / Windows® 8 / Windows® 7 / Server® Vista / Server® 2012R2 / Server® 2012 / Server® 2008R2 / Server® 2008 / Server® 2003R2 / Server® 2003 Mac OS X version 10.5.8 & up Linux*/Citrix

CONSUMABLES

All-in-One cartridges	Standard: Cartridge 737 (2,400 pages[1])[2]

ACCESSORIES/ OPTIONS

Items	-

Footnotes

Duty cycle - [1] Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product

Power consumption - [1] Wireless: Approx. 1.8W or less

Noise level - [1] Declared noise emission in accordance with ISO 9296

Operating Systems Compatibility - [1] Web distribution only. Driver will be available in May, 2016.

All-in-One cartridges - [1] Based on ISO/IEC 19752
[2] Printer ships with 1,700 pages starter cartridge