

# A SMART, A4 COLOUR SINGLE FUNCTION DEVICE WITH INTEGRATED WI-FI AND SECURE PRINT



## i-SENSYS LBP722Cdw

**User-friendly A4 colour single-function printer suitable for small-medium sized businesses with a high print output.**

### Enhanced connectivity

Embrace flexible working with a variety of connectivity features, including Wi-Fi support, NFC and Universal Print by Microsoft.

### Boosted productivity

Maximise your print output with rapid print speeds and an expandable paper capacity of up to 2,300 sheets with additional cassettes.

### Enhanced security

Have confidence in your data security with Secure Print and advanced integrated security software, such as McAfee Embedded Control and TLS1.3 security layer.



#### 38 PPM

Print speed



#### HIGH PRODUCTIVITY

Automatic double-sided printing



#### 2,300 SHEETS

Maximum capacity with additional cassettes



#### WIRELESS CONNECTIVITY

Print from smart phones and tablets, thanks to Wi-Fi and NFC connectivity

### Exceptional image quality

Achieve superior colour graphics, images and texts with laser-quality printing for professional-level documents.

### Improved serviceability

Simple installation, easy maintenance and excellent durability enable minimal downtime and reduced service costs.

The Canon logo, consisting of the word "Canon" in a bold, red, sans-serif font.

TECHNICAL SPECIFICATIONS

PRINTER ENGINE	
Print speed	Single sided (A4): Up to 38 ppm colour and mono Double sided (A4): Up to 38 ipm colour and mono Single sided (A5-Landscape): Up to 59 ppm colour and mono
Printing method	Colour laser beam printing
Print quality	Up to 1200 x 1200 dpi
Warm-up time	Print ready message shown: Approx. 2 seconds or less from power on
First Page Out Time	Colour: approx. 6,3 seconds Mono: approx. 5.3 seconds
Recommended Monthly Print Volume	2,000 - 7,500 pages per month
Duty cycle	Max. 80,000 pages per month¹
Print margins	4 mm-top, bottom, left and right
Advanced printing features	Secure Print Print from USB memory key (JPEG/TIFF/PDF/XPS) Barcode Print² Touch & Print (NFC) iOS: AirPrint, Canon PRINT Business app Android; Mopria certified, Canon Print Service Plug-in, Canon PRINT Business app Microsoft Universal Print
MEDIA HANDLING	
Paper input (Standard)	550-sheet cassette 100-sheet multi-purpose tray
Paper input (Option)	550-sheet cassette x 3 (Paper Feeder PF-D1) 550-sheet cassette (Cassette Feeding Unit-AV1)
Maximum paper input capacity	Up to 2,300 sheets
Paper output	200-sheet face down
Media types	Multi-Purpose Tray: Plain paper, Recycled paper, Heavy Paper, Thin paper, Colour paper, Coated paper, Pre-punched, Post card, Envelope Cassette: Plain paper, Recycled paper, Heavy Paper, Thin paper, Label, Colour paper, Coated paper, Pre-punched
Media sizes	Cassette (Standard): A4, A5, A5 (Landscape), A6, B5, Letter, Executive, Statement, GLTR, 16K, Custom sizes: Min. 101.6 x 148 mm Max. 216.0 x 297 mm.  Multi-purpose tray: A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, ILGL, GLGL, Foolscap, 16K, Post card, Envelop (COM10, Monarch, C5, DL), Custom sizes: Min. 76.2 x 127 mm Max. 216.0 x 355.6 mm.  Cassette (Optional): A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, GLTR, ILGL, GLGL, Foolscap, F4A, 16K, Custom sizes: Min. 101,6 x 148 mm Max. 216,0 x 355,6 mm
Media weights	Cassette (standard and optional): 60 to 163 g/m² Multi-purpose tray: 60 to 216 g/m²
Double sided printing	Automatic Cassette: A4, A5, B5, Legal, Letter, Executive, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, ILGL, GLGL, Foolscap, F4A, 16K Custom size - Min. 148 x 210 mm Max. 216 x 355.6 mm 60 to 163 g/m²
GENERAL FEATURES	
Power requirements	220-240V (±10%) 50/60Hz (±2Hz)
Power consumption	Maximum: Approx. 1500W or less Active: Approx. 729W or less Standby: Approx. 34,4W or less Sleep: Approx. 1,1W or less Typical Electricity Consumption (TEC): 0.45kWh/week ⁹ For detailed information relating to Lot26 regulation, please go to: <a href="http://www.canon-europe.com/For_Work/Lot26/index.aspx">http://www.canon-europe.com/For_Work/Lot26/index.aspx</a>
Noise level	Sound power³ Active: Simplex 65 dB or less (BW) / 66 dB or less (CL) Duplex 67 dB or less (BW) / 68 dB or less (CL) Standby: 48 dB or less Sound pressure³ Active: Simplex 50 dB or less (BW) / 51 dB or less (CL) Duplex 52 dB or less (BW) / 52 dB or less (CL) Standby: 33 dB or less 458 mm x 464 mm x 388 mm
Dimensions (W x D x H)	
Weight	Approx. 29 kg
Operating environment	Temperature: 10 to 30°C (50 to 86°F) Humidity 20 to 80% RH (no condensation)
Control panel	5 Line LCD, 5 LED (Online, Ready, Message, Job and Energy saver), Buttons, 10-key numeric keypad

CONTROLLER	
Processor Speed	1GHz x 2
Memory	2GB
Storage	32GB eMMC (available space 15GB)
Printer Languages	UFR II (Ultra Fast Rendering), PCL5c⁴, PCL6, Adobe® PostScript3
Fonts	93 PCL fonts (93 Roman, 10 Bitmap fonts, 2 OCR fonts) Andale Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese)*5 Barcode Fonts*2 136 PostScript fonts
Interface and connectivity	USB 2.0 High-Speed, 10BASE-T/100 BASE-TX/1000BASE-T  Wireless 802.11b/g/n, Wireless Direct Connection Print: TCP/IP (LPD/Port9100/IPP/IPPS/FTP/WSD)
Network Protocol	Management: SNMPv1, SNMPv3 (IPv4,IPv6)
Software and Printer Management	Security: TLS1.3, IPsec, IP/Mac address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS, IPPS), Dual Network Support Security (wireless): Infrastructure Mode: WEP(64/128 bit), WPA-PSK(TKIP/AES), WPA2-PSK(TKIP/AES), WPA-EAP (AES), WPA2-EAP (AES) Access Point Mode: WPA2-PSK(AES) Wi-Fi Direct Mode: WPA2-PSK (AES) Remote User Interface (RUI), Department ID Management, Toner Status Tool, iW Enterprise Management Console: Server-based software for centralised management of a fleet of devices eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics. Content Delivery System: Server platform enables automatic firmware update to the device.
	Windows® 10 / Windows® 8.1 / Server® 2019 / Server® 2016 / Server® 2012R2 / Server® 2012 / Mac OS X version 10.11 & up Linux⁵/Citrix
	Operating Systems Compatibility
	CONSUMABLES All-in-One cartridges
ACCESSORIES/OPTIONS	Standard: Cartridge 064 Black (6,000 pages*)⁸ Cartridge 064 Cyan (5,000 pages*)⁸ Cartridge 064 Magenta (5,000 pages*)⁸ Cartridge 064 Yellow (5,000 pages*)⁸ High yield: Cartridge 064H Black (13,400 pages*)⁸ Cartridge 064H Cyan (10,400 pages*)⁸ Cartridge 064H Magenta (10,400 pages*)⁸ Cartridge 064H Yellow (10,400 pages*)⁸
	Items Paper Feeder PF-D1 (550-sheet cassette) x 3 CST,Feeding Unit-AV1 (550-sheet cassette pedestal) Barcode Printing Kit-D1 (Enables barcode printing capability) PCL Font Set-A1 (Enables Unicode printing capability on SAP and supports Andale font) Plain Pedestal-P2 Plain Pedestal-AA1 Waste Toner Box WT-B1

Notes

[1] Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product

[2] Accessory - Barcode Printing Kit-D1 - is required

[3] Declared noise emission in accordance with ISO 9296

[4] Commands supported only. Third party driver or direct printing from application required.

[5] Web distribution only. Driver will be available in H2 2021

[7] Based on ISO/IEC 19798

[8] Printer ships with Black: 6,000 pages, C/M/Y: 3,200 pages starter cartridges

[9] As per US ENERGY STAR® version3.0.

