Everything small workgroups need to create high-quality colour print every time.

i-SENSYS
LBP7210Cdn

you can

A compact A4 colour laser printer ideal for small workgroups that demand high-quality print.

This energy efficient network ready, compact colour laser printer is ideal for small workgroups needing fast, professional output with productive automatic double-sided printing.

Key features

- Compact, low profile colour laser printer
- Ideal for small workgroups needing fast output
- 20ppm in colour and mono
- Up to 9600 x 600 dpi equivalent resolution with Automatic Image Refinement
- No waiting with Quick First-Print technologies
- Productive automatic double-sided printing
- 550-sheet max capacity, to keep downtime to a minimum
- Network ready
- Energy efficient and silent in standby
- Maintenance-free All-in-One colour cartridges

What's in the box

Main unit, 718 C/M/Y/K starter cartridge, power cable, CD with driver, manual and starter guide, warranty card.

Dimensions (W x D x H)

414mm x 499mm x 328mm

Supported OS

Windows 7 (32/64bit) / Vista (32/64bit) / XP (32/64bit) / Server 2003 (32/64bit) / Server 2008 (32/64bit) / Server 2008 R2 (64bit)
Mac OS 10.5 and up
(Web distribution only)
Linux (Web distribution only)
Citrix

PRINT   COPY   FAX   SCAN

Canon

i-SENSYS
LBP7210Cdn

1 50-sheet multi purpose tray
2 250-sheet cassette
3 Cartridge 718:
5 cartridges available: Black, Cyan, Magenta, Yellow and Black Value Pack

Specifications:

PRINTER ENGINE	
Print speed	Up to 20ppm colour and mono (A4)
Printing method	Colour laser beam printing
Print quality	Up to 9600 x 600 dpi with Automatic Image Refinement
Print resolution	Up to 600 x 600 dpi
Warm-up time	Approx. 22 seconds or less from power on
First Page Out Time	Approx. 16 seconds or less
Duty cycle	Max. 40,000 pages per month[1]
Print margins	5mm – top, bottom, left and right

MEDIA HANDLING	
Paper input (Standard)	250-sheet cassette 50-sheet multi-purpose tray
Paper input (Option)	250-sheet cassette
Paper output	125-sheet face down
Media types	Plain paper, Heavy paper, Transparency, Label, Envelope, Recyled paper, Coated paper, Index card
Media sizes	Cassette (Standard and optional): A4, B5, A5, Legal, Letter, Executive, Statement, Foolscap, Envelope DL, Envelope COM10, Envelope C5, Envelope B5, Custom sizes: Width: 100.0mm to 215.9mm; Length: 148.0mm to 355.6mm Multi-purpose tray: A4, B5, A5, Legal, Letter, Executive, Statement, Foolscap, Envelope DL, Envelope COM10, Envelope C5, Envelope Monarch, Envelope B5, Index Card, Custom sizes: Width: 76.2mm to 215.9mm; Length: 127.0mm to 355.6mm
Media weights	Cassette (Standard and optional): 60 to 220 g/m² Multi-purpose tray: 60 to 220 g/m²
Double sided printing	Automatic

GENERAL FEATURES	
Power requirements	220-240V (±10%) 50/60Hz (±2Hz)
Power consumption	Maximum: 1170 W or less Active: Average approx. 430 W Standby: Average approx. 20 W Sleep: Average approx. 3 W Typical Electricity Consumption (TEC): 2.2 kWh/week
Noise level	Sound power[2]: Active: 6.7 B or less Standby: 4.3 dB(A) Sound pressure[2]: Active: 52 dB(A) or less Standby: 24 dB(A)
Dimensions (W x D x H)	414mm x 499mm x 328mm
Weight	Approx. 22.3kg
Operating environment	Temperature: 10 to 30ºC (50 to 86ºF) Humidity: 20 to 80% RH (no condensation)
Control panel	9 LED indicators 1 Operation key

CONTROLLER	
Memory	16 MB
Printer languages	CAPT (Canon Advanced Printing Technology)
Interface and connectivity	USB 2.0 High-Speed, 10BASE-T/100BASE-TX
Software and printer management	NetSpot Device Installer, Remote User Interface (RUI)
Operating systems compatibility	Windows 7 (32/64bit) / Vista (32/64bit) / XP (32/64bit) / Server 2003 (32/64bit) / Server 2008 (32/64bit) / Server 2008 R2 (64bit) / Mac OS 10.5 and up[3][4][5] / Linux[3][4] / Citrix

CONSUMABLES	
All-in-One cartridges	Cartridge 718 Black (3,400 pages[6])[7] Cartridge 718 Cyan (2,900 pages[6])[7] Cartridge 718 Magenta (2,900 pages[6])[7] Cartridge 718 Yellow (2,900 pages[6])[7] Cartridge 718 Black VP (6,800 pages [6])[7]

ACCESSORIES / OPTIONS	
Items	Paper Feeder PF-701

Standard disclaimers. All specifications subject to change without notice.

1] Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product
2] Declared noise emission in accordance with ISO 9296
3] English driver only
4] Web distribution only
5] The driver will be released in February 2013
6] Based on ISO/IEC 19798
7] Printer ships with 1,200-page K (Black) and 1,400-page CMY (Cyan, Magenta and Yellow) starter cartridges

Canon Inc
canon.com

Canon Europe
canon-europe.com

European Edition
© Canon Europa N.V., 2012

Canon