

imagePROGRAF
TA-20

COMPACT AND INTUITIVE DEVICE FOR HIGH PRINT QUALITY

A versatile and compact multi-purpose printer designed for schools, offices and retail with low volume print jobs.



- **High Print Quality**
Innovative imaging technology delivers precise printing, with powerful colour from LUCIA TD ink
- **Quiet and compact**
Seamlessly fits into any office, with reduced operation noise and full front accessibility
- **Accurate ink placement**
Print sharp lines with an innovative Air Feeding System that keeps paper flat for high accuracy
- **Strengthened security**
Security requirements and settings for secure communication, secure management and secure interface
- **Ease of use**
3" inch color LCD touchscreen panel with ample icons for immediate access

PRODUCT RANGE



imagePROGRAF TA-30



imagePROGRAF TA-20



imagePROGRAF TM-200

Canon

TECHNICAL SPECIFICATIONS

imagePROGRAF TA-20

TECHNOLOGY

Printer Type	5 colors 24"/610mm
Print Technology	Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head)
Print Resolution	2,400 x 1,200 dpi
Number of Nozzles	15,360 nozzles (MBK 5,120 nozzles, Other Colors 2,560 nozzles each)
Line Accuracy	±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments. CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only
Nozzle Pitch	1,200dpi (2 lines)
Ink Droplet Size	minimum 5 pl per colour
Ink Capacity	Sales Ink: 55ml Bundled Starter Ink: 55ml (2 x MBK, 1 x BK,C,M,Y)
Ink Type	Pigment inks - Matte Black, Black, Cyan, Magenta, Yellow
OS Compatability	Microsoft Windows 32 Bit: Vista, 7, 8, 8.1, 10 Microsoft Windows 64 Bit: Windows 7, 8.1, 10, Windows Server 2008R2, Windows Server 2012/2012R2, Windows Server 2016, Windows Server 2019 Apple Macintosh: OS X 10.10.5-OS X 10.11, macOS 10.12- macOS 10.15
Printer Languages	SG Raster (Swift Graphic Raster),HP-GL/2, HP RTL, JPEG (Ver. JFIF1.02)
Standard Interfaces	USB B Port: Hi-Speed Ethernet: IEEE 802.3 10base-T/IEEE 802.3u 100base-TX/IEEE 802.3ab 1000base-T/IEEE 802.3x Full Duplex Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b * Please refer to user manual how to activate /deactivate the wireless LAN
MEMORY	
Standard memory	2 GB
Hard Drive	NO
PRINT TIME FOR A1 PAGE SIZE	
Media Type	
CAD Drawing	Print Mode Print Time Fast 00:32 min Standard 00:56 min
Plain Paper (A1 size Portrait)	Print Mode Print Time Fast 00:30 min Standard 00:49 min
Poster	
Plain Paper (A1 size Portrait)	Print Mode Print Time Fast 00:58 min Standard 01:46 min
Heavy Coated Paper (A1 paper size)	
MEDIA HANDLING	
Media Feed and Output	Roll Paper: One Roll, Upper-loading, Front Output Cut Sheet: Upper-loading, Front Output (Manual feed using media locking lever)
Media Width	Roll paper: 203.2 - 610 mm Cut sheet: 210 - 431.8 mm
Media Thickness	Roll/Cut: 0.07 - 0.8 mm
Minimum Printable Length	Roll paper: 203.2 mm Cut sheet: 279.4 mm
Maximum Printable Length	Roll paper: 18 m (Varies according to the OS and application) Cut sheet: 594mm
Maximum Media Roll Diameter	150 mm or less
Media Core Size	Internal diameter of roll core: 2"/3"(option)
Margins Recommended area	Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm

Margins Printable area

Media Feed Capacity

Media Take-up roll unit	N/A
Borderless Printing Width (Roll Only)	(Printable) 203.2-610mm *Roll paper only * No size restriction
Maximum number of delivered prints	Standard position: 1 sheet

DIMENSIONS AND WEIGHT

Physical Dimensions WxDxH (mm) and Weight (Kg)	982 x 748 x 438 mm 37 kg (including Roll Holder Set, excluding ink and print head)
Packaged Dimensions WxDxH (mm) and Weight (Kg)	Printer (Main unit with pallet) 1147 x 874 x 542 mm 49 kg

POWER AND OPERATING REQUIREMENTS

Power Supply	AC 100-240V (50-60Hz)
Power Consumption	Operation: 52 W or less Sleep mode: 3.6W or less Default setting for the time to enter the Sleep mode: approx. 5 mins Power off: 0.3 W or less
Operating Environment	Temperature: 15-30°C, Humidity: 10-80% RH (no dew condensation)
Acoustic Noise (Power/Pressure)	Operation: 42 dB (A) (Plain paper, line drawing, standard mode) Standby: 35 dB (A) or less Operation: 5.8 Bels (Plain paper, line drawing, standard mode) (Measured on ISO 7779 standard and described based on ISO9296 standard)
Regulations	Europe: CE mark, Russia: EAC,
Certificates	TUV, CB

WHAT'S INCLUDED

What's in the Box?	Printer, 1 print head, Power Cable, 1 set of starter ink tanks, Set up guide, Quick Guide, Safety/Standard Environment leaflet, User Software CD-ROM (Win), EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet
Software Included	imagePROGRAF TA- Unified Printer Driver, Other software available as Download from Web.

OPTIONS

Optional Items	2/3" Roll Holder: RH2-28
-----------------------	--------------------------

CONSUMABLES

User Replaceable Items	Ink Tank: PFI-030 (55ml) Print Head: PF-06 Cutter Blade: CT-08 Maintenance Cartridge: MC-31
-------------------------------	--

Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.



Canon Inc.
canon.com

Canon Europe
canon-europe.com

English edition
© Canon Europa N.V., 2019