

CITIZEN

Fast, tough and easy to use receipt printer

Protected by Spill-Shield™



One touch top cover

Spill-Shield™ design to prevent damage from moisture or foreign objects to the internal mechanism. This makes it the best protected printer at the POS. No matter where you are: bar, restaurant or shop nothing can stop your printer to do it's job.

Internal power supply

All 80mm POS printers from Citizen offer an internal power supply.

Internal power supply

All 80mm POS printers from Citizen offer an internal power supply.

CT-S2000

POS, Receipt printer (thermal 3 inch / 80mm)

Applications

- Hospitality
- Journal
- Kiosk
- Kitchen
- Retail



Confidence in point-of-sale

TOMORROW'S PRINTING TODAY



USB is default in addition to serial or parallel interface boards. This makes the CT-S2000 a future-proof investment.

Specifications

Model	CT-S2000
Printing Technology	Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	220 mm /sec.
Print Width (maximum)	80 mm
Media Width (min to max)	58 / 60 / 80 / 82.5 mm
Roll Size (max), Core Size	102 mm outside diameter
Main Interface	Dual Interface Serial (RS-232C), USB (version 2.0, full speed)
Optional interfaces	Ethernet (SEH), Serial (RS-232C compliant), Parallel (IEEE 1284 compliant)
Power supply	100 - 240V, 50/60hz
Reliability	200 Million pulses or 150 Km, 2 million cuts
Emulations (Languages)	ESC/POS™
Drivers and software	Free-of-charge from website, including support for various platforms
Flash (Non-Volatile Memory)	384K bytes
Size (W x D x H) and Weight	147x207x147 mm, 1.2 Kg (AC type) / 1.8 Kgs (DC type)
Cutter	Guillotine type, full and partial
EMC and safety standards	CE, TUV, UL, C-UL, FCC class A

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

CT-S2000

POS, Receipt printer (thermal 3 inch / 80mm)

Features & Benefits

- Paper exit: Front exit, top loading
- Printing Speed: Fast print out of receipts - up to 220mm per seconds
- Low space requirement - integrated power supply enables clean work station
- Easy notification - built-in buzzer



The fully loaded high end thermal printer with built in protection