

Robust and secure with enhanced, built-in document solutions

Designed for large workgroups, this high performance colour multifunction printer allows you to print, scan and copy from a single device. Accelerate efficiency with fast print and copy speeds, duplex capabilities, Gigabit Ethernet and integrated advanced document and workflow solutions.

Outstanding value, low cost per page, high reliability and scalability make the C5765dn a versatile solution for demanding business printing needs.



Dell™ Colour Multifunction Printer -C5765dn



Dell Colour Multifunction Printer | C5765dn

High performance multifunction device

Boost productivity with high performance features on a colour multifunction printer.

- Print, scan and copy from one versatile, multifunction colour device and get optimal networking performance with built-in Gigabit Ethernet. Analogue fax function is available with purchase of a Fax Kit, sold separately.
- Print at fast speeds of up to 45 pages per minute (ppm) (A4) in black/ colour¹, with first page out time of less than 9.5 seconds.
- Get superb copy speeds of up to 45 copies per minute (cpm)
- Scan two-sided documents efficiently with the built in 110-sheet Duplex Automatic Document Feeder (DADF). Scan at up to 45 impressions per minute (ipm, simplex).
- Easily meet high volume printing demands with a high duty cycle² of up to 110,000 pages per month.
- Multitask with a 2 GB³ memory to process complex files and tasks simultaneously.



Manage tasks efficiently with built-in advanced document and workflow solutions.

- Scan and convert documents into editable, searchable PDFs directly from the printer with built-in Optical Character Recognition (OCR), making it easy to locate or edit scanned text.
- Streamline workflows with one-touch Job Flow Sheets. Use the Job Flow Editor to take complicated and repetitive tasks and combine them into a simple job flow - ready to activate with a touch of a button.
- Easily scan and route documents to multiple destinations printer, emails, network folders, or any USB memory device.
- Designed to scale with your business, the C5765dn comes with a highly customisable open solution platform, capable of supporting third party and customised imaging solutions4.



Enterprise-level security for strong data protection

Protect sensitive information with comprehensive security features.

- Prevent unauthorised access with powerful network user authentication, including LDAP and Kerberos support.
- Safeguard confidential scan and fax data with digital signature and 256-bit Advanced Encryption Standard (AES) encryption while sharing across a network or across devices.
- Protect print, fax or email jobs with the printer's hard drive encryption feature. Multi-pass secure erase further enhances hard-drive security, reducing the risk of confidential data being compromised when the printer hard disc is accessed illegally.



Convert scanned document into searchable digital files with in-device Optical Character Recognition (OCR) software.



Scan two-sided documents easily with the Duplex Automatic Document Feeder.



Print and easily create marketing collateral with additional finishing options.

^{1.} Measured in accordance with ISO IEC 27434 methodology. Actual print speeds will vary with use.
2. Duty cycle is defined as the maximum number of imaged outputs a device could deliver in a month. This metric provides a comparison of robustness in relation to other Dell printers and multifunction printers.
3. 1 MB means 1, million bytes, 1 GB means 1,000 megabytes or 1,000,000 bytes; total accessible capacity varies depending on operating environment.
4. Requires Software Development Kit (SDK), available from Quarter 1, 2014

Ease of operation

Simplify tasks with easy to use features. Extensive input and finishing options allow various printer configurations to meet varying business printing needs.

- Easily navigate printer menus with the large, intuitive 7-inch colour touch screen.
- Quickly access and print frequently used forms stored on the printer using the My Forms feature1.
- Expand the input capabilities of your printer to meet high volume printing needs with a variety of printing options. Add the optional 1,000-sheet Base Finisher to sort, stack, and staple printed documents.
- Print documents, web content, photos and more, directly from a variety of mobile devices, such as smartphones and tablets, with:
 - Dell Mobile Print app for Android™ mobile devices²
 - Mobile Print App for Dell for iOS mobile devices²

Get outstanding value

Gain long-term savings with a low cost per page and with easy control of colour printing usage.

- Reduce overall printing cost with the optional high yield toner cartridges. Print up to 18,000 pages³ (black) and 12,000 pages³ (Colour).
- Control your colour printing costs by setting user or group level print policies with Dell ColorTrack™.
- Reduce paper consumption by up to 50% with automatic two-sided printing (default print setting). This printer supports printing on recycled, renewable content, and chlorine-free paper.

Excellent service and support

Gain peace of mind with Dell's superb service and support, helping to minimise downtime and keeping productivity at its best.

- The C5765dn comes with standard one year Limited Hardware
- Enjoy fuser maintenance kit replacement for the life of your Limited Hardware Warranty⁴ to help you save on high replacement costs.
- Leverage Dell's expertise for properly configuring and sizing deployments with the optional deployment service.



Supports high volume printing with a high monthly duty cycle⁵ of up to 110,000 pages.



Increase efficiency with fast print speeds of up to 45 ppm⁶ and automatic two-sided printing.



Print directly from mobile devices with **Dell Mobile Print**² (Android[™] OS) and **Mobile** Print App for Dell² (iOS).



Enjoy long-term cost savings with optional toner capacity of up to 18,000 pages³ (black) and 12,000 pages³ (colour).



Ease of operation with intuitive 7-inch touch screen control panel.



Make an impression with high quality colour prints of up to 1200 x 1200 dpi.

^{1.} From November 2013, these solutions will also be available for download as a firmware update from Dell.com/support.

2. Mobile printing support is available from November 2013. Requires the local administrator to provide access to download the relevant app for corporate use. Configuration of the printer and the mobile device must be on the same authorised wireless network.

3. Toner yield based on testing in accordance with ISO/IEC 19798. Yields vary with usage and environmental conditions.

4. For copy of Limited Hardware Warranty, write Dell Products, Dell House, The Boulevard, Cain Road, Bracknell, Berkshire, RG12 1LF, UK or see www.dell.com/warranty. For warranty information for other countries, see website: www.dell.com/servicecontracts and then select the country. Service may be provided by third party. Technician will be dispatched if necessary following phone-based troubleshooting. Subject to parts availability, geographical restrictions and terms of service contract. Service timing dependent upon time of day call placed to Dell. Defective unit must be returned. Replacements may be refurbished.

5. Duty cycle is defined as the maximum number of imaged outputs a device could deliver in a month. This metric provides a comparison of robustness in relation to other Dell printers and multifunction printers.

printers. $6. \, \text{Measured in accordance with ISO IEC 27434 methodology. Actual print speeds will vary with use. }$

The C5765dn is packed with solutions that are customised to improve your workgroup's productivity and efficiency.



Optional Character Recognition

In-device OCR software enables the conversion of hardcopies to searchable and editable PDF files.

Job Flow Editor Utility

Simplify workflows by creating customised one-touch workflow solutions. With this utility, users are able to preset workflows to automatically sort, process and deliver a document to multiple destinations and outputs with minimal manual intervention.

My Forms¹

Create and store frequently used forms on the printer. These forms can be quickly accessed and printed via the My Forms icon on the touch screen control panel.

Eco Copy¹

The Eco Copy function reduces paper consumption and toner used during copying by enabling users to easily select copy options such as multi-page (N-up) and duplex (two-sided).

USB Direct Print/Scan

Front USB port provides easy access to previewing content on flash drives prior to printing or storing scanned files.

Be in full control of the printer fleet with Dell OpenManage™ Printer Manager (OMPM)

Quickly and easily monitor, manage and report the status of network printers from the $Dell^{\mathbb{N}}$ OMPM centralised dashboard.

Use Dell OMPM to:

- Remotely locate printers that have errors and identify problems, enabling IT managers to take the appropriate actions to remedy the situation
- Obtain alerts via email notifications, when a printer needs attention.
- Remotely monitor toner and paper-in-tray status (applicable to most printer models).
- Group multiple printers with similar setups together for easy upgrades of all the printers in the group.

Simplify workload with Dell Open Printer Driver (OPD)

 Eliminate the clutter on PCs by replacing multiple print drivers with one versatile solution, the Dell Open Printer Driver (OPD). It can help to reduce the huge workload of driver deployment and setting changes.



Dell Colour Multifunction Printer | C5765dn



- Duplex Automatic Document Feeder (DADF)
- 2. Flatbed scanner
- 3. 7-inch colour touch screen (resistive)
- 4. 400-sheet output
- 5. 550-sheet input tray
- 6. 150-sheet multipurpose tray

*Refer to page 8 for full configuration options (require separate purchase of optional accessories).

Consumables

Ship-with toner cartridge capacity¹

9,000 pages (black)

12,000 pages (colour - CMY)

Standard capacity toner cartridge¹

9,000 pages (black)

12,000 pages (colour - CMY)

High capacity toner cartridge¹

18,000 pages (black)

Imaging Drum

50,000 page yield (black) 50,000 page yield (colour - CMY)

Toner Waste Container

25,000 page yield

Warranty and service options²

Standard service

1 Year Next Business Day On-site Service after Remote Diagnosis

Service upgrade options

- 1 5 Years Next Business Day On-site Service after Remote Diagnosis
- 1 5 Years Dell ProSupport

C5765dn accessories (sold separately)







1,100-sheet High Capacity Feeder



1,000-sheet Base Finisher

550-sheet input drawer	Increase the paper input capacity to 1,250 sheets by adding the 550-sheet input drawer to the base printer.
1,100-sheet High Capacity Feeder	Increase the paper input capacity to a maximum of 2,350 sheets by adding one 1,100-sheet high capacity feeder and one 550-sheet input drawer to the base printer.
1,000-sheet Base Finisher	Sort, stack and staple your printed documents with the optional Base Finisher.
Fax Kit	Enables connection to standard fax services.
Card Reader Holder	Holder for the optional card reader, installable on the side of the base unit.

^{1.} Toner yield based on testing in accordance with ISO/IEC 19798. Yields vary with usage and environmental conditions.
2. For copy of Limited Hardware Warranty, write Dell Products, Dell House, The Boulevard, Cain Road, Bracknell, Berkshire, RG12 1LF, UK or see www.dell.com/warranty. For warranty information for other countries, see website: www.dell.com/servicecontracts and then select the country. Service may be provided by third party. Technician will be dispatched if necessary following phone-based troubleshooting. Subject to parts availability, geographical restrictions and terms of service contract. Service timing dependent upon time of day call placed to Dell. Defective unit must be returned. Replacements may be refurbished.

Product Specifications

Printer specifications	Print speed	
	Mono	Up to 45 (A4) ppm ¹
	Colour	Up to 45 (A4) ppm ¹
	First page out time from Ready state	Less than or equal to 9.5 seconds (Colour), Less than or equal to 9.0 seconds (Mono)
	Print resolution	600 x 600 dpi (Default), up to 1200 x 1200 dpi (Max)
	Operation panel	7" Colour LCD Touch Screen, 800 x 480 pixels, Backlight: White backlight, Buttons: 27
	Print language	PCL6, Adobe® PostScript 3™, XPS
	Fonts	HP PCL® 6 Emulation: 80 scalable fonts; PostScript® Level 3: 136 Scalable fonts; PDF: 16 scalable fonts
	Processor speed	1 GHz
	Memory	2 GB ²
	Hard disk	80 GB ²
	Maximum duty cycle	Up to 110,000 pages per month ³
	Recommended monthy print volume	4,000 to 15,000 pages per month
Mobile printing	Dell Mobile Print (Android™ OS) ⁴ , Mob	oile Print App for Dell by Thinxtream™ (iOS) ⁴
Printer management	Dell Printer Configuration Web Tool (EWS), Dell ColorTrack
Security	SNMP V3, AES256 Encryption, Authentication with LDAP/Kerberos/SMB servers, Secured PDF, Secure Print, Digital Certification verification	
Indevice solutions	OCR Engine, Job Flow Editor Utility, My Forms ⁵ , USB Direct Print, Eco Copy ⁵ .	
Scan specifications	Scan type	CCD flatbed scanner with DADF
	DADF Input capacity	110 sheets
	Scan resolution	Optical: 600 x 600 dpi, Software Enhanced: 2400 x 2400 dpi (max)
	Scan features	Walk-up Scan (Scan to Email, Scan to FTP, Scan to SMB, Scan to USB, Scan to Internal Storage); Walk-up Scan to Address Book (Email addresses – 2000 entries, Fax addresses - 2000 entries)
	Scanning speed	Up to 45 ipm (Simplex) for both mono and colour at 600 dpi
	Scan to media (file format)	TIFF (Single/Multi), JPEG, PDF (V1.6), XPS
	Scan size (max)	Scan Platen and ADF: (216 mm x 356 mm)
Copy specifications	Copy speed (600 x 600 dpi, Colour/Mono)	Up to 45 cpm (1 to N, N to N)
	First copy out time	From ready state: 7.0 seconds (colour), 5.0 seconds (mono)
	Copy resolution	600 x 600 dpi
	Maximum copies	999
	Copy features	N-up, Annotation, Duplex, Double copy, ID Copy, Job Cancel, Sharpness
	Enlarge	25 % to 400 % (Platen), 25 % to 400 % (ADF)
Fax specifications (with optional fax kit)	Modem speed/Fax transmission speed	Up to 33.6 Kbps
	Speed dial	Up to 2,000 entries
	Fax features	Transmit: Broadcast, Delay/Schedule, Forward, Secure, Polling Receive: Secure, Polling, Receive and forward to email
Automatic Document	ADF type	Duplex Automatic Document Feeder (DADF)
Feeder (ADF)	Input/output capacity	Up to 75 sheets (81 - 128 gsm), and 110 sheets (38 - 80 gsm)
	Media type	Plain paper, Lightweight paper, Heavyweight paper
	Media size	A4 Short Edge Feed (SEF), B5 SEF, A5 Long Edge Feed (LEF)/SEF, Letter (8.5"x 11") SEF, Folio (8.5" x 13") SEF, Legal (8.5" x 14") SEF; Statement (5.5" x 8.5") LEF, 8" x 10" SEF, 8" x 10.5" SEF Custom paper size (min): (125 mm x 85 mm) (simplex); (125 mm x 110 mm) (duplex) Custom
Connectivity	Standard interfaces	paper size (max): (215.9 mm x 355.6 mm) High speed USB 2.0, Gigabit Ethernet port, 2 USB host ports (front and rear)
Operating Systems	Windows	Windows® 8 (32/64 bit), Windows 7 (32/64 bit), Windows Vista (32/64 bit), Windows Server 2008 R1 & R2, Windows XP (32/64 bit), Windows 2003 Server (32/64 bit)
	Macintosh	Macintosh OS 10.5 to 10.8
	Others	SUSE® Linux Enterprise Desktop 10, 11; Red Hat Linux Enterprise Desktop 5, 6; Novell® Netware Support; SAP R/3 Release 4.6B onwards;
		Citrix® Presentation Server™ 4.5, Citrix XenApp 5.0 to 6.5

Standard ray Popes Management Popes			
Media sizes		Standard tray	
Multipurpose tray		3.	paper-L (106 - 163 gsm) / Heavier paper-H (164 - 216 gsm), Coated paper (164 - 216 gsm) Coated paper-L (95 - 105 gsm) / Coated paper-M (106 - 163gsm) / Coated paper-H
Media types and weights Supported Plain paper (Repair weight 60 - 90 gram, Thicker paper (RE) - 105 gram), Coated paper in 105 gram, Coated pa		Media sizes	Custom size (Min): 98 mm x 190 mm;
106 - 16.5 gsm), Cloaded paper 169 - 105 gsm), Coated paper 169 - 105 gsm), Revoked Pstreipoles, Labels, Hagaki cards, Transparency		Multipurpose tray	
Envelope Com 10 (SER), Envelope DL (LEP/SER), C3 (SER), Post Card:		3.	(106 - 163 gsm), Heavier Paper H (164 - 216 gsm), Coated paper L (95 - 105 gsm), Coated paper M (106 - 163 gsm), Coated paper H (164 - 216 gsm); Recycled Paper, Envelopes, Labels, Hagaki
Media types and weights supported Plain paper (60 - 90 gpm), Thicker paper (81 - 105 gpm), Heavier paper L (106 - 163 gpm) / Heavier Paper H (164 - 216 gpm), Coated paper H (106 - 163 gpm), Coated paper H (106 gpm),		Media sizes	Envelope Com-10 (SEF), Envelope Monarch (SEF), Envelope DL (LEF/SEF), C5 (SEF), Post Card; Custom size (Min): 76 mm x 127 mm;
Heavier Paper H IL64 - 216 spml, Coated paper M (106 - 163 spml), Coated paper M (106 spml), Coated		Optional tray	
Custom size (Main): 98 mm x 190 mm; Custom size (Main): 98 mm x 190 mm; Custom size (Main): 216 mm x 356 mm Printable area 2079 mm x 347.6 mm Standard input sources 550-sheet tray; 150-sheet multipurpose tray Additional input capacity 550-sheet single feeder drawer; 1,100-sheet high capacity feeder drawer Maximum input capacity 2,350 sheets Duplexer Automatic two-sided printing (standard) 400 sheets Maximum output capacity 500 sheets of A4 and Letter media size with 90 gsm media weight Physical specifications Dimensions (W x D x H) Printer: 560 mm x 536 mm x 630 mm; Shipping: 705 mm x 768 mm x 845 mm Weight Printer: 560 kg with consumables; Shipping: 69 0 kg Departing environment Temperature: 10 to 32 °C, Humidity: 15 to 85% RH, non-condensing, Allitude: ≤ ft 3,100 m Acoustics (Pressure emission) bystander/Power emission) bystander/Power emission bystander/Power emission) Base configuration (printing): 59d8*/7.458* Power specifications Voltage 220 VAC modet Power consumption (TEC)* 5.5 kWh/week Calas A, ErP Lot 4, RoHS-compliant*, ENERGY STAR® qualified*, WEEE, Blue Angel 2,0 ¹⁰ , REACH, GS Mark Supported languages English, French, German, Spanish and Italian Product certifications Safety certifications English, French, German, Spanish and Italian Product certifications Safety certifications English, French, German, Spanish and Italian Product certifications English, French, German, Spanish and Italian English, French, German, Spanish and Ita			Heavier Paper H (164 - 216 gsm), Coated paper L (95 - 105 gsm), Coated paper M (106 - 163
Paper handling Standard input sources 550-sheet tray; 150-sheet multipurpose tray		Media sizes	Custom size (Min): 98 mm x 190 mm;
Additional input capacity Maximum input capacity Duplexer Standard output capacity Automatic two-sided printing (standard) Maximum output capacity Automatic two-sided printing (standard) Maximum output capacity Automatic two-sided printing (standard) Maximum output capacity Maximum output capacity Sou sheets of A4 and Letter media size with 90 gsm media weight Physical specifications Dimensions (W x D x H) Printer: 560 mm x 536 mm x 630 mm; Shipping: 705 mm x 768 mm x 845 mm Weight Printer: 560 kg with consumables; Shipping: 69.0 kg Printer: 560 kg Printer: 560 kg with consumables; Shipping: 69.0 kg Printer: 560 kg Printer: 560 kg with consumables; Shipping: 69.0 kg Printer: 560 kg Printer: 5		Printable area	207.9 mm x 347.6 mm
Maximum Input capacity 2,350 sheets	Paper handling	Standard input sources	550-sheet tray; 150-sheet multipurpose tray
Duplexer Automatic two-sided printing (standard)		Additional input capacity	550-sheet single feeder drawer; 1,100-sheet high capacity feeder drawer
Standard output capacity Maximum output capacity Physical specifications Dimensions (W x D x H) Printer: 560 mm x 536 mm x 630 mm; Shipping: 705 mm x 768 mm x 845 mm Weight Printer: 560 kg with consumables; Shipping: 69.0 kg Operating environment Temperature: 10 to 32 °C, Humidity: 15 to 85% RH, non-condensing, Altitude: ≤ ft 3.100 m Acoustics (Pressure emission bystander/Power emission) Power specifications Voltage 220 VAC model Power consumption Ready mode: 13.0 W or less Power saver mode: 3.4 W or less Power saver mode: 3.4 W or less Typical energy consumption (TEC)² Environmental compliance Class A, ErP Lot 4, RoHS-compliant®, ENERGY STAR® qualified®, WEEE, Blue Angel 2.0 °°, REACH, GS Mark Mark Supported languages English, French, German, Spanish and Italian Product certifications Safety certifications English, French, German, Spanish and Italian Product certifications Dell Colour Multifunction Printer - C5765dn, Ship-With Black Cartridge (9,000-page yield®), Power cord, Quick Setup Sheet, Software and Instructions CD, Product Information Guide,		Maximum input capacity	2,350 sheets
Physical specifications Dimensions (W x D x H) Printer: 560 mm x 536 mm x 630 mm; Shipping: 705 mm x 768 mm x 845 mm Weight Printer: 56.0 kg with consumables; Shipping: 69.0 kg Operating environment Temperature: 10 to 32 °C, Humidity: 15 to 85% RH, non-condensing, Altitude: £ ff 3.100 m Acoustics (Pressure emission bystander/Power emission) Base configuration (printing): 59dB6/7.45B6		Duplexer	Automatic two-sided printing (standard)
Physical specifications Dimensions (W x D x H) Printer: 560 mm x 536 mm x 630 mm; Shipping: 705 mm x 768 mm x 845 mm Weight Printer: 56.0 kg with consumables; Shipping: 69.0 kg Operating environment Temperature: 10 to 32 °C, Humidity: 15 to 85% RH, non-condensing, Altitude: ≤ ft 3.100 m Storage Temperature: 0 to 35 °C, Humidity: 15 to 80% RH, non-condensing, Altitude: ≤ ft 3.100 m Acoustics (Pressure emission bystander/Power emission) Base configuration (printing): 59d8°/7.458° Power specifications Voltage 220 VAC model 220 · 10%, 240 · 10% VAC, 50 Hz ± 3 Hz/60 Hz ± 3 Hz Power consumption Ready mode: 130 W or less Power saver mode: 3.4 W or less Typical energy consumption (TEC)* 5.5 kWh/week Environmental compliance Class A, ErP Lot 4, RoHS-compliant®, ENERGY STAR® qualified®, WEEE, Blue Angel 2.0®, REACH, GS Mark Supported languages English, French, German, Spanish and Italian Product certifications En 60950-1/IEC 60950-1, IEC60825-1 (Lasen); NEMKO (Nordic); CE Mark (EU); CSA certified for US and Canada; Germany GS Certified; EDA/DHHS (21CFR, Chapter 1, Subchapter J) and other Safety Certifications required by individual countries Other certifications CE mark (EU countries); EN 55022 (Class A); EN55024; EN61000-3-2 (Class A); EN 61000-3-3; RSTTE Directive (EU); FCC CCFR Title 47, Part 15 Class B (USA); FCC Part 68 TCB (USA); CAN		Standard output capacity	400 sheets
Shipping: 705 mm x 768 mm x 845 mm Weight Printer: 56.0 kg with consumables; Shipping: 69.0 kg Operating environment Temperature: 10 to 32 °C, Humidity: 15 to 85% RH, non-condensing, Altitude: £ ft 3.100 m Storage Temperature: 0 to 35 °C, Humidity: 15 to 80% RH, non-condensing, Altitude: £ ft 3.100 m Acoustics (Pressure emission bystander/Power emission) Power specifications Voltage 220 VAC model Power consumption Ready mode: 130 W or less Power saver mode: 34 W or less Typical energy consumption (TEC)' Environmental compliance Class A, ErP Lot 4, RoHS-compliant®, ENERGY STAR® qualified®, WEEE, Blue Angel 2.0%, REACH, GS Mark Supported languages English, French, German, Spanish and Italian Product certifications Safety certifications EN 60950-1/IEC 60950-1, IEC60825-1 (Laser); NEMKO (Nordic); CE Mark (EU); CSA certified for US and Canada, Germany (SS Certified; FDA/DHHS (21CFR, Chapter 1, Subchapter 3) and other Safety Certifications required by individual countries Other certifications CE mark (EU countries); EN 55022 (Class A); EN55024; EN61000-3-2 (Class A); EN 61000-3-3; R&TTE Directive (EU); FCC CER Title 47, Part 15 Class B (USA); FCC Part 68 TCB (USA); CAN ICES-3(B) / NMB-3(B) Contents in box Dell Colour Multifunction Printer - C5765dn, Ship-With Black Cartridge (9.000-page yield¹) Ship-with Colour (CMY) Cartridge (12.000-page yield¹), Power cord, Quick Setup Sheet, Software and Instructions CD, Product Information Guide,		Maximum output capacity	500 sheets of A4 and Letter media size with 90 gsm media weight
Operating environment Temperature: 10 to 32 °C, Humidity: 15 to 85% RH, non-condensing, Altitude: ≤ ft 3,100 m Storage Temperature: 0 to 35 °C, Humidity: 15 to 80% RH, non-condensing, Altitude: ≤ ft 3,100 m Acoustics (Pressure emission bystander/Power emission) Base configuration (printing): 59dB ⁶ /7.45B ⁶ Power specifications Voltage 20 VAC model 220-10%, 240+10% VAC, 50 Hz ± 3 Hz/60 Hz ± 3 Hz Power consumption Ready mode: 130 W or less Power saver mode: 3.4 W or less Typical energy consumption (TEC)² 5.5 kWh/week Environmental compliance Class A, ErP Lot 4, RoHS-compliant®, ENERGY STAR® qualified®, WEEE, Blue Angel 2.0™, REACH, GS Mark Supported languages English, French, German, Spanish and Italian Product certifications EN 60950-1/IEC 60950-1, IEC60825-1 (Lasen); NEMKO (Nordic); CE Mark (EU); CSA certified for US and Canada; Germany GS Certified; FDA/DHHS (21CFR, Chapter 1, Subchapter J) and other Safety Certifications required by individual countries Other certifications CE mark (EU countries); EN 55022 (Class A); EN55024; EN61000-3-2 (Class A); EN 61000-3-3; R&TTE Directive (EU); FCC CFR Title 47, Part 15 Class B (USA); FCC Part 68 TCB (USA); CAN ICES-3(B) / NMB-3(B) Contents in box Dell Colour Multifunction Printer - C5765dn, Ship-With Black Cartridge (9,000-page yield ^(H)), Power cord, Quick Setup Sheet, Software and Instructions CD, Product Information Guide.	Physical specifications	Dimensions (W x D x H)	
Altitude: ≤ ft 3,100 m Storage Temperature: 0 to 35 °C, Humidity: 15 to 80% RH, non-condensing, Altitude: ≤ ft 3,100 m Acoustics (Pressure emission bystander/Power emission) Power specifications Voltage 220 VAC model 220-10%, 240+10% VAC, 50 Hz ± 3 Hz/60 Hz ± 3 Hz Power consumption Ready mode: 130 W or less Power saver mode: 3.4 W or less Typical energy consumption (TEC)? 5.5 kWh/week Environmental compliance Class A, ErP Lot 4, RoHS-compliant®, ENERGY STAR® qualified®, WEEE, Blue Angel 2.0™, REACH, GS Mark Supported languages English, French, German, Spanish and Italian Product certifications EN 60950-1/IEC 60950-1, IEC60825-1 (Laser); NEMKO (Nordic); CE Mark (EU); CSA certified for US and Canada; Germany GS Certified; FDA/DHHS (21CFR, Chapter 1, Subchapter J) and other Safety Certifications required by individual countries Other certifications CE mark (EU countries); EN 55022 (Class A); EN55024; EN61000-3-2 (Class A); EN 61000-3-3; R&TTE Directive (EU); FCC CFR Title 47, Part 15 Class B (USA); FCC Part 68 TCB (USA); CAN ICES-3(B) / NNB-3(B) Contents in box Dell Colour Multifunction Printer - C5765dn, Ship-With Black Cartridge (9,000-page yield™) Ship-wth Colour (CMY) Cartridge (12,000-page yield™) Power cord, Quick Setup Sheet, Software and Instructions CD, Product Information Guide.		Weight	Printer: 56.0 kg with consumables; Shipping: 69.0 kg
Altitude: ≤ ft 3,100 m Acoustics (Pressure emission bystander/Power emission) Power specifications Voltage 220 VAC model 220-10%, 240+10% VAC, 50 Hz ± 3 Hz/60 Hz ± 3 Hz Power consumption Ready mode: 130 W or less Power saver mode: 3.4 W or less Typical energy consumption (TEC)' 5.5 kWh/week Environmental compliance Class A, ErP Lot 4, RoHS-compliant®, ENERGY STAR® qualified®, WEEE, Blue Angel 2.0¹⁰, REACH, GS Mark Supported languages English, French, German, Spanish and Italian Product certifications Safety certifications EN 60950-1/IEC 60950-1, IEC60825-1 (Lasen); NEMKO (Nordic); CE Mark (EU); CSA certified for US and Canada; Germany GS Certified; FDA/DHHS (21CFR, Chapter 1, Subchapter J) and other Safety Certifications required by individual countries Other certifications CE mark (EU countries); EN 55022 (Class A); EN55024; EN61000-3-2 (Class A); EN 61000-3-3; R&TTE Directive (EU); FCC CFR Title 47, Part 15 Class B (USA); FCC Part 68 TCB (USA); CAN ICES-3(B) / NMB-3(B) Contents in box Dell Colour Multifunction Printer - C5765dn, Ship-With Black Cartridge (9,000-page yield¹¹¹) Ship-wth Colour (CMY) Cartridge (12,000-page yield¹¹¹), Power cord, Quick Setup Sheet, Software and Instructions CD, Product Information Guide,		Operating environment	
Power specifications			
Power consumption Ready mode: 130 W or less Power saver mode: 3.4 W or less Power saver mode: 3.4 W or less Typical energy consumption (TEC)? 5.5 kWh/week Environmental compliance Class A, ErP Lot 4, RoHS-compliant®, ENERGY STAR® qualified®, WEEE, Blue Angel 2.0¹®, REACH, GS Mark Supported languages English, French, German, Spanish and Italian Product certifications EN 60950-1/IEC 60950-1, IEC60825-1 (Laser); NEMKO (Nordic); CE Mark (EU); CSA certified for US and Canada; Germany GS Certified; FDA/DHHS (21CFR, Chapter 1, Subchapter J) and other Safety Certifications required by individual countries Other certifications CE mark (EU countries); EN 55022 (Class A); EN55024; EN61000-3-2 (Class A); EN 61000-3-3; R&TTE Directive (EU); FCC CFR Title 47, Part 15 Class B (USA); FCC Part 68 TCB (USA); CAN ICES-3(B) / NMB-3(B) Contents in box Dell Colour Multifunction Printer - C5765dn, Ship-With Black Cartridge (9,000-page yield¹¹) Ship-wth Colour (CMY) Cartridge (12,000-page yield¹¹), Power cord, Quick Setup Sheet, Software and Instructions CD, Product Information Guide,			Base configuration (printing): 59dB ⁶ /7.45B ⁶
Power consumption Ready mode: 130 W or less Power saver mode: 3.4 W or less Power saver mode: 3.4 W or less Typical energy consumption (TEC)7 5.5 kWh/week Class A, ErP Lot 4, RoHS-compliant8, ENERGY STAR® qualified9, WEEE, Blue Angel 2.010, REACH, GS Mark Supported languages English, French, German, Spanish and Italian Product certifications Safety certifications EN 60950-1/IEC 60950-1, IEC60825-1 (Laser); NEMKO (Nordic); CE Mark (EU); CSA certified for US and Canada; Germany GS Certified; FDA/DHHS (21CFR, Chapter 1, Subchapter J) and other Safety Certifications required by individual countries Other certifications CE mark (EU countries); EN 55022 (Class A); EN55024; EN61000-3-2 (Class A); EN 61000-3-3; R&TTE Directive (EU); FCC CFR Title 47, Part 15 Class B (USA); FCC Part 68 TCB (USA); CAN ICES-3(B) / NMB-3(B) Contents in box Dell Colour Multifunction Printer - C5765dn, Ship-With Black Cartridge (9,000-page yield11) Ship-with Colour (CMY) Cartridge (12,000-page yield11), Power cord, Quick Setup Sheet, Software and Instructions CD, Product Information Guide,	Power specifications	Voltage	
Power saver mode: 3.4 W or less Typical energy consumption (TEC)? 5.5 kWh/week Environmental compliance Class A, ErP Lot 4, RoHS-compliant®, ENERGY STAR® qualified®, WEEE, Blue Angel 2.0®, REACH, GS Mark Supported languages English, French, German, Spanish and Italian Product certifications EN 60950-1/IEC 60950-1, IEC60825-1 (Laser); NEMKO (Nordic); CE Mark (EU); CSA certified for US and Canada; Germany GS Certified; FDA/DHHS (21CFR, Chapter 1, Subchapter J) and other Safety Certifications required by individual countries Other certifications CE mark (EU countries); EN 55022 (Class A); EN55024; EN61000-3-2 (Class A); EN 61000-3-3; R&TTE Directive (EU); FCC CFR Title 47, Part 15 Class B (USA); FCC Part 68 TCB (USA); CAN ICES-3(B) / NMB-3(B) Contents in box Dell Colour Multifunction Printer - C5765dn, Ship-With Black Cartridge (9,000-page yield¹¹¹) Ship-wth Colour (CMY) Cartridge (12,000-page yield¹¹¹), Power cord, Quick Setup Sheet, Software and Instructions CD, Product Information Guide,		220 VAC model	220-10%, 240+10% VAC, 50 Hz ± 3 Hz/60 Hz ± 3 Hz
Environmental compliance Class A, ErP Lot 4, RoHS-compliant®, ENERGY STAR® qualified®, WEEE, Blue Angel 2.0¹0, REACH, GS Mark English, French, German, Spanish and Italian Product certifications EN 60950-1/IEC 60950-1, IEC60825-1 (Laser); NEMKO (Nordic); CE Mark (EU); CSA certified for US and Canada; Germany GS Certified; FDA/DHHS (21CFR, Chapter 1, Subchapter J) and other Safety Certifications required by individual countries Other certifications CE mark (EU countries); EN 55022 (Class A); EN55024; EN61000-3-2 (Class A); EN 61000-3-3; R&TTE Directive (EU); FCC CFR Title 47, Part 15 Class B (USA); FCC Part 68 TCB (USA); CAN ICES-3(B) / NMB-3(B) Contents in box Dell Colour Multifunction Printer - C5765dn, Ship-With Black Cartridge (9,000-page yield¹¹¹) Ship-wth Colour (CMY) Cartridge (12,000-page yield¹¹¹), Power cord, Quick Setup Sheet, Software and Instructions CD, Product Information Guide,		Power consumption	Power saver mode: 3.4 W or less
Supported languages English, French, German, Spanish and Italian Product certifications Safety certifications EN 60950-1/IEC 60950-1, IEC60825-1 (Laser); NEMKO (Nordic); CE Mark (EU); CSA certified for US and Canada; Germany GS Certified; FDA/DHHS (21CFR, Chapter 1, Subchapter J) and other Safety Certifications required by individual countries Other certifications CE mark (EU countries); EN 55022 (Class A); EN55024; EN61000-3-2 (Class A); EN 61000-3-3; R&TTE Directive (EU); FCC CFR Title 47, Part 15 Class B (USA); FCC Part 68 TCB (USA); CAN ICES-3(B) / NMB-3(B) Contents in box Dell Colour Multifunction Printer - C5765dn, Ship-With Black Cartridge (9,000-page yield ¹¹) Ship-wth Colour (CMY) Cartridge (12,000-page yield ¹¹), Power cord, Quick Setup Sheet, Software and Instructions CD, Product Information Guide,			
Product certifications EN 60950-1/IEC 60950-1, IEC60825-1 (Laser); NEMKO (Nordic); CE Mark (EU); CSA certified for US and Canada; Germany GS Certified; FDA/DHHS (21CFR, Chapter 1, Subchapter J) and other Safety Certifications required by individual countries Other certifications CE mark (EU countries); EN 55022 (Class A); EN55024; EN61000-3-2 (Class A); EN 61000-3-3; R&TTE Directive (EU); FCC CFR Title 47, Part 15 Class B (USA); FCC Part 68 TCB (USA); CAN ICES-3(B) / NMB-3(B) Contents in box Dell Colour Multifunction Printer - C5765dn, Ship-With Black Cartridge (9,000-page yield ¹¹) Ship-wth Colour (CMY) Cartridge (12,000-page yield ¹¹), Power cord, Quick Setup Sheet, Software and Instructions CD, Product Information Guide,		Environmental compliance	
and Canada; Germany GS Certified; FDA/DHHS (21CFR, Chapter 1, Subchapter J) and other Safety Certifications required by individual countries Other certifications CE mark (EU countries); EN 55022 (Class A); EN55024; EN61000-3-2 (Class A); EN 61000-3-3; R&TTE Directive (EU); FCC CFR Title 47, Part 15 Class B (USA); FCC Part 68 TCB (USA); CAN ICES-3(B) / NMB-3(B) Contents in box Dell Colour Multifunction Printer - C5765dn, Ship-With Black Cartridge (9,000-page yield ¹¹) Ship-wth Colour (CMY) Cartridge (12,000-page yield ¹¹), Power cord, Quick Setup Sheet, Software and Instructions CD, Product Information Guide,	Supported languages	English, French, German, Spanish and	Italian
R&TTE Directive (EU); FCC CFR Title 47, Part 15 Class B (USA); FCC Part 68 TCB (USA); CAN ICES-3(B) / NMB-3(B) Contents in box Dell Colour Multifunction Printer - C5765dn, Ship-With Black Cartridge (9,000-page yield ¹¹) Ship-wth Colour (CMY) Cartridge (12,000-page yield ¹¹), Power cord, Quick Setup Sheet, Software and Instructions CD, Product Information Guide,	Product certifications	Safety certifications	and Canada; Germany GS Certified; FDA/DHHS (21CFR, Chapter 1, Subchapter J) and other Safety
page yield ¹¹), Power cord, Quick Setup Sheet, Software and Instructions CD, Product Information Guide,		Other certifications	R&TTE Directive (EU); FCC CFR Title 47, Part 15 Class B (USA); FCC Part 68 TCB (USA);
	Contents in box	page yield ¹¹), Power cord, Quick Setup	

- 1. Measured in accordance with ISO IEC 27434 methodology. Actual print speeds will vary with use.
 2.1 MB means 1 million bytes, 1 GB means 1,000 megabytes or 1,000,000,000 bytes; total accessible capacity varies depending on operating environment.
 3. Duty cycle is defined as the maximum number of imaged outputs a device could deliver in a month. This metric provides a comparison of robustness in relation to other Dell printers and multifunction printers.
- 3. Duty cycle is defined as the maximum number of imaged outputs a device could deliver in a month. This metric provides a comparison of robustness in relation to other Dell printers and multifunction prir 4. Mobile printing support is available from November 2013. Requires the local administrator to provide access to download the relevant app for corporate use. Configuration of the printer and the mobile device must be on the same authorised wireless network.

 5. From November 2013, these solutions will also be available for download as a firmware update from Dell.com/support.

 6. Tested in accordance with ISO 7779 and reported in accordance with ISO 9296. Acoustics Declared noise emission values of computer and business equipment

 7. For the Typical Energy Consumption value calculation details please visit: www.energystar.gov/ia/products/fap/IE_TEC_Test_Procedure.pdf

 8. Meets the requirements of the EU Directive on the Restriction of the use of certain Hazardous Substances dated January 27, 2003.

 9. For details on energy efficiency of ENERGY STAR® qualified products, refer to: www.energystar.gov

 10. Only applicable to C5765dn base product plus 1,100-sheet High Capacity Feeder and additional 550-sheet tray.

 11. Toner yield based on testing in accordance with ISO/IEC 19798. Yields vary with usage and environmental conditions.

Configuration options

Configuration 1 (Standard)



Total	700-sheet
Multipurpose tray	150-sheet
Standard tray	550-sheet



Configuration 5

Total	700-sheet
Multipurpose tray	150-sheet
Standard tray	550-sheet

With optional 1,000-sheet Base Finisher*

Configuration 2



Total	1 250-sheet
550-sheet drawer	550-sheet
Optional*	
Multipurpose tray	150-sheet
Standard tray	550-sheet



Configuration 6

Total	1,250-sheet
550-sheet drawer	550-sheet
Optional*	
Multipurpose tray	150-sheet
Standard tray	550-sheet

With optional 1,000-sheet Base Finisher*

Configuration 3



Total	1,800-sheet
1,100-sheet High Capacity Feeder	1,100-sheet
Optional*	
Multipurpose tray	150-sheet
Standard tray	550-sheet



Configuration 7

Total	1 800-sheet
1,100-sheet High Capacity Feeder	1,100-sheet
Optional*	
Multipurpose tray	150-sheet
Standard tray	550-sheet

With optional 1,000-sheet Base Finisher*

Configuration 4



Total	2,350-sheet
1,100-sheet High Capacity Feeder	1,100-sheet
Optional* 550-sheet drawer	550-sheet
Multipurpose tray	150-sheet
Standard tray	550-sheet



Configuration 8

Total	2,350-sheet
1,100-sheet High Capacity Feeder	1,100-sheet
Optional* 550-sheet drawer	550-sheet
Multipurpose tray	150-sheet
Standard tray	550-sheet

With optional 1,000-sheet Base Finisher*

©2013 Dell Corporation Limited. Dell, the Dell logo and Dell Toner Management System are registered trademarks or trademarks of Dell Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. Microsoft, Windows NT are registered trademarks or trademarks of Microsoft Corporation. Android and Google Cloud Print are registered trademarks of Google Inc. iPad, iPhone, iPod, and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries. AirPrint and the AirPrint logo are trademarks of Apple Inc. Dell Products, Dell House, The Boulevard, Cain Road, Bracknell, Berkshire, RG12 1LF, UK. Product availability varies by country. Please contact your Dell representative for more information.

^{*} Sold separately.