

HP Color LaserJet Enterprise CM4540 MFP series

Ideal for enterprise, medium and small businesses wanting a reliable workgroup colour solution with high quality, multifunction capabilities and a simple control panel; IT decision makers looking for market-leading management and security features.





HP Color LaserJet Enterprise CM4540 MFP



HP Color LaserJet Enterprise CM4540f MFP



HP Color LaserJet Enterprise CM4540fskm MFP

Easily achieve brilliant colour output.

- Process jobs at the MFP with the award-winning HP Easy Select control panel. Print from the walk-up USB port with a flash drive.
- Achieve sharp contrast and bright colour with high-gloss HP ColorSphere toner. HP ImageREt delivers crisp, consistent detail.
- Save time with pre-installed Original HP LaserJet print cartridges and high-capacity black cartridges 1.
- Improve productivity with paper capacity up to 2,100 sheets²; sort, collate, staple or stack documents with a 900-sheet, 3-bin mailbox ³.

Experience market-leading fleet management and extensibility.

- Save time and money: manage printing fleets with industry-leading HP Web Jetadmin. Easily control who prints in colour with HP Color Access Controls.
- Simple setup wizards for save-to-folder and scan-to-email functions make digital workflows more efficient.
- · Extend your MFP capabilities with a rich portfolio of HP and third-party solutions that are easy to integrate.
- Make printing as mobile as you are with HP ePrint⁴.

Protect your data with advanced security features

- Protect sensitive data stored on your HP MFP with the standard encrypted HP High-Performance Secure Hard Disk
- Attach security solutions to the control panel's hardware integration pocket for a seamless appearance.
- Process jobs securely without compromising efficiency via PIN authentication. Expand the number of IP addresses on your network with IPv6, and implement network access control with IPsec.
- Create, print, scan and share sensitive business information securely via encrypted e-mail and PDFs.

ecohighlights

- Reduce energy use by up to 50% with Instant-on Technology.
- Reduce paper use by up to 50% using automatic two-sided printing.
 Reduce clutter and waste scan, store and share documents digitally

FNFRGY STAR® Qualified

¹ HP Color LaserJet CE264X Black print cartridge not included; please purchase separately.

² The 1x500 sheet paper feeder, 1x500 sheet paper feeder and cabinet and 3x500 sheet paper feeder and stand may be purchased separately for the

³ The 900-sheet, 3-bin stapling mailbox may be purchased separately for the CM4540 and CM4540f models.

⁴ Requires an Internet connection to the printer. Feature works with any Internet- and e-mail-capable device. Print times may vary. For a list of supported documents and image types, see www.hp.com/go/eprintcenter. Some HP LaserJet products will require a firmware

Product walkground

HP Color LaserJet Enterprise CM4540 MFP series

- 1.) Intuitive 8-inch HP Easy Select pivoting touch screen color control panel
- 2.) Hardware Integration Pocket for solution integration
- 3.) 900-sheet 3-bin stapling mailbox
- 4.) Front door allows convenient access to four, all-in-one HP print cartridges
- 5.) Built-in automatic two-sided printing
- 6.) Four 500-sheet input trays for a 2,100-sheet total input capacity
- 7.) 50-sheet ADF scanner processes two-sided documents at full speed Plate-glass scanner handles documents up to legal size
- 8.) 100-sheet multipurpose tray 1 handles heavy custom media up to 220 g/m2 (58 lb bond)
- 9.) Hi-Speed USB 2.0 port
- 10.) HP Jetdirect Gigabit Ethernet embedded print server
- 11.) RJ-11 fax port
- 12.) One open EIO slot
- 13.) 1280MB (not upgradable) total memory and an 800 MHz processor quickly handle complex print jobs
- 14.) HP Secure High Performance embedded hard disk
- 15.) Access port for optional Kensington-style lock



Series at a glance



HP Color LaserJet Enterprise CM4540 MFP

- print and copy speed of up to 40ppm
- up to 600 x 600 dpi effective output quality with HP ImageREt 3600
- 1280 MB RAM
- 800 MHz processor
- Standard input capacity of 600-sheets with one 500-sheet input tray and one 100-sheet multi-purpose tray. Expandable with one optional 500-sheet input tray with or without cabinet or with 3x500 sheet input tray with printer stand.



HP Color LaserJet Enterprise CM4540f MFP

- as base model with built-in analogue fax accessory
- fax speed up to 33.6 kbps
- 1 additional 500-sheet paper feeder with cabinet and stand



HP Color LaserJet Enterprise CM4540fskm MFP

- as base model with built-in analogue fax accessory
- fax speed up to 33.6 kbps
- 3 x 500-sheet paper feeder and stand
- 900-sheet 3-bin stapling mailbox

Recommended accessories



CC422A

HP Color LaserJet 500-sheet Paper Feeder and Cabinet

Spend less time loading paper and more time printing. Meet the printing needs of multiple users or a high-volume printing environments with the 500-sheet paper feeder and cabinet for the HP Color LaserJet CP4020 and CP4520 Printers and CM4540 MFP.



CC423A

HP Color LaserJet 3x500-sheet Paper Feeder and Stand

Spend less time loading paper and more time printing. Meet the printing needs of a high-volume printing environment with the 3x500-sheet paper feeder and stand for the HP Color LaserJet Enterprise CM4540 MFP (CC419A) and CP4520 Printer series.



CC424A

HP 900-sheet 3-bin Stapling Mailbox

Improve workflow management and accommodate multiple users easily with the HP 900-sheet 3-bin Stapling Mailbox. Convenient, automatic job stapling and sorting saves time. Additional output bins mean less need to monitor the MFP.



CC425A

HP Color LaserJet 500-sheet Paper Tray

Enhance productivity with a simple-to-install paper tray that allows you to print more pages without reloading paper and keep two different types of paper loaded.



CC487A

HP LaserJet MFP Analog Fax Accessory 500

Improve workteam productivity and make information sharing more efficient. Simply add embedded analog fax functionality to your HP LaserJet MFP to send and receive documents quickly, easily and securely.



C8091A

HP Staple Cartridge Refill HP Staple Cartridge Refill for

The Staple Carriage Retill for the HP 3000-sheet Stapler/Stacker Box; contains three cartridges of 5,000 staples each.

Ordering information



Accessories

HP Color LaserJet Enterprise CM4540 MFP (CC419A)

100-sheet multipurpose tray; 500-sheet input tray; HP Jetdirect Gigabit Ethernet embedded print server; HP Color LaserJet Print cartridges standard capacity (1 each black, cyan, magenta, yellow); Toner collection unit; CD with software and documentation; Documentation (Getting Started Guide, Support flyer, Wall poster); power cord



HP Color LaserJet Enterprise CM4540f MFP (CC420A)

100-sheet multipurpose tray; 500-sheet input tray; HP Jetdirect Gigabit Ethernet embedded print server; HP Color LaserJet Print cartridges standard capacity (1 each black, cyan, magenta, yellow); Toner collection unit; 1 x 500-sheet paper feeder with cabinet and stand; HP Analog fax accessory 500 (built-in); CD with software and documentation; Documentation (Getting Started Guide, Support flyer, Wall poster); power cord; phone cord



Service & support

HP Color LaserJet Enterprise CM4540fskm MFP (CC421A)

100-sheet multipurpose tray; 500-sheet input tray; HP Jetdirect Gigabit Ethernet embedded print server; HP Color LaserJet Print cartridges standard capacity (1 each black, cyan, magenta, yellow); Toner collection unit; 3 x 500-sheet paper feeder and stand; 900-sheet, 3-bin stapling mailbox; HP Analog fax accessory 500 (built-in); CD with software and documentation; Documentation (Getting Started Guide, Support flyer, Wall poster); power cord; phone cord

Accessories, Supplies and Support

CC422A	HP Color LaserJet 500-sheet Paper Feeder and Cabinet					
CC423A	HP Color LaserJet 3x500-sheet Paper Feeder and Stand					
CC424A	HP 900-sheet 3-bin Stapling Mailbox					
CC425A	HP Color LaserJet 500-sheet Paper Tray					
CC487A	HP LaserJet MFP Analog Fax Accessory 500					
C8091A	HP Staple Cartridge Refill					
Connectivity						
J8007G	HP Jetdirect 690n IPv6/IPSec 802.11g Wireless Print Server					
J8021A	HP Jetdirect ew2500 802.11b/g Wireless Print Server					

Supplies				
CE248A	HP LaserJet MFP ADF Maintenance Kit			
CE260A	HP Color LaserJet CE260A Black Print Cartridge Average cartridge yields 8500 standard pages. Declared yield value in accordance with ISO/IEC 19798*			
CE264X	HP Color LaserJet CE264X High Capacity Black Print Cartridge Average continuous Black Cartridge yield 17,000 standard pages. Declared yield value in accordance with ISO/IEC 19798 in continuous printing.			
CF031A	HP Color LaserJet CF031A Cyan Print Cartridge Average continuous composite Cyan/Yellow/Magenta Cartridge yield 12,500 standard pages. Declared yield value in accordance with ISO/IEC 19798 in continuous printing.			
CF032A	HP Color LaserJet CF032A Yellow Print Cartridge Average continuous composite Cyan/Yellow/Magenta Cartridge yield 12,500 standard pages. Declared yield value in accordance with ISO/IEC 19798 in continuous printing.			
CF033A	HP Color LaserJet CF033A Magenta Print Cartridge Average continuous composite Cyan/Yellow/Magenta Cartridge yield 12,500 standard pages. Declared yield value in accordance with ISO/IEC 19798 in continuous printing.			
CE265A	HP Color LaserJet CE265A Toner Collection Unit (36,000 pages) Toner Collection Unit capacity approximately 36,000 pages (individual experience may vary considerably based on images printed, media used, environmental conditions and other factors).			
CE246A	HP Color LaserJet CE246A 110V Fuser Kit (150,000 pages)			
CE247A	HP Color LaserJet CE247A 220V Fuser Kit (150,000 pages)			
CE249A	HP Color LaserJet CE249A Transfer Kit (150,000 pages)			

	ware Support, 3 years
UV264E H	P Care Pack, Next Business Day Color LaserJet Enterprise CM4540
MFP Hard	ware Support, 4 years
	P Care Pack, Next Business Day Color LaserJet Enterprise CM4540
	ware Support, 5 years
	P Care Pack, 4 Hour Response Time 13x5 Color LaserJet Enterprise MFP Hardware Support, 3 years
	HP Care Pack, Post Warranty Next Business Day Color LaserJet
	CM4540 MFP Hardware Support, 2 years
	HP Care Pack, Post Warranty Next Business Day Color LaserJet
	CM4540 MFP Hardware Support, 1 year
	HP Care Pack, Post Warranty 4 Hour Response Time 13x5 Color
	terprise CM4540 MFP Hardware Support, 1 year
http://www For workflo	lete list of supplies, accessories and services, please refer to x-hp.com w, device management and other solutions, please visit the Global Solutions ww.hp.com/go/gsc
	tion on cartridge page and photo yields, see v.hp.com/qo/pagevield
	r.np.com/ gov/pageyreru peendable support to create the best image possible. We can help you ur printing and imaging environment, protect your IT investment, and grow

UV259E HP Care Pack, Next Business Day Color LaserJet Enterprise CM4540

Technical specifications

Print technology	Laser						
Print speed	First page out: black: CM4540:As fast as 11.5 sec; CM4540f:As fast as 11.5 sec; CM4540fskm:As fast as 12.5 sec, colour: CM4540:As fast as 11.5 sec; CM4540f:As fast as 11.5 sec; CM4540fskm:As fast as 12.5 sec A4black: Up to 40 ppm, color: Up to 40 ppm Exact speed varies depending on the system configuration, software application, driver and document complexity.						
		4, excludes first set of test documents. For more informat		eed varies depending on the system configuration,			
Processor	800 MHz. Intel® LE80578	a document complexity.					
Memory	1280 MB. Not expandable. Ha	ırd Disk Capacity:Standard, HP high-performance embe	dded secure hard disk				
Hard disk	Standard, HP high-performance	Standard, HP high-performance embedded secure hard disk					
Print	Quality HP ImageREt 3600						
	Resolution Printer languages	Black:Up to 600 x 600 dpi, Color:Up to 600 x 600 dpi HP PCL 6, HP PCL 5c (HP PCL 5c driver available from the Web only), HP Postscript level 3 emulation, native PDF printing (v 1.4)					
	Typefaces/fonts	105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP Postscript level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale					
		Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards					
	Duty cycle (monthly, A4) Recommended monthly page	Up to 175000 pages 5000 ю 9000					
	volume	3000 10 7000					
	Print margins (mm)	Top:4.3 mm. Left:4.3 mm. Right:4.3 mm. Bottom:4.3	3 mm				
	Maximum print area	215.9 x 355.6 mm					
Fax	Modem speed Telecom compliance	33.6 kbps Telecom: FS 203 021: R&TTE Directive 1999/5/FC	(Anney II) with CE Marking (Europe): ECC Part 68: other	er Telecom approvals as required by individual countries			
	Fax resolution	Standard: 203 x 98 dpi. Fine: 300 x 300 dpi. Super		or relection approvais as required by marviation commes			
	Quick dialing	Up to 100 numbers (each with 100 destinations). 1					
Digital sending	File formats		Scan to walk-up USB: PDF; JPEG; TIFF; MTIFF; XPS; PDF/	A; Print from walk-up USB: PDF; PS; Print Ready files			
	Features	(.prn, .pcl, .cht) Standard:Scan to Email: Savo to Notwork Folder: S	avortan LISB driver Sand to ETP: Sand to LANI Fav: Sand to	o Internet Fax. Optional:Optional via HP Digital Sending			
	redities		; send-to-workflow; send-to-printer; authentication; digita				
Scan	Туре	Flatbed, ADF. Colour scanning:Yes					
	Scan resolution	Optical:Up to 600 dpi					
	Bit depth Grey scale levels	30-bit 256					
	Scannable area	Minimum media size:No minimum. Maximum media size:215.9 x 355.6 mm					
	Margins for scanned items	Left:4.3 mm. Top:4.3 mm. Right:4.3 mm. Bottom:4.3	3 mm				
Сору	Copy speed Copy resolution	A4black: Up to 40 cpm, color: Up to 40 cpm Up to 600 x 600 dpi (flatbed), up to 600 x 300 dp	: (ADE)				
	Multiple copies	Up to 9999 copies	((\DI)				
	Reduce/enlarge	25 to 400%					
Media handling	Input:	Capacity	Weight	Size			
	Tray 1	sheets (75 g/m²): 100; labels, transparencies, cardstock (163 g/m²): 50; cardstock (216 g/m²): 30; envelopes: 10	60 to 216 g/m ² (plain papers); 105 to 220 g/m ² (glossy papers)	A4; A5; A6; B5 (JIS); B6 (JIS); envelopes (C5, B5, C6, DL ISO); Postcard; Dpostcard			
	Tray 2	sheets (75 g/m²): 500; glossy paper (160 g/m²): 250; glossy paper (220 g/m²): 100	60 to 216 g/m² (plain papers); 105 to 220 g/m² (glossy papers)	A4; A5; B5 (JIS)			
	Tray 3	, 3 , 1 1 (3, ,	60 to 216 g/m² (plain papers); 105 to 220 g/m² (glossy papers)	A4; A5; B5 (JIS)			
	ADF	sheets: 50	60 to 120 g/m ²	A4; A5; B5			
	Duplex printing:Automatic (stand						
Interface and connectivity		5/IPsec 802.11g Wireless Print Server J8007G; HP Jetd	rect ew2500 802.11b/g Wireless Print Server J8021A.	. For more information on HP networking solutions visit			
Operating systems compatibility		http://www.hp.com/go/jetdirect Windows® 7 32-bit and 64-bit; Windows Vista® 32-bit and 64-bit; Microsoft® Windows® XP 32-bit or 64-bit (SP2 or higher), Server 2008 32-bit and 64-bit, and 2008 R2 Edition, Server 2003					
,	windows® 7 32-bit and 64-bit; vindows vista® 32-bit and 64-bit; windows® Ar 32-bit or 64-bit; Strice of an office of a strice						
Network operating systems compatibility	Windows® 7 32-bit and 64-bit; Windows Vista® 32-bit and 64-bit; Microsoft® Windows® XP 32-bit or 64-bit (SP2 or higher), Server 2008 32-bit and 64-bit, and 2008 R2 Edition, Server 2003 32-bit and 64-bit; Citrix® and Windows® Terminal Services (see whitepapers at http://www.hp.com/go/upd, Documentation tab); Novell® (see http://www.novell.com/iprint); Mac OS X v10.4 or higher; Linux (see http://www.hplip.net); UNIX, SAP device types						
	nigner; Linux (see nitp://www.r	Windows® 7; Windows Vista®; Microsoft® Windows® XP SP2 or higher, Server 2003, Server 2008; operating system compatible hardware system requirements, see http://www.microsoft.com system requirements; 220 MB available hard disk space. Mac OS X v10.4 or higher; operating system compatible hardware system requirements, see: http://www.apple.com; 150 MB free hard disk					
Minimum system requirements	Windows® 7; Windows Vista®	; Microsoft® Windows® XP SP2 or higher, Server 2003					
	Windows® 7; Windows Vista® system requirements; 220 MB a space	t; Microsoft® Windows® XP SP2 or higher, Server 2003 vailable hard disk space. Mac OS X v10.4 or higher, o	perating system compatible hardware system requiremen	nts, see: http://www.apple.com; 150 MB free hard disk			
	Windows® 7; Windows Vista® system requirements; 220 MB a space Windows® print driver (HP PCL discrete driver only; UPD PCL 6;	; Microsoft® Windows® XP SP2 or higher, Server 2003 vailable hard disk space. Mac OS X v10.4 or higher, o 6 discrete); SNP alerts; Mac print driver; Installation so	perating system compatible hardware system requirement tware on CD-ROM for Microsoft® Windows® and Mac				
Minimum system requirements Standard software Control panel	Windows® 7; Windows Vista® system requirements; 220 MB a space Windows® print driver (HP PCL discrete driver only; UPD PCL 6; model scripts Rotating (adjustable angle); 20.); Microsoft® Windows® XP SP2 or higher, Server 2003 vailable hard disk space. Mac OS X v10.4 or higher, of 6 discrete); SNP alerts; Mac print driver; Installation so UPD PCL 5, UPD Postscript; HP Web Jetadmin; HP PC \$	perating system compatible hardware system requirement tware on CD-ROM for Microsoft® Windows® and Mac end Fax Driver; HP Save-to-Folder setup wizard; HP Ser	nts, see: http://www.apple.com; 150 MB free hard disk Drivers on the web:Windows® Printing system; PCL 6			
Standard software Control panel	Windows® 7; Windows Vista® system requirements; 220 MB a space Windows® print driver (HP PCL discrete driver only; UPD PCL 6; model scripts Rotating (adjustable angle); 20. Attention, Sleep); Hardware Inte); Microsoft® Windows® XP SP2 or higher, Server 2003 vailable hard disk space. Mac OS X v10.4 or higher, of 6 discrete); SNP alerts; Mac print driver; Installation so UPD PCL 5, UPD Postscript; HP Web Jetadmin; HP PC \$	perating system compatible hardware system requirement tware on CD-ROM for Microsoft® Windows® and Mac iend Fax Driver; HP Save-to-Folder setup wizard; HP Ser buttons (Start, Stop, Sleep, Reset, Clear, Brightness Up/	nts, see: http://www.apple.com; 150 MB free hard disk Drivers on the web:Windows® Printing system; PCL 6 ad-to-Email setup wizard; Mac driver; Linux driver; UNIX Down); numeric keypad; LED status lights (Ready, Data,			
Standard software Control panel Power	Windows® 7; Windows Vista® system requirements; 220 MB a space Windows® print driver (HP PCL discrete driver only; UPD PCL 6; model scripts Rotating (adjustable angle); 20. Attention, Sleep); Hardware Inte Requirements:hput voltage: 22((manual-off). Typical electricity c	p; Microsoft® Windows® XP SP2 or higher, Server 200: vailable hard disk space. Mac OS X v10.4 or higher, of discrete); SNP alerts; Mac print driver; Installation so UPD PCL 5, UPD Postscript; HP Web Jetadmin; HP PC 5.5 cm colour graphical display; touchscreen; job control segration Pocket; walk-up USB 0.1 to 240 VAC (+/- 10%), 50 Hz (+/- 2 Hz), 6 A. Const consumption (TEC) 8.062 kWh/Week. Values subject to	perating system compatible hardware system requirement tware on CD-ROM for Microsoft® Windows® and Mac send Fax Driver; HP Save-to-Folder setup wizard; HP Ser buttons (Start, Stop, Sleep, Reset, Clear, Brightness Up/ mption:780 watts (printing), 850 watts (copy or scan), 6 change. Power numbers are the highest values measure	nts, see: http://www.apple.com; 150 MB free hard disk Drivers on the web:Windows® Printing system; PCL 6 tid-to-Email setup wizard; Mac driver; Linux driver; UNIX Down); numeric keypad; LED status lights (Ready, Data, Watts (standby), 21.5 watts (sleep), 0.3 watts d using all standard voltages.			
Standard software Control panel Power Dimensions (w x d x h)	Windows® 7; Windows Vista® system requirements; 220 MB a space Windows® print driver (HP PCL discrete driver only; UPD PCL 6; model scripts Rotating (adjustable angle); 20. Attention, Sleep); Hardware Inte Requirements:Input voltage: 22((manual-off). Typical electricity Out of package: CM4540:905. mm; CM45401skm:856 x 760 x	b; Microsoft® Windows® XP SP2 or higher, Server 2003 vailable hard disk space. Mac OS X v10.4 or higher, of discrete); SNP alerts; Mac print driver; Installation so UPD PCL 5, UPD Postscript; HP Web Jetadmin; HP PC ST or colour graphical display; touchscreen; job control egration Pocket; walk-up USB D10 240 VAC (+/-10%), 50 Hz (+/-2 Hz), 6 A. Constronsumption (TEC) 8.062 kWh/Week. Values subject to x 623 x 575 mm; CM4540f:909 x 668 x 1119 mm; C x 1743 mm	perating system compatible hardware system requirement tware on CD-ROM for Microsoft® Windows® and Mac- iend Fax Driver; HP Save-to-Folder setup wizard; HP Ser- buttons (Start, Stop, Sleep, Reset, Clear, Brightness Up/ mption:780 watts (printing), 850 watts (copy or scan), (change. Power numbers are the highest values measure w4540fskm:1072 x 668 x 1119 mm. Packaged:CM45	nts, see: http://www.apple.com; 150 MB free hard disk Drivers on the web:Windows® Printing system; PCL 6 ad-to-Email setup wizard; Mac driver; Linux driver; UNIX Down); numeric keypad; LED status lights (Ready, Data, watts (standby), 21.5 watts (sleep), 0.3 watts d using all standard voltages. 40:746 x 659 x 700 mm; CM4540f:856 x 760 x 1498			
Control panel Power Dimensions (w x d x h) Weight	Windows® 7; Windows Vista® system requirements; 220 MB a space Windows® print driver (HP PCL discrete driver only; UPD PCL 6; model scripts Rotating (adjustable angle); 20. Attention, Sleep); Hardware Inte Requirements:Input voltage: 22(manual-off). Typical electricity out of package:CM4540:905 mm; CM45401skm:856 x 760 x Out of package:CM4540:54.8	b; Microsoft® Windows® XP SP2 or higher, Server 200: vailable hard disk space. Mac OS X v10.4 or higher, of discrete); SNP alerts; Mac print driver; Installation so UPD PCL 5, UPD Postscript; HP Web Jetadmin; HP PC ST or colour graphical display; touchscreen; job control gration Pocket; walk-up USB Or to 240 VAC (+/- 10%), 50 Hz (+/- 2 Hz), 6 A. Constronsumption (TEC) 8.062 kWh/Week. Values subject to x 623 x 575 mm; CM4540f:909 x 668 x 1119 mm; Cx 1743 mm. kg; CM4540f:75.7 kg; CM4540fskm:88.6 kg. Packag	perating system compatible hardware system requirement tware on CD-ROM for Microsoft® Windows® and Mac- iend Fax Driver; HP Save-to-Folder setup wizard; HP Ser buttons (Start, Stop, Sleep, Reset, Clear, Brightness Up/ mption:780 watts (printing), 850 watts (copy or scan), 6 change. Power numbers are the highest values measure v4540fskm:1072 x 668 x 1119 mm. Packaged:CM45. ed:CM4540:62 kg; CM4540f:94.8 kg; CM4540fskm:1	nts, see: http://www.apple.com; 150 MB free hard disk Drivers on the web:Windows® Printing system; PCL 6 ad-to-Email setup wizard; Mac driver; Linux driver; UNIX Down); numeric keypad; LED status lights (Ready, Data, watts (standby), 21.5 watts (sleep), 0.3 watts d using all standard voltages. 40:746 x 659 x 700 mm; CM4540f:856 x 760 x 1498			
Control panel Power Dimensions (w x d x h) Weight Printer management	Windows® 7; Windows Vista® system requirements; 220 MB a space Windows® print driver (HP PCL discrete driver only; UPD PCL 6; model scripts Rotating (adjustable angle); 20. Attention, Sleep); Hardware Intel Requirements:Input voltage: 22 (manual-off). Typical electricity of Out of package:CM4540:905. mm; CM4540fskm:856 x 760 x Out of package:CM4540:54.8 HP Web Jetadmin (Web only);	p; Microsoft® Windows® XP SP2 or higher, Server 200: vailable hard disk space. Mac OS X v10.4 or higher, of discrete); SNP alerts; Mac print driver; Installation soi UPD PCL 5, UPD Postscript; HP Web Jetadmin; HP PC 5.5 cm colour graphical display; touchscreen; job control gration Pocket; walkup USB 0.10 to 240 VAC (+/-10%), 50 Hz (+/-2 Hz), 6 A. Const. consumption (TEC) 8.062 kWh/Week. Values subject to x 623 x 575 mm; CM4540f;909 x 668 x 1119 mm; Cx 1743 mm kg; CM4540f;75.7 kg; CM4540fskm:88.6 kg. Packag; Status Notification Pop-up (SNP) for domains less than 1	perating system compatible hardware system requirement ware on CD-ROM for Microsoft® Windows® and Mackend Fax Driver; HP Save-to-Folder setup wizard; HP Serbuttons (Start, Stop, Sleep, Reset, Clear, Brightness Up/mption:780 watts (printing), 850 watts (copy or scan), 6change. Power numbers are the highest values measure w4540fskm:1072 x 668 x 1119 mm. Packaged:CM45.ed:CM4540:62 kg; CM4540f:94.8 kg; CM4540fskm:100 users	nts, see: http://www.apple.com; 150 MB free hard disk . Drivers on the web:Windows® Printing system; PCL 6 td-to-Email setup wizard; Mac driver; Linux driver; UNIX Down); numeric keypad; LED status lights (Ready, Data, P1 watts (standby), 21.5 watts (sleep), 0.3 watts d using all standard voltages. 40:746 x 659 x 700 mm; CM4540f:856 x 760 x 1498			
Control panel Power Dimensions (w x d x h) Weight Printer management Security management	Windows® 7; Windows Vista® system requirements; 220 MB a space Windows® print driver (HP PCL discrete driver only; UPD PCL 6; model scripts Rotating (adjustable angle); 20. Attention, Sleep); Hardware Inte Requirements:Input voltage: 222 (manual-off). Typical electricity out of package:CM4540:905. mm; CM4540fskm:856 x 760 x Out of package:CM4540:548. HP Web Jetadmin (Web only). Management security: SNMPv3 Support for WJA-10 IPsec Confi	by Microsoft® Windows® XP SP2 or higher, Server 2003 vailable hard disk space. Mac OS X v10.4 or higher, of discretely. SNP alerts; Mac print driver; Installation so UPD PCL 5, UPD Postscript; HP Web Jetadmin; HP PC ST conclour graphical display; touchscreen; job control egration Pocket; walk-up USB Dio 240 VAC (+/-10%), 50 Hz (+/-2 Hz), 6 A. Constronsumption (TEC) 8.062 kWh/Week. Values subject to x 623 x 575 mm; CM4540f:909 x 668 x 1119 mm; Cx 1743 mm kg; CM4540f:75.7 kg; CM4540fskm:88.6 kg. Packags Status Notification Pop-up (SNP) for domains less than 1 x, SSL/TLS, 802.1X authentication (EAP-PEAP, EAP-TLS), guration using IPsec Plug-in	perating system compatible hardware system requirement ware on CD-ROM for Microsoft® Windows® and Maciend Fax Driver; HP Save-to-Folder setup wizard; HP Serbuttons (Start, Stop, Sleep, Reset, Clear, Brightness Up/mption:780 watts (printing), 850 watts (copy or scan), 'change. Power numbers are the highest values measure w4540fskm:1072 x 668 x 1119 mm. Packaged:CM45-sd:CM4540:62 kg; CM4540f:94.8 kg; CM4540fskm:100 users JPP over TLS, IPsec/Firewall with Certificate, Pre-Shared I	nts, see: http://www.apple.com; 150 MB free hard disk Drivers on the web:Windows® Printing system; PCL 6 ad-to-Email setup wizard; Mac driver; Linux driver; UNIX Down); numeric keypad; LED status lights (Ready, Data, P1 watts (standby), 21.5 watts (sleep), 0.3 watts d using all standard voltages. 40:746 x 659 x 700 mm; CM4540f:856 x 760 x 1498 11.4 kg Key Authentication, and Kerberos Authentication;			
Control panel Power Dimensions (w x d x h) Weight Printer management Security management	Windows® 7; Windows Vista® system requirements; 220 MB a space Windows® print driver (HP PCL discrete driver only; UPD PCL 6; model scripts Rotating (adjustable angle); 20. Attention, Sleep); Hardware Intel Requirements:Input voltage: 22 (manual-6ft). Typical electricity of United States (manual-6ft). Typical electricity of United States (M4540548. HP Web Jetadmin (Web only); Management security: SNMPv3 Support for WJA-1 0 IPsec Confi Operating temperature: 10 to 36 temperature: 10 to 35 C. Storage	thicrosoft® Windows® XP SP2 or higher, Server 2003 vailable hard disk space. Mac OS X v10.4 or higher, of discrete); SNP alerts; Mac print driver; Installation so UPD PCL 5, UPD Postscript; HP Web Jetadmin; HP PC 5.5 cm colour graphical display; touchscreen; job control gration Pocket; walk-up USB 0.1 to 240 VAC (+/-10%), 50 Hz (+/-2 Hz), 6 A. Const. consumption (TEC) 8.062 kWh/Week. Values subject to x 623 x 575 mm; CM4540f:909 x 668 x 1119 mm; Ct. 1743 mm kg; CM4540f:75.7 kg; CM4540fskm:88.6 kg. Packag Status Notification Pop-up (SNP) for domains less than 1, SSL/TLS, 802.1X authentication (EAP-PEAP, EAP-TLS), guration using IPsec Plug-in 20° C. Recommended operating temperature: 15 to 27° (e humidity: 10 to 90% RH	perating system compatible hardware system requirement ware on CD-ROM for Microsoft® Windows® and Maciend Fax Driver; HP Save-to-Folder setup wizard; HP Serbuttons (Start, Stop, Sleep, Reset, Clear, Brightness Up/mption:780 watts (printing), 850 watts (copy or scan), 'change. Power numbers are the highest values measure w4540fskm:1072 x 668 x 1119 mm. Packaged:CM45-sd:CM4540:62 kg; CM4540f:94.8 kg; CM4540fskm:100 users JPP over TLS, IPsec/Firewall with Certificate, Pre-Shared I	nts, see: http://www.apple.com; 150 MB free hard disk Drivers on the web:Windows® Printing system; PCL 6 ad-to-Email setup wizard; Mac driver; Linux driver; UNIX Down); numeric keypad; LED status lights (Ready, Data, P1 watts (standby), 21.5 watts (sleep), 0.3 watts d using all standard voltages. 40:746 x 659 x 700 mm; CM4540f:856 x 760 x 1498 11.4 kg Key Authentication, and Kerberos Authentication;			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	Windows® 7; Windows Vista® system requirements; 220 MB a space Windows® print driver (HP PCL discrete driver only; UPD PCL 6; model scripts Rotating (adjustable angle); 20. Attention, Sleep); Hardware Inte Requirements:Input voltage: 22(manual-off). Typical electricity of package:CM4540:905: mm; CM4540fskm:856 x 760. Out of package:CM4540:54.8. HP Web Jetadmin (Web only); Management security: SNMPV3 Support for WJA-10 IPsec Confi Operating temperature: 10 to 37 temperature: 10 to 37 temperature: 10 to 37 c. Storag Acoustic Power Emissions: 7.3 B	i, Microsoft® Windows® XP SP2 or higher, Server 200: vailable hard disk space. Mac OS X v10.4 or higher, of discrete); SNP alerts; Mac print driver; Installation so UPD PCL 5, UPD Postscript; HP Web Jetadmin; HP PC S or colour graphical display; touchscreen; job control egration Pocket; walk-up USB 10 240 VAC (+/-10%), 50 Hz (+/-2 Hz), 6 A. Constronsumption (TEC) 8.062 kWh/Week. Values subject to x 623 x 575 mm; CN4540f:909 x 668 x 1119 mm; Ct 1743 mm kg; CM4540f:75.7 kg; CM4540fskm:88.6 kg. Packag: Status Notification Pop-up (SNP) for domains less than 1 x, SSL/TLS, 802.1X authentication (EAP-PEAP, EAPTLS), guration using IPsec Plug-in or C. Recommended operating temperature: 15 to 27° (enhanced to the publication to 90% RH (A)	perating system compatible hardware system requirement ware on CD-ROM for Microsoft® Windows® and Maciend Fax Driver; HP Save-to-Folder setup wizard; HP Serbuttons (Start, Stop, Sleep, Reset, Clear, Brightness Up/mption:780 watts (printing), 850 watts (copy or scan), 'change. Power numbers are the highest values measure w4540fskm:1072 x 668 x 1119 mm. Packaged:CM45-sd:CM4540:62 kg; CM4540f:94.8 kg; CM4540fskm:100 users JPP over TLS, IPsec/Firewall with Certificate, Pre-Shared I	nts, see: http://www.apple.com; 150 MB free hard disk Drivers on the web:Windows® Printing system; PCL 6 ad-to-Email setup wizard; Mac driver; Linux driver; UNIX Down); numeric keypad; LED status lights (Ready, Data, P1 watts (standby), 21.5 watts (sleep), 0.3 watts d using all standard voltages. 40:746 x 659 x 700 mm; CM4540f:856 x 760 x 1498 11.4 kg Key Authentication, and Kerberos Authentication;			
Control panel Power Dimensions (w x d x h) Weight Printer management Security management	Windows® 7; Windows Vista® system requirements; 220 MB a space Windows® print driver (HP PCL discrete driver only; UPD PCL 6; model scripts Rotating (adjustable angle); 20. Attention, Sleep); Hardware Inte Requirements:Input voltage: 22(manualoff). Typical electricity c Out of package:CM4540:905: mm; CM4540fskm:856 x 760 out of package:CM4540:54.8 HP Web Jetadmin (Web only); Management security: SNMPv3 Support for WJA-10 IPsec Confi Operating temperature: 10 to 35° C . Storag Acoustic Power Emissions: 57 CISPR 22: 2005+A1/EN 5502 2004/108/EC with CE Markin CE Markin CE Markin	i, Microsoft® Windows® XP SP2 or higher, Server 200: vailable hard disk space. Mac OS X v10.4 or higher, of discrete); SNP alerts; Mac print driver; Installation so UPD PCL 5, UPD Postscript; HP Web Jetadmin; HP PC 5.5 cm colour graphical display; touchscreen; job control gration Pocket; walkup USB 0.1 to 240 VAC (+/-10%), 50 Hz (+/-2 Hz), 6 A. Const. consumption (TEC) 8.062 kWh/Week. Values subject to x 623 x 575 mm; CM4540f;909 x 668 x 1119 mm; Cx 1743 mm kg; CM4540f;75.7 kg; CM4540fskm:88.6 kg. Packag: Status Notification Pop-up (SNP) for domains less than 1 x 551/TLS, 802.1X authentication (EAP-PEAP, EAP-TLS), guration using IPsec Plug-in 20° C. Recommended operating temperature: 15 to 27° (tel humidity: 10 to 90% RH (A) dB(A) 2: 2006+A1 Class A, EN 61000-32: 2006, EN 6100	perating system compatible hardware system requirement ware on CD-ROM for Microsoft® Windows® and Mackend Fax Driver; HP Save-to-Folder setup wizard; HP Serbuttons (Start, Stop, Sleep, Reset, Clear, Brightness Up/buttons (Start, Stop, Sleep, Reset, Clear, Brightness Up/ching. Rower numbers are the highest values measure w4540fskm:1072 x 668 x 1119 mm. Packaged:CM45.ed:CM4540:62 kg; CM4540f:94.8 kg; CM4540fskm:100 users PP over TLS, IPsec/Firewall with Certificate, Pre-Shared ID. C. Operating humidity:10 to 80% RH. Operati	nts, see: http://www.apple.com; 150 MB free hard disk Drivers on the web:Windows® Printing system; PCL 6 ad-to-Email setup wizard; Mac driver; Linux driver; UNIX Down); numeric keypad; LED status lights (Ready, Data, P1 watts (standby), 21.5 watts (sleep), 0.3 watts d using all standard voltages. 40:746 x 659 x 700 mm; CM4540f:856 x 760 x 1498 11.4 kg Key Authentication, and Kerberos Authentication; dity recommended:30 to 70% RH . Storage Title 47 CFR, GB 9254-2008, EMC Directive ational); EN 60950-1+A11 (EU); IEC 60825-1+A1+A2;			

http://www.hp.com/uk









