THE POWERFUL PRINTER FOR SMALLER OFFICES

For both smaller teams and single users this tough, durable and reliable device is the perfect choice. With up to 40 ppm in black and white this device is capable of handling large workloads. Its aesthetic design, great usability and flexibility in paper handling make it a must for small teams. Due to its long-life components, running costs and environmental impact are exceptionally low.

- ▶ Up to 40 pages per minute in A4 with up to 1,200 dpi resolution
- Duplex unit for double-sided printing as standard
- ▶ 100-sheet multi-purpose tray, 500-sheet universal cassette
- ▶ 5 line LCD display for easy navigation and clear messages
- ▶ High capacity of 128 MB RAM for complex documents as standard
- ► Convenient printing directly from USB Flash memory device
- ▶ Powerful options for enhanced functionality and performance
- ▶ Optional Gigabit or wireless network functionality
- ► Exceptionally low printing costs in its class

Double sided printing saves environmental resources and money.





The option of an additional interface like wireless LAN for advanced flexibility in the office.







FS-2100D

MONOCHROME PRINTER FOR A4 FORMATS



ECOSYS stands for ECOlogy, ECOnomy and SYStem-printing.

With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflowenhancing functions as required. Integrated system software provides long-term cross-network compatibility. KYOCERA's long-life components cost you and the environment less.

PRESCRIBE IIe

With the KYOCERA page design and control language PRESCRIBE IIe even complex graphics, logos and forms (multipart forms) can be created independently on the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required relieving the load on the network

KYOCERA NetViewer

KYOCERA NetViewer enables complete monitoring and control of all ECOSYS printers and digital KYOCERA multifunction units from any Windows© PC, providing ideal network administration. It also supports the standardised SNMP protocol.

The Command Center RX enables the control and management of various settings by accessing the device via Web browser. E.g. automatic updating of screens, customising user screens and viewing department and restriction settings.

USB Host Interface for USB Flash Memory

Documents can be printed directly from a USB Flash Memory (e.g. USB stick) via the USB host interface. The documents stored as PDF. XPS, TIFF or JPEG are selected directly via the printer's control panel. No computer is required.

Technology: KYOCERA ECOSYS Laser

Control panel: 5 line LCD display with alphanumeric keypad

Engine speed: Up to 40 pages per minute in A4

Resolution: 1,200 dpi Duty cycle: Max. 150,000 pages per month

Warm-up time: Approx. 15 seconds or less from power on

Time to first page: Approx. 9 seconds or less

Dimensions (W x D x H): 380 mm x 416 mm x 285 mm

Weight: Approx. 13.5 kg (main unit) Power source: 220/240 V, 50/60 Hz

Power consumption

Printing: 564 W Stand-by: 11.5 W

Power-Saving (ECOpower): 3.0 W

Typical Electricity Consumption (TEC): 2.24 kWh/week

Noise: (Sound pressure level: ISO 7779 / ISO 9296)

Printing: 52.4 dB(A) LpA Stand-by: 25.9 dB(A) LpA

Safety standards GS, TÜV, CE

This unit is manufactured according to the ISO 9001 quality standard and the ISO 14001 environmental standard.

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCFRA under normal environmental conditions.

Input capacity

100-sheet multi-purpose tray; 60-220 g/m²; A4, A5, A6, B5, Letter, Legal, Custom (70 x 148 - 216 x 356 mm) 500-sheet universal paper cassette, 60-120 g/m²: A4, A5, B5, Letter, Legal, Custom (140 x 210 - 216 x 356 mm) Max. input capacity incl. options: 2,600 sheets

Duplex unit

Duplex as standard supports A4, A5, B5, Letter, Legal, Custom (140 x 210 mm - 216 x 356 mm), 60-120 g/m²

Output capacity

250 sheet face-down

Your KYOCERA Business Partner:

CPU: PowerPC 465/500 MHz

Memory: 128 MB RAM, max, 1,152 MB RAM

Standard interface

USB 2.0 (Hi-Speed), 2 USB Host Interfaces, Slot for optional internal print server or SSD hard disc, Slot for optional SD/ SDHC-Card

Controller language: PRESCRIBE IIe

Emulations

PCL6 (PCL5c / PCL-XL), PostScript* 3 (KPDL 3), XPS Direct Print", PDF Direct Print 1.7, IBM Proprinter X24E, Epson LQ-850 with automatic emulation sensing

Operating systems

All current Windows operating systems, Mac OS X Version 10.4 or higher, UNIX, LINUX as well as other operating systems on request

Fonts/Barcodes

93 scalable fonts for PCL/PostScript*, 8 fonts for Windows Vista*, 1 Bitmap font, 45 barcodes (e.g. EAN8, EAN13, EAN128) with automatic generation of checksums as well as support of two-dimensional barcodes PDF-417 under PRESCRIBE (PCL and other barcodes available as an option)

Integrated Accounting: 100 department codes

TK-3100 Toner-Kit: Microfine toner for 12,500 pages A4 Capacity of starter toner is 6,000 pages A4 Average continuous toner yield in accordance with ISO/IEC 19752

PF-320 Paper feeder (max. 4 units)

Max. 500 sheets: 60-120 g/m²: A4, A5, B5, Letter, Legal. Custom (148 x 210 mm - 216 x 356 mm)

PF-315+ Bulk paper feeder and PB-325 Printer base Max. 2,000 sheet, 60-220 g/m2, not to be combined with PF-320

CB-360 Cabinet

Wooden desk with storage capacity

Memory upgrade

MDDR2-512: 512 MB, MDDR2-1024: 1.024 MB

SD/SDHC*-Card

1 slot (up to 32 GB) for storage of documents incl. Private

HD-6 SSD hard disc

32 GB for easy document management

Data security kit (E) in line with security level EAL3

USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available

Optional interface

IB-50: Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT (RJ-45)

IB-51: Wireless LAN (802.11b/g/n)

IB-32: Parallel IEEE1284 interface kit

2-year warranty as standard, KYOCERA quarantees the drums and developers for 3 years or maximum 300,000 pages (whichever occurs sooner), provided the printer is used and cleaned in accordance with the service instructions.

Up to 5-year on-site warranty extension for printer and options.



KYOLIFE Up to 5-year on-site warranty extension for printer and options.





KYOCERA Document Solutions (UK) Ltd, 8 Beacontree Plaza, Gillette Way, Reading RG2 OBS Tel: 0118 931 1500, Fax: 0118 931 1108 www.kyoceradocumentsolutions.co.uk email: info@duk.kyocera.com

KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

** Requires memory expansion

