



Lexmark™

## CX622ade

Reliability. Security. Productivity.



CX622ade



This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

# Lexmark CX622ade

The multifunction Lexmark CX622ade combines a high-impact colour print speed of up to 37 ppm\* with single-pass, two-sided scanning that can reach 94 images per minute. In addition to reliably handling diverse media types and sizes, it comes with tools to help you minimise toner consumption and improve colour accuracy.

## Ready when you are

- ▶ A 1.2-GHz quad-core processor and up to 6 GB memory drives printing at up to 37 ppm\*.
- ▶ Scan at up to 47 pages per minute, or 94 images per minute for two-sided documents.
- ▶ The steel frame and durable design stands up to heavy use and harsh environments.
- ▶ Long-life fuser and imaging components extend uptime.
- ▶ Unison™ Toner replacement cartridges deliver up to 7,000 colour and 10,500 monochrome pages\*\*.
- ▶ Keep printing in black even when colour toner is empty.
- ▶ An optional hard drive offers improved system performance, enhanced scanning capabilities and additional productivity and convenience apps, including optional OCR.

## Colour that keeps saving

- ▶ PANTONE® calibration, embedded colour sample pages and Lexmark Colour Replacement produce accurate, professional colour output in-house.
- ▶ Save toner with a suite of tools that let you choose when and how much colour to print.

## Input that works

- ▶ Reliable, flexible media handling supports cardstock, small media, and envelopes from the main tray or a convenient single-sheet feeder.
- ▶ 251 pages of standard input can grow to 1,451.

## Interact with ease

- ▶ The tiltable 10.9 cm e-Task touch screen comes with convenience and productivity apps and is customisable to meet your needs.
- ▶ A front USB port allows walk-up printing from popular file formats without a computer.
- ▶ The compact footprint allows flexible placement in more locations.
- ▶ Connect easily via Ethernet, USB, or simple mobile printing options.

## Full-spectrum security

- ▶ Lexmark's full-spectrum security architecture helps keep your information safe - in the document, on the device and over the network.
- ▶ Keypoint Intelligence - Buyers Lab honoured Lexmark with a prestigious BLI PaceSetter award for Document Imaging Security\*\*\*.



## Built for planet earth

- ▶ Energy management features reduce power consumption in active use or sleep mode.
- ▶ Standard two-sided printing saves paper.
- ▶ Recycle cartridges through the award-winning Lexmark Cartridge Collection Programme (LCCP).

\*Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

\*\*Average continuous black or continuous composite colour (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See [www.lexmark.com/yields](http://www.lexmark.com/yields) for more information.

\*\*\*Award based on Western Europe data

## Lexmark CX622ade



- 1 CX622ade with 10.9 cm e-Task colour touch screen  
462 x 442 x 588 mm
- 2 650-sheet duo tray  
133 x 424 x 416 mm
- 3 550-sheet tray  
133 x 424 x 416 mm

Adjustable printer stand (not shown)  
521 x 653 x 625 mm

Swivel cabinet (not shown)  
263 x 476 x 600 mm

■ Standard  
■ Optional

Note 1: Supports one optional 650-sheet duo tray; or one optional 650-sheet duo tray and one optional 550-sheet tray with the 650-sheet duo tray on top.  
Note 2: All measurements are shown as height x width x depth. For more information about supported configurations, refer to the Printer, Option and Stand Compatibility Guide at [http://www.lexmark.com/publications/furniture\\_safety/](http://www.lexmark.com/publications/furniture_safety/)

© 2018 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. AirPrint and the AirPrint Logo are trademarks of Apple, Inc. Google Cloud Print is a trademark of Google, Inc. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are trademarks, service marks, and certification marks of Mopria Alliance, Inc. in the United States and other countries. PANTONE®, PANTONE® Goe™ and other Pantone, Inc. trademarks are property of Pantone, Inc. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit ([http:// www.openssl.org/](http://www.openssl.org/)).

| Product specifications                                          |                                                                                                                                                                                                                                                                                                                                                                                                              | Lexmark CX622ade |
|-----------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| Printing                                                        |                                                                                                                                                                                                                                                                                                                                                                                                              |                  |
| Display                                                         | Lexmark e-Task 10.9 cm (4.3-inch) colour touch screen                                                                                                                                                                                                                                                                                                                                                        |                  |
| Print Speed: Up to <sup>5</sup>                                 | Black: 37 ppm / Colour: 37 ppm                                                                                                                                                                                                                                                                                                                                                                               |                  |
| Time to First Page: As fast as / Time to First Page: as fast as | Black: <8 seconds / Colour: <8 seconds                                                                                                                                                                                                                                                                                                                                                                       |                  |
| Print Resolution                                                | Black: 1200 x 1200 dpi, 4800 Colour Quality (2400 x 600 dpi) / Colour: 1200 x 1200 dpi, 4800 Colour Quality (2400 x 600 dpi)                                                                                                                                                                                                                                                                                 |                  |
| Memory / Processor                                              | standard: 2048 MB / maximum: 6144 MB / Quad Core, 1200 w/ GPU MHz                                                                                                                                                                                                                                                                                                                                            |                  |
| Hard Disk                                                       | Option available                                                                                                                                                                                                                                                                                                                                                                                             |                  |
| Recommended Monthly Page Volume <sup>1</sup>                    | 1,500 - 10,000 Pages                                                                                                                                                                                                                                                                                                                                                                                         |                  |
| Maximum Monthly Duty Cycle: Up to <sup>2</sup>                  | 100,000 pages per month                                                                                                                                                                                                                                                                                                                                                                                      |                  |
| Copying                                                         |                                                                                                                                                                                                                                                                                                                                                                                                              |                  |
| Copy Speed: Up to <sup>5</sup>                                  | Black: 38 cpm / Colour: 38 cpm                                                                                                                                                                                                                                                                                                                                                                               |                  |
| Time to First Copy: As fast as / Time to First Copy: as fast as | black: 8 seconds / colour: 8.5 seconds                                                                                                                                                                                                                                                                                                                                                                       |                  |
| Scanning                                                        |                                                                                                                                                                                                                                                                                                                                                                                                              |                  |
| Scanner Type / ADF Scan                                         | Flatbed scanner with ADF / DADF (single pass Duplex)                                                                                                                                                                                                                                                                                                                                                         |                  |
| A4/Ltr Duplex Scan Speed: Up to                                 | Mono: 94 / 100 sides per minute / Colour: 60 / 64 sides per minute                                                                                                                                                                                                                                                                                                                                           |                  |
| A4/Ltr Simplex Scan Speed: Up to                                | Mono: 47 / 50 sides per minute / Colour: 30 / 32 sides per minute                                                                                                                                                                                                                                                                                                                                            |                  |
| ADF Paper Input Capacity: Up to                                 | 100 pages 75 gsm bond                                                                                                                                                                                                                                                                                                                                                                                        |                  |
| Faxing                                                          |                                                                                                                                                                                                                                                                                                                                                                                                              |                  |
| Modem Speed                                                     | Max is 33,600 bps, V.34 Half-Duplex Kbps                                                                                                                                                                                                                                                                                                                                                                     |                  |
| Supplies <sup>6</sup>                                           |                                                                                                                                                                                                                                                                                                                                                                                                              |                  |
| Laser Cartridge Yields (up to)                                  | 1,400-page Colour (CMY) Cartridges, 2,000-page Black Cartridge, 5,000-page Colour (CMY) Extra High Yield Cartridges, 8,500-page Black Extra High Yield Cartridge, Average continuous cartridge yield is stated number of standard pages as listed. Declared yield value in accordance with ISO/IEC 19798., 7,000-page Colour (CMY) Ultra High Yield Cartridges, 10,500-page Black Ultra High Yield Cartridge |                  |
| Photoconductor Estimated Yield: Up to <sup>4</sup>              | 125,000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage                                                                                                                                                                                                                                                                                                                       |                  |
| Cartridge(s) Shipping with Product                              | 2,000-page Colour (CMY) Return Programme Toner Cartridges, 3,000-page Black Starter Return Programme Toner Cartridge                                                                                                                                                                                                                                                                                         |                  |
| Paper Handling                                                  |                                                                                                                                                                                                                                                                                                                                                                                                              |                  |
| Included Paper Handling                                         | 250-Sheet Input, 150-Sheet Output Bin, Integrated Duplex, Single-Sheet Manual Feed                                                                                                                                                                                                                                                                                                                           |                  |
| Optional Paper Handling                                         | 550-Sheet Tray, 550-Sheet Duo Tray with 100-Sheet Feeder                                                                                                                                                                                                                                                                                                                                                     |                  |
| Paper Input Capacity: Up to                                     | Standard: 250+1 pages 75 gsm bond / Maximum: 1,450+1 pages 75 gsm bond                                                                                                                                                                                                                                                                                                                                       |                  |
| Paper Output Capacity: Up to                                    | Standard: 150 pages 75 gsm bond / Maximum: 150 pages 75 gsm bond                                                                                                                                                                                                                                                                                                                                             |                  |
| Media Types Supported                                           | Card Stock, Paper Labels, Plain Paper, Vinyl Labels, Refer to the Card Stock & Label Guide.                                                                                                                                                                                                                                                                                                                  |                  |
| Media Sizes Supported                                           | 10 Envelope, 7 3/4 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6                                                                                                                                                                                                                                                        |                  |
| General Information <sup>3</sup>                                |                                                                                                                                                                                                                                                                                                                                                                                                              |                  |
| Standard Ports                                                  | USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear USB 2.0 Specification Hi-Speed Certified port (Type A)                                                                                                                                                                                                 |                  |
| Optional Network Ports                                          | Marknet N8372 WiFi Option                                                                                                                                                                                                                                                                                                                                                                                    |                  |
| Noise Level: Operating                                          | Print: 52 dBA / Copy: 55 dBA / Scan: 51 dBA                                                                                                                                                                                                                                                                                                                                                                  |                  |
| Specified Operating Environment                                 | Humidity: 8 to 80% Relative Humidity, Temperature: 10 to 32°C (50 to 90°F), Altitude: 0 - 2,896 Metres (9,500 Feet)                                                                                                                                                                                                                                                                                          |                  |
| Product Guarantee                                               | 1-Year Onsite Repair, Next Business Day                                                                                                                                                                                                                                                                                                                                                                      |                  |
| Size (mm - H x W x D) / Weight                                  | 462 x 442 x 588 mm / 27.1 kg                                                                                                                                                                                                                                                                                                                                                                                 |                  |

All information in this brochure is subject to change without notice. Lexmark is not liable for any errors or omissions.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

<sup>1</sup>"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. <sup>2</sup>"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. <sup>3</sup>Printers are sold subject to certain license/agreement conditions. See [www.lexmark.com/printerlicense](http://www.lexmark.com/printerlicense) for details. <sup>4</sup>Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. <sup>5</sup>Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds). <sup>6</sup>Product functions only with replacement cartridges designed for use in a specific geographical region. See [www.lexmark.com/regions](http://www.lexmark.com/regions) for more details.