



Lexmark CX331adwe

Small. Dependable. Secure.

Compact and lightweight, the Lexmark CX331adwe multifunction brings colour printing, scanning, copying, faxing and touch-screen convenience to small workgroups. It offers colour output at up to 24 pages per minute* in a package that fits almost anywhere. There's Wi-Fi to support mobile users and Lexmark full-spectrum security is built in.



Compact colour versatility

- ▶ Get colour output at up to 24 pages per minute*, plus automatic-feed single-side scanning and analogue faxing.
- ▶ Tackle your printing workload with the power of a 1-GHz processor and 512 MB of memory.
- ▶ Connect via standard Wi-Fi, ethernet and USB.
- ▶ Simplify mobile printing via Lexmark Mobile Print app, as well as Mopria® and AirPrint technologies.
- ▶ The 7.2 cm touch screen offers built-in workflow capabilities like scan to network, scan to e-mail and Lexmark's own Cloud Connector****.

Easy to set up, easy to keep going

- ▶ Compact dimensions of 344 mm high x 411 mm wide x 394 mm deep helps it fit almost anywhere.
- ▶ Unison™ Toner replacement cartridges deliver up to 4,500 pages** of high-quality output.

- ▶ The steel frame and lifetime imaging components mean long life and minimal maintenance.

Robust, built-in security

- ▶ Lexmark's full-spectrum security architecture helps keep your information safe—on the document, the device, over the network, and everywhere in between.

Built for planet earth

- ▶ Built-in energy-saving mode goes from sleep to print to sleep with nothing to set.
- ▶ This printer is rated EPEAT® Silver*** and is ENERGY STAR® certified.
- ▶ Recycle cartridges through the award-winning Lexmark Cartridge Collection Programme (LCCP).



* Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

** Average continuous black or continuous composite colour (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See www.lexmark.com/yields for more information.

*** EPEAT ratings may vary by location. See www.epeat.net for registration status by country.

**** Cloud Connector feature will be available by end of 2019. Devices purchased prior to availability can get this feature via free firmware update at support.lexmark.com/firmware.

Product Specifications		Lexmark CX331adwe
Printing		
Display	7.2 cm (2.8-inch) LCD touch panel	
Print Speed	Up to: Black: 24 ppm ¹ (A4) / Colour: 24 ppm ¹ (A4)	
Time to First Page	as fast as: Black: 10.6 seconds / Colour: 10.6 seconds	
Print Resolution	Black: 4800 Colour Quality / Colour: 4800 Colour Quality	
Memory	standard: 512 MB / maximum: 512 MB	
Hard Disk	Not Available	
Recommended Monthly Page Volume	600 - 2,500 Pages ²	
Maximum Monthly Duty Cycle	Up to: 50,000 pages per month ³	
Copying		
Copy Speed	Up to: Black: 24.7 cpm ¹ (A4) / Colour: 24.7 cpm ¹ (A4)	
Time to First Copy	as fast as: black: 13.1 seconds / colour: 13.1 seconds	
Scanning		
Scanner Type / ADF Scan	Flatbed scanner with ADF / Simplex	
A4/Ltr Simplex Scan Speed	Up to: Mono: 20 / 21 sides per minute / Colour: 20 / 21 sides per minute	
ADF Paper Input Capacity	Up to: 50 pages 75 gsm bond	
Faxing		
Modem Speed	Max is 33,600 bps, V.34 Half-Duplex Kbps	
Supplies ⁴		
Laser Cartridge Yields	up to: 4,500 ⁵ -page Black High Yield Cartridge / up to: 4,500 ⁵ -page Colour (CMY) High Yield Cartridges / up to: 1,500 ⁵ -page Black and Colour (CMYK) Cartridges	
Cartridge(s) Shipping with Product	750 ⁵ -page Black Return Programme Toner Cartridge, 500 ⁵ -page Colour (CMY) Return Programme Toner Cartridge	
Paper Handling		
Included Paper Handling	100-Sheet Output Bin, Integrated Duplex, Single-Sheet Manual Feed, 250-Sheet Input	
Paper Input Capacity	Up to: Standard: 250+1 pages 75 gsm bond / Maximum: 250+1 pages 75 gsm bond	
Paper Output Capacity	Up to: Standard: 100 pages 75 gsm bond / Maximum: 100 pages 75 gsm bond	
Media Types Supported	Hagaki Card, Paper Labels, Card Stock, Plain Paper, Envelopes, Glossy paper, Refer to the Paper & Speciality Media Guide	
Media Sizes Supported	A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Hagaki Card, Letter, B5 Envelope, Statement, C5 Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope	
General Information ⁶		
Standard Ports	Gigabit Ethernet (10/100/1000), Front Hi-Speed USB port Compatible with USB 2.0 Specification (Type A), 802.11b/g/n Wireless, USB 2.0 Specification Hi-Speed Certified (Type B)	
Noise Level	Operating: 50 dBA (Print) / 50 dBA (Copy) / 44 dBA (Scan)	
Specified Operating Environment	Humidity: 8 to 80% Relative Humidity / Altitude: 0 - 3,048 Metres (10,000 Feet) / Temperature: 10 to 32°C (50 to 90°F)	
Product Guarantee	1-Onsite Repair, 3 -5 Business Days	
Size / Weight	H x W x D: 344.4 x 411.2 x 394.1 mm / 19.4 kg	
ENERGY STAR Typical Electricity Consumption	TEC: 0.35 kilowatt-hours per week	

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹ Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

² "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³ "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴ Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. ⁵ Average continuous cartridge yield is stated number of standard pages as listed. Declared yield value in accordance with ISO/IEC 19798. ⁶ Printers are sold subject to certain licence/agreement conditions. See www.lexmark.com/printerlicense for details.

© 2019 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. AirPrint and the AirPrint Logo are trademarks of Apple, Inc. Google Cloud Print™ is a trademark of Google, LLC. Mopria®, the Mopria® Logo™ and the Mopria® Alliance logos are registered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorised use is strictly prohibited. All other trademarks are the property of their respective owners. This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).