




Microline Dot Matrix Printer

ML280 Elite 9-Pin Dot Matrix Printer

The reliable and affordable printer for industrial and point of sale applications

As the entry level printer in our 9-pin dot matrix range, the ML280 Elite is fast and robust, yet compact and light. A true demand document printer with bottom feed and short tear, its special size makes it ideal for customer service environments and industrial workstation applications.

Highlights:

- Compact 80 column dot matrix printer
- OKI Printing Solutions unique, high durability 9-pin print head
- Multi-part continuous forms handling (original + 3 copies)
- Up to 375 characters per second print speed
- Ideal for data logging, label printing and point of sale use
- Suited to harsh environments
- DC version also available for remote or mobile use



ML280

		ML280 ELITE	ML280 ELITE DC
General	Number of pins	9	
	No. of multi-part forms	4 (one original + 3 copies)	
Speed and throughput	Super speed draft (12cpi only)	375cps	300cps
	High speed draft (all cpi)	333cps	240cps
	Utility (all cpi)	250cps	200cps
	Near letter quality (all cpi)	62.5cps	50cps
	Fastest print speed	375cps	300cps
Font & print features	Carriage width (10cpi)	80 columns	
	Max. in compression mode	160 columns	
	Character pitch	10/12/15/17.1/20 pitch & proportional	
	Graphics resolution	Up to 240 x 216 dpi	
	Typeface & Font	Utility, High Speed Draft, NLQ, Barcodes	
	Typestyle	Emphasised, Enhanced, Double Width, Italics	
Emulations & Interfaces	Printer emulations	Epson LX, IBM Graphics or Oki MicroLine	
	Standard interfaces	Centronics Parallel, USB	
	Optional interfaces	Serial RS 232C/RS 422/Current Loop	
Paper handling	Continuous paper	76.2 — 241.3mm	
	First printable line (from top of page)	Cut sheet: 15mm, Continuous: 16.9mm	
	Standard	Autoload single sheet, Platen pin feed, Low tear-off, Paper end detection	
	Optional	Roll paper stand, Pull tractor feed, Single bin sheet feeder	
Physical	Dimensions (HxWxD)	80 x 372 x 275mm	
	Weight	4.5kg	4.0kg
	Memory	128KB	
	Noise level	51dB (quiet mode)	
Power	Power requirements	220V-240V AC	9.6 — 31.2V DC
	Frequency	50/60Hz	
Reliability	Print head life	200 million characters	
	Ribbon life	3 million characters (re-inking cartridge)	
	MTBF	20,000 hours	

Consumables Information: Only use genuine OKI Printing Solutions Original consumables to ensure the best quality and performance from your hardware. Non OKI Printing Solutions Original products may damage your printer's performance and invalidate your warranty. Specifications subject to change without notice. All trademarks acknowledged.



OKI EUROPE LTD.
 Central House, Balfour Road
 Hounslow, Middlesex TW3 1HY
 United Kingdom
 T +44(0) 20 8219 2190
 F +44(0) 20 8219 2199
WWW.OKIPRINTINGSOLUTIONS.COM

OKI
 PRINTING SOLUTIONS