

> PRINT > COPY > SCAN > FAX

TASKalfa 6053ci

A4/A3 (SRA3) COLOUR MULTIFUNCTIONAL

OUR HERO WITH HIGH SPEED PRODUCTIVITY



Intuitive 10.1"colour touch screen.



Outstanding image quality - standard 1200 x 1200dpi. Flexible paper handling from A6 to SRA3,





Standard data security kit ensures the highest levels of document encryption.







Fiery[™] controller ensures the highest productivity colour print output.



The combination of outstanding colour quality, high speeds and high-capacity document processing makes the new TASKalfa 6053ci a very impressive multifunctional device. Supported by advanced technology, productivity is further enhanced with flexible paper-handling options and fast, economical and reliable printing. And when it comes to optimising workflows, this colour multifunctional, with its range of digital functions, unique HyPAS™ software platform and optional Fiery™ controller puts the power firmly in your hands. A standard data security function also allows peace of mind, knowing that all documents that are sent to and printed from or held on this device are automatically overwritten and encrypted.



In today's landscape, securing your printing environment is a competitive advantage for your organisation. The new TASKalfa 6053ci runs sophisticated security features to protect your business data from costly data breaches.

Technology: KYOCERA TASKalfa Laser Colour, HyPAS solution platform

Touch panel size: 256.5 mm (10.1 inch) full-colour touch panel display, speaker for job notification, 15° - 90° swivel mounted

Engine speed (pages per minute): Up to 55/27 ppm A4/A3 in colour, up to 60/30 ppm A4/A3 in black and white; Duplex print speed: 60 ppm A4; Duplex copy speed

Resolution: 4800dpi equivalent x 1200dpi (print), 600 x

600 dpi (scan/copy)

Warm-up time from power on: Approx. 17 seconds or less
Time to first print: Approx. 3.8 / 5.1 seconds or less
in black and white / colour

Time to first copy: Approx. 4.1/ 6.2 seconds or less in black and white / colour (DP); Approx. 3.4/ 4.4 seconds or less in black and white / colour (Platen)

CPU: QorlQ T1024 (Dual Core) 1.2GHz Memory (standard max.): 4 GB RAM + 8 GB SSD

Standard interface: Standard interface: USB 3.0 (Super-Speed USB), 4 x USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT, IPv6, IPv4, IPSec, (1008ase1) 1008ase1x 10008ase1, 1Pv6, 1Pv6

Power source: AC 220 V Power consumption: Printing: 990 W Copying: 990 W Ready mode: 60 W Low power mode: 50 W Sleep mode: 0.7 W

Sleep mode: 0.7 W Moise (sound pressure level ISO 7779 measurement distance of 1 meter): Copying/Printing: 69 dB (A) Stand-by: 35 dB (A) Safety standards: GS, TÜV, CE.

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Multipurpose tray: 150 sheets, 52 - 300 g/m2 (Banner 136 – 163 g/m²), A6R – SRA3 (320 x 450 mm), Custom (98 x 148 to 297 x 457.2 mm), Banner max. 304.8 x 1,220 mm; Standard universal paper cassette, 2 x 500 sheets, 52 – 300 g/m², Upper cassette A6R up to A4R, lower cassette A6R up to SRA3, Max. input capacity with options: 7,150 sheets A4

Duplex unit: Duplex as standard supports
AGR – SRA3, 64 – 256 g/m²
Output capacity: Standard 500 sheets face-down, max. output capacity 4,300 sheets

Controller language: PRESCRIBE Emulations: PCL6 (PCL5c / PCL-XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and

Openating systems: All current Windows operating systems, Mac OS X Version 10.9 or higher, UNIX LINUX, as well as other operating systems on request Fonts/barcodes: 93 outline fonts (PCL), 136 fonts (KPDL3), 8 fonts (Windows Vista), 1 Bitmap font, 45 types of one-

dimensional barcodes plus two-dimensional barcode

Print features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec,SNMPv3, quick copy, proof and hold, private print, iob storage functionality

Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, NFC, Direct Wi-Fi, Google cloud print

COPY FUNCTIONS

Max. original size: A3 / Ledger Continuous copying: 1 – 9999 Zoom range: 25 – 400% in 1% steps Preset magnification ratios: 5R/5E, Exposure mode: Auto, manual: 16 steps Image adjustments: Text + photo, text, photo,

Diagram/map
Features: Scan-once-copy-many, electronic sort, 2in1, 4in1, image repeat, page numbering, cover mode, booklet copy, interrupt copy, form overlay, margin shift, auto cassette change, skip blank page, ID copy

SCAN FUNCTIONS

Functionality: Scan to e-mail, Scan to FTP, Scan to SMB Scan to USB Host, Scan to box, Network TWAIN, WIA/WSD

Scan speed: 220 images per minute (300 dpi, A4, with DP-7130) in black and white and colour

DP-7130) in black and white and colour
Scan resolution: 600dpi x 600dpi, 400dpi x 400dpi,
200dpi x 400dpi, 300dpi x 300dpi, 200dpi x 200dpi x
200dpi x 100dpi; 256 greyscales per colour
Max. scan size: A3, Ledger
Original recognition: Text, photo, text + photo, Light Text /

Fine Line, optimised for OCR
File types: TIFF, PDF, PDF/A, JPEG, Open XPS, Encrypted
PDF, High compression PDF, PDF/A-1a/b, PDF/A-2a/b/u, Searchable PDF(option), MS Office file(option)

FAX FUNCTIONS (OPTIONAL)

Compatibility: ITU-T Super G3 Modem speed: Max. 33.6 kbps Transmission speed: Max. 3 seconds (JBIG) Scanning speed: 2.0 seconds or less Maximum original size: A3, Banner up to 1,600 mm Compression method: JBIG, MMR, MR, MH

Features: Network faxing, rotate transmission, rotate reception, encrypted transmission and reception, duplex fax reception, memory

reception, mailbox, remote diagnostics, polling transmission and reception, broadcast, Optional Internetfax, dual fax with second fax system 12

CONSUMABLES

Average continuous toner yield in accordance with 5% coverage A4. **TK-8515K Toner-Kit:** Toner black for 30,000 pages A4

TK-8515C, TK-8515M, TK-8515Y Toner-Kits: Toner cyan, magenta, yellow for 20,000 pages WT-8500 Waste Toner Bottle: 40,000 sheets (in accord-

ance with 5% coverage black and white:colour = 7:3) **Staple cartridge: SH-10** 5000 x 3 staples, for DF-7100, DF-7120 and BF-730

SH-12 5000 x 3 staples, for DF-7110 **SH-14** 5000 x 5 staples, for DF-7130

OPTIONS

Fax System 12 Internet Fax Kit (A) Internet rax Kit (A)
Scan Extension Kit (A):
Scan to searchable PDF solution (embedded OCR),
convert to PDF or MS Office (docx, xlsx, pptx)
Printing System 15: Fiery Controller
Printing System Interface Kit 15: Interface board for Fiery

DP-7100 Document processor: (Reversing), 140 sheets, 35–160 g/m² (simplex), 50–120 g/m² (duplex), A6R–Banner up to 1,900 mm

DP-7110 Document processor: (one-path duplex scanning) 270 sheets at 50 - 80 g/m², 35 – 220 g/m² (simplex), 50 – 220 g/m² (duplex), A6R – A3, Banner up to 1,900 mm DP-7130 Document processor: (one-path duplex scanning with ultrasonic sensor), 270 sheets at 50 - 80 g/m², 35-220 g/m² (simplex), 50-220 g/m² (duplex), A6R-A3, Banner up to 1,900 mm

DT-730(B) Document tray PF-7100 Paper feeder: 2x 500 sheets, 52 – 300 g/m²,

PF-7110 Paper feeder: 2x 1,500 sheets, 52 - 300 g/m², A4,

PF-7120 A4 side Deck: 3,000 sheets, 60 - 300 g/m², A4, B5 DF-7100 Inner finisher: 500 sheets A4, 52-300 g/m²,

DF-7110* Document finisher + AK-7110:

DF-7110* Document finisher + AK-7110:

Main tray: 4,000 sheets A4;
Sub tray: 200 sheets A4; 52–300 g/m²; A6R – SRA3
Stapling up to 65 sheets A4 or 30 sheets A3 at 3 positions
DF-7120* Document finisher + AK-7110:
1,000 sheets A4, 52–300 g/m², A6R – SRA3,
Stapling up to 50 sheets A4 or 30 sheets A3 at 3 position
DF-7130* Document finisher + AK-7110: Main tray: 4,000
sheets A4; Sub tray: 200 sheets 52–300 g/m² A6R–SRA3;
Stapling up to 100 sheets A4 or 50 sheets A3 at 3 position

AK-7110 Attachment kit for DF-7110, DF-7120 and DF-7130, 100 sheets, 52–300 g/m², A6R–SRA3, * Bridge unit

AK-7110 is required when using a finisher PH-7C/PH-7D Punch unit for DF-7110/DF-7120/ DF-7130: 2-hole/4-hole/Swedish type, 60 – 256 g/m², ASR – A3 MT-730(B) Mailbox sorter for DF-7110:

MT-730(B) Mailbox sorter for DF-7110:
7 bins x 100 sheets A4, 50 sheets A3,B4, 60 – 163 g/m²
BF-730 Booklet and tri-folding unit for DF-7110
Half-folding: 52–256 g/m², A3, B4, A4R
Booklet: Max. 16 sheets (64 pages, 60–90 g/m²)
Non-staple folding: Max. 5 sheets (60–90 g/m²)
Tri-folding: Max. 5 sheets (60–105 g/m², A4R)
Multi tri-folding: 5 sheets (60–90 g/m²), 3 sheets
(91–105 g/m²)

Will thirdding; 5 sheets (60 - 90 g/m²) 8F-9100 Booklet and tri-folding unit for DF-7130 Half-folding; 52 - 256 g/m², A3, B4, A4R Booklet: Max 20 sheets (80 pages, 60-90 g/m²) or Max 13 sheets (52 pages 91-105 g/m²) Non-staple: Max 5 sheets (60-90 g/m²) or Max 3

sheets(91-105g/m²) Tri-folding : Max 5 sheets(60-90g/m²) or Max 3 sheets(91-

105g/m²)

JS-7100 Job separator: 100-sheet internal job separator, 52 – 300 g/m², ASR – SRA3 PH-7120: Inner punch unit for DF-7100 inner finisher PH-7130: Inner punch unit for DF-7100 inner finisher/ Swedish type

Banner Guide 10: Banner paper feeding guide, 10 sheets

NK-7120 Numeric keypad
USB IC Card Reader + Card Authentication Kit (B):

Support for various authentication keys available. The card holder is standard UG-33 AC: ThinPrint support UG-34 AC: Emulation (IBM Proprinter/EPSON LQ-850/

Diablo 630)

Optional interface

IB-35: Direct Wi-Fi Interface IB-50: Gigabit-Ethernet board 10 BaseT/100 BaseTX/

IB-51: Wireless LAN Interface (802.11b/g/n)

Platen cover (E) CB-7100W: Wooden cabinet CB-7110M: Metal cabinet















KYOCERA Document Solutions (UK) Ltd, Eldon Court, 75-77 London Road, Reading RG15BS Tel: 0118 931 1500, Fax: 0118 931 1108 www.kyoceradocumentsolutions.co.uk, info@duk.kyocera.com

KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

