FELLOWES Venus 2 A3

Large Office Laminator with InstaHeat

Fully automatic laminator with 30 second warm-up and 6-roller engine for superior results - Heavy use

- Unique AutoSense system detects pouch thickness and self adjusts to the optimal laminating setting
- High speed warm-up. Ready to laminate in 30 seconds with InstaHeat Technology
- Laminates an A4 pouch in as little as 18 seconds (1000mm/ min)
- Robust 6-roller laminator for superior lamination quality, can laminate up to 250 microns (2x250)
- 100% jamfree when used with Fellowes branded pouches
- Simple 1-touch user interface with a reverse mode for clearing misfed documents
- Sleepmode is activated after periods of inactivity, reducing energy consumption
- HeatGuard technology contains heat inside the laminator, keeping it comfortable to the touch Includes 10 pouch starter kit (A4 80 micron)



SPECIFICATIONS

Model Name	Number of rollers	Heat-up time	Laminating settings	Speed	Max Micron	Warranty
Venus 2	6 rollers	30 seconds	AutoSense	1000mm/ min	250 micron	2 years



FELLOWES Venus 2 A3

Unique Features



Touch Panel - Power button



Back tray to support the laminate result

InstaHeat









High speed warm-up. Ready to laminate after 30 or 60 seconds with InstaHeat Technology

Unique AutoSense system detects pouch thickness and selfadjusts to the optimal laminating setting

Unique low friction laminating offers jam free performance with Fellowes branded pouches

Patented safety system reduces the surface temperature of the laminator, ensuring it is always safe to touch

Automatically activated after periods of inactivity to reduce energy consumption



Compatible with Fellowes Preserve 250 micron pouches

Felowes

LOGISTICS

Item code	Name	Retail Barcode	Outer barcode	Product Dims (mm) / Weight	Outer Dims (mm) / Weight	Quantity per outer
5734201	Venus 2 A3	EU - 043859641239	EU- 50043859641234			
(EU/ 220V)	101103 2 710			121x546 x 172/ 6.5 kg	168 x 278 x 588/ 7kg	1
	commercial packaging					
5734801	Venus 2 125	US - 043859641291	US-50043859641296			
(US/ 110V)				121 x 546 x 172/ 6.5 kg	168 x 278 x 588/ 7kg	1
	commercial packaging					

