ML5520eco/ML5521eco Specifications





High volume, high speed printing and energy savings

The ML5520eco and 136 column ML5521eco dot matrix printers are perfect for high speed, high volume data listing and multi-part forms applications, where fast throughput and reliability are a must.

Designed to be tough enough for mission critical printing in the most demanding of environments these high performance desktop printers have provided many years of dependable service to industry. Now enhanced with the latest power management technology power consumption is reduced to just 1.5W in "Sleep mode" to deliver significant energy savings over the products long life.

Application and media friendly

The ML5520/1eco printers can handle cut sheets, continuous feed paper and multi-part forms. They are ideal for the fast printing of receipts, invoices, picking lists, reports and spread sheets in industrial and retail applications. Their powerful 9-pin print head can produce up to 6 copies simultaneously for highly efficient document production.

Top, bottom and rear paper input paths and a builtin rear push tractor feed unit provide flexibility. Optional bottom push and top pull tractor units are available to allow the loading of two different media types simultaneously or the feeding of heavier papers and labels. A Roll Paper Stand option is available for the ML5520eco for fast printing of long passenger lists, call logs, data logs etc.

Helping the environment and saving money

The ML5520/1eco printers have been enhanced to be eco-friendly. OKI's SoC (System on Chip) technology reduces power consumption to an impressively low 1.5W in "Sleep mode" helping to reduce your carbon footprint as well as keeping your running costs and energy consumption to a minimum.

OKI's commitment to customers

The OKI brand is one of proven reliability and value. With almost half a century of experience in the impact printer industry, you are guaranteed a best-in-class performance and great value for money products. And, for total peace of mind, just register your printer and take advantage of our extended three year on-site warranty at no extra cost.

Highlights:

- Up to 570 characters per second (cps) print speed
- 80 and 136 column versions available
- OKI Microline, IBM and Epson emulations
- Scalable fonts and barcode support
- Eco-friendly technology, sleep mode consumes just 1.5W
- Powerful, highly durable 9-pin print head
- Multi-part paper-handling (original + 5 copies)
- Easy change 4 million character cartridge ribbon
- Low-tear and auto-park help eliminate wastage
- USB and Parallel interfaces with RS232 and Network options
- Manufactured at a CarbonZero facility
- Three-year warranty as standard (product registration required)

Variants available:

ML5520eco Narrow carriage ML5521eco Wide carriage



ML5520eco and ML5521eco - Dot Matrix Printers

| PRINTER | | GENERAL FEATURES | |
|--|---|----------------------------------|--|
| Number of pins | 9 | Input buffer | 128Kbytes |
| Columns | ML5520eco: 80 (10cpi); 160 (maximum in compression mode) | Power supply | Single phase 220 to 240VAC, +/- 10%, frequency 50/60Hz |
| | ML5521eco: 136 (10cpi); 272 (maximum in compression mode) | Power consumption | ISO/IEC 10561 Letter, Draft, Range1: 40.2W; |
| Character pitch | 10/12/15/17.1/20 pitch and proportional | | Sleep mode: <1.5W (with no optional attachments) |
| Graphics resolution | Up to 240 x 216 dpi | Noise level | Normal: 56dB(A); Quiet: 52dB(A) |
| Print speed | Super Speed Draft: 570cps (12cpi); High Speed Draft: 507cps (10/12cpi); Utility: 380cps (10/12cpi); Near Letter Quality: 95cps (10/12cpi) | Dimensions (HxWxD) | ML5520eco: 120 x 398 x 345mm ML5521eco: 120 x 552 x 345mm |
| | | Weight | ML5520eco: 5.9kg approx; ML5521eco: 7.7kg approx |
| | | Print Head life | 200 million characters |
| INTERFACE AND EMULATIONS | | Reliability | MTBF: 20,000 hours |
| Interfaces | Centronics IEEE 1284 parallel interface, USB 2.0 | Warranty | 3 years extended warranty upon registration within 30 days of purchase |
| Optional interfaces | Ethernet 10/100, Serial RS232C | | , , |
| Emulations | Epson FX, IBM ProPrinter, OKI MicroLine (ML) | Product order numbers | ML5520eco: 01308602; ML5521eco: 01308702 |
| Typeface & font | SSD, HSD, NLQ-Courier (scalable), NLQ-Gothic (scalable), OCR-B | | |
| Typestyle | Emphasised, Enhanced, Double Width, Double Height, Italics, Bold, Superscript, Subscript, Underline, Overscore | Accessories (Order Numbers) | |
| Paras dan | UPC-A, UPC-E, EAN8, EAN13, Code39, Interleaved 2of5, | Single Bin Cut Sheet Feeder | ML5520eco: 44497402; ML5521eco: 44497502 |
| Barcodes | Code128 (A/B/C), POSTNET | Push Tractor (bottom feed) | ML5520eco: 09002366; ML5521eco: 09002370 |
| Printer driver ¹ | Windows 2000 / XP (32-bit & 64-bit) / Vista (32-bit & 64-bit) / 7 (32-bit & 64-bit) / Server 2003 (32-bit & 64-bit) / Server 2008 (32-bit & 64-bit) / Server 2003 | Pull Tractor (bottom/rear feeds) | ML5520eco: 09002365; ML5521eco: 09002369 |
| | | Roll Paper Stand | 09002332 (ML5520eco only) |
| PAPER HANDLING | | Serial RS232C | 44455102 |
| TAPER HANDEING | | Network Card | 44455302 |
| Paper | Cut Sheet (single sheet), Continuous Paper (single-part, multipart), Roll paper (ML5520eco only), Envelope, Card, Label (cut sheet and fan fold) | Consumables (Order Number) | |
| Continuous paper (width) | ML5520eco: 76.2 - 254.0mm; ML5521eco: 76.2 - 406.4mm | Ribbon | |
| Continuous envelopes | ML5520eco: 165 x 92mm ML5521eco: 241 x 105mm (Bottom feed only) | (4 million characters) | 01126301 |
| First printable line (from top of page) | Continuous (multi-parts): 0.5mm Cut sheet (single sheet): 0.5mm | | |
| No of multi-part forms | Up to 6 (one original + 5 copies) | | |
| Multi-part paper thickness | Bottom push feed: 0.44mm; rear push feed & top/rear push- pull feed: 0.38mm; Bottom pull feed: 0.44mm | | |
| Paper feeding | Manual insertion: Top in, top out; Push Tractor: rear in, top out; Optional Push/Pull tractor: rear or bottom in, top out | | |
| Optional paper feeding | Single Bin Cut Sheet Feeder, Bottom Push Tractor (bottom feed), Top mounted Pull Tractor (bottom/rear feed), Roll Paper Stand (ML5520eco only) | | |

¹Check local OKI Printing Solutions website for latest driver releases and OS compatibility

Consumables Information: Only use genuine OKI Printing Solutions Original consumables to ensure the best quality and performance from your hardware. Non OKI Printing Solutions Original products may damage your printer's performance and invalidate your warranty.



Simply Unique - 3 Year Warranty

Our devices are manufactured to the highest standards of quality and technology, which has been confirmed by independent tests. We are so convinced of the high quality of our products that we are offering you an extension of the standard warranty period to 3 years – for free! Simply register your product within 30 days of purchase to be eligible for our unique all inclusive offer. Fully covered by OKI! For further information please visit: www.okiprintingsolutions.co.uk/warranty.

Without registration, the standard pan-European 1 year warranty applies.

WARNING! This product complies with EN55022 Class B. However when fitted with the optional network interface card or optional cut sheet feeder, compliance to EN55022 is Class A. In a domestic environment this configuration may cause radio interference, in which case the user may be required to take adequate control measures.



T+44(0) 1753 819819
F+44(0) 1753 819899
www.okiprintingsolutions.co.uk

OKI SYSTEMS (UK) LTD.
550 Dundee Road, Slough
Berkshire, SL1 4LE
United Kingdom

